



SUBMITTAL DATA
SHEET METAL FITTINGS

CONNECTING COLLARS

Connecting Collars

(Tolerance on all sizes +/- 1/8")

Nom. Dia.	O.D.	Length No Damper	Length Standard Damper	Length With Build Out
4"	3.875	5.5"	5.5"	7.5"
6"	5.875	5.5"	5.5"	7.5"
8"	7.875	5.5"	5.5"	7.5"
10"	9.875	5.5"	5.5"	7.5"
12"	11.875	5.5"	5.5"	7.5"
14"	13.875	7.5"	7.5"	7.5"
16"	15.875	7.5"	7.5"	7.5"
18"	17.875	7.5"	7.5"	7.5"
20"	19.875	7.5"	7.5"	7.5"

Fitting Model

- SL No Damper
- SLD Standard Damper – Spring End Bearing with Handle and Wingnut
- SLD1 2" Damper Handle Extension
- SLD3 2" Build Out – 3/8 " square shaft, Nylon End Bearings and Locking Handle

Standard Construction

- Galvanized Steel, 26 Ga. thru 12" Dia., 24 Ga. on 14" Dia. and above
All Fitting Models Beaded on each end

Gauge Options

- 24 Gauge
- 22 Gauge
- 20 Gauge
- Other _____

Material Options

- Galvanized Steel
- Aluminum
- Stainless Steel
- Other _____