

Capacity	Duty	MODEL	rope falls	Hook lift	460V/3PH/60HZ						Foot mounted hoists		Trolley type		
					single speed	dual speed	single speed	dual speed		Either dual speed or single speed with forced ventilation + encoder cavity motors	monorail	low headroom	birail		
kg	FEM	XM	N.	m	ft/min	ft/min	kW	A	kW	A	Included	\$\$	\$\$	\$\$	
3200	2m	308NS4H10	4/1	10	15.8	15,8/5,3	3	7.8	3/1	6,6/6,3	Std.	**	**	**	
		308NS4H13		13	15.8	15,8/5,3	3	7.8	3/1	6,6/6,3	Std.	**	**	**	
		308VS4H10		10	23.6	23,6/7,9	3	7.8	3/1	6,6/6,3	Std.	**	**	**	
		308VS4H13		13	23.6	23,6/7,9	3	7.8	3/1	6,6/6,3	Std.	**	**	**	
		316NS2H10	2/1	10	31.5	31,5/10,5	6	12.5	6/2	12,6/10,2	Std.	**	**	**	
		316NS2H14		14	31.5	31,5/10,5	6	12.5	6/2	12,6/10,2	Std.	**	**	**	
		316NS2H20		20	31.5	31,5/10,5	6	12.5	6/2	12,6/10,2	Std.	**	**	**	
		316NS2H26		26	31.5	31,5/10,5	6	12.5	6/2	12,6/10,2	Std.	**	**	**	
5000	2m	312NS4H10	2/1	10	15.8	15,8/5,3	4.8	10	4,8/1,6	9,7/9,5	Std.	**	**	**	
		312NS4H13		13	15.8	15,8/5,3	4.8	10	4,8/1,6	9,7/9,5	Std.	**	**	**	
		312VS4H10		10	23.6	23,6/7,9	7.2	15	7,2/2,3	15,2/12,8	Std.	**	**	**	
		312VS4H13		13	23.6	23,6/7,9	7.2	15	7,2/2,3	15,2/12,8	Std.	**	**	**	
		525NS2H10	2/1	10	31.5	31,5/10,5	9.6	20.9	9,6/3,2	18/17,6	Std.	**	**	**	
		525NS2H14		14	31.5	31,5/10,5	9.6	20.9	9,6/3,2	18/17,6	Std.	**	**	**	
		525NS2H20		20	31.5	31,5/10,5	9.6	20.9	9,6/3,2	18/17,6	Std.	**	**	**	
		525NS2H26		26	31.5	31,5/10,5	9.6	20.9	9,6/3,2	18/17,6	Std.	**	**	**	
10000	2m	525NS4H10	4/1	10	15.8	15,8/5,3	9.6	20.9	9,6/3,2	18/17,6	Std.	**	**	**	
		525NS4H13		13	15.8	15,8/5,3	9.6	20.9	9,6/3,2	18/17,6	Std.	**	**	**	
		525VS4H10		10	23.6	23,6/7,9	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
		525VS4H13		13	23.6	23,6/7,9	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
12500	2m	732NS4H9,5	4/1	10	15.8	15,8/5,3	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
		732NS4H13		13	15.8	15,8/5,3	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
		732NS4H16,5		16,5	15.8	15,8/5,3	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
16000	1Am	740NS4H9,5	4/1	10	15.8	15,8/5,3	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
		740NS4H13		13	15.8	15,8/5,3	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
		740NS4H16,5		16,5	15.8	15,8/5,3	14.4	25.1	14,4/4,8	30,4/30,3	Std.	**	**	**	
20000	1Am	750VS4H9	4/1	9	15.8	15,8/5,3	18	32	18/6	33,4/25,7	Std.	**	**	**	
		750VS4H13		12.5	15.8	15,8/5,3	18	32	18/6	33,4/25,7	Std.	**	**	**	
		750VS4H16		16.0	15.8	15,8/5,3	18	32	18/6	33,4/25,7	Std.	**	**	**	
	2m	950NS4H10	4/1	10	14.8	14,8/4,9	19.2	35	19,2/6,4	36/29,7	Std.	**	**	**	
		950NS4H16		16	14.8	14,8/4,9	19.2	35	19,2/6,4	36/29,7	Std.	**	**	**	
		950NS4H24		24	14.8	14,8/4,9	19.2	35	19,2/6,4	36/29,7	Std.	**	**	**	

\*-NOTE: Standard Offerings Shown. Larger Capacities, Double-Reeved Units, and Special Applications/Configurations Are Available, Please Call.

\*\* -NOTE: Please Call For Pricing or to Discuss Distribution In Your Area.