



## Pumping Tees

- Ductile iron construction on 3000 PSI tees
- Carbon Steel construction on 5000 PSI tees
- Zinc phosphate coated for better thread lubrication
- Multiple thread combinations
- Corrosion resistant coatings available
- 1" NPT standard bleeder port



Most Common Models (Other Models Available) 3000 PSI Working Pressure Heavy Duty Tees				
Bottom Thread (Tubing or LP)	Top Thread (Tubing or LP)	Major Side Outlet (LP)	Height	Weight
2"	2"	2"	6"	9 lbs.
2" Male	2"	2"	7-1/4"	7 lbs.
2"	2-1/2"	2"	7-1/4"	13lbs.
2"	3"	3"	8"	21 lbs.
2-1/2"	2"	2"	7-1/4"	13 lbs.
2-1/2"	2-1/2"	2"	7-1/4"	13 lbs.
2-1/2" Male	2-1/2"	2"	8"	10 lbs.
2-1/2"	3"	2"	8"	20 lbs.
2-1/2"	3"	3"	8"	18 lbs.
3"	3"	3"	8"	18 lbs.
3" Male	3"	3"	9-1/2"	19 lbs.
4"	4"	4"	7-3/4"	18 lbs.



5000 PSI Working Pressure Carbon Steel Pumping Tees				
Bottom Thread (Tubing)	Top Thread (Tubing)	Major Side Outlet (LP)	Height	Weight
2"	2"	2"		
2-1/2"	2-1/2"	2"		
3"	3"	3"		