

IF IT DOESN'T SAY YOU CAN, YOU PROBABLY CAN'T! ASK FIRST.

DRIVERS IN STREET STOCK CLASS WILL HAVE TO BE APPROVED BY TRACK. NO CHERRY PICKING.

STREET STOCK CLASS IS LIMITED TO STREET STOCK ONLY!!!! DRIVER MAY NOT RUN ANY OTHER CLASS BESIDES FACTORY STOCK!!!!

General Rules

1. Must be 1955 or newer, 107.5 minimum wheelbase, 2 or 4 door sedan except Sport Mods. No convertibles,

station wagons, or sport cars.

2. All glass must be removed, any flammable interior parts must be removed, all light assemblies, handles, etc....and

all chrome except bumpers must be removed.

3. Full factory floor pan or equivalent. Full factory front firewall or

equivalent must be retained. Front fender wells may be removed. Fenders and quarter panels may be trimmed

as needed for tire clearance. Exterior body panels are to be OEM or may be fabricated using sheet metal, but

must maintain OEM body lines and contours. No slab sided Late Model type bodies are allowed.

4. Doors must be welded or bolted shut, gutting of all interior panels including trunk floor allowed. Metal firewall

between driver and fuel cell required for safety.

5. Front and rear bumpers may be an OEM type or fabricated using pipe or tubing no larger than 2" OD and with a

wall thickness no greater than .125". Fabricated front and rear bumper heights not to exceed 10". Bumpers must

have ends capped, plated, turned in or otherwise prepared in such fashion to prevent the hooking of other cars

and cutting tires. NO SHARP EDGES.

6. Aftermarket nose and tail pieces are allowed.

7. Must have front and rear tow straps.

Roll Cage and Bracing

1. 4 post – 6 point (2 braces from top of cage back to frame) roll cage must be welded directly to factory frame fully

framed cars. Uni-body cars only. Cage must be welded to minimum 6" x 6" x 1/4" thick plates that are securely

welded to body strong points. Sub frames may be tied together. Three driver's side door bars and 2 passenger

side door bars minimum.

2. Roll cage and door bars must be constructed using at least 1 1/2" OD pipe or tubing with a minimum .125" wall

thickness. 1 3/4" OD .95" wall OK too. Door bars must be tied together top to bottom in at least 2 places.

3. Full front and rear loops with associated bracing allowed.

4. Nerf bars allowed. Can be round, rectangular or Lexan. Must be within 1/2" of body and ends must be either

capped or tapered or turned into body. NO SHARP EDGES.

5. Plating of frame allowed only on hump over rear axle or for repairs. Track tech will make final decision about what

constitutes a repair. Rear frame rails may be replaced with square or round tubing to a point no further forward

than behind rear axle where hump over rear axle begins.

6. Driver compartment: Minimum three windshield bars in front of driver. Aluminum high-back seat only and must

be bolted in using minimum 0.375 inch bolts. Driver seat may be no further back than rear edge of B-pillar. Driver

must be sealed off from track, driveline engine and fuel cel.. Dash not to extend more than 24 inches back from

center of lower windshield opening. Dash must be flat, rear can be no higher than front except for cowl in front

of driver. No other interior tin or covers. Inside rear quarter panels. Below window level, may be cut out. Doors

and driver side B-pillar may be gutted. No cutting out of firewalls, roof, kick panels, rocker panels, except for roll

cage clearance. All holes in firewalls and floor must be covered with metal. OEM floor may be replaced from OEM

front firewall to OEM rear firewall using steel fabricated floor pan. 18 gauge or minimum 0.049 inch thickness,

securely welded to frame. Must remain flat. OEM appearing from frame rail to frame rail, no higher or lower

than frame rail. Exception in maximum eight inch tall drivershaft tunnel similar to OEM tunnel in size. Rear firewall

and speaker deck must be metal and be of OEM design for that make and model. No mirrors of any kind. If your

car doesn't conform to these rules, under the tracks decision, you may be able to add weight in front of the firewall

to justify your infraction.

Engines

1. GM and Ford 360 CID maximum allowed. Mopar 365 maximum allowed. No bore and stroke combinations not

offered by OEM allowed. Blocks must be cast iron OEM.

2. Engine and frame must be same manufacturer: GM in GM, etc

3. Domed or pop up pistons of any kind not allowed.

4. Stock crankshafts or stock replacement scat and steel stock appearing I-beam style connecting rods only. No dry

sump or external oil pumps allowed.

5. 5.7 Length Stock Appearing Rods ONLY.

6. Hydraulic flat tappet cams only. No solid lift cams allowed.

7. Aluminum low rise. No high rise intakes (even if they are OEM) or aftermarket intakes allowed. OEM cast iron or

any dual plane low rise aluminum intake.

8. Stud girdles ok.

9. Cylinder heads must be cast iron OEM. Vortech (part #'s 10239906 and 12558062) EQ and Dart stock replacement heads are legal. No

porting or angle milling allowed. No full roller rocker arms. Screw in studs, guide plates, roller rockers and polylocks OK.

10. OEM distributor only, aftermarket coil module OK. No MSD boxes or other aftermarket ignition parts not listed

above allowed. MSD Ignition #8727CT rev limiter or equivalent will be mandatory on a 6200rpm limit

11. 2 barrel carburetor only. Aftermarket carb spaces or adapters allowed with the use of a Holley list #4412 and

4412 CT 500 CFM 2 barrel only. Choke hardware must be removed, but choke horn must remain unmodified. No

airflow work allowed on any carburetor. No screw in air bleeds. No more than 2" adapter/spacer Maximum 2 3/8" gaskets included.

Carburetor must have two return springs.

12. Only 1 radiator allowed. It can be stock or racing and must be placed vertically in front of engine. Aftermarket

reduction pulleys OK.

13. Engine can be set back but #1 spark plug can be no further back than even with upper ball joint.

14. Exhaust may be cast iron manifolds or chassis style headers only.

Transmission/Drive Shaft

1. OEM automatic or standard only.

2. Automatics must run fully functional torque converter no less than 10" in diameter.

3. Standards must run OEM fully iron flywheel, clutch, and pressure plate with friction face no less than 10" in

diameter. No mini clutches.

4. Must have at least two forward gears and one reverse, plus neutral position. With motor running and car in still

position, must be able to engage car in gear and move forward, then backward.

5. No five speed or more transmissions, "in and out" boxes, or quick change devices allowed.

6. Functioning shift levers must be in OEM location.

7. Flywheel/flexplate must be bolted directly to end of crankshaft and pressure plate must be bolted directly to

flywheel/flexplate. One flywheel/flexplate only and all driveline components within bellhousing must rotate

consistent with engine RPM while car is in any gear. Unaltered flexplate must be full OEM or OEM replacement.

8. Manual must be OEM or OEM replacement case and explosion proof steel bellhousing – minimum 270 degrees

around top of the clutch/flywheel area.

9. Automatic must remain in OEM or OEM replacement case with a functioning OEM appearing pump. Aluminum

OEM bellhousing may be replaced with aftermarket explosion proof steel or aluminum bellhousing. Original OEM

bellhousing must have approved scattershield constructed of minimum 1/4 " by 3" steel, 270 degrees around

flexplate. Conveyor belt type belting of 1/4" thickness can be used for scattershield.

10. Drive Shaft is minimum 2" diameter steel drive shaft and must be painted white. Steel slip-yokes only. 360 degree

drive shaft loop required and must be constructed of at least 1/4" by 2" steel, or 1" tubing, mounted 6" back from

front U-joint.

Rear Ends

1. Passenger car or light truck rear ends allowed. Rear ends may be locked by welding or other means. 9" Ford

floaters rear end legal but must have stock suspension in stock location. NO TOLERANCE.

2. Floaters OK. (safety)

Suspension and Brakes

1. All front and rear suspension including mounts must remain absolutely stock, unmodified and in their original

locations. Racing springs. OK. Load bolts and weight jacks not allowed. Tubular upper control arms OK. No Heim

end trailing arms of any kind.

2. Racing shocks OK, heim end shocks OK in stock location.

3. Steering box and/or idler arm cannot be moved. Steering may be quickened by aftermarket steering quickener

or other means.

4. Brakes must be functional on at least 3 wheels but 4 wheels recommended. Aftermarket peddle and master

cylinder but no driver adjustable bias controls allowed.

Wheel and Tires

1. Steel wheels only not to exceed 8" in width, may be reinforced and/or reversed but must maintain no less than

2" backspacing. Wheels must be retained by no less than 5ea 1" lug nuts. Racing studs and lugs recommended.

4 lug hubs and wheels OK for cars so equipped from factory but MUST be equipped with both racing studs and

lugs. Bead locks allowed on right side only.

2. Tires are to be 60 or 70 series DOT stamped street tread steel belted radials only. Tires must be available at local

retailers. No special, knobby, snow, recaps AT or racing tires allowed except for any tire stamped or marketed as

an IMCA G60, Hoosier 500. Asphalt tires OK and can be grooved. American Racer IMCA tire also legal.

3. Grooving NOT permitted except on asphalt tires. Grinding glaze off tread OK.

Fuel and Fuel System

1. Gasoline only.

2. No electric fuel pumps. For year 2018 blocks with no manual fuel pump boss may run electric fuel pump but only

with oil pressure switch.

3. Racing fuel cell only. Must be securely mounted in trunk area to rear bracing and cannot be visible from outside

of car. Any fuel line ran through passenger compartment must be contained within rigid conduit. Vent must come

from tank and make a 360 degree loop with a PVC of some device one way ball.

Battery

1. Battery must be in plastic box securely mounted to floor pan or in trunk area.

2. Battery must be capable of starting car and car must be able to idle in neutral and move forward and backward

from a standing position with engine running.

Weight

1. Minimum weight after completion of feature event with driver is 3100 pounds.

Seat and Safety

1. Metal racing seat only. Must be securely mounted to roll cage and/or frame using a minimum of 4ea. 3/8" grade

5 or better bolts and nuts.

2. 5 point racing harness required and to be secured with minimum 3/8" grade 5 or better bolts and nuts.

3. Properly mounted window net or arm restraints must be used.

4. Driver must be equipped with an approved helmet, neck brace, gloves and wear drivers suit that effectively covers

drivers body.

5. Steering wheel must be equipped with quick release.

6. Drive shaft loop must be installed no more than 6" rearward of front U-joint.

7. Fuel Cell: Must be securely fastened inside trunk and no part of fuel cell may be forward of any part of rear-end.

Must be in steel container and mounted by minimum two (2) one-eighth (0.125) inch solid steel straps that are two (2) inches wide around the fuel cell. Must have check valve. Fuel cell vent (including cap

vent) must have check valves, flapper spring or ball-type filler valve. Fuel lines passing through the cockpit must be enclosed in metal pipe or metal conduit. Fuel filters are not allowed in cockpit. D-Ring fuel caps will not be allowed.

8. Every race car in each class must have a fire extinguisher mounted within reach of the driver except Sprint Class.

9. Every 4-Wheeler or ATV of any kind must have a fire extinguisher mounted on board.