



Technical Data Sheet

SK 007 data 16/05/2013

Product: **PRESTOIL G12+ 100%**

Description: New protective fluid assuring a good protection in all cooling circuits specially in aluminium ones. Produced without silicates, nitrites and phosphates it avoids deposits formation aiding upkeep automotive performances.

Specification:

- ASTM D 3306**
- ASTM D 4656**
- ASTM D 4985**
- BS 6580**
- FORD WSS-M97B44-D**
- FVV Heft R443**
- MAN 324 tipo SNF**
- MB 325.3**
- MTU MTL 5048**
- VW/AUDI/SEAT/SKODA TL 774 D/F (G12 / G12+)**



Technical Data Sheet

SK 006 data 16/05/2013

Product: **PRESTOIL G12 100%**

Properties:

Specifications	Test Method	Unit	Value
Appearance	VISUAL		Clear
Color	VISUAL	c.c.r.	Pink
Specific Gravity 20/20°C	ASTM D 1122	Kg/l	1.117
Boiling Point	ASTM D 1120	°C	>160
Flash Point	DIN ISO 2592	°C	>120
pH 50% water	ASTM D 1287	-	8.0 ÷ 9.0
Alkaline Reserve HCl N/10	ASTM D 1121	ml	8.5 ÷ 11.0
Ash	ASTM D 1119	% w	2.0
Water	ASTM D 1123	% w	3.0

The data shown here are indicative only and do not constitute specific

TABLE OF MIXING PURE PRODUCT

ANTIFREEZE	20%	30%	40%	50%	52%
FREEZING TEMP. (°C)	-9	-17	-26	-36	-41
BOILING TEMP. (°C)	+118	+120	+122	+123	+125