



Touch Probe TC52



# For small machining centres compact touch probe with multidirectional measuring mechanism

- Detection of workpiece position
- Correction of workpiece orientation
- Thermal compensation of the machine tool
- Contour measurement

#### Your benefit:

- Measuring speed up to 2 m/min
- Precise, non-lobing touch characteristics
- No-wear, optoelectronic measuring mechanism
- Use of two measuring systems with one IR receiver
- Extended battery life
- Precise measurement even with coolant
- Proven and robust design



### **DUO-Mode**

Sequential use of two measuring systems with one infrared receiver.



Ø13


0

# **Technical data**


Protection class	IP68
Approach directions	±X, ±Y, -Z
Measuring force in XY   Z	2,3 N / 0,65 N (LF)*   5,7 N / 1,6 N (LF)*
Max. deflection XY   Z	± 11°   6 mm
Max. acceleration	50 m/s <sup>2</sup>
Repeatability	0,3 μm 2σ
Max. probing speed	2 m/min
Mass	250 g
Signal transmission   Range	Infrared   $\pm 60$ ° in Z, 360 ° in X/Y
Battery	Saft Lithium LS14250 (1/2AA, 3,6V) 1200 mAh
Tool holder	BTH 25 (HSK, SK, BT, VDI,)
Storage/Operating temperature  * Stylus L= 30 mm	-20 °C +70 °C   +5 °C +50 °C




TC52 – for small machining centers



Fast workpiece measurement



Non-lobing touch characteristics



Modern and precise measuring mechanism with optoelectronic signal generation



Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

#### Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 Fax: +44 1543 251746 E-Mail: info@blum-novotest.co.uk

## Blum LMT, Inc.

4144 Olympic Boulevard Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com