



Technical Data Sheet

SK 006 data 16/05/2013

Product: **PRESTOIL ANTIFREEZE 100% C.**

Description: Concentrate antifreeze of new generation suitable for all cooling circuits, its special additivation avoids corrosion also on aluminium and alloy circuits, preserving v/s deposits, scales and ensuring a good thermic exchange.

Specification:

| | |
|-----------------------------|----------------------------|
| BS 8580 (GB) | SAE J 1034 |
| CUNA NC 956-16 (I) | FVV Heft R 443 (D) |
| JIS K 2234 (J) | UNE 26361-88 (E) |
| Afnor R 15/601 (F) | KSM 2142 (K) |
| EMPA (CH) | ASTM D 3306 and 498 |
| NATOS 759 | EL 1415c (Military) |
| Porsche/VW/Audi/Seat | Skoda TL 774 C |
| Mercedes DBL 7700 | MAN 324 |
| GM US 8277 M | Volvo (Reg. n.260) |
| Ford WSS-M97B44-C | Chrysler MS 8176 |
| BMW N 600 690 | GM US 8277 M |
| Ford ESD M97 649-A | Opel GM QL 130130 |



Technical Data Sheet

SK 006 data 16/05/2013

Product: **PRESTOIL ANTIFREEZE 100% C.**

Properties:

| Specifications | Test Method | Unit | Value |
|-----------------------------|-------------|--------|-------|
| Appearance | VISUAL | | Clear |
| Color | VISUAL | c.c.r. | BLUE |
| Specific Gravity 20/20°C | ASTM D 1122 | Kg/l | 1.115 |
| Chlorides (NaCl) | ASTM D 1384 | ppm | <5 |
| Sulfates (So4) | ASTM D 1384 | ppm | <5 |
| Acidity (CH3COOH) | ASTM D 1384 | ppm | <10 |
| Iron and Metals | ASTM D 1384 | ppm | <5 |
| Anhydrous Title | ASTM D 1384 | % Peso | 99.7 |
| Water | ASTM D 1123 | % Peso | 0.030 |

The data shown here are indicative only and do not constitute specific

| TABLE OF MIXING PURE PRODUCT | | | | | |
|------------------------------------|------|------|------|------|------|
| ANTIFREEZE | 20% | 30% | 40% | 50% | 52% |
| FREEZING TEMP. (°C) | -9 | -17 | -26 | -36 | -41 |
| BOILING TEMP. (°C) | +118 | +120 | +122 | +123 | +125 |