



# Fabric Specification Sheet

## Style: The Standard - 12oz 4-Ply Window Shade

**Available Widths:** 36", 45", 54", 63", 72", \*77"  
 (91 cm, 114 cm, 137 cm, 160 cm, 183 cm, 196 cm)  
 (Other widths and colors available upon request with 200 yard minimum order)  
 \*White Only

**Roll Lengths:** 30 yards standard (Other lengths available on request)  
 (27.4 m)

**Shipping:** Rolls shipped on 1.317" (3.2 cm) ID paper core  
 Optional 3" (7.67 cm) ID Paper core available

**Construction:** 4 ply lamination (73% Vinyl and 27% Fiberglass)  
 (Each vinyl is equal thickness and weight)

**Surface Texture:** As laminated – Various Embossing Patterns Available

**Thread Count:** 60 threads per square inch (+4 / -6)  
 (23 per square cm)

**Weight:** 12.5 oz. per square yard (+ / - 2.0)  
 (424 grams per square meter) (+ / - 68)

**Thickness:** 12.5 mil (+ / - 2.0)  
 (.318 mm) (+ / - .05)

**Instron Tear Strength:** Warp 26 Lbs/In Fill 18 Lbs/In

**Instron Breaking Strength:** Warp 100 Lbs/In Fill 77 Lbs/In

**Opacity:** Blackout

**Visual check**

**Washability:** Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents and gentle rubbing are recommended.

**Flammability:** NFPA 701 Test Method 1 - 2015 Edition  
 FMVSS & CMVSS 302  
 California State Marshal Section 13115 Registration No. FA-35803

**Other Tests Passed:** ASTM G-21 – Resistance to Fungi  
 ASTM E1428-9 – Pink Staining  
 AATCC 16, Option 3 – 2003 – Colorfastness to Light  
 AATCC Test Method 30  
 (ATCC 6275 Aspergillus Niger)  
 (ATCC 9645 Trichoderma Virus)  
 ASTM D4834-03 – Lead  
 CSA-Can 600-08 – Lead  
 UL GreenGuard Gold Certified

No.	Color	Ts	Rs	As	Tv	Rv	Av	Tv	O-F	SC (Single Glass)			SC (Insulating Glass)		
										1/8" CI	1/4" CI	1/4" H.A	1/2" CI	1" CI	1" H.A.
11	White 4 Ply	Tr	77	23	Tr	NA	NA	NA	NA	NA	0.22	NA	NA	0.2	NA
23	Bone 4 Ply	Tr	69	31	Tr	59	41	Tr	0.2	0.27	0.28	0.29	0.26	0.28	0.23
47	Grey 4 Ply	Tr	45	55	Tr	Tr	Tr	NA	NA	0.44	0.43	0.37	NA	NA	NA
49	Dark Grey 4 Ply	Tr	30	70	Tr	28	72	Tr	0.2	0.55	0.53	0.42	0.52	0.49	0.35
10	Black 4 Ply	Tr	5	95	Tr	Tr	Tr	NA	NA	0.72	0.68	0.5	NA	NA	NA



Revised 1/2020

MAILING ADDRESS  
 P.O. Box 1017  
 Warsaw, IN 46581

STREET ADDRESS  
 102 Enterprise Drive  
 Warsaw, IN 46580

PHONE  
 (574) 269-1280

FAX  
 (574) 269-7747

E-MAIL  
 Mail@indianacoatedfabrics.com

WEBSITE  
 www.indianacoatedfabrics.com