



Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to 40°C
Pulse rate and width:	Typical on time 15ms, off time 1.5-2.0sec (controlled by astable circuit)
Pulse rate variation:	5%/volt, ±20% for temperatures 0°C to +40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12 Coated with USP Class VI material

MODEL	BATTERY	BATTERY CAPACITY (days)			DIMENSIONS (mm)			WEIGHT (grams)	PRICE GROUP
		30 ppm*	35 ppm	40 ppm	A	B	C		
F1415	337	24	20	18	6	12	6	0.50	A
F1425	317	36	31	27	7	12	7	0.65	A
F1435	319	48	41	36	7	14	7	0.85	A

*15 ms pulse width

All models available only in 48.000-151.98MHz, and 164.000-167.99MHz ranges.

Warranty life is 50% of battery capacity.

470 First Ave. No., Box 398 • Isanti, MN 55040
763.444.9267 • fax:763.444.9384 • sales@atstrack.com • www.atstrack.com