

H-CPLT-3 Commercial Plumbing Trainer

Purpose

The **Hampden H-CPLT-3** Commercial Plumbing Trainer demonstrates the setup and use of a shallow bowl wash fountain and a service sink.

Components

- 3'- 6" X 8'- 0" platform dimensions:
Aluminum frame, waterproof treated 3/4" plywood floor
- 6" rear wall 4' X 8' – Wood stud frame, aluminum plate front, clear lexan back
- Floor mounted washfountain 36" semi circular
- Power outlet
- Service sink w/ Service sink faucet
- Waste line rodding exercise under floor
- Water – cold and hot connections on right side of floor platform (for water hook up)
- Rodding waste line left side w/female adapter w/plug
- Rodding waste line right side pipe penetrate 4" past platform (for waste hook up)
- 4 heavy duty wheels all 4 rotating, two locking



Hampden Model H-CPLT-3

Fixtures

- Washfountain – Bradley Sentry Semi-Circular Shallow Bowl Washfountain
 - o Floor mounted
 - o Off line vent with supplies from below
 - o Foot control hold open air valve
 - o Standard pedestal height
 - o Tempered line supply
 - o No soap dispenser
 - o With Back splash
- Service sink American Standard Akron Service Sink with drilled back 2 holes on 8" center and rim guard
 - o Faucet: exposed yoke wall mount with vacuum breaker and stops in shank
 - o Trap Standard: cast iron P trap standard to wall and strainer for 2"
- Drum trap –

Piping

- Water supply – copper tube
- Waste – PVC schedule 40

All Hampden units are available for operation at any voltage or frequency



Hampden
ENGINEERING CORPORATION