

# 9018

Printing date 09/25/2014

Revised On 09/25/2014

## 1 Identification of the substance and manufacturer

**Trade name:** MRO RYDER YELLOW  
**Product code:** 0006201446  
**Product category:** PC9a Paints and coatings.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178  
 Phone: 815-895-9101 www.seymourpaint.com  
**Emergency telephone number:** CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*



## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Carc. 2 H351 Suspected of causing cancer.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.  
 Eye Irrit. 2A H319 Causes serious eye irritation.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

### Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer.

### Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
 If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Read label before use.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Do not handle until all safety precautions have been read and understood.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Use personal protective equipment as required.  
 Do not breathe dust/fume/gas/mist/vapours/spray.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

| Chemical Description               | Percentage |
|------------------------------------|------------|
| 67-64-1 Acetone                    | 18.94%     |
| 74-98-6 propane                    | 15.69%     |
| 106-97-8 n-butane                  | 9.21%      |
| 7727-43-7 barium sulphate, natural | 7.99%      |
| 108-10-1 methyl isobutyl ketone    | 5.53%      |
| 2807-30-9 Glycol Ether EP          | 5.11%      |
| 13463-67-7 titanium dioxide        | 4.43%      |
| 107-87-9 Methyl Propyl Ketone      | 2.86%      |
| 110-19-0 isobutyl acetate          | 2.78%      |
| 1330-20-7 xylene (mix)             | 2.45%      |
| 108-65-6 PM acetate                | 2.07%      |
| 82199-12-0 Novaperm Yellow Pigment | 1.12%      |

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
**After swallowing:** Rinse out mouth and then drink plenty of water.

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO RYDER YELLOW

(Contd. of page 1)

**Most important symptoms and effects:**

Rinse mouth with water. Do not induce vomiting.

**Indication of any immediate medical attention needed:**

Dizziness

No further relevant information available.

**5 Fire-fighting measures****Extinguishing agents:**

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

**Special hazards:**

Can form explosive gas-air mixtures.

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**Wear protective equipment. Keep unprotected persons away.  
Use respiratory protective device against the effects of fumes/dust/aerosol.**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

**7 Handling and storage****Precautions for safe handling  
Storage requirements:**

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.  
Store locked up.**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm  |
| REL (USA) | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm  |
| TLV (USA) | Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm<br>Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm<br>BEI |

**74-98-6 propane**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| TLV (USA) | refer to Appendix F                                |

**106-97-8 n-butane**

|           |   |
|-----------|---|
| REL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm   |
| TLV (USA) | Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm |

**7727-43-7 barium sulphate, natural**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 15* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
| REL (USA) | Long-term value: 10* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
| TLV (USA) | Long-term value: 5* mg/m <sup>3</sup><br>*inhalable fraction; E                 |

**108-10-1 methyl isobutyl ketone**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 410 mg/m <sup>3</sup> , 100 ppm  |
| REL (USA) | Short-term value: 300 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 205 mg/m <sup>3</sup> , 50 ppm       |
| TLV (USA) | Short-term value: 307 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 82 mg/m <sup>3</sup> , 20 ppm<br>BEI |

**107-87-9 Methyl Propyl Ketone**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 200 ppm  |
| REL (USA) | Long-term value: 530 mg/m <sup>3</sup> , 150 ppm  |
| TLV (USA) | Short-term value: 529 mg/m <sup>3</sup> , 150 ppm |

**110-19-0 isobutyl acetate**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm |
| REL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 150 ppm |
| TLV (USA) | Long-term value: 713 mg/m <sup>3</sup> , 150 ppm |

**1330-20-7 xylene (mix)**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
|-----------|--|

(Contd. on page 3)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO RYDER YELLOW

(Contd. of page 2)

|  |  |
|--|--|
| REL (USA)  | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm        |
| TLV (USA)  | Short-term value: 651 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 434 mg/m <sup>3</sup> , 100 ppm<br>BEI |
| <b>108-65-6 PM acetate</b>                       |  |
| WEEL (USA)                                       | Long-term value: 50 ppm  |
| <b>Ingredients with biological limit values:</b> |  |
| <b>67-64-1 Acetone</b>                           |  |
| BEI (USA)  | 50 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: Acetone (nonspecific)                           |
| <b>108-10-1 methyl isobutyl ketone</b>           |  |
| BEI (USA)  | 1 mg/L<br>Medium: urine<br>Time: end of shift<br>Parameter: MIBK   |
| <b>1330-20-7 xylene (mix)</b>                    |  |
| BEI (USA)  | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids                 |

|                             |   |
|-----------------------------|---|
| <b>Hygienic protection:</b> | Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.  |
| <b>Breathing equipment:</b> | A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene. |
| <b>Hand protection:</b>     | Protective gloves. The glove material must be impermeable and resistant to the substance.   |
| <b>Eye protection:</b>      | Tightly sealed goggles  |

## 9 Physical and chemical properties

|  |  |
|--|--|
| <b>Appearance:</b>                             | Aerosol.   |
| <b>Odor:</b>                                   | Aromatic   |
| <b>Odor threshold:</b>                         | Not determined.  |
| <b>pH-value:</b>                               | Not determined.  |
| <b>Melting point/Melting range</b>             | Undetermined.  |
| <b>Boiling point:</b>                          | -44 °C (-47 °F)  |
| <b>Flash point:</b>                            | -19 °C (-2 °F)   |
| <b>Flammability (solid, gas):</b>              | Extremely flammable.                                     |
| <b>Decomposition temperature:</b>              | Not determined.  |
| <b>Auto igniting:</b>                          | Product is not self-igniting.                            |
| <b>Danger of explosion:</b>                    | In use, may form flammable/explosive vapour-air mixture. |
| <b>Lower Explosion Limit:</b>                  | 1.7 Vol %  |
| <b>Upper Explosion Limit:</b>                  | 10.9 Vol %   |
| <b>Vapor pressure:</b>                         | Not determined.  |
| <b>Relative Density:</b>                       | Between 0.77 and 0.85 (Water equals 1.00)                |
| <b>Vapour density</b>                          | Not determined.  |
| <b>Evaporation rate</b>                        | Not applicable.  |
| <b>Partition coefficient: n-octanol/water:</b> | Not determined.  |
| <b>Solubility:</b>                             | Not determined.  |
| <b>Viscosity:</b>                              | Not determined.  |
| <b>VOC content:</b>                            | 493.8 g/l / 4.12 lb/gl                                   |
| <b>VOC content (less exempt solvents):</b>     | 46.4 %   |
| <b>MIR Value:</b>                              | 1.08   |
| <b>Solids content:</b>                         | 34.1 %   |

## 10 Stability and reactivity

|  |  |
|--|--|
| <b>Reactivity:</b>                         | Stable at normal temperatures.   |
| <b>Conditions to avoid:</b>                | Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. |
| <b>Chemical stability:</b>                 | Not fully evaluated.   |
| <b>Possibility of hazardous reactions:</b> | No dangerous reactions known.  |
| <b>Incompatible materials:</b>             | No further relevant information available.   |

(Contd. on page 4)

US4

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO RYDER YELLOW

**Hazardous decomposition:** No dangerous decomposition products known.

(Contd. of page 3)

**11 Toxicological information****LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

**108-10-1 methyl isobutyl ketone**

Oral LD50 2100 mg/kg (rat)

Dermal LD50 16000 mg/kg (rab)

Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

**13463-67-7 titanium dioxide**

Oral LD50 &gt;20000 mg/kg (rat)

Dermal LD50 &gt;10000 mg/kg (rbt)

Inhalative LC50/4 h &gt;6.82 mg/l (rat)

**110-19-0 isobutyl acetate**

Oral LD50 4763 mg/kg (rbt)

**1330-20-7 xylene (mix)**

Oral LD50 8700 mg/kg (rat)

Dermal LD50 2000 mg/kg (rbt)

Inhalative LC50/4 h 6350 mg/l (rat)

**108-65-6 PM acetate**

Oral LD50 8500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

**Information on toxicological effects:** No data available.**Sensitization:** No sensitizing effects known.**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

|            |                        |    |
|------------|------------------------|----|
| 108-10-1   | methyl isobutyl ketone | 2B |
| 13463-67-7 | titanium dioxide       | 2B |
| 1330-20-7  | xylene (mix)           | 3  |

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

|                                       |   |
|---------------------------------------|---|
| <b>Aquatic toxicity:</b>              | Hazardous for water, do not empty into drains.                                      |
| <b>Persistence and degradability:</b> | The product is degradable after prolonged exposure to natural weathering processes. |
| <b>Bioaccumulative potential:</b>     | No further relevant information available.  |
| <b>Mobility in soil:</b>              | No further relevant information available.  |
| <b>Other adverse effects:</b>         | No further relevant information available.  |

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

|                                      |                       |
|--------------------------------------|-----------------------|
| <b>UN-Number</b>                     | UN1950                |
| <b>DOT</b>                           | Aerosols, flammable   |
| <b>ADR</b>                           | 1950 Aerosols         |
| <b>Transport hazard class(es):</b>   |                       |
| <b>Class</b>                         | 2.1                   |
| <b>Marine pollutant:</b>             | No                    |
| <b>Special precautions for user:</b> | Warning: Gases        |
| <b>EMS Number:</b>                   | F-D,S-U               |
| <b>Packaging Group:</b>              | --                    |
| <b>UN "Model Regulation":</b>        | UN1950, Aerosols, 2.1 |

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

(Contd. on page 5)  
US4

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/25/2014

Revised On 09/25/2014

Trade name: MRO RYDER YELLOW

(Contd. of page 4)

**SARA Section 313 (Specific toxic chemical listings):**

7727-43-7 barium sulphate, natural

108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

**CPSC:**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

**EPA:**

67-64-1 Acetone

7727-43-7 barium sulphate, natural

108-10-1 methyl isobutyl ketone

110-19-0 isobutyl acetate

1330-20-7 xylene (mix)

I

D, CBD(inh), NL(oral)

I

D

I

**USDA (United States Department of Agriculture):**

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

**16 Other information****Contact:**

Regulatory Affairs

US4