



APPLICATIONS

LED VAPOR TIGHT fixture is the heavy-duty, super-bright alternative to traditional tube and strip light fixtures. The fixture is dust tight as well as water and impact resistant for use in harsh environments. Ideal for basement, car washes, food processing facilities, industrial facilities, parking garages, public areas, and warehouses.

SPECIFICATION FEATURES

CONSTRUCTION

Injection molded polycarbonate housing. High transmission opal polycarbonate creates excellent light distribution and uniformity. Built-in constant current LED driver with highly efficient LED module.

ELECTRICAL

Bi-level option, Nextech driver, Epistar or Bridgelux LED chip.

INSTALLATION

Suitable for Ceiling Mount or Suspended Mount. Suitable for damp locations.

CERTIFICATION AND WARRANTY

DLC Premium, L70 Rated, UL, CE, FCC, RoHS Listed. 5-year warranty.

Ordering Example: rFA-VT4-45-50

Product Series: rFA-VT4

FIXTURE	WATTAGE	CCT	VOLTAGE	DIMMING
VT4= Vapor Tight 4 Foot	45= 45 Watt	40= 4000K 50= 5000K	[Blank]= 100-277V	[Blank]= Non-Dimmable DIM= 0-10V Dimmable

TECHNICAL PARAMETERS

Fixture	rFA-VT4-45-xx	rFA-VT4-45-xx-DIM
Power Consumption	45W	45W
Efficacy	125lm/W	125lm/W
Input Voltage (AC)	120-277V	120-277V
Delivered Lumens	5,625lm	5,625lm
CCT	4000K / 5000K	4000K / 5000K
CRI	83	83
THD	<15%	<15%
Power Factor	>0.9	>0.9
Dimmable	Non-Dimmable	0-10V
Certification	DLC, UL	DLC, UL
Lifespan (Hours)	50,000	50,000
Warranty	5-Years	5-Years

