www.giuliano-automotive.com



The best choice for the average tyre shop with budget goal.

DIGITAL ELECTRONIC 2-D WHEEL BALANCER WITH LED DISPLAY







by





Discover on our website!

PLANNED ENHANCEMENT

USB port for firmware updating via PC/notebook

Intuitive, Easy-to-use Control Panel

FUNCTIONS -

- Automatic measuring of wheel diameter and distance
- Automatic START and STOP
- Static and dynamic balancing
- OPTIMATCH function
- Self-calibration

WIDTH ESTIMATION




The width of the rim automatically suggested according to the measured diameter and distance.



A very practical Wheel Lifter reduces effort and increases productivity







Programs for selecting the best correction planes for any kind and shape of alloy rim.

SELF SELECTION MODE

Self-recognition of the Working program.



HIDDEN WEIGHT





 Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

OPPOSIT POSITION





 Opposite Weight function (OPF), enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (at 6:00).

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- · Wheel lifter and much more

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	110V 1ph (50/60) Hz
Cycle time	6 sec. (5 3/4"x14") 15 kg.
Balancing speed	< 150 rpm
Balancing precision	÷ 1 g
Net weight with guard	85 kg
Max. overall dimensions	1100x1100x1500 H mm

STANDARD ACCESSORIES





Cones and



quick clamping ring nut Counterweight pliers



