


COOLING CAPACITY: 18,000 - 60,000 BTU/H

ENERGY-EFFICIENT SPLIT SYSTEM AIR CONDITIONER 13 SEER / 1½ TO 5 TONS



Contents

Nomenclature.....	2
Product Specifications.....	3
Expanded Cooling Data	4
AHRI Ratings	20
Wiring Diagrams	54
Dimensions	56
Accessories	56

Standard Features

- Energy-efficient compressor
- Factory-installed filter drier
- Copper tube/aluminum fin coil
- Service valves with sweat connections and easy-access gauge ports
- Contactor with lug connection
- Ground lug connection
- AHRI Certified; ETL Listed

Cabinet Features

- Heavy-gauge galvanized-steel cabinet with louvered sound control top
- Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval
- Steel louver coil guard
- Single-panel access to controls with space provided for field-installed accessories



* Complete warranty details available from your local dealer or at www.amana-hac.com. To receive the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec.

G		S		X		13		036		1		AA			
1		2		3		4,5		6,7,8		9		10,11			
Brand										Engineering					
G Goodman® Brand										Major & Minor Revisions (not used for inventory or ordering)					
Product Category										Electrical					
S Split System										1 208/230 V, 1 Phase, 60 Hz					
										2 220/240 V, 1 Phase, 50 Hz					
										3 208/230 V, 3 Phase, 60 Hz					
Unit Type										Nominal Capacity					
X Condenser R-410A										018 1½ Tons		030 2½ Tons		042 3½ Tons	
Z Heat Pump R-410A										019 1½ Tons		031 2½ Tons		043 3½ Tons	
										024 2 Tons		036 3 Tons		048 4 Tons	
										025 2 Tons		037 3 Tons		060 5 Tons	
Efficiency															
13		13 SEER		16		16 SEER									
14		14 SEER		18		18 SEER									

	GSX13 0181E*	GSX13 0181EH	GSX13 0181EJ	GSX13 0241E*	GSX13 0301B*	GSX13 0301L*	GSX13 0361E*	GSX13 0421B*	GSX13 0481B*	GSX13 0601B*	GSX13 0611A*
CAPACITIES											
Nominal Cooling (BTU/h)	18,000	18,000	18,000	23,000	30,000	30,000	36,000	42,000	48,000	60,000	60,000
SEER / EER	13/11	13/11	13/11	13/11	13/11	13 / 11	13/11	13/11	13/11	13/11	13/11
Decibels	75	75	75	75	73	74	74	75	76	77	72
COMPRESSOR											
RLA	6.7	6.7	6.0	7.7	12.8	10.5	14.1	17.9	19.9	25.0	26.4
LRA	41	37.5	37.5	37	64	47	77	112	109	134	134
CONDENSER FAN MOTOR											
Horsepower	1/8	1/8	1/8	1/8	1/8	1/8	1/4	1/4	1/4	1/4	1/4
FLA	0.7	0.65	0.65	0.65	0.65	0.7	1.2	1.2	1.2	1.2	1.3
REFRIGERATION SYSTEM											
Refrigerant Line Size ¹											
Liquid Line Size ("O.D.)	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Suction Line Size ("O.D.)	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	7/8"	1 1/8"	1 1/8"	1 1/8"	7/8"
Refrigerant Connection Size											
Liquid Valve Size ("O.D.)	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Suction Valve Size ("O.D.) ^{4 5}	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4" ⁴	7/8" ⁵	7/8" ⁵	7/8" ⁵	3/4"
Valve Type	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat	Sweat
Refrigerant Charge	44	58	58	60	60	68	62	80	91	94	111
Shipped with Orifice Size	0.051	0.051	0.051	0.055	0.061	0.067	0.070	0.076	0.080	0.086	0.086
ELECTRICAL DATA											
Voltage (60 Hz)	208/230	208/230-60	208/230-60	208/230	208/230	208/230-60	208/230	208/230	208/230	208/230	208/230
Minimum Circuit Ampacity ²	9.1	9.1	8.2	10.3	16.7	13.8	18.8	23.6	26.1	32.5	34.3
Max. Overcurrent Protection ³	15 amps	15 amps	15 amps	15 amps	25 amps	20	30 amps	40 amps	45 amps	50 amps	60 amps
Min / Max Volts	197/253	197/253	197/253	197/253	197/253	197/253	197/253	197/253	197/253	197/253	197/253
Electrical Conduit Size	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"	1/2" or 3/4"
EQUIPMENT WEIGHT (LBS)	102	102	102	103	115	138	118	171	175	184	211
SHIP WEIGHT (LBS)	117	117	117	120	132	153	135	189	193	202	233

¹ Line sizes denoted for 25' line sets, tested and rated in accordance with AHRI Standard 210/240. For other line-set lengths or sizes, refer to the installation & Operating instructions and/or the long line-set guidelines.

² Wire size should be determined in accordance with National Electrical Codes; extensive wire runs will require larger wire sizes.

³ Must use time-delay fuses or HACR-type circuit breakers of the same size as noted.

⁴ Installer will need to supply 3/4" to 7/8" adapters for suction line connections.

⁵ Installer will need to supply 7/8" to 1 1/8" adapters for suction line connections.

NOTES

- Always check the S&R plate for electrical data on the unit being installed.
- Unit is charged with refrigerant for 15' of 3/8" liquid line. System charge must be adjusted per Installation Instructions Final Charge Procedure.
- This product may not be installed in the Southeast (including Hawaii) or Southwest Regions as of Jan. 1, 2015.

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
525	MBh	15.6	16.2	17.7	-	15.3	15.8	17.3	-	14.9	15.4	16.9	-	14.5	15.1	16.5	-	13.8	14.3	15.7	-	12.8	13.3	14.5	-
	S/T	0.70	0.59	0.41	-	0.73	0.61	0.42	-	0.75	0.62	0.43	-	0.77	0.64	0.45	-	0.80	0.67	0.46	-	0.81	0.67	0.47	-
	Δ T	19.3	16.7	12.7	-	19.5	16.9	12.8	-	19.5	16.9	12.8	-	19.6	17.0	12.9	-	19.4	16.8	12.7	-	18.1	15.7	11.9	-
	kW	1.02	1.04	1.08	-	1.11	1.13	1.17	-	1.18	1.21	1.25	-	1.25	1.28	1.32	-	1.30	1.33	1.38	-	1.35	1.38	1.43	-
	Amps	4.3	4.4	4.5	-	4.6	4.7	4.9	-	5.0	5.1	5.3	-	5.4	5.5	5.7	-	5.7	5.8	6.0	-	6.0	6.2	6.4	-
	Hi PR	203	219	231	-	228	245	259	-	259	279	294	-	295	318	335	-	332	357	377	-	367	395	417	-
	Lo PR	102	109	119	-	108	115	126	-	113	120	131	-	118	126	137	-	124	132	144	-	128	136	149	-
600	MBh	16.4	17.0	18.7	-	16.0	16.6	18.2	-	15.7	16.2	17.8	-	15.3	15.8	17.4	-	14.5	15.0	16.5	-	13.4	13.9	15.3	-
	S/T	0.71	0.60	0.41	-	0.74	0.62	0.43	-	0.76	0.63	0.44	-	0.78	0.65	0.45	-	0.81	0.68	0.47	-	0.82	0.69	0.47	-
	Δ T	18.0	15.6	11.8	-	18.2	15.8	12.0	-	18.2	15.8	12.0	-	18.4	15.9	12.1	-	18.1	15.7	11.9	-	16.9	14.6	11.1	-
	kW	1.03	1.06	1.09	-	1.12	1.14	1.18	-	1.19	1.22	1.27	-	1.26	1.29	1.34	-	1.32	1.35	1.40	-	1.37	1.40	1.45	-
	Amps	4.3	4.4	4.6	-	4.7	4.8	4.9	-	5.1	5.2	5.4	-	5.4	5.6	5.7	-	5.8	5.9	6.1	-	6.1	6.3	6.5	-
	Hi PR	206	221	234	-	231	248	262	-	263	283	298	-	299	322	340	-	336	362	382	-	372	400	422	-
	Lo PR	104	110	121	-	110	117	127	-	114	121	132	-	120	127	139	-	126	134	146	-	130	138	151	-
650	MBh	16.9	17.6	19.2	-	16.5	17.1	18.8	-	16.1	16.7	18.3	-	15.8	16.3	17.9	-	15.0	15.5	17.0	-	13.9	14.4	15.7	-
	S/T	0.73	0.61	0.42	-	0.76	0.63	0.44	-	0.78	0.65	0.45	-	0.80	0.67	0.46	-	0.83	0.69	0.48	-	0.84	0.70	0.48	-
	Δ T	17.5	15.1	11.5	-	17.7	15.3	11.6	-	17.7	15.3	11.6	-	17.8	15.4	11.7	-	17.6	15.2	11.6	-	16.4	14.2	10.8	-
	kW	1.05	1.07	1.11	-	1.14	1.16	1.20	-	1.21	1.24	1.29	-	1.28	1.31	1.36	-	1.34	1.37	1.42	-	1.39	1.42	1.47	-
	Amps	4.4	4.5	4.6	-	4.7	4.9	5.0	-	5.2	5.3	5.5	-	5.5	5.6	5.8	-	5.9	6.0	6.2	-	6.2	6.4	6.6	-
	Hi PR	209	225	238	-	235	253	267	-	267	287	304	-	304	327	346	-	342	368	389	-	378	407	430	-
	Lo PR	106	112	123	-	112	119	130	-	116	123	135	-	122	130	142	-	128	136	148	-	132	141	153	-

		OUTDOOR AMBIENT TEMPERATURE																105°F				
		65°F								75°F								95°F				
		85°F																105°F				
	MBh	15.9	16.4	17.7	19.0	15.5	16.0	17.3	18.6	15.2	15.6	16.9	18.1	14.8	15.2	16.5	17.7	14.0	14.5	15.7	16.8	
525	S/T	0.80	0.72	0.54	0.35	0.83	0.74	0.56	0.36	0.85	0.76	0.58	0.37	0.88	0.78	0.59	0.38	0.91	0.81	0.62	0.40	
	Δ T	22.3	20.5	16.8	11.6	22.5	20.7	17.0	11.7	22.6	20.8	17.0	11.7	22.7	20.9	17.1	11.8	22.4	20.6	16.9	11.7	
	kW	1.03	1.05	1.09	1.13	1.12	1.14	1.18	1.22	1.19	1.22	1.26	1.31	1.26	1.29	1.33	1.38	1.32	1.35	1.39	1.44	
	Amps	4.3	4.4	4.6	4.7	4.7	4.8	4.9	5.1	5.1	5.2	5.4	5.6	5.4	5.5	5.7	5.9	5.8	5.9	6.1	6.3	
	Hi PR	205	221	233	243	230	248	262	273	262	282	297	310	298	321	339	353	335	361	381	398	
	Lo PR	104	110	120	128	109	116	127	135	114	121	132	141	119	127	139	148	125	133	145	155	
		MBh	16.7	17.2	18.6	20.0	16.3	16.8	18.2	19.5	15.9	16.4	17.8	19.1	15.5	16.0	17.3	18.6	14.8	15.2	16.5	17.7
600	S/T	0.81	0.73	0.55	0.35	0.84	0.75	0.57	0.37	0.86	0.77	0.58	0.38	0.89	0.80	0.60	0.39	0.92	0.83	0.63	0.40	
	Δ T	20.8	19.1	15.7	10.8	21.0	19.4	15.9	11.0	21.1	19.4	15.9	11.0	21.2	19.5	16.0	11.1	20.9	19.3	15.8	10.9	
	kW	1.04	1.07	1.10	1.14	1.13	1.16	1.20	1.24	1.21	1.23	1.28	1.32	1.27	1.30	1.35	1.40	1.33	1.36	1.41	1.46	
	Amps	4.4	4.5	4.6	4.8	4.7	4.8	5.0	5.2	5.1	5.2	5.4	5.6	5.5	5.6	5.8	6.0	5.8	6.0	6.2	6.4	
	Hi PR	208	224	236	246	233	251	265	276	265	285	301	314	302	325	343	358	340	366	386	403	
	Lo PR	105	112	122	130	111	118	129	137	115	123	134	142	121	129	141	150	127	135	147	157	
		MBh	17.2	17.7	19.2	20.6	16.8	17.3	18.7	20.1	16.4	16.9	18.3	19.6	16.0	16.5	17.9	19.2	15.2	15.7	17.0	18.2
650	S/T	0.83	0.74	0.56	0.36	0.86	0.77	0.58	0.37	0.88	0.79	0.60	0.38	0.91	0.81	0.62	0.40	0.94	0.84	0.64	0.41	
	Δ T	20.2	18.6	15.2	10.5	20.4	18.8	15.4	10.7	20.5	18.8	15.4	10.7	20.6	19.0	15.5	10.7	20.3	18.7	15.3	10.6	
	kW	1.06	1.08	1.12	1.16	1.15	1.17	1.21	1.26	1.22	1.25	1.30	1.34	1.29	1.32	1.37	1.42	1.35	1.38	1.43	1.48	
	Amps	4.4	4.5	4.7	4.9	4.8	4.9	5.1	5.3	5.2	5.3	5.5	5.7	5.6	5.7	5.9	6.1	5.9	6.1	6.3	6.5	
	Hi PR	211	228	240	251	237	255	270	281	270	290	307	320	307	331	349	364	346	372	393	410	
	Lo PR	107	114	124	132	113	120	131	139	117	125	136	145	123	131	143	152	129	137	150	160	

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																														
				65°F					75°F					85°F					95°F					105°F					115°F					
				ENTERING INDOOR WET BULB TEMPERATURE																														
59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71			
525	MBh	16.2	16.5	17.7	18.9	15.8	16.1	17.3	18.4	15.4	15.8	16.8	18.0	15.0	15.4	16.4	17.6	14.3	14.6	15.6	16.7	13.2	13.5	14.5	15.5	13.2	13.5	14.5	15.5	13.2	13.5	14.5	15.5	
	S/T	0.88	0.82	0.67	0.50	0.91	0.85	0.69	0.52	0.93	0.87	0.71	0.53	0.96	0.90	0.73	0.55	1.00	0.94	0.76	0.57	1.01	0.94	0.77	0.57	1.01	0.94	0.77	0.57	1.01	0.94	0.77	0.57	
	Δ T	24.8	23.8	20.7	16.5	25.2	24.1	21.0	16.7	25.2	24.1	21.0	16.8	25.4	24.3	21.1	16.9	25.0	24.0	20.8	16.6	23.4	22.4	19.5	15.5	23.4	22.4	19.5	15.5	23.4	22.4	19.5	15.5	
	kW	1.04	1.06	1.10	1.14	1.13	1.15	1.19	1.23	1.23	1.20	1.23	1.27	1.32	1.27	1.30	1.35	1.39	1.33	1.36	1.41	1.46	1.38	1.41	1.46	1.51	1.38	1.41	1.46	1.51	1.38	1.41	1.46	1.51
	Amps	4.3	4.4	4.6	4.8	4.7	4.8	5.0	5.2	5.1	5.2	5.4	5.6	5.5	5.6	5.8	6.0	5.8	6.0	6.2	6.4	6.2	6.3	6.5	6.8	6.2	6.3	6.5	6.8	6.2	6.3	6.5	6.8	
600	Hi PR	207	223	235	246	232	250	264	276	264	285	300	313	301	324	342	357	339	365	385	402	374	403	425	444	374	403	425	444	374	403	425	444	
	Lo PR	105	111	121	129	110	118	128	137	115	122	133	142	121	128	140	149	126	134	147	156	131	139	152	162	131	139	152	162	131	139	152	162	
	MBh	17.0	17.4	18.6	19.8	16.6	17.0	18.1	19.4	16.2	16.6	17.7	18.9	15.8	16.2	17.3	18.5	15.0	15.4	16.4	17.5	13.9	14.2	15.2	16.2	13.9	14.2	15.2	16.2	13.9	14.2	15.2	16.2	
	S/T	0.89	0.84	0.68	0.51	0.92	0.87	0.70	0.53	0.95	0.89	0.72	0.54	0.98	0.92	0.75	0.56	1.00	0.95	0.77	0.58	1.00	0.96	0.78	0.58	1.00	0.96	0.78	0.58	1.00	0.96	0.78	0.58	
	Δ T	23.2	22.2	19.3	15.5	23.5	22.5	19.6	15.6	23.5	22.5	19.6	15.7	23.7	22.7	19.7	15.8	23.0	22.4	19.5	15.5	21.3	20.9	18.2	14.5	21.3	20.9	18.2	14.5	21.3	20.9	18.2	14.5	
650	kW	1.05	1.08	1.11	1.15	1.14	1.17	1.21	1.25	1.22	1.25	1.29	1.33	1.28	1.32	1.36	1.41	1.34	1.38	1.42	1.48	1.39	1.43	1.48	1.53	1.39	1.43	1.48	1.53	1.39	1.43	1.48	1.53	
	Amps	4.4	4.5	4.7	4.8	4.8	4.9	5.0	5.2	5.2	5.3	5.5	5.7	5.5	5.7	5.9	6.1	5.9	6.0	6.2	6.5	6.2	6.4	6.6	6.9	6.2	6.4	6.6	6.9	6.2	6.4	6.6	6.9	
	Hi PR	210	226	239	249	236	254	268	279	268	288	304	318	305	328	347	362	343	369	390	407	379	408	431	450	379	408	431	450	379	408	431	450	
	Lo PR	106	113	123	131	112	119	130	138	116	124	135	144	122	130	142	151	128	136	149	158	132	141	154	164	132	141	154	164	132	141	154	164	
	MBh	17.5	17.9	19.1	20.5	17.1	17.5	18.7	20.0	16.7	17.1	18.2	19.5	16.3	16.7	17.8	19.0	15.5	15.8	16.9	18.1	14.3	14.7	15.7	16.7	14.3	14.7	15.7	16.7	14.3	14.7	15.7	16.7	
80	S/T	0.91	0.85	0.69	0.52	0.94	0.88	0.72	0.54	0.97	0.91	0.74	0.55	1.00	0.94	0.76	0.57	1.00	0.94	0.79	0.59	1.00	1.00	0.80	0.60	1.00	1.00	0.80	0.60	1.00	1.00	0.80	0.60	
	Δ T	22.5	21.6	18.8	15.0	22.8	21.9	19.0	15.2	22.8	21.9	19.0	15.2	23.1	22.0	19.2	15.3	21.9	22.4	18.9	15.1	20.3	20.7	17.7	14.1	20.3	20.7	17.7	14.1	20.3	20.7	17.7	14.1	
	kW	1.07	1.09	1.13	1.17	1.16	1.18	1.22	1.27	1.24	1.26	1.31	1.36	1.30	1.34	1.38	1.43	1.36	1.40	1.45	1.50	1.42	1.45	1.50	1.55	1.42	1.45	1.50	1.55	1.42	1.45	1.50	1.55	
	Amps	4.5	4.6	4.7	4.9	4.8	4.9	5.1	5.3	5.2	5.4	5.6	5.8	5.6	5.8	5.9	6.2	6.0	6.1	6.3	6.6	6.3	6.5	6.7	7.0	6.3	6.5	6.7	7.0	6.3	6.5	6.7	7.0	
	Hi PR	214	230	243	253	240	258	272	284	273	293	310	323	310	334	353	368	349	376	397	414	386	415	439	457	386	415	439	457	386	415	439	457	
80	Lo PR	108	115	125	133	114	121	132	141	118	126	137	146	124	132	144	154	130	139	151	161	135	143	157	167	135	143	157	167	135	143	157	167	

525	MBh	16.5	16.8	17.6	18.7	16.1	16.4	17.2	18.3	15.7	16.0	16.8	17.9	15.3	15.6	16.3	17.4	14.5	14.8	15.5	16.6	13.5	13.7	14.4	15.3
	S/T	0.92	0.89	0.80	0.65	0.95	0.92	0.83	0.67	0.98	0.94	0.85	0.69	1.00	0.97	0.88	0.71	1.00	1.00	0.91	0.74	1.00	1.00	0.92	0.75
	Δ T	26.5	26.1	24.6	21.3	26.8	26.4	24.9	21.6	26.9	26.4	25.0	21.6	26.8	26.6	25.1	21.8	25.5	26.0	24.8	21.5	23.6	24.1	23.2	20.0
	kW	1.05	1.07	1.11	1.15	1.14	1.16	1.20	1.24	1.21	1.24	1.28	1.33	1.28	1.31	1.36	1.41	1.34	1.37	1.42	1.47	1.39	1.42	1.47	1.53
	Amps	4.4	4.5	4.6	4.8	4.7	4.9	5.0	5.2	5.2	5.3	5.5	5.7	5.5	5.6	5.8	6.1	5.9	6.0	6.2	6.4	6.2	6.4	6.6	6.8
600	Hi PR	209	225	238	248	235	253	267	278	267	287	303	317	304	327	346	361	342	368	389	406	378	407	430	448
	LoPR	106	112	123	131	112	119	130	138	116	123	135	143	122	130	141	151	128	136	148	158	132	140	153	163
	MBh	17.3	17.6	18.5	19.7	16.9	17.2	18.0	19.2	16.5	16.8	17.6	18.8	16.1	16.4	17.2	18.3	15.3	15.6	16.3	17.4	14.2	14.4	15.1	16.1
	S/T	0.93	0.90	0.81	0.66	0.97	0.93	0.84	0.68	0.99	0.96	0.86	0.70	1.00	0.99	0.89	0.72	1.00	1.00	0.93	0.75	1.00	1.00	0.93	0.76
	Δ T	24.8	24.3	23.0	19.9	25.1	24.6	23.3	20.2	25.1	24.7	23.3	20.2	24.7	24.8	23.5	20.3	23.4	23.9	23.2	20.0	21.7	22.1	21.6	18.7
650	kW	1.06	1.08	1.12	1.16	1.15	1.18	1.22	1.26	1.23	1.26	1.30	1.35	1.30	1.33	1.37	1.42	1.36	1.39	1.44	1.49	1.41	1.44	1.49	1.54
	Amps	4.4	4.5	4.7	4.9	4.8	4.9	5.1	5.3	5.2	5.3	5.5	5.7	5.6	5.7	5.9	6.1	5.9	6.1	6.3	6.5	6.3	6.4	6.7	6.9
	Hi PR	212	228	241	251	238	256	270	282	271	291	308	321	308	332	350	365	347	373	394	411	383	412	435	454
	LoPR	107	114	124	132	113	120	131	140	118	125	136	145	123	131	143	153	129	138	150	160	134	142	155	166
	MBh	17.8	18.2	19.0	20.3	17.4	17.8	18.6	19.8	17.0	17.3	18.2	19.4	16.6	16.9	17.7	18.9	15.8	16.1	16.8	18.0	14.6	14.9	15.6	16.6
600	S/T	0.95	0.92	0.83	0.67	0.99	0.95	0.86	0.70	1.00	0.98	0.88	0.72	1.00	1.00	0.91	0.74	1.00	1.00	0.95	0.77	1.00	1.00	0.95	0.77
	Δ T	24.1	23.7	22.4	19.4	24.3	23.9	22.6	19.6	24.1	24.0	22.7	19.6	23.5	23.9	22.8	19.7	22.3	22.7	22.5	19.5	20.6	21.0	21.0	18.2
	kW	1.08	1.10	1.14	1.18	1.17	1.19	1.23	1.28	1.25	1.28	1.32	1.37	1.32	1.35	1.40	1.45	1.38	1.41	1.46	1.51	1.43	1.46	1.51	1.57
	Amps	4.5	4.6	4.8	4.9	4.9	5.0	5.2	5.4	5.3	5.4	5.6	5.8	5.7	5.8	6.0	6.2	6.0	6.2	6.4	6.6	6.4	6.6	6.7	7.0
	Hi PR	216	232	245	256	242	261	275	287	275	296	313	326	314	337	356	372	353	380	401	418	390	419	443	462
600	LoPR	109	116	126	135	115	122	134	142	120	127	139	148	126	134	146	155	132	140	153	163	136	145	158	168

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																			
				65°F						75°F						85°F						95°F						105°F						115°F					
				ENTERING INDOOR WET BULB TEMPERATURE																																			
900	MBh	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71										
	S/T	0.73	0.61	0.42	-	0.76	0.63	0.44	-	0.78	0.65	0.45	-	0.80	0.67	0.46	-	0.83	0.69	0.48	-	0.84	0.70	0.49	-	0.84	0.70	0.49	-										
	ΔT	17	15	11	-	17	15	11	-	17	15	11	-	17	15	11	-	17	15	11	-	16	14	10	-	16	14	10	-										
	kW	1.63	1.66	1.71	-	1.75	1.78	1.83	-	1.85	1.89	1.95	-	1.94	1.98	2.04	-	2.02	2.06	2.13	-	2.09	2.13	2.20	-	2.09	2.13	2.20	-										
	Amps	5.8	6.0	6.2	-	6.3	6.4	6.7	-	6.8	7.0	7.2	-	7.3	7.5	7.7	-	7.8	8.0	8.2	-	8.2	8.4	8.7	-	8.2	8.4	8.7	-										
70	Hi PR	228	246	259	-	256	276	291	-	291	314	331	-	332	357	377	-	373	402	424	-	413	444	469	-	413	444	469	-										
	Lo PR	105	112	122	-	111	118	129	-	115	123	134	-	121	129	141	-	127	135	147	-	131	140	152	-	131	140	152	-										
	MBh	21.9	22.7	24.8	-	21.4	22.2	24.3	-	20.9	21.6	23.7	-	20.4	21.1	23.1	-	19.3	20.0	22.0	-	17.9	18.6	20.3	-	17.9	18.6	20.3	-										
	S/T	0.70	0.58	0.40	-	0.72	0.60	0.42	-	0.74	0.62	0.43	-	0.76	0.64	0.44	-	0.79	0.66	0.46	-	0.80	0.67	0.46	-	0.80	0.67	0.46	-										
	ΔT	18	15	12	-	18	15	12	-	18	15	12	-	18	15	12	-	18	15	12	-	16	14	11	-	16	14	11	-										
800	kW	1.62	1.65	1.70	-	1.73	1.77	1.82	-	1.84	1.87	1.93	-	1.93	1.97	2.03	-	2.00	2.05	2.11	-	2.07	2.11	2.18	-	2.07	2.11	2.18	-										
	Amps	5.8	5.9	6.1	-	6.2	6.4	6.6	-	6.8	6.9	7.2	-	7.2	7.4	7.7	-	7.7	7.9	8.1	-	8.2	8.4	8.6	-	8.2	8.4	8.6	-										
	Hi PR	226	243	257	-	254	273	288	-	288	310	328	-	329	354	373	-	370	398	420	-	408	440	464	-	408	440	464	-										
	Lo PR	104	111	121	-	110	117	127	-	114	121	132	-	120	127	139	-	126	134	146	-	130	138	151	-	130	138	151	-										
	MBh	20.2	20.9	22.9	-	19.7	20.4	22.4	-	19.3	20.0	21.9	-	18.8	19.5	21.3	-	17.8	18.5	20.3	-	16.5	17.1	18.8	-	16.5	17.1	18.8	-										
700	S/T	0.67	0.56	0.39	-	0.70	0.58	0.40	-	0.71	0.60	0.41	-	0.74	0.62	0.43	-	0.76	0.64	0.44	-	0.77	0.64	0.45	-	0.77	0.64	0.45	-										
	ΔT	18	15	12	-	18	16	12	-	18	16	12	-	18	16	12	-	18	16	12	-	17	14	11	-	17	14	11	-										
	kW	1.58	1.61	1.66	-	1.69	1.73	1.78	-	1.79	1.83	1.89	-	1.88	1.92	1.98	-	1.96	2.00	2.06	-	2.02	2.06	2.13	-	2.02	2.06	2.13	-										
	Amps	5.6	5.7	5.9	-	6.1	6.2	6.4	-	6.6	6.7	7.0	-	7.0	7.2	7.4	-	7.5	7.7	7.9	-	7.9	8.1	8.4	-	7.9	8.1	8.4	-										
	Hi PR	219	236	249	-	246	265	280	-	280	301	318	-	319	343	362	-	359	386	407	-	396	426	450	-	396	426	450	-										
Lo PR	101	107	117	-	106	113	124	-	111	118	129	-	116	124	135	-	122	130	141	-	126	134	146	-	126	134	146	-											

900	MBh	22.9	23.6	25.5	27.4	22.4	23.0	24.9	26.8	21.9	22.5	24.4	26.1	21.3	22.0	23.8	25.5	20.3	20.9	22.6	24.2	18.8	19.3	20.9	22.4
	S/T	0.83	0.74	0.56	0.36	0.86	0.77	0.58	0.37	0.88	0.79	0.60	0.38	0.91	0.81	0.62	0.40	0.95	0.85	0.64	0.41	0.95	0.85	0.65	0.42
	ΔT	19	18	15	10	20	18	15	10	20	18	15	10	20	18	15	10	20	18	15	10	18	17	14	10
	kW	1.64	1.67	1.72	1.77	1.76	1.79	1.85	1.91	1.86	1.90	1.96	2.02	1.96	2.00	2.06	2.13	2.04	2.08	2.15	2.21	2.10	2.15	2.22	2.29
	Amps	5.9	6.0	6.2	6.4	6.3	6.5	6.7	7.0	6.9	7.1	7.3	7.6	7.4	7.5	7.8	8.1	7.8	8.0	8.3	8.6	8.3	8.5	8.8	9.1
800	Hi PR	231	248	262	273	259	279	294	307	294	317	334	349	335	361	381	397	377	406	429	447	417	448	474	494
	Lo PR	106	113	123	131	112	119	130	139	116	124	135	144	122	130	142	151	128	136	149	158	133	141	154	164
	MBh	22.3	22.9	24.8	26.6	21.7	22.4	24.2	26.0	21.2	21.8	23.6	25.4	20.7	21.3	23.1	24.8	19.7	20.2	21.9	23.5	18.2	18.8	20.3	21.8
	S/T	0.79	0.71	0.54	0.34	0.82	0.73	0.56	0.36	0.84	0.75	0.57	0.37	0.87	0.78	0.59	0.38	0.90	0.81	0.61	0.39	0.91	0.81	0.62	0.40
	ΔT	20	19	15	11	20	19	15	11	21	19	15	11	21	19	16	11	20	19	15	11	19	18	14	10
700	kW	1.63	1.66	1.71	1.76	1.75	1.78	1.84	1.89	1.85	1.89	1.95	2.01	1.94	1.98	2.04	2.11	2.02	2.06	2.13	2.20	2.09	2.13	2.20	2.27
	Amps	5.8	6.0	6.2	6.4	6.3	6.4	6.7	6.9	6.8	7.0	7.2	7.5	7.3	7.5	7.7	8.0	7.8	8.0	8.2	8.5	8.2	8.4	8.7	9.1
	Hi PR	228	246	260	271	256	276	291	304	291	314	331	345	332	357	377	393	373	402	424	443	413	444	469	489
	Lo PR	105	112	122	130	111	118	129	137	115	123	134	143	121	129	141	150	127	135	147	157	131	140	152	162
	MBh	20.5	21.1	22.9	24.6	20.1	20.7	22.4	24.0	19.6	20.2	21.8	23.4	19.1	19.7	21.3	22.9	18.2	18.7	20.2	21.7	16.8	17.3	18.7	20.1
75	S/T	0.76	0.68	0.52	0.33	0.79	0.71	0.54	0.34	0.81	0.73	0.55	0.35	0.84	0.75	0.57	0.36	0.87	0.78	0.59	0.38	0.88	0.78	0.59	0.38
	ΔT	21	19	16	11	21	19	16	11	21	19	16	11	21	19	16	11	21	19	16	11	19	18	15	10
	kW	1.59	1.62	1.67	1.72	1.71	1.74	1.79	1.85	1.81	1.84	1.90	1.96	1.90	1.94	2.00	2.06	1.97	2.01	2.08	2.14	2.04	2.08	2.15	2.22
	Amps	5.7	5.8	6.0	6.2	6.1	6.3	6.5	6.7	6.6	6.8	7.0	7.3	7.1	7.3	7.5	7.8	7.6	7.7	8.0	8.3	8.0	8.2	8.5	8.8
	Hi PR	222	238	252	263	249	267	282	295	283	304	321	335	322	346	366	382	362	390	412	429	400	431	455	474
75	Lo PR	102	108	118	126	108	114	125	133	112	119	130	138	117	125	136	145	123	131	143	152	127	135	148	157

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																			
				65°F						75°F						85°F						95°F						105°F						115°F					
				59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71								
900	MBh	23.3	23.8	25.5	27.2	22.8	23.3	24.9	26.6	22.2	22.7	24.3	26.0	21.7	22.2	23.7	25.3	20.6	21.1	22.5	24.1	19.1	19.5	20.8	22.3	19.1	19.5	20.8	22.3										
	S/T	0.91	0.85	0.69	0.52	0.94	0.88	0.72	0.54	0.97	0.91	0.74	0.55	1.00	0.94	0.76	0.57	1.00	1.00	0.79	0.59	1.00	1.00	0.80	0.60	1.00	1.00	0.80	0.60										
	ΔT	22	21	18	14	22	21	18	15	22	21	18	15	22	21	18	15	21	22	18	15	20	20	17	14	20	20	17	14										
	kW	1.65	1.69	1.74	1.79	1.77	1.81	1.86	1.92	1.88	1.92	1.98	2.04	1.97	2.01	2.08	2.14	2.05	2.10	2.16	2.23	2.12	2.17	2.24	2.31	2.12	2.17	2.24	2.31										
	Amps	5.9	6.1	6.3	6.5	6.4	6.6	6.8	7.0	7.0	7.1	7.4	7.6	7.4	7.6	7.9	8.2	7.9	8.1	8.4	8.7	8.4	8.6	8.9	9.2	8.4	8.6	8.9	9.2										
	Hi PR	233	251	265	276	261	281	297	310	297	320	338	352	339	364	385	401	381	410	433	452	421	453	478	499	421	453	478	499										
80	LoPR	107	114	124	132	113	120	131	140	118	125	137	145	123	131	143	153	129	138	150	160	134	142	155	166	134	142	155	166										
	MBh	22.6	23.1	24.7	26.4	22.1	22.6	24.2	25.8	21.6	22.1	23.6	25.2	21.1	21.5	23.0	24.6	20.0	20.5	21.9	23.4	18.5	18.9	20.2	21.6	18.5	18.9	20.2	21.6										
	S/T	0.87	0.81	0.66	0.50	0.90	0.84	0.69	0.51	0.92	0.87	0.70	0.53	0.95	0.89	0.73	0.54	0.99	0.93	0.75	0.56	1.00	0.93	0.76	0.57	1.00	0.93	0.76	0.57										
	ΔT	23	22	19	15	23	22	19	15	23	22	19	15	23	22	19	15	23	22	19	15	21	20	18	14	21	20	18	14										
	kW	1.64	1.67	1.72	1.78	1.76	1.79	1.85	1.91	1.86	1.90	1.96	2.02	1.96	2.00	2.06	2.13	2.04	2.08	2.15	2.21	2.10	2.15	2.22	2.29	2.10	2.15	2.22	2.29										
	Amps	5.9	6.0	6.2	6.4	6.3	6.5	6.7	7.0	6.9	7.1	7.3	7.6	7.4	7.5	7.8	8.1	7.8	8.0	8.3	8.6	8.3	8.5	8.8	9.1	8.3	8.5	8.8	9.1										
700	Hi PR	231	248	262	273	259	279	294	307	294	317	335	349	335	361	381	397	377	406	429	447	417	448	474	494	417	448	474	494										
	LoPR	106	113	123	131	112	119	130	139	116	124	135	144	122	130	142	151	128	136	149	158	133	141	154	164	133	141	154	164										
	MBh	20.9	21.4	22.8	24.4	20.4	20.9	22.3	23.8	19.9	20.4	21.8	23.3	19.4	19.9	21.2	22.7	18.5	18.9	20.2	21.6	17.1	17.5	18.7	20.0	17.1	17.5	18.7	20.0										
	S/T	0.84	0.79	0.64	0.48	0.87	0.81	0.66	0.50	0.89	0.83	0.68	0.51	0.92	0.86	0.70	0.52	0.95	0.89	0.73	0.54	0.96	0.90	0.73	0.55	0.96	0.90	0.73	0.55										
	ΔT	23	22	19	15	23	22	19	15	23	22	19	15	23	22	19	15	23	22	19	15	22	21	18	14	22	21	18	14										
	kW	1.60	1.63	1.68	1.73	1.72	1.75	1.81	1.86	1.82	1.86	1.92	1.98	1.91	1.95	2.01	2.08	1.99	2.03	2.09	2.16	2.05	2.10	2.16	2.23	2.05	2.10	2.16	2.23										
85	Amps	5.7	5.9	6.0	6.3	6.2	6.3	6.5	6.8	6.7	6.9	7.1	7.4	7.2	7.3	7.6	7.9	7.6	7.8	8.1	8.4	8.1	8.3	8.6	8.9	8.1	8.3	8.6	8.9										
	Hi PR	224	241	254	265	251	270	285	298	286	307	324	338	325	350	370	385	366	394	416	434	404	435	459	479	404	435	459	479										
	LoPR	103	109	119	127	109	116	126	134	113	120	131	140	119	126	138	147	124	132	144	154	129	137	149	159	129	137	149	159										
	MBh	23.7	24.2	25.3	27.0	23.2	23.6	24.8	26.4	22.6	23.1	24.2	25.8	22.1	22.5	23.6	25.1	21.0	21.4	22.4	23.9	19.4	19.8	20.7	22.1	19.4	19.8	20.7	22.1										
	S/T	0.95	0.92	0.83	0.67	0.99	0.95	0.86	0.70	1.00	0.98	0.88	0.72	1.00	1.00	0.91	0.74	1.00	1.00	0.95	0.77	1.00	1.00	0.95	0.77	1.00	1.00	0.95	0.77										
	ΔT	23	23	22	19	23	23	22	19	23	23	22	19	23	23	22	19	21	22	22	19	20	20	20	17	21	22	20	17										
900	kW	1.66	1.70	1.75	1.80	1.79	1.82	1.88	1.94	1.89	1.93	1.99	2.06	1.99	2.03	2.09	2.16	2.07	2.11	2.18	2.25	2.14	2.18	2.25	2.33	2.14	2.18	2.25	2.33										
	Amps	6.0	6.1	6.3	6.6	6.5	6.6	6.8	7.1	7.0	7.2	7.4	7.7	7.5	7.7	7.9	8.2	8.0	8.2	8.5	8.8	8.5	8.7	9.0	9.3	8.5	8.7	9.0	9.3										
	Hi PR	235	253	267	279	264	284	300	313	300	323	341	356	342	368	389	405	385	414	437	456	425	457	483	504	425	457	483	504										
	LoPR	108	115	126	134	114	122	133	141	119	126	138	147	125	133	145	154	131	139	152	162	135	144	157	167	135	144	157	167										
	MBh	23.0	23.5	24.6	26.2	22.5	22.9	24.0	25.6	22.0	22.4	23.5	25.0	21.4	21.9	22.9	24.4	20.4	20.8	21.7	23.2	18.9	19.2	20.1	21.5	18.9	19.2	20.1	21.5										
	S/T	0.91	0.88	0.79	0.64	0.94	0.91	0.82	0.67	0.97	0.93	0.84	0.68	1.00	0.96	0.87	0.71	1.00	1.00	0.90	0.73	1.00	1.00	0.91	0.74	1.00	1.00	0.91	0.74										
800	ΔT	24	24	22	19	24	24	23	20	24	24	23	20	25	24	23	20	23	24	23	20	22	22	21	18	22	22	21	18										
	kW	1.65	1.69	1.74	1.79	1.77	1.81	1.86	1.92	1.88	1.92	1.98	2.04	1.97	2.01	2.08	2.14	2.05	2.10	2.16	2.23	2.12	2.17	2.24	2.31	2.12	2.17	2.24	2.31										
	Amps	5.9	6.1	6.3	6.5	6.4	6.6	6.8	7.0	7.0	7.1	7.4	7.6	7.4	7.6	7.9	8.2	7.9	8.1	8.4	8.7	8.4	8.6	8.9	9.2	8.4	8.6	8.9	9.2										
	Hi PR	233	251	265	276	261	281	297	310	297	320	338	352	339	364	385	401	381	410	433	452	421	453	478	499	421	453	478	499										
	LoPR	107	114	124	132	113	120	131	140	118	125	137	145	123	131	143	153	129	138	150	160	134	142	155	166	134	142	155	166										
	MBh	21.3	21.7	22.7	24.2	20.8	21.2	22.2	23.7	20.3	20.7	21.7	23.1	19.8	20.2	21.1	22.5	18.8	19.2	20.1	21.4	17.4	17.7	18.6	19.8	17.4	17.7	18.6	19.8										
700	S/T	0.88	0.85	0.76	0.62	0.91	0.88	0.79	0.64	0.93	0.90	0.81	0.66	0.96	0.93	0.84	0.68	1.00	0.96	0.87	0.71	1.00	0.97	0.88	0.71	1.00	0.97	0.88	0.71										
	ΔT	25	24	23	20	25	24	23	20	25	24	23	20	25	25	23	20	25	24	23	20	23	23	21	19	23	23	21	19										
	kW	1.61	1.65	1.70	1.75	1.73	1.77	1.82	1.88	1.83	1.87	1.93	1.99	1.93	1.97	2.03	2.09	2.00	2.05	2.11	2.18	2.07	2.11	2.18	2.25	2.07	2.11	2.18	2.25										
	Amps	5.8	5.9	6.1	6.3	6.2	6.4	6.6	6.8	6.8	6.9	7.2	7.4	7.2	7.4	7.7	7.9	7.7	7.9	8.1	8.5	8.2	8.4	8.6	9.0	8.2	8.4	8.6	9.0										
	Hi PR	226	243	257	268	254	273	288	301	288	310	328	342	328	353	373	389	370	398	420	438	408	439	464	484	408	439	464	484										
	LoPR	104	110	121	128	110	117	127	136	114	121	132	141	120	127	139	148	126	134	146	155	130	138	151	161	130	138	151	161										
DB: Entering Indoor Dry Bulb Temperature		Shaded area reflects AHRI conditions																												Amps = outdoor unit amps (comp.+fan)									
High and low pressures are measured at																																							

		OUTDOOR AMBIENT TEMPERATURE																																			
		65°F						75°F						85°F						95°F						105°F						115°F					
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71								
70	MBh	24.9	25.8	28.3	-	24.4	25.2	27.7	-	23.8	24.6	27.0	-	23.2	24.0	26.3	-	22.0	22.8	25.0	-	20.4	21.2	23.2	-	20.4	21.2	23.2	-								
	S/T	0.72	0.60	0.42	-	0.74	0.62	0.43	-	0.76	0.64	0.44	-	0.79	0.66	0.46	-	0.82	0.68	0.47	-	0.82	0.69	0.48	-	0.82	0.69	0.48	-								
	Δ T	19	16	12	-	19	16	13	-	19	16	13	-	19	17	13	-	19	16	12	-	18	15	12	-	18	15	12	-								
	kW	1.60	1.64	1.70	-	1.74	1.78	1.85	-	1.87	1.91	1.98	-	1.97	2.02	2.10	-	2.07	2.12	2.20	-	2.15	2.20	2.28	-	2.15	2.20	2.28	-								
	Amps	6.6	6.8	7.0	-	7.2	7.4	7.7	-	7.9	8.1	8.4	-	8.5	8.7	9.0	-	9.1	9.3	9.6	-	9.6	9.9	10.2	-	9.6	9.9	10.2	-								
1050	Hi PR	209	224	237	-	234	252	266	-	266	286	303	-	303	326	345	-	341	367	388	-	377	406	428	-	377	406	428	-								
	Lo PR	103	109	119	-	109	116	126	-	113	120	131	-	119	126	138	-	124	132	144	-	128	137	149	-	128	137	149	-								
	MBh	27.0	28.0	30.7	-	26.4	27.4	30.0	-	25.8	26.7	29.3	-	25.1	26.1	28.5	-	23.9	24.7	27.1	-	22.1	22.9	25.1	-	22.1	22.9	25.1	-								
	S/T	0.74	0.62	0.43	-	0.77	0.64	0.45	-	0.79	0.66	0.46	-	0.82	0.68	0.47	-	0.85	0.71	0.49	-	0.85	0.71	0.49	-	0.85	0.71	0.49	-								
	Δ T	18	15	12	-	18	15	12	-	18	15	12	-	18	16	12	-	18	15	12	-	17	14	11	-	17	14	11	-								
1125	kW	1.65	1.69	1.75	-	1.79	1.83	1.90	-	1.92	1.97	2.04	-	2.03	2.08	2.16	-	2.13	2.18	2.26	-	2.21	2.26	2.35	-	2.21	2.26	2.35	-								
	Amps	6.8	7.0	7.3	-	7.4	7.6	7.9	-	8.1	8.3	8.6	-	8.7	9.0	9.3	-	9.3	9.6	9.9	-	9.9	10.2	10.6	-	9.9	10.2	10.6	-								
	Hi PR	215	231	244	-	241	260	274	-	274	295	312	-	313	336	355	-	352	378	400	-	389	418	442	-	389	418	442	-								
	Lo PR	106	113	123	-	112	119	130	-	116	124	135	-	122	130	142	-	128	136	149	-	132	141	154	-	132	141	154	-								
	MBh	27.3	28.3	31.0	-	26.7	27.6	30.3	-	26.0	27.0	29.5	-	25.4	26.3	28.8	-	24.1	25.0	27.4	-	22.3	23.2	25.4	-	22.3	23.2	25.4	-								
875	S/T	0.76	0.63	0.44	-	0.79	0.66	0.45	-	0.81	0.67	0.47	-	0.83	0.70	0.48	-	0.86	0.72	0.50	-	0.87	0.73	0.50	-	0.87	0.73	0.50	-								
	Δ T	17	15	11	-	17	15	11	-	17	15	11	-	17	15	11	-	17	15	11	-	16	14	10	-	16	14	10	-								
	kW	1.65	1.69	1.75	-	1.80	1.84	1.91	-	1.92	1.97	2.04	-	2.04	2.09	2.16	-	2.13	2.18	2.26	-	2.21	2.27	2.35	-	2.21	2.27	2.35	-								
	Amps	6.9	7.0	7.3	-	7.5	7.7	7.9	-	8.2	8.4	8.7	-	8.8	9.0	9.3	-	9.4	9.6	10.0	-	10.0	10.2	10.6	-	10.0	10.2	10.6	-								
	Hi PR	216	232	245	-	242	260	275	-	275	296	313	-	314	337	356	-	353	380	401	-	390	419	443	-	390	419	443	-								
Lo PR	106	113	123	-	112	119	130	-	117	124	136	-	123	130	142	-	128	137	149	-	133	141	154	-	133	141	154	-									

		OUTDOOR AMBIENT TEMPERATURE																																					
		65°F						75°F						85°F						95°F						105°F						115°F							
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71		
875	MBh	25.4	26.1	28.3	30.3	24.8	25.5	27.6	29.6	24.2	24.9	26.9	28.9	23.6	24.3	26.3	28.2	22.4	23.1	25.0	26.8	20.8	21.4	23.1	24.8	20.8	21.4	23.1	24.8	20.8	21.4	23.1	24.8	20.8	21.4	23.1	24.8		
	S/T	0.82	0.73	0.55	0.36	0.85	0.76	0.57	0.37	0.87	0.78	0.59	0.38	0.89	0.80	0.61	0.39	0.93	0.83	0.63	0.40	0.94	0.84	0.63	0.41	0.94	0.84	0.63	0.41	0.94	0.84	0.63	0.41	0.94	0.84	0.63	0.41		
	ΔT	22	20	16	11	22	20	17	11	22	20	17	11	22	20	17	12	22	20	16	11	20	19	15	11	20	19	15	11	20	19	15	11	20	19	15	11		
	kW	1.62	1.66	1.72	1.78	1.76	1.80	1.87	1.93	1.88	1.93	2.00	2.07	1.99	2.04	2.12	2.19	2.09	2.14	2.22	2.30	2.17	2.22	2.30	2.39	2.17	2.22	2.30	2.39	2.17	2.22	2.30	2.39	2.17	2.22	2.30	2.39		
	Amps	6.7	6.9	7.1	7.4	7.3	7.5	7.7	8.1	8.0	8.2	8.5	8.8	8.6	8.8	9.1	9.5	9.2	9.4	9.7	10.1	9.7	10.1	10.4	10.8	9.7	10.1	10.4	10.8	9.7	10.1	10.4	10.8	9.7	10.1	10.4	10.8		
1050	Hi PR	211	227	239	250	236	254	269	280	269	289	306	319	306	330	348	363	345	371	392	408	381	410	433	451	381	410	433	451	381	410	433	451	381	410	433	451		
	LoPR	104	110	121	128	110	117	127	136	114	121	132	141	120	127	139	148	125	134	146	155	130	138	151	161	130	138	151	161	130	138	151	161	130	138	151	161		
	MBh	27.5	28.3	30.6	32.9	26.8	27.6	29.9	32.1	26.2	27.0	29.2	31.3	25.6	26.3	28.5	30.6	24.3	25.0	27.1	29.0	22.5	23.2	25.1	26.9	22.5	23.2	25.1	26.9	22.5	23.2	25.1	26.9	22.5	23.2	25.1	26.9		
	S/T	0.85	0.76	0.57	0.37	0.88	0.78	0.59	0.38	0.90	0.80	0.61	0.39	0.93	0.83	0.63	0.40	0.96	0.86	0.65	0.42	0.97	0.87	0.66	0.42	0.97	0.87	0.66	0.42	0.97	0.87	0.66	0.42	0.97	0.87	0.66	0.42		
	ΔT	20	19	15	11	21	19	16	11	21	19	16	11	21	19	16	11	20	19	15	11	19	18	14	10	19	18	14	10	19	18	14	10	19	18	14	10		
75	kW	1.66	1.70	1.76	1.83	1.81	1.85	1.92	1.99	1.94	1.98	2.06	2.13	2.05	2.10	2.18	2.26	2.15	2.20	2.28	2.36	2.23	2.28	2.37	2.46	2.23	2.28	2.37	2.46	2.23	2.28	2.37	2.46	2.23	2.28	2.37	2.46		
	Amps	6.9	7.1	7.3	7.6	7.5	7.7	8.0	8.3	8.2	8.4	8.7	9.1	8.8	9.1	9.4	9.8	9.4	9.7	10.0	10.4	10.0	10.3	10.7	11.1	10.0	10.3	10.7	11.1	10.0	10.3	10.7	11.1	10.0	10.3	10.7	11.1		
	Hi PR	217	234	247	257	244	262	277	289	277	298	315	329	316	340	359	374	355	382	404	421	393	422	446	465	393	422	446	465	393	422	446	465	393	422	446	465		
	LoPR	107	114	124	132	113	120	131	140	118	125	136	145	123	131	143	153	129	138	150	160	134	142	155	166	134	142	155	166	134	142	155	166	134	142	155	166		
	1125	MBh	27.8	28.6	30.9	33.2	27.1	27.9	30.2	32.4	26.5	27.2	29.5	31.6	25.8	26.6	28.8	30.9	24.5	25.3	27.3	29.3	22.7	23.4	25.3	27.2	22.7	23.4	25.3	27.2	22.7	23.4	25.3	27.2	22.7	23.4	25.3	27.2	
S/T		0.86	0.77	0.58	0.38	0.89	0.80	0.61	0.39	0.92	0.82	0.62	0.40	0.95	0.85	0.64	0.41	0.98	0.88	0.66	0.43	0.99	0.89	0.67	0.43	0.99	0.89	0.67	0.43	0.99	0.89	0.67	0.43	0.99	0.89	0.67	0.43		
ΔT		20	18	15	10	20	18	15	10	20	18	15	10	20	18	15	10	20	18	15	10	18	17	14	10	18	17	14	10	18	17	14	10	18	17	14	10		
kW		1.67	1.71	1.77	1.83	1.81	1.86	1.92	1.99	1.94	1.99	2.06	2.14	2.06	2.11	2.18	2.26	2.15	2.21	2.29	2.37	2.24	2.29	2.37	2.46	2.24	2.29	2.37	2.46	2.24	2.29	2.37	2.46	2.24	2.29	2.37	2.46		
Amps		6.9	7.1	7.4	7.7	7.5	7.7	8.0	8.3	8.2	8.5	8.8	9.1	8.9	9.1	9.4	9.8	9.5	9.7	10.1	10.5	10.1	10.3	10.7	11.1	10.1	10.3	10.7	11.1	10.1	10.3	10.7	11.1	10.1	10.3	10.7	11.1		
75	Hi PR	218	234	248	258	245	263	278	290	278	299	316	330	317	341	360	375	356	383	405	422	394	424	447	467	394	424	447	467	394	424	447	467	394	424	447	467		
	LoPR	107	114	125	133	113	121	132	140	118	125	137	146	124	132	144	153	130	138	151	161	134	143	156	166	134	143	156	166	134	143	156	166	134	143	156	166		

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
80	Mbh	25.8	26.4	28.2	30.1	25.2	25.8	27.5	29.4	24.6	25.1	26.9	28.7	24.0	24.5	26.2	28.0	22.8	23.3	24.9	26.6	21.1	21.6	23.1	24.7
	S/T	0.89	0.84	0.68	0.5	0.93	0.87	0.71	0.53	0.95	0.89	0.73	0.5	0.98	0.92	0.75	0.56	1.02	0.96	0.78	0.6	1.03	0.96	0.78	0.59
	ΔT	24	23	20	16	25	24	20	16	25	24	20	16	25	24	21	16	24	23	20	16	23	22	19	15
	kW	1.63	1.67	1.73	1.8	1.77	1.82	1.88	1.95	1.90	1.95	2.02	2.1	2.01	2.06	2.14	2.21	2.11	2.16	2.24	2.3	2.19	2.24	2.32	2.41
	Amps	6.8	6.9	7.2	7.5	7.4	7.6	7.8	8.1	8.1	8.3	8.6	8.9	8.7	8.9	9.2	9.6	9.2	9.5	9.8	10.2	9.8	10.1	10.5	10.9
	Hi PR	213	229	242	252.3	239	257	271	283	272	292	309	322.0	309	333	352	367	348	375	396	412.5	385	414	437	456
1050	Lo PR	105	112	122	129.7	111	118	129	137	115	123	134	142.4	121	129	140	150	127	135	147	156.8	131	139	152	162
	Mbh	28.0	28.6	30.5	32.6	27.3	27.9	29.8	31.9	26.7	27.2	29.1	31.1	26.0	26.6	28.4	30.4	24.7	25.3	27.0	28.8	22.9	23.4	25.0	26.7
	S/T	0.93	0.87	0.71	0.5	0.96	0.90	0.73	0.55	0.99	0.92	0.75	0.6	1.00	0.95	0.78	0.58	1.00	0.99	0.81	0.6	1.00	1.00	0.81	0.61
	ΔT	23	22	19	15	23	22	19	15	23	22	19	15	23	22	19	15	22	22	19	15	20	20	18	14
	kW	1.68	1.72	1.78	1.8	1.82	1.87	1.94	2.01	1.95	2.00	2.07	2.2	2.07	2.12	2.20	2.28	2.17	2.22	2.30	2.4	2.25	2.31	2.39	2.48
	Amps	7.0	7.2	7.4	7.7	7.6	7.8	8.1	8.4	8.3	8.5	8.8	9.2	8.9	9.1	9.5	9.9	9.5	9.8	10.1	10.5	10.1	10.4	10.8	11.2
1125	Hi PR	219	236	249	260.1	246	265	280	292	280	301	318	331.9	319	343	362	378	359	386	408	425.3	396	427	451	470
	Lo PR	108	115	126	133.7	114	122	133	141	119	126	138	146.8	125	133	145	154	131	139	152	161.6	135	144	157	167
	Mbh	28.2	28.9	30.8	33.0	27.6	28.2	30.1	32.2	26.9	27.5	29.4	31.4	26.3	26.8	28.7	30.7	25.0	25.5	27.2	29.1	23.1	23.6	25.2	27.0
	S/T	0.95	0.89	0.72	0.5	0.98	0.92	0.75	0.56	1.00	0.94	0.77	0.6	1.00	0.97	0.79	0.59	1.00	1.00	0.82	0.6	1.00	1.00	0.83	0.62
	ΔT	22	21	18	15	22	21	18	15	22	21	18	15	21	21	19	15	20	21	18	15	19	19	17	14
	kW	1.68	1.72	1.78	1.8	1.83	1.87	1.94	2.01	1.96	2.01	2.08	2.2	2.07	2.13	2.20	2.28	2.17	2.23	2.31	2.4	2.26	2.31	2.40	2.49
85	Amps	7.0	7.2	7.4	7.7	7.6	7.8	8.1	8.4	8.3	8.5	8.8	9.2	8.9	9.2	9.5	9.9	9.6	9.8	10.2	10.6	10.2	10.4	10.8	11.2
	Hi PR	220	237	250	260.9	247	266	281	293	281	302	319	332.9	320	344	364	379	360	387	409	426.6	398	428	452	471
	Lo PR	108	115	126	134.1	115	122	133	142	119	127	138	147.3	125	133	145	155	131	139	152	162.1	136	144	157	168

875	Mbh	26.3	26.8	28.0	29.9	25.7	26.1	27.4	29.2	25.0	25.5	26.7	28.5	24.4	24.9	26.1	27.8	23.2	23.7	24.8	26.4	21.5	21.9	23.0	24.5
	S/T	0.94	0.90	0.82	0.66	0.97	0.94	0.85	0.69	1.00	0.96	0.87	0.70	1.00	0.99	0.90	0.73	1.00	1.00	0.93	0.75	1.00	1.00	0.94	0.76
	ΔT	26	25	24	21	26	26	24	21	26	26	24	21	26	26	25	21	24	25	24	21	23	23	23	20
	kW	1.65	1.69	1.75	1.81	1.79	1.83	1.90	1.97	1.92	1.96	2.04	2.11	2.03	2.08	2.16	2.24	2.13	2.18	2.26	2.34	2.21	2.26	2.35	2.43
	Amps	6.8	7.0	7.3	7.6	7.4	7.6	7.9	8.2	8.1	8.3	8.6	9.0	8.7	9.0	9.3	9.7	9.3	9.6	9.9	10.3	9.9	10.2	10.6	11.0
	Hi PR	215	231	244	255	241	260	274	286	274	295	312	325	312	336	355	370	352	378	399	417	388	418	441	460
1050	Lo PR	106	113	123	131	112	119	130	138	116	124	135	144	122	130	142	151	128	136	149	158	132	141	154	164
	Mbh	28.5	29.0	30.4	32.4	27.8	28.3	29.7	31.7	27.1	27.7	29.0	30.9	26.5	27.0	28.3	30.1	25.1	25.6	26.8	28.6	23.3	23.7	24.9	26.5
	S/T	0.97	0.94	0.85	0.69	1.00	0.97	0.88	0.71	1.00	1.00	0.90	0.73	1.00	1.00	0.93	0.75	1.00	1.00	0.96	0.78	1.00	1.00	0.97	0.79
	ΔT	24	24	23	19	24	24	23	20	24	24	23	20	23	24	23	20	22	22	23	20	20	21	21	18
	kW	1.69	1.73	1.80	1.86	1.84	1.89	1.95	2.03	1.97	2.02	2.09	2.17	2.09	2.14	2.22	2.30	2.19	2.24	2.32	2.41	2.27	2.33	2.41	2.50
	Amps	7.0	7.2	7.5	7.8	7.7	7.9	8.1	8.5	8.4	8.6	8.9	9.3	9.0	9.2	9.6	10.0	9.6	9.9	10.2	10.6	10.2	10.5	10.9	11.3
1125	Hi PR	222	239	252	263	249	268	283	295	283	304	321	335	322	347	366	382	362	390	412	430	400	431	455	475
	Lo PR	109	116	127	135	115	123	134	143	120	128	139	148	126	134	146	156	132	140	153	163	137	145	159	169
	Mbh	28.7	29.3	30.7	32.7	28.1	28.6	30.0	32.0	27.4	27.9	29.3	31.2	26.7	27.3	28.5	30.4	25.4	25.9	27.1	28.9	23.5	24.0	25.1	26.8
	S/T	0.99	0.96	0.86	0.70	1.00	0.99	0.90	0.73	1.00	1.00	0.92	0.74	1.00	1.00	0.95	0.77	1.00	1.00	0.98	0.80	1.00	1.00	0.99	0.80
	ΔT	23	23	22	19	23	23	22	19	22	23	22	19	22	22	22	19	21	21	22	19	19	20	20	18
	kW	1.70	1.74	1.80	1.87	1.85	1.89	1.96	2.03	1.98	2.03	2.10	2.18	2.09	2.15	2.22	2.31	2.19	2.25	2.33	2.42	2.28	2.33	2.42	2.51
85	Amps	7.1	7.2	7.5	7.8	7.7	7.9	8.2	8.5	8.4	8.6	8.9	9.3	9.0	9.3	9.6	10.0	9.7	9.9	10.3	10.7	10.3	10.5	10.9	11.4
	Hi PR	222	239	253	263	249	268	283	296	284	305	322	336	323	348	367	383	364	391	413	431	402	432	456	476
	Lo PR	110	117	127	135	116	123	134	143	120	128	140	149	126	134	147	156	132	141	154	164	137	146	159	169

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects AHRI conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																			
				65						75						85						95						105						115					
				ENTERING INDOOR WET BULB TEMPERATURE																																			
70			59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71									
			MbH	32.9	34.1	37.4	-	32.2	33.3	36.5	-	31.4	32.5	35.7	-	30.6	31.7	34.8	-	29.1	30.2	33.0	-	29.1	30.2	33.0	-	27.0	27.9	30.6	-								
			S/T	0.77	0.65	0.45	-	0.80	0.67	0.46	-	0.82	0.69	0.48	-	0.85	0.71	0.49	-	0.88	0.74	0.51	-	0.88	0.74	0.51	-	0.89	0.74	0.51	-								
			Δ T	17	15	11	-	18	15	12	-	18	15	12	-	18	15	12	-	17	15	11	-	17	15	11	-	16	14	11	-								
			kW	2.44	2.49	2.55	-	2.61	2.65	2.73	-	2.75	2.80	2.88	-	2.88	2.94	3.02	-	2.99	3.05	3.14	-	2.99	3.05	3.14	-	3.08	3.14	3.24	-								
1050			/anos	9.7	9.9	10.0	-	10.1	10.3	10.5	-	10.6	10.8	11.0	-	11.0	11.2	11.4	-	11.4	11.6	11.8	-	11.4	11.6	11.8	-	11.8	12.0	12.2	-								
			Hi PR	183	197	208	-	205	221	234	-	234	252	266	-	266	286	302	-	299	322	340	-	299	322	340	-	331	356	376	-								
			Lo PR	95	101	110	-	100	107	117	-	104	111	121	-	110	117	127	-	115	122	134	-	115	122	134	-	119	126	138	-								
			MbH	32.0	33.1	36.3	-	31.2	32.4	35.5	-	30.5	31.6	34.6	-	29.7	30.8	33.8	-	28.2	29.3	32.1	-	28.2	29.3	32.1	-	26.2	27.1	29.7	-								
			S/T	0.74	0.62	0.43	-	0.76	0.64	0.44	-	0.78	0.65	0.45	-	0.81	0.68	0.47	-	0.84	0.70	0.49	-	0.84	0.70	0.49	-	0.85	0.71	0.49	-								
			Δ T	18	16	12	-	18	16	12	-	18	16	12	-	18	16	12	-	18	16	12	-	18	16	12	-	17	15	11	-								
			kW	2.42	2.47	2.54	-	2.59	2.64	2.71	-	2.73	2.78	2.86	-	2.86	2.91	3.00	-	2.96	3.02	3.11	-	2.96	3.02	3.11	-	3.06	3.12	3.21	-								
			/anos	9.7	9.8	10.0	-	10.1	10.2	10.4	-	10.6	10.7	10.9	-	11.0	11.1	11.3	-	11.4	11.5	11.8	-	11.4	11.5	11.8	-	11.8	11.9	12.2	-								
			Hi PR	181	195	206	-	203	219	231	-	231	249	263	-	264	284	299	-	296	319	337	-	296	319	337	-	328	353	372	-								
			Lo PR	94	100	109	-	99	106	116	-	103	110	120	-	109	116	126	-	114	121	132	-	114	121	132	-	118	125	137	-								
			MbH	29.5	30.6	33.5	-	28.8	29.9	32.7	-	28.1	29.2	31.9	-	27.4	28.4	31.2	-	26.1	27.0	29.6	-	26.1	27.0	29.6	-	24.2	25.0	27.4	-								
			S/T	0.71	0.59	0.41	-	0.74	0.62	0.43	-	0.76	0.63	0.44	-	0.78	0.65	0.45	-	0.81	0.68	0.47	-	0.81	0.68	0.47	-	0.82	0.68	0.47	-								
			Δ T	18	16	12	-	19	16	12	-	19	16	12	-	19	16	12	-	18	16	12	-	18	16	12	-	17	15	11	-								
			kW	2.37	2.42	2.48	-	2.53	2.58	2.65	-	2.67	2.72	2.80	-	2.79	2.85	2.93	-	2.90	2.96	3.04	-	2.90	2.96	3.04	-	2.99	3.05	3.14	-								
			/anos	9.6	9.7	9.8	-	10.0	10.1	10.3	-	10.4	10.5	10.7	-	10.8	10.9	11.1	-	11.2	11.3	11.6	-	11.2	11.3	11.6	-	11.6	11.7	12.0	-								
			Hi PR	176	189	200	-	197	212	224	-	224	242	255	-	256	275	291	-	288	309	327	-	288	309	327	-	318	342	361	-								
			Lo PR	91	97	106	-	96	103	112	-	100	107	116	-	105	112	122	-	110	117	128	-	110	117	128	-	114	121	133	-								

75	1350	Mbh	33.5	34.5	37.3	40.0	32.7	33.7	36.4	39.1	31.9	32.9	35.6	38.2	31.1	32.1	34.7	37.3	29.6	30.5	33.0	35.4	27.4	28.2	30.5	32.8
		S/T	0.88	0.79	0.60	0.38	0.91	0.81	0.62	0.40	0.93	0.84	0.63	0.41	0.96	0.86	0.65	0.42	1.00	0.90	0.68	0.44	1.00	0.90	0.68	0.44
		Δ T	20	18	15	10	20	19	15	11	20	19	15	11	20	19	15	11	20	19	15	11	19	17	14	10
		kW	2.46	2.50	2.57	2.65	2.62	2.67	2.75	2.83	2.77	2.82	2.91	2.99	2.90	2.96	3.04	3.14	3.01	3.07	3.16	3.26	3.10	3.17	3.26	3.36
		/anos	9.8	9.9	10.1	10.3	10.2	10.3	10.5	10.7	10.7	10.8	11.0	11.3	11.1	11.2	11.4	11.7	11.5	11.7	11.9	12.2	11.9	12.1	12.3	12.6
	Hi PR	185	199	210	219	208	223	235	246	236	254	268	280	269	289	306	319	303	326	344	359	334	360	380	396	
	Lo PR	96	102	112	119	101	108	118	126	105	112	123	130	111	118	129	137	116	124	135	144	120	128	139	149	
	1200	Mbh	32.5	33.5	36.2	38.9	31.8	32.7	35.4	38.0	31.0	31.9	34.5	37.1	30.2	31.1	33.7	36.2	28.7	29.6	32.0	34.4	26.6	27.4	29.7	31.8
		S/T	0.84	0.75	0.57	0.37	0.87	0.78	0.59	0.38	0.89	0.80	0.60	0.39	0.92	0.82	0.62	0.40	0.95	0.85	0.65	0.42	0.96	0.86	0.65	0.42
		Δ T	21	19	16	11	21	19	16	11	21	19	16	11	21	20	16	11	21	19	16	11	20	18	15	10
kW		2.44	2.49	2.56	2.63	2.61	2.66	2.73	2.81	2.75	2.80	2.89	2.97	2.88	2.94	3.02	3.11	2.99	3.05	3.14	3.23	3.08	3.14	3.24	3.34	
/anos		9.7	9.9	10.0	10.2	10.1	10.3	10.5	10.7	10.6	10.8	11.0	11.2	11.0	11.2	11.4	11.6	11.4	11.6	11.8	12.1	11.8	12.0	12.2	12.5	
Hi PR	183	197	208	217	206	221	234	244	234	252	266	277	266	287	303	316	300	322	340	355	331	356	376	392		
Lo PR	95	101	110	118	100	107	117	124	104	111	121	129	110	117	127	136	115	122	134	142	119	127	138	147		
1050	Mbh	30.0	30.9	33.4	35.9	29.3	30.2	32.7	35.1	28.6	29.5	31.9	34.2	27.9	28.7	31.1	33.4	26.5	27.3	29.6	31.7	24.6	25.3	27.4	29.4	
	S/T	0.81	0.72	0.55	0.35	0.84	0.75	0.57	0.36	0.86	0.77	0.58	0.37	0.89	0.79	0.60	0.39	0.92	0.82	0.62	0.40	0.93	0.83	0.63	0.40	
	Δ T	21	20	16	11	21	20	16	11	22	20	16	11	22	20	16	11	21	20	16	11	20	18	15	10	
	kW	2.39	2.43	2.50	2.57	2.55	2.60	2.67	2.75	2.69	2.74	2.82	2.90	2.81	2.87	2.95	3.04	2.92	2.98	3.07	3.16	3.01	3.07	3.16	3.26	
	/anos	9.6	9.7	9.9	10.1	10.0	10.1	10.3	10.5	10.5	10.6	10.8	11.0	10.8	11.0	11.2	11.4	11.2	11.4	11.6	11.9	11.6	11.8	12.0	12.3	
Hi PR	178	191	202	211	199	215	227	236	227	244	258	269	258	278	293	306	291	313	330	344	321	345	365	380		
Lo PR	92	98	107	114	97	104	113	121	101	108	118	125	106	113	124	132	112	119	130	138	115	123	134	143		

DB: Entering Indoor Dry Bulb Temperature High and low pressures are measured at the liquid and suction service valves.	Shaded area reflects ACCA (TVA) conditions kW = Total system power	Amps = outdoor unit amps (comp.+fan) Design Subcooling 9 ± 3 °F @ the liquid service valve, ARI 95 test conditions
---	---	---

IDB		AIRFLOW		OUTDOOR AMBIENT TEMPERATURE																																			
				65°F						75°F						85°F						95°F						105°F						115°F					
				ENTERING INDOOR WET BULB TEMPERATURE																																			
80	1350	MBh	34.1	34.8	37.2	39.8	33.3	34.0	36.3	38.8	32.5	33.2	35.5	37.9	31.7	32.4	34.6	37.0	30.1	30.8	32.9	35.1	27.9	28.5	30.5	32.6													
		S/T	0.96	0.90	0.74	0.6	1.00	0.94	0.76	0.57	1.00	0.96	0.78	0.6	1.00	1.00	0.81	0.60	1.00	1.00	0.84	0.6	1.00	1.00	0.84	0.63													
		Δ T	22	21	19	15	23	22	19	15	22	22	19	15	22	22	19	15	21	21	19	15	19	19	18	14													
		kW	2.48	2.52	2.59	2.7	2.64	2.69	2.77	2.85	2.79	2.85	2.93	3.0	2.92	2.98	3.07	3.16	3.03	3.09	3.19	3.3	3.13	3.19	3.29	3.39													
		/anos	9.8	10.0	10.1	10.3	10.2	10.4	10.6	10.8	10.7	10.9	11.1	11.3	11.1	11.3	11.5	11.8	11.5	11.7	12.0	12.2	12.0	12.1	12.4	12.7													
		Hi PR	187	201	212	221.5	210	226	238	249	238	257	271	282.7	272	292	309	322	306	329	347	362.2	338	363	384	400													
		Lo PR	97	103	113	120.0	103	109	119	127	107	113	124	131.8	112	119	130	138	117	125	136	145.1	121	129	141	150													
		MBh	33.1	33.8	36.1	38.6	32.3	33.0	35.3	37.7	31.5	32.2	34.4	36.8	30.8	31.4	33.6	35.9	29.2	29.9	31.9	34.1	27.1	27.7	29.6	31.6													
80	1200	S/T	0.92	0.86	0.70	0.5	0.95	0.89	0.73	0.54	0.98	0.92	0.75	0.6	1.00	0.95	0.77	0.58	1.00	0.98	0.80	0.6	1.00	0.99	0.81	0.60													
		Δ T	23	22	19	16	24	23	20	16	24	23	20	16	24	23	20	16	22	22	20	16	21	21	18	15													
		kW	2.46	2.50	2.57	2.6	2.62	2.67	2.75	2.83	2.77	2.82	2.91	3.0	2.90	2.96	3.05	3.14	3.01	3.07	3.16	3.3	3.10	3.17	3.26	3.36													
		/anos	9.8	9.9	10.1	10.3	10.2	10.3	10.5	10.7	10.7	10.8	11.0	11.3	11.1	11.2	11.5	11.7	11.5	11.7	11.9	12.2	11.9	12.1	12.3	12.6													
		Hi PR	185	199	210	219.3	208	223	236	246	236	254	268	279.9	269	289	306	319	303	326	344	358.6	334	360	380	396													
		Lo PR	96	102	112	118.8	102	108	118	126	105	112	123	130.5	111	118	129	137	116	124	135	143.6	120	128	140	149													
		MBh	30.5	31.2	33.3	35.6	29.8	30.5	32.6	34.8	29.1	29.8	31.8	34.0	28.4	29.0	31.0	33.2	27.0	27.6	29.5	31.5	25.0	25.5	27.3	29.2													
		S/T	0.89	0.83	0.68	0.5	0.92	0.86	0.70	0.52	0.94	0.88	0.72	0.5	0.97	0.91	0.74	0.55	1.01	0.95	0.77	0.6	1.02	0.95	0.78	0.58													
1050		Δ T	24	23	20	16	24	23	20	16	24	23	20	16	24	23	20	16	24	23	20	16	22	21	19	15													
		kW	2.41	2.45	2.52	2.6	2.57	2.62	2.69	2.77	2.71	2.76	2.84	2.9	2.84	2.89	2.98	3.07	2.94	3.00	3.09	3.2	3.03	3.10	3.19	3.29													
		/anos	9.7	9.8	9.9	10.1	10.0	10.2	10.4	10.6	10.5	10.6	10.8	11.1	10.9	11.1	11.3	11.5	11.3	11.5	11.7	11.9	11.7	11.9	12.1	12.4													
		Hi PR	179	193	204	212.7	201	217	229	239	229	246	260	271.5	261	281	296	309	293	316	333	347.8	324	349	368	384													
		Lo PR	93	99	108	115.3	98	105	114	122	102	109	119	126.6	107	114	125	133	113	120	131	139.3	117	124	135	144													
		85	1350	MBh	34.7	35.3	37.0	39.5	33.9	34.5	36.2	38.6	33.1	33.7	35.3	37.7	32.3	32.9	34.4	36.7	30.6	31.2	32.7	34.9	28.4	28.9	30.3	32.3											
				S/T	1.00	0.98	0.88	0.71	1.00	1.00	0.91	0.74	1.00	1.00	0.94	0.76	1.00	1.00	0.97	0.78	1.00	1.00	0.96	0.81	1.00	1.00	0.96	0.82											
				Δ T	24	23	22	19	23	24	22	19	23	23	22	19	22	22	23	20	21	21	22	19	19	20	21	18											
kW	2.49			2.54	2.61	2.68	2.66	2.71	2.79	2.87	2.81	2.87	2.95	3.04	2.94	3.00	3.09	3.19	3.06	3.12	3.21	3.31	3.15	3.22	3.31	3.42													
/anos	9.9			10.0	10.2	10.4	10.3	10.4	10.6	10.8	10.8	10.9	11.1	11.4	11.2	11.4	11.6	11.8	11.6	11.8	12.0	12.3	12.0	12.2	12.5	12.7													
Hi PR	189			203	214	224	212	228	241	251	241	259	274	285	274	295	312	325	309	332	351	366	341	367	387	404													
Lo PR	98			104	114	121	104	110	120	128	108	114	125	133	113	120	131	140	118	126	138	147	123	130	142	152													
MBh	33.7			34.3	35.9	38.3	32.9	33.5	35.1	37.5	32.1	32.7	34.3	36.6	31.3	31.9	33.4	35.7	29.7	30.3	31.8	33.9	27.6	28.1	29.4	31.4													
85	1200	S/T	0.96	0.93	0.84	0.68	1.00	0.96	0.87	0.71	1.00	0.99	0.89	0.72	1.00	1.00	0.92	0.75	1.00	1.00	0.96	0.78	1.00	1.00	0.96	0.78													
		Δ T	25	24	23	20	25	25	23	20	25	25	23	20	24	24	24	20	23	23	23	20	21	22	22	19													
		kW	2.48	2.52	2.59	2.67	2.64	2.69	2.77	2.85	2.79	2.85	2.93	3.02	2.92	2.98	3.07	3.16	3.03	3.09	3.19	3.28	3.13	3.19	3.29	3.39													
		/anos	9.8	10.0	10.1	10.3	10.2	10.4	10.6	10.8	10.7	10.9	11.1	11.3	11.1	11.3	11.5	11.8	11.5	11.7	12.0	12.2	12.0	12.1	12.4	12.7													
		Hi PR	187	201	212	221	210	226	238	249	238	257	271	283	272	292	309	322	306	329	347	362	338	363	384	400													
		Lo PR	97	103	113	120	103	109	119	127	107	113	124	132	112	119	130	138	117	125	136	145	121	129	141	150													
		MBh	31.1	31.7	33.2	35.4	30.3	30.9	32.4	34.6	29.6	30.2	31.6	33.7	28.9	29.5	30.9	32.9	27.5	28.0	29.3	31.3	25.4	25.9	27.2	29.0													
		S/T	0.93	0.90	0.81	0.66	0.96	0.93	0.84	0.68	0.99	0.95	0.86	0.70	1.00	0.98	0.89	0.72	1.00	1.00	0.92	0.75	1.00	1.00	0.93	0.75													
1050		Δ T	25	25	24	20	26	25	24	21	26	25	24	21	25	25	24	21	24	25	24	20	22	23	22	19													
		kW	2.42	2.47	2.54	2.61	2.59	2.64	2.71	2.79	2.73	2.78	2.86	2.95	2.86	2.91	3.00	3.09	2.96	3.02	3.11	3.21	3.06	3.12	3.21	3.31													
		/anos	9.7	9.8	10.0	10.2	10.1	10.2	10.4	10.6	10.6	10.7	10.9	11.1	11.0	11.1	11.3	11.6	11.4	11.5	11.7	12.0	11.8	11.9	12.2	12.5													
		Hi PR	181	195	206	215	203	219	231	241	231	249	263	274	263	284	299	312	296	319	337	351	327	352	372	388													
		Lo PR	94	100	109	116	99	106	115	123	103	110	120	128	109	115	126	134	114	121	132	141	118	125	137	146													
		MBh	31.1	31.7	33.2	35.4	30.3	30.9	32.4	34.6	29.6	30.2	31.6	33.7	28.9	29.5	30.9	32.9	27.5	28.0	29.3	31.3	25.4	25.9	27.2	29.0													
		S/T	0.93	0.90	0.81	0.66	0.96	0.93	0.84	0.68	0.99	0.95	0.86	0.70	1.00	0.98	0.89	0.72	1.00	1.00	0.92	0.75	1.00	1.00	0.93	0.75													
		Δ T	25	25	24	20	26	25	24	21	26	25	24	21	25	25	24	21	24	25	24	20	22	23	22	19													
1050		kW	2.42	2.47	2.54	2.61	2.59	2.64	2.71	2.79	2.73	2.78	2.86	2.95	2.86	2.91	3.00	3.09	2.96	3.02	3.11	3.21	3.06	3.12	3.21	3.31													
		/anos	9.7	9.8	10.0	10.2	10.1	10.2	10.4	10.6	10.6	10.7	10.9	11.1	11.0	11.1	11.3	11.6	11.4	11.5	11.7	12.0	11.8	11.9	12.2	12.5													
		Hi PR	181	195	206	215	203	219	231	241	231	249	263	274	263	284	299	312	296	319	337	351	327	352	372	388													
		Lo PR	94	100	109	116	99	106	115	123	103	110	120	128	109	115	126	134	114	121	132	141	118	125	137	146													
		MBh	31.1	31.7	33.2	35.4	30.3	30.9	32.4	34.6	29.6	30.2	31.6	33.7	28.9	29.5	30.9	32.9	27.5	28.0	29.3	31.3																	

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
70	MBh	36.0	37.3	40.9	-	35.2	36.4	39.9	-	34.3	35.6	39.0	-	33.5	34.7	38.0	-	31.8	33.0	36.1	-	29.5	30.5	33.5	-
	S/T	0.69	0.57	0.40	-	0.71	0.59	0.41	-	0.73	0.61	0.42	-	0.75	0.63	0.44	-	0.78	0.65	0.45	-	0.79	0.66	0.46	-
	ΔT	19	16	12	-	19	16	12	-	19	16	12	-	19	16	12	-	19	16	12	-	17	15	11	-
	kW	2.78	2.84	2.92	-	2.98	3.04	3.13	-	3.15	3.21	3.31	-	3.30	3.37	3.47	-	3.43	3.50	3.61	-	3.54	3.61	3.73	-
	Amps	10.7	10.9	11.2	-	11.5	11.8	12.1	-	12.5	12.7	13.2	-	13.3	13.6	14.0	-	14.1	14.5	14.9	-	14.9	15.3	15.8	-
	Hi PR	209	225	238	-	235	253	267	-	267	288	304	-	304	328	346	-	343	369	389	-	378	407	430	-
	Lo PR	101	107	117	-	106	113	124	-	111	118	129	-	116	124	135	-	122	130	141	-	126	134	146	-
	MBh	39.0	40.4	44.3	-	38.1	39.5	43.3	-	37.2	38.5	42.2	-	36.3	37.6	41.2	-	34.5	35.7	39.1	-	31.9	33.1	36.3	-
	S/T	0.71	0.59	0.41	-	0.74	0.62	0.43	-	0.76	0.63	0.44	-	0.78	0.65	0.45	-	0.81	0.68	0.47	-	0.82	0.68	0.47	-
	ΔT	18	16	12	-	18	16	12	-	18	16	12	-	19	16	12	-	18	16	12	-	17	15	11	-

75	MBh	36.6	37.7	40.8	43.8	35.8	36.8	39.9	42.8	34.9	35.9	38.9	41.8	34.1	35.1	38.0	40.7	32.4	33.3	36.1	38.7	30.0	30.9	33.4	35.8
	S/T	0.78	0.70	0.53	0.34	0.81	0.72	0.55	0.35	0.83	0.74	0.56	0.36	0.86	0.77	0.58	0.37	0.89	0.79	0.60	0.39	0.90	0.80	0.61	0.39
	ΔT	21	20	16	11	22	20	16	11	22	20	16	11	22	20	16	11	22	20	16	11	20	19	15	10
	kW	2.80	2.86	2.94	3.03	3.00	3.06	3.15	3.24	3.17	3.24	3.33	3.44	3.33	3.39	3.50	3.61	3.46	3.53	3.64	3.75	3.57	3.64	3.76	3.88
	Amps	10.8	11.0	11.3	11.8	11.6	11.9	12.2	12.7	12.6	12.9	13.3	13.8	13.4	13.7	14.2	14.7	14.2	14.6	15.1	15.6	15.1	15.4	15.9	16.5
	Hi PR	212	228	240	251	237	256	270	281	270	291	307	320	308	331	350	365	346	372	393	410	382	411	434	453
	Lo PR	102	108	118	126	108	114	125	133	112	119	130	138	117	125	136	145	123	131	143	152	127	135	148	157
	MBh	39.7	40.8	44.2	47.4	38.7	39.9	43.2	46.3	37.8	38.9	42.2	45.2	36.9	38.0	41.1	44.1	35.1	36.1	39.1	41.9	32.5	33.4	36.2	38.8
	S/T	0.81	0.72	0.55	0.35	0.84	0.75	0.57	0.37	0.86	0.77	0.58	0.37	0.89	0.79	0.60	0.39	0.92	0.82	0.62	0.40	0.93	0.83	0.63	0.40
	ΔT	21	19	16	11	21	20	16	11	21	20	16	11	22	20	16	11	21	20	16	11	20	18	15	10

IDB: Entering Indoor Dry Bulb Temperature
 High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
80	MBh	37.3	38.1	40.7	43.5	36.4	37.2	39.7	42.5	35.5	36.3	38.8	41.5	34.7	35.4	37.8	40.5	32.9	33.6	36.0	38.4	30.5	31.2	33.3	35.6
	S/T	0.86	0.80	0.65	0.49	0.89	0.83	0.68	0.51	0.91	0.85	0.69	0.52	0.94	0.88	0.72	0.54	0.97	0.91	0.74	0.56	0.98	0.92	0.75	0.56
	Δ T	24	23	20	16	24	23	20	16	24	23	20	16	24	23	20	16	24	23	20	16	22	22	19	15
	kW	2.82	2.88	2.96	3.05	3.02	3.08	3.17	3.27	3.20	3.26	3.36	3.46	3.35	3.42	3.53	3.64	3.48	3.56	3.67	3.78	3.60	3.67	3.79	3.91
	Amps	10.8	11.1	11.4	11.9	11.7	12.0	12.4	12.8	12.7	13.0	13.4	13.9	13.5	13.8	14.3	14.8	14.4	14.7	15.2	15.8	15.2	15.6	16.1	16.7
	Hi PR	214	230	243	253	240	258	273	284	273	294	310	323	311	334	353	368	350	376	397	414	386	416	439	458
	Lo PR	103	109	119	127	109	116	126	134	113	120	131	140	119	126	138	147	124	132	144	154	129	137	149	159
	MBh	40.4	41.3	44.1	47.1	39.4	40.3	43.1	46.0	38.5	39.3	42.0	44.9	37.6	38.4	41.0	43.8	35.7	36.5	39.0	41.6	33.0	33.8	36.1	38.6
	S/T	0.89	0.83	0.68	0.51	0.92	0.86	0.70	0.52	0.94	0.88	0.72	0.54	0.97	0.91	0.74	0.56	1.00	0.95	0.77	0.58	1.00	0.96	0.78	0.58
	Δ T	24	23	20	16	24	23	20	16	24	23	20	16	24	23	20	16	23	23	20	16	22	21	18	15
1400	kW	2.89	2.94	3.03	3.12	3.09	3.15	3.25	3.35	3.27	3.34	3.44	3.55	3.43	3.50	3.61	3.72	3.57	3.64	3.76	3.88	3.68	3.76	3.88	4.01
	Amps	11.1	11.4	11.8	12.2	12.0	12.3	12.7	13.2	13.0	13.3	13.8	14.3	13.9	14.2	14.7	15.2	14.8	15.1	15.6	16.2	15.6	16.0	16.5	17.2
	Hi PR	220	237	250	261	247	266	281	293	281	303	320	333	320	345	364	380	360	388	410	427	398	428	452	472
	Lo PR	106	113	123	131	112	119	130	139	116	124	135	144	122	130	142	151	128	136	149	158	133	141	154	164
	MBh	41.6	42.5	45.4	48.5	40.6	41.5	44.3	47.4	39.6	40.5	43.3	46.3	38.7	39.5	42.2	45.1	36.7	37.6	40.1	42.9	34.0	34.8	37.2	39.7
	S/T	0.93	0.87	0.71	0.53	0.96	0.90	0.74	0.55	1.00	0.93	0.75	0.56	1.00	0.96	0.78	0.58	1.00	1.00	0.81	0.60	1.00	1.00	0.82	0.61
	Δ T	23	22	19	15	23	22	19	15	23	22	19	15	23	22	19	15	21	22	19	15	20	20	18	14
	kW	2.91	2.96	3.05	3.14	3.11	3.18	3.27	3.37	3.30	3.36	3.47	3.58	3.46	3.53	3.64	3.75	3.60	3.67	3.79	3.91	3.71	3.79	3.91	4.04
	Amps	11.2	11.5	11.9	12.3	12.1	12.4	12.8	13.3	13.1	13.5	13.9	14.4	14.0	14.4	14.8	15.4	14.9	15.3	15.8	16.4	15.8	16.2	16.7	17.3
	Hi PR	223	240	253	264	250	269	284	296	284	306	323	337	324	348	368	383	364	392	414	431	402	433	457	477
Lo PR	107	114	124	132	113	120	131	140	118	125	137	145	123	131	143	153	129	138	150	160	134	142	155	166	

1225	MBh	37.9	38.6	40.5	43.2	37.0	37.7	39.5	42.2	36.2	36.9	38.6	41.2	35.3	36.0	37.7	40.2	33.5	34.2	35.8	38.2	31.0	31.6	33.1	35.4
	S/T	0.90	0.87	0.78	0.63	0.93	0.90	0.81	0.66	0.95	0.92	0.83	0.67	0.98	0.95	0.86	0.70	1.00	0.99	0.89	0.72	1.00	0.99	0.90	0.73
	Δ T	26	25	24	21	26	25	24	21	26	25	24	21	26	26	24	21	25	25	24	21	23	24	22	19
	kW	2.84	2.90	2.98	3.07	3.04	3.11	3.20	3.29	3.22	3.29	3.39	3.49	3.38	3.45	3.55	3.66	3.51	3.58	3.70	3.81	3.63	3.70	3.82	3.94
	Amps	10.9	11.2	11.6	12.0	11.8	12.1	12.5	12.9	12.8	13.1	13.5	14.0	13.6	14.0	14.4	15.0	14.5	14.9	15.3	15.9	15.4	15.7	16.2	16.8
	Hi PR	216	232	245	256	242	261	275	287	276	297	313	327	314	338	357	372	353	380	401	418	390	420	443	462
	Lo PR	104	110	121	128	110	117	127	136	114	121	132	141	120	127	139	148	126	134	146	155	130	138	151	161
	MBh	41.1	41.9	43.9	46.8	40.1	40.9	42.8	45.7	39.2	39.9	41.8	44.6	38.2	39.0	40.8	43.5	36.3	37.0	38.8	41.3	33.6	34.3	35.9	38.3
	S/T	0.93	0.90	0.81	0.66	0.96	0.93	0.84	0.68	0.99	0.95	0.86	0.70	1.00	0.98	0.89	0.72	1.00	1.00	0.92	0.75	1.00	1.00	0.93	0.75
	Δ T	25	25	23	20	25	25	24	20	25	25	24	20	25	25	24	21	24	24	23	20	22	23	22	19
1400	kW	2.91	2.96	3.05	3.14	3.11	3.18	3.27	3.37	3.30	3.36	3.47	3.58	3.46	3.53	3.64	3.75	3.60	3.67	3.79	3.91	3.71	3.79	3.91	4.04
	Amps	11.2	11.5	11.9	12.3	12.1	12.4	12.8	13.3	13.1	13.5	13.9	14.4	14.0	14.4	14.8	15.4	14.9	15.3	15.8	16.4	15.8	16.2	16.7	17.3
	Hi PR	223	240	253	264	250	269	284	296	284	306	323	337	324	348	368	383	364	392	414	431	402	433	457	477
	Lo PR	107	114	124	132	113	120	131	140	118	125	137	145	123	131	143	153	129	138	150	160	134	142	155	166
	MBh	42.3	43.1	45.2	48.2	41.3	42.1	44.1	47.1	40.3	41.1	43.1	45.9	39.4	40.1	42.0	44.8	37.4	38.1	39.9	42.6	34.6	35.3	37.0	39.4
	S/T	0.98	0.94	0.85	0.69	1.00	0.98	0.88	0.71	1.00	1.00	0.90	0.73	1.00	1.00	0.93	0.76	1.00	1.00	0.97	0.78	1.00	1.00	0.98	0.79
	Δ T	24	24	22	19	24	24	23	20	24	24	23	20	23	23	23	20	22	22	23	20	20	21	21	18
	kW	2.93	2.99	3.07	3.17	3.14	3.20	3.30	3.40	3.32	3.39	3.49	3.60	3.49	3.56	3.67	3.78	3.62	3.70	3.82	3.94	3.74	3.82	3.94	4.07
	Amps	11.3	11.6	12.0	12.4	12.2	12.5	12.9	13.4	13.3	13.6	14.0	14.5	14.2	14.5	15.0	15.5	15.0	15.4	15.9	16.5	15.9	16.3	16.9	17.5
	Hi PR	225	242	255	266	252	271	287	299	287	309	326	340	327	352	371	387	368	396	418	436	406	437	462	481
	Lo PR	108	115	126	134	114	122	133	141	119	126	138	147	125	133	145	154	131	139	152	162	135	144	157	167

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects AHRI conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

		OUTDOOR AMBIENT TEMPERATURE																							
		65°F				75°F				85°F				95°F				105°F				115°F			
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71
70	MBh	40.4	41.9	45.9	-	39.5	40.9	44.8	-	38.5	39.9	43.7	-	37.6	38.9	42.7	-	35.7	37.0	40.5	-	33.1	34.3	37.5	-
	S/T	0.71	0.59	0.41	-	0.73	0.61	0.42	-	0.75	0.63	0.44	-	0.78	0.65	0.45	-	0.81	0.67	0.47	-	0.81	0.68	0.47	-
	Δ T	19	16	12	-	19	16	12	-	19	16	13	-	19	17	13	-	19	16	12	-	18	15	12	-
	kW	3.17	3.23	3.32	-	3.39	3.46	3.56	-	3.59	3.66	3.77	-	3.77	3.84	3.96	-	3.91	4.00	4.12	-	4.04	4.13	4.26	-
	Amps	11.6	11.9	12.3	-	12.6	12.9	13.3	-	13.7	14.0	14.5	-	14.6	15.0	15.5	-	15.5	15.9	16.5	-	16.5	16.9	17.4	-
	Hi PR	215	231	244	-	241	259	274	-	274	295	311	-	312	336	354	-	351	377	399	-	388	417	440	-
	Lo PR	104	111	121	-	110	117	128	-	115	122	133	-	120	128	140	-	126	134	146	-	130	139	151	-
	MBh	43.8	45.4	49.7	-	42.7	44.3	48.5	-	41.7	43.2	47.4	-	40.7	42.2	46.2	-	38.7	40.1	43.9	-	35.8	37.1	40.7	-
	S/T	0.73	0.61	0.43	-	0.76	0.64	0.44	-	0.78	0.65	0.45	-	0.81	0.67	0.47	-	0.84	0.70	0.48	-	0.84	0.70	0.49	-
	Δ T	18	16	12	-	19	16	12	-	19	16	12	-	19	16	12	-	19	16	12	-	17	15	11	-
1600	kW	3.24	3.30	3.40	-	3.47	3.54	3.65	-	3.67	3.75	3.87	-	3.86	3.94	4.06	-	4.01	4.09	4.22	-	4.14	4.23	4.36	-
	Amps	12.0	12.3	12.7	-	12.9	13.2	13.7	-	14.1	14.4	14.9	-	15.0	15.4	15.9	-	16.0	16.4	16.9	-	16.9	17.4	17.9	-
	Hi PR	221	238	251	-	248	267	282	-	282	304	321	-	321	346	365	-	362	389	411	-	400	430	454	-
	Lo PR	108	114	125	-	114	121	132	-	118	126	137	-	124	132	144	-	130	138	151	-	134	143	156	-
	MBh	45.1	46.7	51.2	-	44.0	45.6	50.0	-	43.0	44.5	48.8	-	41.9	43.5	47.6	-	39.8	41.3	45.2	-	36.9	38.2	41.9	-
	S/T	0.77	0.64	0.45	-	0.80	0.67	0.46	-	0.82	0.68	0.47	-	0.85	0.71	0.49	-	0.88	0.73	0.51	-	0.88	0.74	0.51	-
	Δ T	18	15	12	-	18	16	12	-	18	16	12	-	18	16	12	-	18	15	12	-	17	14	11	-
	kW	3.26	3.33	3.42	-	3.50	3.57	3.67	-	3.70	3.78	3.90	-	3.89	3.97	4.09	-	4.04	4.13	4.26	-	4.18	4.26	4.40	-
	Amps	12.1	12.4	12.8	-	13.0	13.4	13.8	-	14.2	14.5	15.0	-	15.2	15.5	16.0	-	16.1	16.5	17.1	-	17.1	17.5	18.1	-
	Hi PR	223	240	254	-	251	270	285	-	285	307	324	-	325	349	369	-	365	393	415	-	404	434	459	-
	Lo PR	109	116	126	-	115	122	133	-	119	127	139	-	125	133	146	-	131	140	152	-	136	144	158	-

75	MBh	41.1	42.3	45.8	49.1	40.1	41.3	44.7	48.0	39.2	40.3	43.7	46.8	38.2	39.3	42.6	45.7	36.3	37.4	40.5	43.4	33.6	34.6	37.5	40.2
	S/T	0.81	0.72	0.55	0.35	0.83	0.75	0.56	0.36	0.86	0.77	0.58	0.37	0.88	0.79	0.60	0.38	0.92	0.82	0.62	0.40	0.92	0.83	0.63	0.40
	Δ T	22	20	16	11	22	20	17	11	22	20	17	11	22	20	16	11	22	20	16	11	20	19	15	11
	kW	3.19	3.25	3.35	3.45	3.42	3.49	3.59	3.70	3.62	3.69	3.80	3.92	3.79	3.87	3.99	4.12	3.95	4.03	4.15	4.29	4.08	4.16	4.29	4.43
	Amps	11.7	12.0	12.4	12.9	12.7	13.0	13.4	13.9	13.8	14.1	14.6	15.1	14.7	15.1	15.6	16.2	15.7	16.1	16.6	17.2	16.6	17.0	17.6	18.3
	Hi PR	217	233	246	257	243	262	276	288	277	298	314	328	315	339	358	373	354	381	403	420	391	421	445	464
	Lo PR	105	112	122	130	111	118	129	138	116	123	134	143	122	129	141	150	127	136	148	158	132	140	153	163
	MBh	44.5	45.8	49.6	53.2	43.5	44.8	48.4	52.0	42.4	43.7	47.3	50.8	41.4	42.6	46.1	49.5	39.3	40.5	43.8	47.0	36.4	37.5	40.6	43.6
	S/T	0.84	0.75	0.57	0.36	0.87	0.77	0.59	0.38	0.89	0.79	0.60	0.39	0.92	0.82	0.62	0.40	0.95	0.85	0.64	0.41	0.96	0.86	0.65	0.42
	Δ T	21	20	16	11	22	20	16	11	22	20	16	11	22	20	16	11	21	20	16	11	20	18	15	10
1600	kW	3.26	3.33	3.42	3.53	3.50	3.57	3.68	3.79	3.70	3.78	3.90	4.02	3.89	3.97	4.09	4.22	4.04	4.13	4.26	4.39	4.18	4.26	4.40	4.54
	Amps	12.1	12.4	12.8	13.2	13.1	13.4	13.8	14.3	14.2	14.5	15.0	15.6	15.2	15.5	16.1	16.7	16.1	16.5	17.1	17.7	17.1	17.5	18.1	18.8
	Hi PR	223	240	254	265	251	270	285	297	285	307	324	338	325	349	369	385	365	393	415	433	404	434	459	478
	Lo PR	109	116	126	134	115	122	133	142	119	127	139	148	125	133	146	155	131	140	153	162	136	145	158	168
	MBh	45.8	47.2	51.1	54.8	44.8	46.1	49.9	53.6	43.7	45.0	48.7	52.3	42.6	43.9	47.5	51.0	40.5	41.7	45.1	48.5	37.5	38.6	41.8	44.9
	S/T	0.88	0.78	0.59	0.38	0.91	0.81	0.61	0.40	0.93	0.83	0.63	0.41	0.96	0.86	0.65	0.42	1.00	0.89	0.67	0.43	1.00	0.90	0.68	0.44
	Δ T	21	19	15	11	21	19	16	11	21	19	16	11	21	19	16	11	21	19	16	11	19	18	15	10
	kW	3.29	3.35	3.45	3.55	3.52	3.59	3.70	3.82	3.73	3.81	3.93	4.05	3.92	4.00	4.12	4.26	4.07	4.16	4.29	4.43	4.21	4.30	4.44	4.58
	Amps	12.2	12.5	12.9	13.4	13.2	13.5	13.9	14.5	14.3	14.7	15.1	15.7	15.3	15.7	16.2	16.8	16.3	16.7	17.2	17.9	17.3	17.7	18.3	19.0
	Hi PR	226	243	256	267	253	272	288	300	288	310	327	341	328	353	373	389	369	397	419	437	408	439	463	483
	Lo PR	110	117	127	136	116	123	135	143	120	128	140	149	127	135	147	157	133	141	154	164	137	146	159	170

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

		OUTDOOR AMBIENT TEMPERATURE																																			
		65°F						75°F						85°F						95°F						105°F						115°F					
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71				
80	MbH	41.8	42.7	45.6	48.8	40.8	41.7	44.6	47.7	39.9	40.7	43.5	46.5	38.9	39.7	42.5	45.4	36.9	37.8	40.3	43.1	34.2	35.0	37.4	39.9	34.2	35.0	37.4	39.9	34.2	35.0	37.4	39.9				
	S/T	0.88	0.83	0.67	0.50	0.92	0.86	0.70	0.52	0.94	0.88	0.72	0.54	0.97	0.91	0.74	0.55	1.01	0.94	0.77	0.57	1.01	0.95	0.77	0.58	1.01	0.95	0.77	0.58	1.01	0.95	0.77	0.58				
	Δ T	24	23	20	16	25	24	20	16	25	24	20	16	25	24	21	16	24	23	20	16	23	22	19	15	23	22	19	15	23	22	19	15				
	kW	3.21	3.28	3.37	3.47	3.44	3.51	3.62	3.73	3.65	3.72	3.83	3.95	3.82	3.90	4.03	4.15	3.98	4.06	4.19	4.32	4.11	4.20	4.33	4.47	4.11	4.20	4.33	4.47	4.11	4.20	4.33	4.47				
	Amps	11.9	12.1	12.5	13.0	12.8	13.1	13.6	14.1	13.9	14.3	14.7	15.3	14.9	15.2	15.8	16.3	15.8	16.2	16.8	17.4	16.8	17.2	17.8	18.5	16.8	17.2	17.8	18.5	16.8	17.2	17.8	18.5				
	Hi PR	219	236	249	259	246	264	279	291	279	301	317	331	318	342	362	377	358	385	407	424	395	426	449	469	358	426	449	469	358	426	449	469				
	Lo PR	106	113	124	132	112	120	131	139	117	124	136	145	123	131	143	152	129	137	149	159	133	142	155	165	133	142	155	165	133	142	155	165				
1600	MbH	45.3	46.3	49.5	52.9	44.2	45.2	48.3	51.6	43.2	44.1	47.2	50.4	42.1	43.1	46.0	49.2	40.0	40.9	43.7	46.7	37.1	37.9	40.5	43.3	37.1	37.9	40.5	43.3	37.1	37.9	40.5	43.3				
	S/T	0.92	0.86	0.70	0.52	0.95	0.89	0.72	0.54	0.97	0.91	0.74	0.56	1.00	0.94	0.77	0.57	1.00	0.98	0.80	0.60	1.00	0.99	0.80	0.60	1.00	0.99	0.80	0.60	1.00	0.99	0.80	0.60				
	Δ T	24	23	20	16	24	23	20	16	24	23	20	16	24	23	20	16	23	23	20	16	21	21	19	15	23	23	20	16	21	21	19	15				
	kW	3.29	3.35	3.45	3.56	3.52	3.59	3.70	3.82	3.73	3.81	3.93	4.05	3.92	4.00	4.12	4.26	4.07	4.16	4.29	4.43	4.21	4.30	4.44	4.58	4.21	4.30	4.44	4.58	4.21	4.30	4.44	4.58				
	Amps	12.2	12.5	12.9	13.4	13.2	13.5	13.9	14.5	14.3	14.7	15.2	15.7	15.3	15.7	16.2	16.8	16.3	16.7	17.3	17.9	17.3	17.7	18.3	19.0	17.3	17.7	18.3	19.0	17.3	17.7	18.3	19.0				
	Hi PR	226	243	256	267	253	272	288	300	288	310	327	341	328	353	373	389	369	397	419	437	408	439	463	483	408	439	463	483	408	439	463	483				
	Lo PR	110	117	127	136	116	123	135	143	120	128	140	149	127	135	147	157	133	141	154	164	137	146	159	170	137	146	159	170	137	146	159	170				
1800	MbH	46.7	47.7	50.9	54.4	45.6	46.6	49.7	53.2	44.5	45.5	48.6	51.9	43.4	44.3	47.4	50.6	41.2	42.1	45.0	48.1	38.2	39.0	41.7	44.6	38.2	39.0	41.7	44.6	38.2	39.0	41.7	44.6				
	S/T	0.96	0.90	0.73	0.55	1.00	0.93	0.76	0.57	1.00	0.96	0.78	0.58	1.00	0.94	0.77	0.57	1.00	0.98	0.80	0.62	1.00	1.00	0.84	0.63	1.00	0.98	0.80	0.62	1.00	1.00	0.84	0.63				
	Δ T	23	22	19	15	23	22	19	15	23	22	19	15	22	23	19	16	21	22	19	15	20	20	18	14	21	22	19	15	20	20	18	14				
	kW	3.31	3.38	3.48	3.58	3.55	3.62	3.73	3.85	3.76	3.84	3.96	4.08	3.95	4.03	4.16	4.29	4.11	4.19	4.33	4.47	4.24	4.33	4.47	4.62	4.24	4.33	4.47	4.62	4.24	4.33	4.47	4.62				
	Amps	12.3	12.6	13.0	13.5	13.3	13.6	14.1	14.6	14.4	14.8	15.3	15.9	15.4	15.8	16.4	17.0	16.4	16.8	17.4	18.1	17.4	17.9	18.5	19.2	17.4	17.9	18.5	19.2	17.4	17.9	18.5	19.2				
	Hi PR	228	245	259	270	256	275	291	303	291	313	331	345	331	356	376	393	373	401	423	442	412	443	468	488	412	443	468	488	412	443	468	488				
	Lo PR	111	118	129	137	117	125	136	145	122	129	141	151	128	136	148	158	134	143	156	166	139	147	161	171	139	147	161	171	139	147	161	171				

1400	MBh	42.5	43.4	45.4	48.5	41.5	42.4	44.4	47.3	40.6	41.3	43.3	46.2	39.6	40.3	42.2	45.1	37.6	38.3	40.1	42.8	34.8	35.5	37.2	39.7
	S/T	0.93	0.89	0.81	0.65	0.96	0.93	0.84	0.68	0.98	0.95	0.86	0.70	1.00	0.98	0.88	0.72	1.00	1.00	0.92	0.74	1.00	1.00	0.93	0.75
	Δ T	26	25	24	21	26	26	24	21	26	26	24	21	26	26	25	21	25	25	24	21	23	23	20	20
	kW	3.24	3.30	3.40	3.50	3.47	3.54	3.65	3.76	3.67	3.75	3.86	3.99	3.85	3.94	4.06	4.19	4.01	4.09	4.22	4.36	4.14	4.23	4.36	4.50
	Amps	12.0	12.2	12.6	13.1	12.9	13.2	13.7	14.2	14.0	14.4	14.9	15.4	15.0	15.4	15.9	16.5	16.0	16.4	16.9	17.6	16.9	17.4	17.9	18.6
	Hi PR	221	238	251	262	248	267	282	294	282	304	321	334	321	346	365	381	361	389	411	428	399	430	454	473
Lo PR	108	114	125	133	114	121	132	140	118	126	137	146	124	132	144	153	130	138	151	161	134	143	156	166	
1600	MBh	46.1	47.0	49.2	52.5	45.0	45.9	48.1	51.3	43.9	44.8	46.9	50.1	42.9	43.7	45.8	48.8	40.7	41.5	43.5	46.4	37.7	38.5	40.3	43.0
	S/T	0.96	0.93	0.84	0.68	1.00	0.96	0.87	0.70	1.00	0.98	0.89	0.72	1.00	1.00	0.92	0.74	1.00	1.00	0.95	0.77	1.00	1.00	0.96	0.78
	Δ T	25	25	24	20	26	25	24	21	25	25	24	21	25	25	24	21	23	24	24	21	22	22	19	19
	kW	3.31	3.38	3.48	3.58	3.55	3.62	3.73	3.85	3.76	3.84	3.96	4.08	3.95	4.03	4.16	4.29	4.11	4.19	4.33	4.47	4.24	4.33	4.47	4.62
	Amps	12.3	12.6	13.0	13.5	13.3	13.6	14.1	14.6	14.4	14.8	15.3	15.9	15.4	15.8	16.4	17.0	16.4	16.8	17.4	18.1	17.4	17.9	18.5	19.2
	Hi PR	228	245	259	270	256	275	291	303	291	313	331	345	331	356	376	393	373	401	423	442	412	443	468	488
Lo PR	111	118	129	137	117	125	136	145	122	129	141	151	128	136	148	158	134	143	156	166	139	147	161	171	
1800	MBh	47.5	48.4	50.7	54.1	46.4	47.3	49.5	52.8	45.3	46.1	48.3	51.6	44.2	45.0	47.1	50.3	42.0	42.8	44.8	47.8	38.9	39.6	41.5	44.3
	S/T	1.00	0.97	0.88	0.71	1.00	1.00	0.91	0.74	1.00	1.00	0.93	0.76	1.00	1.00	0.96	0.78	1.00	1.00	1.00	0.81	1.00	1.00	1.00	0.82
	Δ T	24	24	23	20	24	24	23	20	23	24	23	20	23	23	23	20	21	22	23	20	20	20	21	18
	kW	3.34	3.40	3.50	3.61	3.58	3.65	3.76	3.88	3.79	3.87	3.99	4.11	3.98	4.06	4.19	4.32	4.14	4.23	4.36	4.50	4.28	4.37	4.51	4.65
	Amps	12.4	12.7	13.1	13.6	13.4	13.7	14.2	14.7	14.6	14.9	15.4	16.0	15.6	16.0	16.5	17.1	16.6	17.0	17.6	18.2	17.6	18.0	18.6	19.3
	Hi PR	230	248	262	273	258	278	294	306	294	316	334	348	335	360	380	397	376	405	428	446	416	448	473	493
Lo PR	112	119	130	138	118	126	137	146	123	131	143	152	129	137	150	160	135	144	157	167	140	149	163	173	

		OUTDOOR AMBIENT TEMPERATURE																								
		65°F				75°F				85°F				95°F				105°F				115°F				
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	
70	1500	MBh	50.1	51.9	56.8	-	48.9	50.7	55.5	-	47.7	49.5	54.2	-	46.6	48.3	52.9	-	44.2	45.8	50.2	-	41.0	42.5	46.5	-
		S/T	0.67	0.56	0.39	-	0.69	0.58	0.40	-	0.71	0.59	0.41	-	0.73	0.61	0.42	-	0.76	0.64	0.44	-	0.77	0.64	0.44	-
		ΔT	21	18	13	-	21	18	14	-	21	18	14	-	21	18	14	-	21	18	14	-	19	17	13	-
		kW	3.87	3.95	4.07	-	4.16	4.24	4.38	-	4.41	4.50	4.65	-	4.63	4.73	4.89	-	4.82	4.93	5.09	-	4.99	5.10	5.26	-
		Amps	14.4	14.8	15.3	-	15.6	16.0	16.5	-	17.0	17.4	18.0	-	18.2	18.6	19.2	-	19.3	19.8	20.5	-	20.5	21.0	21.7	-
		HI PR	229	246	260	-	257	276	292	-	292	314	332	-	333	358	378	-	374	403	425	-	413	445	470	-
		LO PR	101	108	118	-	107	114	125	-	111	119	129	-	117	125	136	-	123	130	142	-	127	135	147	-
70	1750	MBh	54.2	56.2	61.6	-	53.0	54.9	60.1	-	51.7	53.6	58.7	-	50.4	52.3	57.3	-	47.9	49.7	54.4	-	44.4	46.0	50.4	-
		S/T	0.69	0.58	0.40	-	0.72	0.60	0.42	-	0.74	0.62	0.43	-	0.76	0.64	0.44	-	0.79	0.66	0.46	-	0.80	0.66	0.46	-
		ΔT	20	17	13	-	20	17	13	-	20	17	13	-	20	17	13	-	20	17	13	-	19	16	12	-
		kW	3.96	4.04	4.17	-	4.26	4.35	4.48	-	4.52	4.62	4.76	-	4.75	4.85	5.01	-	4.95	5.05	5.22	-	5.12	5.23	5.40	-
		Amps	14.8	15.2	15.7	-	16.1	16.4	17.0	-	17.5	17.9	18.5	-	18.7	19.1	19.8	-	19.9	20.4	21.1	-	21.1	21.6	22.4	-
		HI PR	236	254	268	-	265	285	301	-	301	324	342	-	343	369	390	-	386	415	438	-	426	459	484	-
		LO PR	105	111	122	-	111	118	128	-	115	122	133	-	121	128	140	-	126	135	147	-	131	139	152	-
2000		MBh	55.9	57.9	63.4	-	54.6	56.5	62.0	-	53.3	55.2	60.5	-	52.0	53.9	59.0	-	49.4	51.2	56.1	-	45.7	47.4	51.9	-
		S/T	0.73	0.61	0.42	-	0.75	0.63	0.44	-	0.77	0.65	0.45	-	0.80	0.67	0.46	-	0.83	0.69	0.48	-	0.83	0.70	0.48	-
		ΔT	19	16	12	-	19	16	12	-	19	16	12	-	19	16	13	-	19	16	12	-	18	15	12	-
		kW	3.99	4.07	4.20	-	4.29	4.38	4.52	-	4.56	4.65	4.80	-	4.79	4.89	5.05	-	4.99	5.10	5.26	-	5.16	5.27	5.44	-
		Amps	15.0	15.3	15.8	-	16.2	16.6	17.2	-	17.6	18.1	18.7	-	18.9	19.3	20.0	-	20.1	20.6	21.3	-	21.3	21.8	22.6	-
		HI PR	238	256	271	-	267	288	304	-	304	327	346	-	346	373	394	-	390	419	443	-	430	463	489	-
		LO PR	106	112	123	-	112	119	130	-	116	123	135	-	122	130	142	-	128	136	148	-	132	141	153	-

75	1500	MBh	50.9	52.4	56.7	60.9	49.7	51.2	55.4	59.5	48.5	50.0	54.1	58.1	47.3	48.8	52.8	56.6	45.0	46.3	50.1	53.8	41.7	42.9	46.4	49.8
		S/T	0.76	0.68	0.51	0.33	0.79	0.70	0.53	0.34	0.81	0.72	0.55	0.35	0.83	0.75	0.56	0.36	0.87	0.77	0.59	0.38	0.87	0.78	0.59	0.38
		ΔT	24	22	18	12	24	22	18	13	24	22	18	13	24	22	18	13	24	22	18	12	22	21	17	12
		kW	3.90	3.98	4.10	4.23	4.19	4.28	4.41	4.55	4.45	4.54	4.68	4.84	4.67	4.77	4.93	5.09	4.86	4.97	5.13	5.30	5.03	5.14	5.31	5.48
		Amps	14.6	14.9	15.4	16.0	15.8	16.1	16.7	17.3	17.1	17.6	18.1	18.8	18.3	18.8	19.4	20.2	19.5	20.0	20.7	21.5	20.7	21.2	21.9	22.8
		HI PR	231	249	263	274	259	279	295	307	295	317	335	350	336	362	382	398	378	407	430	448	418	449	475	495
		LO PR	103	109	119	127	108	115	126	134	113	120	131	139	118	126	137	146	124	132	144	153	128	136	149	159
	1750	MBh	55.1	56.8	61.5	66.0	53.9	55.5	60.0	64.4	52.6	54.1	58.6	62.9	51.3	52.8	57.2	61.4	48.7	50.2	54.3	58.3	45.1	46.5	50.3	54.0
		S/T	0.79	0.71	0.53	0.34	0.82	0.73	0.55	0.36	0.84	0.75	0.57	0.36	0.86	0.77	0.59	0.38	0.90	0.80	0.61	0.39	0.91	0.81	0.61	0.39
		ΔT	23	21	17	12	23	21	17	12	23	21	17	12	23	21	18	12	23	21	17	12	21	20	16	11
2000		kW	3.99	4.07	4.20	4.33	4.29	4.38	4.52	4.66	4.56	4.65	4.80	4.96	4.79	4.89	5.05	5.22	4.99	5.10	5.26	5.44	5.16	5.27	5.44	5.63
		Amps	15.0	15.3	15.8	16.4	16.2	16.6	17.2	17.8	17.6	18.1	18.7	19.4	18.9	19.3	20.0	20.8	20.1	20.6	21.3	22.1	21.3	21.8	22.6	23.5
		HI PR	238	256	271	282	267	288	304	317	304	327	346	360	346	373	394	411	390	419	443	462	431	463	489	510
		LO PR	106	112	123	131	112	119	130	138	116	123	135	144	122	130	142	151	128	136	148	158	132	141	153	163
		MBh	56.8	58.5	63.3	67.9	55.5	57.1	61.8	66.4	54.2	55.8	60.4	64.8	52.8	54.4	58.9	63.2	50.2	51.7	55.9	60.0	46.5	47.9	51.8	55.6
		S/T	0.83	0.74	0.56	0.36	0.86	0.77	0.58	0.37	0.88	0.79	0.59	0.38	0.91	0.81	0.61	0.39	0.94	0.84	0.64	0.41	0.95	0.85	0.64	0.41
		ΔT	22	20	16	11	22	20	16	11	22	20	16	11	22	20	17	11	22	20	16	11	20	19	15	11
		kW	4.02	4.11	4.23	4.37	4.33	4.42	4.56	4.70	4.59	4.69	4.84	5.00	4.83	4.93	5.09	5.26	5.03	5.14	5.31	5.48	5.20	5.32	5.49	5.67
		Amps	15.1	15.5	16.0	16.6	16.4	16.8	17.3	18.0	17.8	18.2	18.8	19.6	19.0	19.5	20.2	20.9	20.3	20.8	21.5	22.3	21.5	22.0	22.8	23.7
		HI PR	241	259	274	285	270	291	307	320	307	331	349	364	350	376	398	415	394	424	447	466	435	468	494	515
		LO PR	107	114	124	132	113	120	131	139	117	125	136	145	123	131	143	152	129	137	150	160	133	142	155	165

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

		OUTDOOR AMBIENT TEMPERATURE																																															
		65°F								75°F								85°F								95°F								105°F								115°F							
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71																
80	MBh	51.8	52.9	56.6	60.5	50.6	51.7	55.2	59.1	49.4	50.5	53.9	57.6	48.2	49.2	52.6	56.2	45.8	46.8	50.0	53.4	42.4	43.3	46.3	49.5	42.4	43.3	46.3	49.5	42.4	43.3	46.3	49.5																
	S/T	0.83	0.78	0.64	0.48	0.86	0.81	0.66	0.49	0.89	0.83	0.68	0.51	0.91	0.86	0.70	0.52	0.95	0.89	0.72	0.54	0.96	0.90	0.73	0.55	0.96	0.90	0.73	0.55	0.96	0.90	0.73	0.55																
	ΔT	26	25	22	18	27	26	22	18	27	26	22	18	27	26	22	18	27	26	22	18	25	24	21	17	25	24	21	17	25	24	21	17																
	kW	3.93	4.01	4.13	4.26	4.22	4.31	4.45	4.59	4.48	4.58	4.72	4.88	4.71	4.81	4.97	5.13	4.90	5.01	5.17	5.34	5.07	5.18	5.35	5.53	5.07	5.18	5.35	5.53	5.07	5.18	5.35	5.53																
	Amps	14.7	15.1	15.6	16.1	15.9	16.3	16.8	17.5	17.3	17.7	18.3	19.0	18.5	19.0	19.6	20.4	19.7	20.2	20.9	21.7	20.9	21.4	22.2	23.0	20.9	21.4	22.2	23.0	20.9	21.4	22.2	23.0																
	HI PR	234	251	265	277	262	282	298	311	298	321	339	353	339	365	386	402	382	411	434	453	422	454	479	500	422	454	479	500	422	454	479	500																
	LO PR	104	110	120	128	109	116	127	135	114	121	132	141	119	127	139	148	125	133	145	155	129	138	150	160	129	138	150	160	129	138	150	160																
	MBh	56.1	57.4	61.3	65.5	54.8	56.0	59.9	64.0	53.5	54.7	58.4	62.5	52.2	53.4	57.0	60.9	49.6	50.7	54.2	57.9	45.9	46.9	50.2	53.6	45.9	46.9	50.2	53.6	45.9	46.9	50.2	53.6																
	S/T	0.86	0.81	0.66	0.49	0.90	0.84	0.68	0.51	0.92	0.86	0.70	0.52	0.95	0.89	0.72	0.54	0.98	0.92	0.75	0.56	0.99	0.93	0.76	0.57	0.99	0.93	0.76	0.57	0.99	0.93	0.76	0.57																
	ΔT	25	24	21	17	26	25	22	17	26	25	22	17	26	25	22	17	26	25	21	17	24	23	20	16	24	23	20	16	24	23	20	16																
2000	kW	4.02	4.11	4.23	4.37	4.33	4.42	4.56	4.70	4.59	4.69	4.84	5.00	4.83	4.93	5.09	5.26	5.03	5.14	5.31	5.48	5.20	5.32	5.49	5.67	5.20	5.32	5.49	5.67	5.20	5.32	5.49	5.67																
	Amps	15.1	15.5	16.0	16.6	16.4	16.8	17.3	18.0	17.8	18.2	18.8	19.6	19.0	19.5	20.2	20.9	20.3	20.8	21.5	22.3	21.5	22.0	22.8	23.7	21.5	22.0	22.8	23.7	21.5	22.0	22.8	23.7																
	HI PR	241	259	274	285	270	291	307	320	307	331	349	364	350	377	398	415	394	424	447	467	435	468	494	515	435	468	494	515	435	468	494	515																
	LO PR	107	114	124	132	113	120	131	140	117	125	136	145	123	131	143	152	129	137	150	160	133	142	155	165	133	142	155	165	133	142	155	165																
	MBh	57.8	59.1	63.1	67.5	56.5	57.7	61.6	65.9	55.1	56.3	60.2	64.3	53.8	55.0	58.7	62.8	51.1	52.2	55.8	59.6	47.3	48.4	51.7	55.2	47.3	48.4	51.7	55.2	47.3	48.4	51.7	55.2																
	S/T	0.91	0.85	0.69	0.52	0.94	0.88	0.72	0.54	0.96	0.90	0.74	0.55	1.00	0.93	0.76	0.57	1.00	0.97	0.79	0.59	1.00	1.00	0.79	0.59	1.00	1.00	0.79	0.59	1.00	1.00	0.79	0.59																
	ΔT	24	23	20	16	24	23	20	16	24	23	20	16	25	24	20	16	23	23	20	16	22	22	19	15	22	22	19	15	22	22	19	15																
	kW	4.05	4.14	4.27	4.40	4.36	4.45	4.59	4.74	4.63	4.73	4.88	5.04	4.87	4.97	5.13	5.30	5.07	5.18	5.35	5.53	5.24	5.36	5.54	5.72	5.24	5.36	5.54	5.72	5.24	5.36	5.54	5.72																
	Amps	15.2	15.6	16.1	16.7	16.5	16.9	17.5	18.1	18.0	18.4	19.0	19.8	19.2	19.7	20.4	21.1	20.5	21.0	21.7	22.5	21.7	22.3	23.0	23.9	21.7	22.3	23.0	23.9	21.7	22.3	23.0	23.9																
	HI PR	243	262	276	288	273	294	310	323	310	334	353	368	353	380	402	419	398	428	452	471	439	473	499	521	439	473	499	521	439	473	499	521																
LO PR	108	115	125	133	114	121	132	141	118	126	137	146	124	132	144	154	130	139	151	161	135	143	157	167	135	143	157	167	135	143	157	167																	
85	MBh	52.7	53.7	56.3	60.0	51.5	52.5	55.0	58.6	50.3	51.2	53.7	57.2	49.0	50.0	52.3	55.8	46.6	47.5	49.7	53.1	43.1	44.0	46.1	49.1	43.1	44.0	46.1	49.1	43.1	44.0	46.1	49.1																
	S/T	0.87	0.84	0.76	0.62	0.91	0.87	0.79	0.64	0.93	0.90	0.81	0.66	0.96	0.93	0.83	0.68	1.00	0.96	0.87	0.70	1.00	0.97	0.87	0.71	1.00	0.97	0.87	0.71	1.00	0.97	0.87	0.71																
	ΔT	28	28	26	23	29	28	27	23	29	28	27	23	29	28	27	23	28	28	26	23	26	26	25	21	28	28	26	23	26	26	25	21																
	kW	3.96	4.04	4.17	4.30	4.26	4.35	4.48	4.62	4.52	4.61	4.76	4.92	4.75	4.85	5.01	5.17	4.94	5.05	5.22	5.39	5.11	5.23	5.40	5.58	5.11	5.23	5.40	5.58	5.11	5.23	5.40	5.58																
	Amps	14.8	15.2	15.7	16.3	16.0	16.4	17.0	17.6	17.5	17.9	18.5	19.2	18.7	19.1	19.8	20.5	19.9	20.4	21.1	21.9	21.1	21.6	22.4	23.2	21.1	21.6	22.4	23.2	21.1	21.6	22.4	23.2																
	HI PR	236	254	268	280	265	285	301	314	301	324	342	357	343	369	390	406	386	415	438	457	426	459	484	505	426	459	484	505	426	459	484	505																
	LO PR	105	111	121	129	110	118	128	137	115	122	133	142	121	128	140	149	126	134	147	156	131	139	152	162	131	139	152	162	131	139	152	162																
	MBh	57.1	58.2	61.0	65.0	55.8	56.9	59.6	63.5	54.5	55.5	58.1	62.0	53.1	54.2	56.7	60.5	50.5	51.4	53.9	57.5	46.7	47.7	49.9	53.2	46.7	47.7	49.9	53.2	46.7	47.7	49.9	53.2																
	S/T	0.91	0.87	0.79	0.64	0.94	0.91	0.82	0.66	0.96	0.93	0.84	0.68	0.99	0.96	0.87	0.70	1.00	1.00	0.90	0.73	1.00	1.00	0.91	0.74	1.00	1.00	0.91	0.74	1.00	1.00	0.91	0.74																
	ΔT	27	27	25	22	28	27	26	22	28	27	26	22	28	27	26	22	27	27	25	22	25	25	24	21	27	27	25	22	25	25	24	21																
2000	kW	4.05	4.14	4.27	4.40	4.36	4.45	4.59	4.74	4.63	4.73	4.88	5.04	4.87	4.97	5.13	5.30	5.07	5.18	5.35	5.53	5.24	5.36	5.54	5.72	5.24	5.36	5.54	5.72	5.24	5.36	5.54	5.72																
	Amps	15.2	15.6	16.1	16.7	16.5	16.9	17.5	18.1	18.0	18.4	19.0	19.8	19.2	19.7	20.4	21.1	20.5	21.0	21.7	22.5	21.7	22.3	23.0	23.9	21.7	22.3	23.0	23.9	21.7	22.3	23.0	23.9																
	HI PR	243	262	276	288	273	294	310	323	310	334	353	368	353	380	402	419	398	428	452	471	439	473	499	521	439	473	499	521	439	473	499	521																
	LO PR	108	115	125	133	114	121	132	141	118	126	137	146	124	132	144	154	130	139	151	161	135	143	157	167	135	143	157	167	135	143	157	167																
	MBh	58.8	60.0	62.8	67.0	57.5	58.6	61.3	65.4	56.1	57.2	59.9	63.9	54.7	55.8	58.4	62.3	52.0	53.0	55.5	59.2	48.2	49.1	51.4	54.8	48.2	49.1	51.4	54.8	48.2	49.1	51.4	54.8																
	S/T	0.95	0.92	0.83	0.67	0.99	0.95	0.86	0.70	1.00	0.97	0.88	0.71	1.00	1.00	0.91	0.74</																																

		OUTDOOR AMBIENT TEMPERATURE																											
		65				75				85				95				105				115							
		ENTERING INDOOR WET BULB TEMPERATURE																											
IDB	AIRFLOW	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71	59	63	67	71				
70	1500	MBh	53.8	55.7	61.0	-	52.5	54.4	59.6	-	51.3	53.1	58.2	-	50.0	51.8	56.8	-	47.5	49.2	53.9	-	44.0	45.6	50.0	-			
		S/T	0.66	0.55	0.38	-	0.68	0.57	0.39	-	0.70	0.58	0.40	-	0.72	0.60	0.42	-	0.75	0.62	0.43	-	0.75	0.63	0.44	-			
		ΔT	22	19	14	-	22	19	14	-	22	19	14	-	22	19	14	-	22	19	14	-	20	18	13	-			
		kW	3.97	4.05	4.18	-	4.27	4.37	4.51	-	4.54	4.64	4.80	-	4.78	4.89	5.05	-	4.99	5.10	5.27	-	5.16	5.28	5.45	-			
		Amps	15.4	15.8	16.3	-	16.7	17.1	17.6	-	18.1	18.6	19.2	-	19.4	19.9	20.6	-	20.7	21.2	21.9	-	22.0	22.5	23.3	-			
		HI PR	228	245	259	-	256	275	291	-	291	313	331	-	331	357	377	-	373	401	424	-	412	443	468	-			
70	1750	LO PR	98	104	114	-	103	110	120	-	107	114	125	-	113	120	131	-	118	126	137	-	122	130	142	-			
		MBh	55.4	57.4	62.9	-	54.1	56.1	61.4	-	52.8	54.7	59.9	-	51.5	53.4	58.5	-	48.9	50.7	55.6	-	45.3	47.0	51.5	-			
		S/T	0.69	0.57	0.40	-	0.71	0.60	0.41	-	0.73	0.61	0.42	-	0.75	0.63	0.44	-	0.78	0.65	0.45	-	0.79	0.66	0.46	-			
		ΔT	20	17	13	-	20	18	13	-	20	18	13	-	20	18	13	-	20	17	13	-	19	16	12	-			
		kW	4.00	4.09	4.21	-	4.31	4.40	4.54	-	4.58	4.68	4.84	-	4.82	4.93	5.09	-	5.03	5.14	5.31	-	5.20	5.32	5.50	-			
		Amps	15.5	15.9	16.4	-	16.8	17.2	17.8	-	18.3	18.8	19.4	-	19.6	20.1	20.8	-	20.9	21.4	22.2	-	22.2	22.7	23.5	-			
2000	2000	HI PR	230	248	262	-	258	278	294	-	294	316	334	-	335	360	380	-	377	405	428	-	416	448	473	-			
		LO PR	99	105	115	-	104	111	121	-	108	115	126	-	114	121	132	-	119	127	139	-	124	131	143	-			
		MBh	55.6	57.7	63.2	-	54.3	56.3	61.7	-	53.0	55.0	60.2	-	51.8	53.6	58.8	-	49.2	51.0	55.8	-	45.5	47.2	51.7	-			
		S/T	0.70	0.58	0.40	-	0.72	0.60	0.42	-	0.74	0.62	0.43	-	0.77	0.64	0.44	-	0.79	0.66	0.46	-	0.80	0.67	0.46	-			
		ΔT	18	15	12	-	18	16	12	-	18	16	12	-	18	16	12	-	18	16	12	-	17	15	11	-			
		kW	4.03	4.12	4.25	-	4.34	4.44	4.58	-	4.62	4.72	4.88	-	4.86	4.97	5.13	-	5.07	5.18	5.36	-	5.25	5.37	5.55	-			
75	1500	Amps	15.7	16.0	16.6	-	17.0	17.4	18.0	-	18.5	18.9	19.6	-	19.8	20.3	21.0	-	21.1	21.6	22.4	-	22.4	22.9	23.7	-			
		HI PR	233	250	264	-	261	281	297	-	297	319	337	-	338	364	384	-	380	409	432	-	420	452	477	-			
		LO PR	100	106	116	-	105	112	122	-	110	117	127	-	115	122	134	-	121	128	140	-	125	133	145	-			
		MBh	54.7	56.3	60.9	65.4	53.4	55.0	59.5	63.9	52.1	53.7	58.1	62.3	50.9	52.4	56.7	60.8	48.3	49.7	53.8	57.8	44.7	46.1	49.9	53.5			
		S/T	0.75	0.67	0.50	0.32	0.77	0.69	0.52	0.34	0.79	0.71	0.54	0.35	0.82	0.73	0.55	0.36	0.85	0.76	0.57	0.37	0.86	0.77	0.58	0.37			
		ΔT	25	23	19	13	25	23	19	13	25	23	19	13	26	23	19	13	25	23	19	13	23	22	18	12			
1750	1750	kW	4.00	4.09	4.22	4.35	4.31	4.40	4.55	4.69	4.58	4.68	4.84	5.00	4.82	4.93	5.09	5.26	5.03	5.14	5.31	5.49	5.20	5.32	5.50	5.69			
		Amps	15.5	15.9	16.4	17.1	16.8	17.2	17.8	18.5	18.3	18.8	19.4	20.2	19.6	20.1	20.8	21.6	20.9	21.4	22.2	23.0	22.2	22.7	23.5	24.4			
		HI PR	230	248	262	273	258	278	294	306	294	316	334	348	335	360	380	397	377	405	428	446	416	448	473	493			
		LO PR	99	105	115	122	104	111	121	129	108	115	126	134	114	121	132	141	119	127	139	148	124	131	143	153			
		MBh	56.3	58.0	62.7	67.3	55.0	56.6	61.3	65.8	53.7	55.3	59.8	64.2	52.4	53.9	58.4	62.6	49.8	51.2	55.5	59.5	46.1	47.5	51.4	55.1			
		S/T	0.78	0.70	0.53	0.34	0.81	0.72	0.55	0.35	0.83	0.74	0.56	0.36	0.86	0.77	0.58	0.37	0.89	0.80	0.60	0.39	0.90	0.80	0.61	0.39			
2000	2000	ΔT	23	21	17	12	23	22	18	12	23	22	18	12	24	22	18	12	23	21	18	12	22	20	16	11			
		kW	4.03	4.12	4.25	4.39	4.34	4.44	4.58	4.73	4.62	4.72	4.88	5.04	4.86	4.97	5.14	5.31	5.07	5.18	5.36	5.54	5.25	5.37	5.55	5.74			
		Amps	15.7	16.1	16.6	17.2	17.0	17.4	18.0	18.7	18.5	18.9	19.6	20.3	19.8	20.3	21.0	21.8	21.1	21.6	22.4	23.2	22.4	22.9	23.7	24.7			
		HI PR	233	250	264	276	261	281	297	309	297	320	337	352	338	364	384	401	380	409	432	451	420	452	478	498			
		LO PR	100	106	116	123	105	112	122	130	110	117	127	136	115	122	134	142	121	128	140	149	125	133	145	154			
		MBh	56.6	58.3	63.1	67.7	55.3	56.9	61.6	66.1	53.9	55.5	60.1	64.5	52.6	54.2	58.7	63.0	50.0	51.5	55.7	59.8	46.3	47.7	51.6	55.4			
75	1750	S/T	0.79	0.71	0.54	0.35	0.82	0.73	0.56	0.36	0.84	0.75	0.57	0.37	0.87	0.78	0.59	0.38	0.90	0.81	0.61	0.39	0.91	0.81	0.62	0.40			
		ΔT	21	19	16	11	21	19	16	11	21	19	16	11	21	19	16	11	21	19	16	11	19	18	15	10			
		kW	4.06	4.15	4.28	4.42	4.38	4.48	4.62	4.77	4.66	4.76	4.92	5.08	4.90	5.01	5.18	5.35	5.11	5.23	5.40	5.59	5.29	5.41	5.59	5.78			
		Amps	15.8	16.2	16.7	17.4	17.1	17.6	18.1	18.8	18.7	19.1	19.8	20.5	20.0	20.5	21.2	22.0	21.3	21.8	22.6	23.5	22.6	23.2	24.0	24.9			
		HI PR	235	253	267	278	264	284	300	312	300	323	341	355	341	367	388	405	384	413	437	455	424	457	482	503			
		LO PR	101	107	117	125	106	113	124	132	111	118	129	137	116	124	135	144	122	130	141	151	126	134	146	156			
IDB: Entering Indoor Dry Bulb Temperature		Shaded area reflects ACCA (TVA) conditions																								Amps = outdoor unit amps (comp.+fan)			
		High and low pressures are measured at the liquid and suction service valves.																								kW = Total system power			

IDB: Entering Indoor Dry Bulb Temperature

High and low pressures are measured at the liquid and suction service valves.

Shaded area reflects ACCA (TVA) conditions

Amps = outdoor unit amps (comp.+fan)

kW = Total system power

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E*	ACNF18XX16D*		16,800	12,800	13.0	10.8	600	5039733
	ACNF24XX16D*		17,000	13,000	13.0	10.8	600	5039734
	ARUF18B14A*		17,200	13,100	13.0	11.0	600	5360107
	ARUF18B14A*+TXV		17,200	13,100	13.0	11.0	600	5378529
	ARUF18B14A*+TXV+HSK		17,200	13,100	13.0	11.0	600	9113421
	ARUF24B14C*+TXV		17,200	13,100	13.5	11.0	600	7084829
	ARUF24B14C*+TXV+HSK		17,200	13,100	13.5	11.0	600	9113434
	ARUF25B14A*		18,000	13,700	13.0	11.0	570	7984175
	ASPT25B14A*		17,600	13,400	14.0	12.0	580	8242040
	ASPT25B14A*+HSK		17,600	13,400	14.0	12.0	580	9113529
	ASPT29B14A*		18,000	13,700	14.0	12.0	560	8242041
	ASPT29B14A*+HSK		18,000	13,700	14.0	12.0	560	9113530
	ASPT30C14A*		18,000	13,700	14.0	12.0	580	5722522
	ASPT30C14A*+HSK		18,000	13,700	14.0	12.0	580	9113426
	AVPTC24B14A*		17,600	13,400	14.0	12.0	600	5924342
	AVPTC24B14A*+HSK		17,600	13,400	14.0	12.0	600	9113427
	AVPTC25B14A*		17,800	13,600	14.0	12.0	640	8996110
	AVPTC25B14A*+HSK		17,800	13,600	14.0	12.0	640	9113531
	AVPTC29B14A*		18,000	13,700	14.0	12.0	585	8996111
	AVPTC29B14A*+HSK		18,000	13,700	14.0	12.0	585	9113532
	AVPTC30C14A*		18,000	13,700	14.0	12.0	615	5924442
	AVPTC30C14A*+HSK		18,000	13,700	14.0	12.0	615	9113428
	AWUF18XX16B*		17,200	13,100	13.0	11.0	600	5039739
	AWUF24XX16B*		17,400	13,300	13.0	11.0	650	7487211
	AWUF31XX16A*		17,200	13,100	14.0	11.3	600	5039740
	CA*F1824*6D*	G*EC960303ANA*	17,800	13,600	13.5	11.5	650	10515927
	CA*F1824*6D*	G*EC960403ANA*	17,800	13,600	13.5	11.5	610	10515932
	CA*F1824*6D*	G*EC960603ANA*	17,400	13,300	14.0	11.5	580	10515937
	CA*F1824*6D*	G*EC960403BNA*	17,800	13,600	13.5	11.5	625	10338172
	CA*F1824*6D*	G*VC80603B*B*	17,800	13,900	14.0	11.5	600	9923146
	CA*F1824*6D*	G*VC80803B*B*	17,800	13,900	14.0	11.5	600	9923159
	CA*F1824*6D*	A*VM970803BNA*	17,800	13,600	14.0	11.5	630	7353498
	CA*F1824*6D*	A*VC960603BNA*	17,800	13,600	14.0	11.5	600	7353495
	CA*F1824*6D*	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365239
	CA*F1824*6D*	G*VM970803BNA*	17,800	13,600	14.0	11.5	630	7353503
	CA*F1824*6D*	G*E80603B*B*	17,800	13,600	14.0	11.5	640	5039744
	CA*F1824*6D*	G*VC960403BNA*	17,800	13,600	14.0	11.5	625	7353499
	CA*F1824*6D*	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365345
	CA*F1824*6D*	G*VC80604B*B*	18,000	13,700	14.0	11.5	670	5039746
	CA*F1824*6D*	A*VC80604B*B*	18,000	13,700	14.0	11.5	675	5039742
	CA*F1824*6D*	G*VC960803BNA*	17,800	13,600	14.0	11.5	630	7353501
	CA*F1824*6D*	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365224
	CA*F1824*6D*	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365340
	CA*F1824*6D*	G*VM970603BNA*	17,800	13,600	14.0	11.5	600	7353502
	CA*F1824*6D*	G*VC960603BNA*	17,800	13,600	14.0	11.5	600	7353500
	CA*F1824*6D*	A*VC960403BNA*	17,800	13,600	14.0	11.5	625	7353494
	CA*F1824*6D*	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365229
	CA*F1824*6D*	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365335

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CA*F1824*6D*	A*EH800603B*A*	17,800	13,600	14.0	11.5	640	6944831
	CA*F1824*6D*	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365234
	CA*F1824*6D*	A*VC960803BNA*	17,800	13,600	14.0	11.5	630	7353496
	CA*F1824*6D*	A*VM970603BNA*	17,800	13,600	14.0	11.5	600	7353497
	CA*F1824*6D*	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365330
	CA*F1824*6D*+EEP		17,800	13,600	13.0	11.0	650	5039750
	CA*F1824*6D*+MBVC1200**-1A*		18,200	13,900	14.0	11.5	640	5039751
	CA*F1824*6D*+TXV	G*VM970603BNA*	17,800	13,600	14.0	11.5	600	7353512
	CA*F1824*6D*+TXV	A*VM970603BNA*	17,800	13,600	14.0	11.5	600	7353507
	CA*F1824*6D*+TXV	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365225
	CA*F1824*6D*+TXV	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365331
	CA*F1824*6D*+TXV	G*VC960803BNA*	17,800	13,600	14.0	11.5	630	7353511
	CA*F1824*6D*+TXV	A*VC960603BNA*	17,800	13,600	14.0	11.5	600	7353505
	CA*F1824*6D*+TXV	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365235
	CA*F1824*6D*+TXV	G*VC960603BNA*	17,800	13,600	14.0	11.5	600	7353510
	CA*F1824*6D*+TXV	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365341
	CA*F1824*6D*+TXV	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365240
	CA*F1824*6D*+TXV	A*VC960803BNA*	17,800	13,600	14.0	11.5	630	7353506
	CA*F1824*6D*+TXV	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365336
	CA*F1824*6D*+TXV	G*VM970803BNA*	17,800	13,600	14.0	11.5	630	7353513
	CA*F1824*6D*+TXV	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365346
	CA*F1824*6D*+TXV	G*VC960403BNA*	17,800	13,600	14.0	11.5	625	7353509
	CA*F1824*6D*+TXV	A*VM970803BNA*	17,800	13,600	14.0	11.5	630	7353508
	CA*F1824*6D*+TXV	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365230
	CA*F1824*6D*+TXV	A*VC960403BNA*	17,800	13,600	14.0	11.5	625	7353504
	CA*F1824*6D*+TXV+HSK	G*EC960303ANA*	17,800	13,600	14.0	12.0	650	10515928
	CA*F1824*6D*+TXV+HSK	G*EC960403ANA*	17,800	13,600	14.0	11.5	610	10515933
	CA*F1824*6D*+TXV+HSK	G*EC960603ANA*	17,400	13,300	14.0	12.0	580	10515938
	CA*F1824*6D*+TXV+HSK	G*EC960403BNA*	17,800	13,600	14.0	12.0	625	10338173
	CA*F1824*6D*+TXV+HSK	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923147
	CA*F1824*6D*+TXV+HSK	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923160
	CA*F1824*6D*+TXV+HSK	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	9113514
	CA*F1824*6D*+TXV+HSK	G*VC960403BNA*	17,800	13,600	14.0	11.5	625	9113440
	CA*F1824*6D*+TXV+HSK	G*VM970603BNA*	17,800	13,600	14.0	11.5	600	9113443
	CA*F1824*6D*+TXV+HSK	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	9113511
	CA*F1824*6D*+TXV+HSK	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	9113523
	CA*F1824*6D*+TXV+HSK	A*VM970803BNA*	17,800	13,600	14.0	11.5	630	9113439
	CA*F1824*6D*+TXV+HSK	A*VM970603BNA*	17,800	13,600	14.0	11.5	600	9113438
	CA*F1824*6D*+TXV+HSK	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	9113508
	CA*F1824*6D*+TXV+HSK	A*VC960803BNA*	17,800	13,600	14.0	11.5	630	9113437
	CA*F1824*6D*+TXV+HSK	A*VC960603BNA*	17,800	13,600	14.0	11.5	600	9113436
	CA*F1824*6D*+TXV+HSK	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	9113526
	CA*F1824*6D*+TXV+HSK	A*VC960403BNA*	17,800	13,600	14.0	11.5	625	9113435
	CA*F1824*6D*+TXV+HSK	G*VM970803BNA*	17,800	13,600	14.0	11.5	630	9113444
	CA*F1824*6D*+TXV+HSK	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	9113517
	CA*F1824*6D*+TXV+HSK	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	9113520
	CA*F1824*6D*+TXV+HSK	G*VC960603BNA*	17,800	13,600	14.0	11.5	600	9113441
	CA*F1824*6D*+TXV+HSK	G*VC960803BNA*	17,800	13,600	14.0	11.5	630	9113442

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CA*F1824*6D*+TXV+HSK	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	9113505
	CA*F3030*6D*+EEP		18,000	13,700	13.0	11.0	650	5561904
	CA*F3030*6D*+EEP+TXV		18,000	13,700	13.0	11.0	650	5581977
	CA*F3030*6D*+EEP+TXV+HSK		18,000	13,700	13.0	11.0	650	9113423
	CA*F3131*6D*+EEP		18,000	13,700	13.0	11.0	650	5561905
	CA*F3131*6D*+EEP+TXV		18,000	13,700	13.0	11.0	650	5561906
	CA*F3131*6D*+EEP+TXV+HSK		18,000	13,700	13.0	11.0	650	9113422
	CA*F3636*6D*	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923148
	CA*F3636*6D*	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923161
	CA*F3636*6D*	A*VC960603BNA*	18,400	14,000	14.0	11.5	600	7353515
	CA*F3636*6D*	A*VC960403BNA*	18,400	14,000	14.0	11.5	625	7353514
	CA*F3636*6D*	A*VC960803BNA*	18,400	14,000	14.0	11.5	630	7353516
	CA*F3636*6D*	G*VC960803BNA*	18,400	14,000	14.0	11.5	630	7353521
	CA*F3636*6D*	A*VM970803BNA*	18,400	14,000	14.0	11.5	630	7353518
	CA*F3636*6D*	G*VC960603BNA*	18,400	14,000	14.0	11.5	600	7353520
	CA*F3636*6D*	G*VM970603BNA*	18,400	14,000	14.0	11.5	600	7353522
	CA*F3636*6D*	G*VM970803BNA*	18,400	14,000	14.0	11.5	630	7353523
	CA*F3636*6D*	G*VC960403BNA*	18,400	14,000	14.0	11.5	625	7353519
	CA*F3636*6D*	A*VM970603BNA*	18,400	14,000	14.0	11.5	600	7353517
	CA*F3636*6D*+TXV	A*VC960603BNA*	18,400	14,000	14.0	11.5	600	7353525
	CA*F3636*6D*+TXV	G*VC960403BNA*	18,400	14,000	14.0	11.5	625	7353529
	CA*F3636*6D*+TXV	G*VC960803BNA*	18,400	14,000	14.0	11.5	630	7353531
	CA*F3636*6D*+TXV	A*VC960403BNA*	18,400	14,000	14.0	11.5	625	7353524
	CA*F3636*6D*+TXV	G*VC960603BNA*	18,400	14,000	14.0	11.5	600	7353530
	CA*F3636*6D*+TXV	A*VM970603BNA*	18,400	14,000	14.0	11.5	600	7353527
	CA*F3636*6D*+TXV	G*VM970603BNA*	18,400	14,000	14.0	11.5	600	7353532
	CA*F3636*6D*+TXV	A*VM970803BNA*	18,400	14,000	14.0	11.5	630	7353528
	CA*F3636*6D*+TXV	A*VC960803BNA*	18,400	14,000	14.0	11.5	630	7353526
	CA*F3636*6D*+TXV	G*VM970803BNA*	18,400	14,000	14.0	11.5	630	7353533
	CA*F3636*6D*+TXV+HSK	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923149
	CA*F3636*6D*+TXV+HSK	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923162
	CA*F3636*6D*+TXV+HSK	G*VM970603BNA*	18,400	14,000	14.0	11.5	600	9113453
	CA*F3636*6D*+TXV+HSK	G*VM970803BNA*	18,400	14,000	14.0	11.5	630	9113454
	CA*F3636*6D*+TXV+HSK	A*VC960803BNA*	18,400	14,000	14.0	11.5	630	9113447
	CA*F3636*6D*+TXV+HSK	A*VC960603BNA*	18,400	14,000	14.0	11.5	600	9113446
	CA*F3636*6D*+TXV+HSK	G*VC960603BNA*	18,400	14,000	14.0	11.5	600	9113451
	CA*F3636*6D*+TXV+HSK	A*VM970803BNA*	18,400	14,000	14.0	11.5	630	9113449
	CA*F3636*6D*+TXV+HSK	A*VC960403BNA*	18,400	14,000	14.0	11.5	625	9113445
	CA*F3636*6D*+TXV+HSK	G*VC960803BNA*	18,400	14,000	14.0	11.5	630	9113452
	CA*F3636*6D*+TXV+HSK	A*VM970603BNA*	18,400	14,000	14.0	11.5	600	9113448
	CA*F3636*6D*+TXV+HSK	G*VC960403BNA*	18,400	14,000	14.0	11.5	625	9113450
	CAPT3131*4A*	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365241
	CAPT3131*4A*	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353535
	CAPT3131*4A*	A*VC80604B*B*	18,000	13,700	14.0	11.5	675	5948598
	CAPT3131*4A*	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365337
	CAPT3131*4A*	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353543
	CAPT3131*4A*	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365347
	CAPT3131*4A*	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365332

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CAPT3131*4A*	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353534
	CAPT3131*4A*	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353541
	CAPT3131*4A*	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365231
	CAPT3131*4A*	ADVC80603B*B*	18,000	13,700	14.0	11.5	675	5948610
	CAPT3131*4A*	G*VC80604B*B*	18,000	13,700	14.0	11.5	675	5948614
	CAPT3131*4A*	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353539
	CAPT3131*4A*	G*E80603B*B*	18,000	13,700	14.0	11.5	650	5948612
	CAPT3131*4A*	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353540
	CAPT3131*4A*	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353537
	CAPT3131*4A*	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353542
	CAPT3131*4A*	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353536
	CAPT3131*4A*	A*EH800603B*A*	18,000	13,700	14.0	11.5	650	6944836
	CAPT3131*4A*	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353538
	CAPT3131*4A*	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365342
	CAPT3131*4A*	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365226
	CAPT3131*4A*	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365236
	CAPT3131*4A*+EEP		17,400	13,300	13.0	11.0	650	5611304
	CAPT3131*4A*+EEP+HSK		17,400	13,300	13.0	11.0	650	9113424
	CAPT3131*4A*+HSK	G*EC960303ANA*	17,800	13,600	13.5	11.5	650	10515929
	CAPT3131*4A*+HSK	G*EC960403ANA*	17,800	13,600	13.5	11.5	610	10515934
	CAPT3131*4A*+HSK	G*EC960603ANA*	17,400	13,300	14.0	12.0	580	10515939
	CAPT3131*4A*+HSK	G*EC960403BNA*	18,000	13,700	14.0	12.0	625	10338174
	CAPT3131*4A*+HSK	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923150
	CAPT3131*4A*+HSK	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923163
	CAPT3131*4A*+HSK	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	9113459
	CAPT3131*4A*+HSK	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	9113461
	CAPT3131*4A*+HSK	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	9113455
	CAPT3131*4A*+HSK	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	9113515
	CAPT3131*4A*+HSK	A*EH800603B*A*	18,000	13,700	14.0	11.5	650	9113433
	CAPT3131*4A*+HSK	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	9113462
	CAPT3131*4A*+HSK	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	9113463
	CAPT3131*4A*+HSK	A*VC80604B*B*	18,000	13,700	14.0	11.5	675	9113429
	CAPT3131*4A*+HSK	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	9113518
	CAPT3131*4A*+HSK	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	9113521
	CAPT3131*4A*+HSK	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	9113464
	CAPT3131*4A*+HSK	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	9113524
	CAPT3131*4A*+HSK	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	9113457
	CAPT3131*4A*+HSK	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	9113506
	CAPT3131*4A*+HSK	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	9113458
	CAPT3131*4A*+HSK	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	9113512
	CAPT3131*4A*+HSK	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	9113456
	CAPT3131*4A*+HSK	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	9113509
	CAPT3131*4A*+HSK	G*VC80604B*B*	18,000	13,700	14.0	11.5	675	9113432
	CAPT3131*4A*+HSK	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	9113527
	CAPT3131*4A*+HSK	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	9113460
	CAPT3131*4A*+HSK	G*E80603B*B*	18,000	13,700	14.0	11.5	650	9113431
	CAPT3131*4A*+HSK	ADVC80603B*B*	18,000	13,700	14.0	11.5	675	9113430
	CAPT3131*4A*+MBVC1200**-1A*		17,400	13,300	14.0	11.5	650	5611305

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CAPT3131*4A*+MBVC1200**-1A*+HSK		17,400	13,300	14.0	11.5	650	9113425
	CHPF1824A6C*+EEP		17,800	13,600	13.0	11.0	650	5039752
	CHPF2430B6C*	G*EC960303ANA*	17,800	13,600	13.5	11.5	650	10515930
	CHPF2430B6C*	G*EC960403ANA*	17,800	13,600	13.5	11.5	610	10515935
	CHPF2430B6C*	G*EC960603ANA*	17,400	13,300	14.0	11.5	580	10515940
	CHPF2430B6C*	G*EC960403BNA*	18,000	13,700	13.5	11.5	625	10338175
	CHPF2430B6C*	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923151
	CHPF2430B6C*	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923164
	CHPF2430B6C*	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365227
	CHPF2430B6C*	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365333
	CHPF2430B6C*	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353547
	CHPF2430B6C*	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353552
	CHPF2430B6C*	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365242
	CHPF2430B6C*	G*E80603B*B*	18,000	13,700	14.0	11.5	640	5039754
	CHPF2430B6C*	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353546
	CHPF2430B6C*	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365343
	CHPF2430B6C*	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353549
	CHPF2430B6C*	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353544
	CHPF2430B6C*	A*EH800603B*A*	18,000	13,700	14.0	11.5	640	6944845
	CHPF2430B6C*	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353553
	CHPF2430B6C*	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353548
	CHPF2430B6C*	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365237
	CHPF2430B6C*	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365338
	CHPF2430B6C*	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353550
	CHPF2430B6C*	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365348
	CHPF2430B6C*	A*VC80604B*B*	17,700	13,500	14.0	11.5	660	5039796
	CHPF2430B6C*	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353551
	CHPF2430B6C*	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353545
	CHPF2430B6C*	G*VC80604B*B*	17,700	13,500	14.0	11.5	660	5039798
	CHPF2430B6C*	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365232
	CHPF2430B6C*+EEP		17,800	13,600	13.0	11.0	650	5039758
	CHPF2430B6C*+MBVC1200**-1A*		18,200	13,900	14.0	11.5	650	5039759
	CHPF2430B6C*+TXV	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353556
	CHPF2430B6C*+TXV	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353560
	CHPF2430B6C*+TXV	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365339
	CHPF2430B6C*+TXV	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365228
	CHPF2430B6C*+TXV	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365238
	CHPF2430B6C*+TXV	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353555
	CHPF2430B6C*+TXV	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353559
	CHPF2430B6C*+TXV	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	7365233
	CHPF2430B6C*+TXV	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365349
	CHPF2430B6C*+TXV	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353563
	CHPF2430B6C*+TXV	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	7365344
	CHPF2430B6C*+TXV	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353554
	CHPF2430B6C*+TXV	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353562
	CHPF2430B6C*+TXV	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353561
	CHPF2430B6C*+TXV	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353557
	CHPF2430B6C*+TXV	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	7365243

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CHPF2430B6C*+TXV	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	7365334
	CHPF2430B6C*+TXV	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353558
	CHPF2430B6C*+TXV+HSK	G*EC960303ANA*	17,800	13,600	14.0	12.0	650	10515931
	CHPF2430B6C*+TXV+HSK	G*EC960403ANA*	17,800	13,600	14.0	11.5	610	10515936
	CHPF2430B6C*+TXV+HSK	G*EC960603ANA*	17,400	13,300	14.0	11.5	580	10515941
	CHPF2430B6C*+TXV+HSK	G*EC960403BNA*	18,000	13,700	14.0	12.0	625	10338176
	CHPF2430B6C*+TXV+HSK	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923152
	CHPF2430B6C*+TXV+HSK	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923165
	CHPF2430B6C*+TXV+HSK	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	9113465
	CHPF2430B6C*+TXV+HSK	G*EC960402BNA*	17,800	13,600	14.0	11.5	600	9113510
	CHPF2430B6C*+TXV+HSK	A*EC960803BNA*	17,800	13,600	14.0	11.5	575	9113528
	CHPF2430B6C*+TXV+HSK	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	9113468
	CHPF2430B6C*+TXV+HSK	G*EC960603BNA*	17,400	13,300	14.0	11.5	550	9113513
	CHPF2430B6C*+TXV+HSK	A*EC960603BNA*	17,400	13,300	14.0	11.5	550	9113525
	CHPF2430B6C*+TXV+HSK	A*EC960402BNA*	17,800	13,600	14.0	11.5	600	9113522
	CHPF2430B6C*+TXV+HSK	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	9113466
	CHPF2430B6C*+TXV+HSK	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	9113473
	CHPF2430B6C*+TXV+HSK	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	9113467
	CHPF2430B6C*+TXV+HSK	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	9113470
	CHPF2430B6C*+TXV+HSK	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	9113471
	CHPF2430B6C*+TXV+HSK	A*EC960302BNA*	17,800	13,600	14.0	11.5	600	9113519
	CHPF2430B6C*+TXV+HSK	G*EC960803BNA*	17,800	13,600	14.0	11.5	575	9113516
	CHPF2430B6C*+TXV+HSK	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	9113472
	CHPF2430B6C*+TXV+HSK	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	9113474
	CHPF2430B6C*+TXV+HSK	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	9113469
	CHPF2430B6C*+TXV+HSK	G*EC960302BNA*	17,800	13,600	14.0	11.5	600	9113507
	CHPF3636B6C*	G*VC80603B*B*	17,600	13,800	14.0	11.5	600	9923153
	CHPF3636B6C*	G*VC80803B*B*	17,600	13,800	14.0	11.5	600	9923166
	CHPF3636B6C*	G*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353570
	CHPF3636B6C*	A*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353566
	CHPF3636B6C*	A*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353564
	CHPF3636B6C*	G*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353569
	CHPF3636B6C*	G*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353572
	CHPF3636B6C*	G*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353573
	CHPF3636B6C*	A*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353565
	CHPF3636B6C*	A*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353568
	CHPF3636B6C*	A*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353567
	CHPF3636B6C*	G*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353571
	CHPF3636B6C*+TXV	A*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353577
	CHPF3636B6C*+TXV	G*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353581
	CHPF3636B6C*+TXV	A*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353576
	CHPF3636B6C*+TXV	A*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353574
	CHPF3636B6C*+TXV	A*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353578
	CHPF3636B6C*+TXV	A*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353575
	CHPF3636B6C*+TXV	G*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353583
	CHPF3636B6C*+TXV	G*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353582
	CHPF3636B6C*+TXV	G*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353580
	CHPF3636B6C*+TXV	G*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353579

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CHPF3636B6C*+TXV+HSK	G*VC80603B*B*	17,600	13,800	14.0	11.5	600	9923154
	CHPF3636B6C*+TXV+HSK	G*VC80803B*B*	17,600	13,800	14.0	11.5	600	9923167
	CHPF3636B6C*+TXV+HSK	G*VC960403BNA*	18,200	13,900	14.0	11.5	625	9113480
	CHPF3636B6C*+TXV+HSK	A*VM970603BNA*	18,200	13,900	14.0	11.5	600	9113478
	CHPF3636B6C*+TXV+HSK	A*VC960603BNA*	18,200	13,900	14.0	11.5	600	9113476
	CHPF3636B6C*+TXV+HSK	G*VM970803BNA*	18,200	13,900	14.0	11.5	630	9113484
	CHPF3636B6C*+TXV+HSK	G*VM970603BNA*	18,200	13,900	14.0	11.5	600	9113483
	CHPF3636B6C*+TXV+HSK	G*VC960603BNA*	18,200	13,900	14.0	11.5	600	9113481
	CHPF3636B6C*+TXV+HSK	A*VM970803BNA*	18,200	13,900	14.0	11.5	630	9113479
	CHPF3636B6C*+TXV+HSK	G*VC960803BNA*	18,200	13,900	14.0	11.5	630	9113482
	CHPF3636B6C*+TXV+HSK	A*VC960803BNA*	18,200	13,900	14.0	11.5	630	9113477
	CHPF3636B6C*+TXV+HSK	A*VC960403BNA*	18,200	13,900	14.0	11.5	625	9113475
	CSCF1824N6D*	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923155
	CSCF1824N6D*	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923168
	CSCF1824N6D*	A*EH800603B*A*	18,000	13,700	14.0	11.5	640	6944850
	CSCF1824N6D*	A*VC80604B*B*	17,700	13,500	14.0	11.5	660	5039800
	CSCF1824N6D*	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353585
	CSCF1824N6D*	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	7353590
	CSCF1824N6D*	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353587
	CSCF1824N6D*	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353589
	CSCF1824N6D*	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353591
	CSCF1824N6D*	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353593
	CSCF1824N6D*	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	7353584
	CSCF1824N6D*	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	7353592
	CSCF1824N6D*	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	7353586
	CSCF1824N6D*	G*E80603B*B*	18,000	13,700	14.0	11.5	640	5039760
	CSCF1824N6D*	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	7353588
	CSCF1824N6D*	G*VC80604B*B*	17,700	13,500	14.0	11.5	660	5039801
	CSCF1824N6D*+EEP		17,800	13,600	13.0	11.0	650	5039763
	CSCF1824N6D*+TXV	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	7354991
	CSCF1824N6D*+TXV	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	7354989
	CSCF1824N6D*+TXV	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	7354986
	CSCF1824N6D*+TXV	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	7354988
	CSCF1824N6D*+TXV	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	7354985
	CSCF1824N6D*+TXV	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	7354994
	CSCF1824N6D*+TXV	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	7354990
	CSCF1824N6D*+TXV	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	7354987
	CSCF1824N6D*+TXV	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	7354992
	CSCF1824N6D*+TXV	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	7354993
	CSCF1824N6D*+TXV+HSK	G*VC80603B*B*	18,000	14,100	14.0	11.5	600	9923156
	CSCF1824N6D*+TXV+HSK	G*VC80803B*B*	18,000	14,100	14.0	11.5	600	9923169
	CSCF1824N6D*+TXV+HSK	A*VC960803BNA*	18,000	13,700	14.0	11.5	630	9113497
	CSCF1824N6D*+TXV+HSK	G*VC960603BNA*	18,000	13,700	14.0	11.5	600	9113501
	CSCF1824N6D*+TXV+HSK	G*VC960803BNA*	18,000	13,700	14.0	11.5	630	9113502
	CSCF1824N6D*+TXV+HSK	A*VM970803BNA*	18,000	13,700	14.0	11.5	630	9113499
	CSCF1824N6D*+TXV+HSK	G*VC960403BNA*	18,000	13,700	14.0	11.5	625	9113500
	CSCF1824N6D*+TXV+HSK	A*VC960403BNA*	18,000	13,700	14.0	11.5	625	9113495
	CSCF1824N6D*+TXV+HSK	A*VC960603BNA*	18,000	13,700	14.0	11.5	600	9113496

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0181E* (Contd.)	CSCF1824N6D*+TXV+HSK	G*VM970803BNA*	18,000	13,700	14.0	11.5	630	9113504
	CSCF1824N6D*+TXV+HSK	G*VM970603BNA*	18,000	13,700	14.0	11.5	600	9113503
	CSCF1824N6D*+TXV+HSK	A*VM970603BNA*	18,000	13,700	14.0	11.5	600	9113498
	CSCF3036N6D*	G*VC80603B*B*	17,800	13,900	14.0	11.5	600	9923157
	CSCF3036N6D*	G*VC80803B*B*	17,800	13,900	14.0	11.5	600	9923170
	CSCF3036N6D*	G*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353599
	CSCF3036N6D*	A*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353597
	CSCF3036N6D*	A*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353594
	CSCF3036N6D*	A*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353598
	CSCF3036N6D*	G*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353603
	CSCF3036N6D*	A*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353596
	CSCF3036N6D*	G*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353602
	CSCF3036N6D*	G*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353600
	CSCF3036N6D*	A*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353595
	CSCF3036N6D*	G*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353601
	CSCF3036N6D*+TXV	A*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353608
	CSCF3036N6D*+TXV	G*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353610
	CSCF3036N6D*+TXV	G*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353611
	CSCF3036N6D*+TXV	A*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353604
	CSCF3036N6D*+TXV	A*VC960603BNA*	18,200	13,900	14.0	11.5	600	7353605
	CSCF3036N6D*+TXV	G*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353612
	CSCF3036N6D*+TXV	G*VC960403BNA*	18,200	13,900	14.0	11.5	625	7353609
	CSCF3036N6D*+TXV	A*VM970603BNA*	18,200	13,900	14.0	11.5	600	7353607
	CSCF3036N6D*+TXV	A*VC960803BNA*	18,200	13,900	14.0	11.5	630	7353606
	CSCF3036N6D*+TXV	G*VM970803BNA*	18,200	13,900	14.0	11.5	630	7353613
	CSCF3036N6D*+TXV+HSK	G*VC80603B*B*	17,800	13,900	14.0	11.5	600	9923158
	CSCF3036N6D*+TXV+HSK	G*VC80803B*B*	17,800	13,900	14.0	11.5	600	9923171
	CSCF3036N6D*+TXV+HSK	A*VM970803BNA*	18,200	13,900	14.0	11.5	630	9113489
	CSCF3036N6D*+TXV+HSK	G*VM970603BNA*	18,200	13,900	14.0	11.5	600	9113493
	CSCF3036N6D*+TXV+HSK	A*VM970603BNA*	18,200	13,900	14.0	11.5	600	9113488
	CSCF3036N6D*+TXV+HSK	G*VM970803BNA*	18,200	13,900	14.0	11.5	630	9113494
	CSCF3036N6D*+TXV+HSK	A*VC960403BNA*	18,200	13,900	14.0	11.5	625	9113485
	CSCF3036N6D*+TXV+HSK	G*VC960603BNA*	18,200	13,900	14.0	11.5	600	9113491
	CSCF3036N6D*+TXV+HSK	A*VC960603BNA*	18,200	13,900	14.0	11.5	600	9113486
	CSCF3036N6D*+TXV+HSK	A*VC960803BNA*	18,200	13,900	14.0	11.5	630	9113487
	CSCF3036N6D*+TXV+HSK	G*VC960403BNA*	18,200	13,900	14.0	11.5	625	9113490
	CSCF3036N6D*+TXV+HSK	G*VC960803BNA*	18,200	13,900	14.0	11.5	630	9113492
GSX13 0241E*	ACNF24XX16D*		22,400	16,600	13.0	11.0	770	8377184
	ACNF30XX16D*		22,600	16,700	13.0	11.0	845	8377323
	ARUF24B14C*+TXV+HSK		22,000	16,300	13.0	11.0	800	8377163
	ARUF29B14A*		23,400	17,300	13.0	11.0	860	8377265
	ASPT24B14A*+HSK		23,000	17,000	13.8	11.8	810	8377322
	ASPT25B14A*+HSK		23,000	17,000	14.0	12.0	800	8377172
	ASPT29B14A*+HSK		23,800	17,600	14.0	12.0	790	8377349
	ASPT30C14A*+HSK		23,400	17,300	14.0	12.0	845	8377211
	AVPTC24B14A*+HSK		22,600	16,700	14.0	12.0	800	8377161
	AVPTC25B14A*		23,000	17,000	14.0	12.0	850	8996112
	AVPTC25B14A*+HSK		23,000	17,000	14.0	12.0	850	9113533

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	AVPTC29B14A*		23,400	17,300	14.0	12.0	795	8996113
	AVPTC29B14A*+HSK		23,400	17,300	14.0	12.0	795	9113534
	AVPTC30C14A*+HSK		23,400	17,300	14.0	12.0	780	8377246
	AWUF24XX16B*		23,000	17,000	13.0	11.0	800	8377259
	AWUF30XX16B*		23,200	17,200	13.0	11.0	800	8377356
	AWUF31XX16A*		23,000	17,000	14.0	11.3	800	8377213
	AWUF32XX16A*		23,000	17,000	14.0	11.3	800	8377134
	CA*F1824*6D*	G*EC960303ANA*	23,000	17,000	13.5	11.5	800	10515945
	CA*F1824*6D*	G*EC960403ANA*	23,000	17,000	13.5	11.5	800	10515950
	CA*F1824*6D*	G*EC960603ANA*	23,000	17,000	13.5	11.5	775	10515942
	CA*F1824*6D*	G*EC960403BNA*	22,600	16,700	14.0	11.5	800	10338177
	CA*F1824*6D*	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923172
	CA*F1824*6D*	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923185
	CA*F1824*6D*	G*VC80804C*B*	23,000	17,500	14.0	11.6	800	9923198
	CA*F1824*6D*	G*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377346
	CA*F1824*6D*	G*E80603B*B*	23,000	17,000	14.0	11.5	860	8377182
	CA*F1824*6D*	A*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377194
	CA*F1824*6D*	G*VC80604B*B*	23,000	17,000	14.0	11.6	820	8377114
	CA*F1824*6D*	A*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377315
	CA*F1824*6D*	G*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377298
	CA*F1824*6D*	A*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377336
	CA*F1824*6D*	G*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377248
	CA*F1824*6D*	G*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377131
	CA*F1824*6D*	G*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377250
	CA*F1824*6D*	G*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377154
	CA*F1824*6D*	A*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377124
	CA*F1824*6D*	G*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377324
	CA*F1824*6D*	A*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377354
	CA*F1824*6D*	A*EH800603B*A*	23,000	17,000	14.0	11.5	860	8377217
	CA*F1824*6D*	A*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377306
	CA*F1824*6D*	A*VC80604B*B*	23,000	17,000	14.0	11.6	820	8377177
	CA*F1824*6D*	G*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377223
	CA*F1824*6D*	G*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377160
	CA*F1824*6D*	A*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377138
	CA*F1824*6D*	A*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377191
	CA*F1824*6D*	A*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377309
	CA*F1824*6D*	G*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377244
	CA*F1824*6D*	A*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377239
	CA*F1824*6D*	A*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377151
	CA*F1824*6D*	G*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377262
	CA*F1824*6D*+EEP		23,000	17,000	13.0	11.0	800	8377316
	CA*F1824*6D*+MBVC1200**-1A*		23,000	17,000	14.0	11.5	800	8377227
	CA*F1824*6D*+TXV+HSK	G*EC960303ANA*	23,000	17,000	14.0	11.5	800	10515946
	CA*F1824*6D*+TXV+HSK	G*EC960403ANA*	23,000	17,000	14.0	11.5	800	10515951
	CA*F1824*6D*+TXV+HSK	G*EC960603ANA*	23,000	17,000	14.0	11.5	775	10515943
	CA*F1824*6D*+TXV+HSK	G*EC960403BNA*	22,600	16,700	14.0	12.0	800	10338178
	CA*F1824*6D*+TXV+HSK	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923173
	CA*F1824*6D*+TXV+HSK	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923186

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	CA*F1824*6D*+TXV+HSK	G*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377156
	CA*F1824*6D*+TXV+HSK	A*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377339
	CA*F1824*6D*+TXV+HSK	G*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377225
	CA*F1824*6D*+TXV+HSK	G*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377179
	CA*F1824*6D*+TXV+HSK	A*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377141
	CA*F1824*6D*+TXV+HSK	G*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377363
	CA*F1824*6D*+TXV+HSK	A*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377203
	CA*F1824*6D*+TXV+HSK	G*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377238
	CA*F1824*6D*+TXV+HSK	G*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377332
	CA*F1824*6D*+TXV+HSK	G*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377135
	CA*F1824*6D*+TXV+HSK	G*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377281
	CA*F1824*6D*+TXV+HSK	A*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377209
	CA*F1824*6D*+TXV+HSK	A*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377145
	CA*F1824*6D*+TXV+HSK	G*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377201
	CA*F1824*6D*+TXV+HSK	G*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377137
	CA*F1824*6D*+TXV+HSK	G*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377173
	CA*F1824*6D*+TXV+HSK	A*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377328
	CA*F1824*6D*+TXV+HSK	A*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377167
	CA*F1824*6D*+TXV+HSK	A*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377283
	CA*F1824*6D*+TXV+HSK	A*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377341
	CA*F1824*6D*+TXV+HSK	A*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377304
	CA*F1824*6D*+TXV+HSK	A*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377236
	CA*F3030*6D*+EEP		23,000	17,000	13.0	11.0	800	8377118
	CA*F3030*6D*+EEP+TXV+HSK		23,000	17,000	13.0	11.0	800	8377116
	CA*F3131*6D*+EEP		23,000	17,000	13.0	11.0	800	8377220
	CA*F3131*6D*+EEP+TXV+HSK		23,000	17,000	13.0	11.0	800	8377202
	CA*F3636*6D*	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923174
	CA*F3636*6D*	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923187
	CA*F3636*6D*	G*VM970803BNA*	23,600	17,500	14.0	11.5	810	8377185
	CA*F3636*6D*	G*VC960603BNA*	23,600	17,500	14.0	11.5	815	8377307
	CA*F3636*6D*	A*VM970603BNA*	23,600	17,500	14.0	11.5	815	8377199
	CA*F3636*6D*	A*VC960603BNA*	23,600	17,500	14.0	11.5	815	8377166
	CA*F3636*6D*	G*VC960803BNA*	23,600	17,500	14.0	11.5	810	8377360
	CA*F3636*6D*	A*VM970803BNA*	23,600	17,500	14.0	11.5	810	8377270
	CA*F3636*6D*	A*VC960803BNA*	23,600	17,500	14.0	11.5	810	8377280
	CA*F3636*6D*	G*VM970603BNA*	23,600	17,500	14.0	11.5	815	8377215
	CA*F3636*6D*	G*VC960403BNA*	23,600	17,500	14.0	11.5	805	8377200
	CA*F3636*6D*	A*VC960403BNA*	23,600	17,500	14.0	11.5	805	8377197
	CA*F3636*6D*+EEP		23,000	17,000	13.0	11.0	800	8377278
	CA*F3636*6D*+EEP+TXV+HSK		23,000	17,000	13.0	11.0	800	8377158
	CA*F3636*6D*+TXV+HSK	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923175
	CA*F3636*6D*+TXV+HSK	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923188
	CA*F3636*6D*+TXV+HSK	A*VC960403BNA*	23,600	17,500	14.0	11.5	805	8377333
	CA*F3636*6D*+TXV+HSK	G*VM970603BNA*	23,600	17,500	14.0	11.5	815	8377325
	CA*F3636*6D*+TXV+HSK	A*VC960803BNA*	23,600	17,500	14.0	11.5	810	8377256
	CA*F3636*6D*+TXV+HSK	G*VC960603BNA*	23,600	17,500	14.0	11.5	815	8377251
	CA*F3636*6D*+TXV+HSK	G*VM970803BNA*	23,600	17,500	14.0	11.5	810	8377233
	CA*F3636*6D*+TXV+HSK	G*VC960403BNA*	23,600	17,500	14.0	11.5	805	8377230

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	CA*F3636*6D*+TXV+HSK	A*VC960603BNA*	23,600	17,500	14.0	11.5	815	8377188
	CA*F3636*6D*+TXV+HSK	G*VC960803BNA*	23,600	17,500	14.0	11.5	810	8377299
	CA*F3636*6D*+TXV+HSK	A*VM970803BNA*	23,600	17,500	14.0	11.5	810	8377140
	CA*F3636*6D*+TXV+HSK	A*VM970603BNA*	23,600	17,500	14.0	11.5	815	8377155
	CA*F3743*6D*	A*VM970804CNA*	23,600	17,500	14.0	11.5	800	8377320
	CA*F3743*6D*	A*VC960804CNA*	23,600	17,500	14.0	11.5	800	8377303
	CA*F3743*6D*	G*VM970804CNA*	23,600	17,500	14.0	11.5	800	8377308
	CA*F3743*6D*	G*VC960804CNA*	23,600	17,500	14.0	11.5	800	8377231
	CA*F3743*6D*+TXV+HSK	A*VC960804CNA*	23,600	17,500	14.0	11.5	800	8377305
	CA*F3743*6D*+TXV+HSK	A*VM970804CNA*	23,600	17,500	14.0	11.5	800	8377295
	CA*F3743*6D*+TXV+HSK	G*VM970804CNA*	23,600	17,500	14.0	11.5	800	8377255
	CA*F3743*6D*+TXV+HSK	G*VC960804CNA*	23,600	17,500	14.0	11.5	800	8377183
	CAPT3131*4A*+EEP+HSK		22,400	16,600	13.0	11.0	800	8377110
	CAPT3131*4A*+HSK	G*EC960303ANA*	23,000	17,000	13.5	11.5	800	10515947
	CAPT3131*4A*+HSK	G*EC960403ANA*	23,000	17,000	13.5	11.5	800	10515952
	CAPT3131*4A*+HSK	G*EC960603ANA*	23,000	17,000	13.5	11.5	775	10515944
	CAPT3131*4A*+HSK	G*EC960403BNA*	23,000	17,000	14.0	12.0	800	10338179
	CAPT3131*4A*+HSK	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923176
	CAPT3131*4A*+HSK	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923189
	CAPT3131*4A*+HSK	G*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377136
	CAPT3131*4A*+HSK	ADVC80603B*B*	23,000	17,000	14.0	11.5	800	8377319
	CAPT3131*4A*+HSK	G*VC80604B*B*	23,000	17,000	14.0	11.5	830	8377165
	CAPT3131*4A*+HSK	A*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377144
	CAPT3131*4A*+HSK	G*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377345
	CAPT3131*4A*+HSK	A*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377314
	CAPT3131*4A*+HSK	G*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377310
	CAPT3131*4A*+HSK	G*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377331
	CAPT3131*4A*+HSK	A*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377170
	CAPT3131*4A*+HSK	G*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377115
	CAPT3131*4A*+HSK	A*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377153
	CAPT3131*4A*+HSK	G*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377318
	CAPT3131*4A*+HSK	G*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377274
	CAPT3131*4A*+HSK	A*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377276
	CAPT3131*4A*+HSK	A*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377253
	CAPT3131*4A*+HSK	G*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377338
	CAPT3131*4A*+HSK	A*EH800603B*A*	23,000	17,000	14.0	11.5	800	8377224
	CAPT3131*4A*+HSK	A*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377193
	CAPT3131*4A*+HSK	G*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377241
	CAPT3131*4A*+HSK	A*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377264
	CAPT3131*4A*+HSK	G*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377192
	CAPT3131*4A*+HSK	G*E80603B*B*	23,000	17,000	14.0	11.5	800	8377214
	CAPT3131*4A*+HSK	A*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377257
	CAPT3131*4A*+HSK	A*VC80604B*B*	23,000	17,000	14.0	11.5	830	8377254
	CAPT3131*4A*+HSK	A*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377175
	CAPT3131*4A*+HSK	A*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377130
	CAPT3131*4A*+HSK	G*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377122
	CAPT3131*4A*+MBVC1200**-1A*+HSK		22,800	16,900	14.0	11.5	800	8377210
	CAPT3743*4A*+HSK	G*VC960804CNA*	23,600	17,500	14.0	11.5	800	8377340

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	CAPT3743*4A*+HSK	A*VC960804CNA*	23,600	17,500	14.0	11.5	800	8377235
	CAPT3743*4A*+HSK	G*VM970804CNA*	23,600	17,500	14.0	11.5	800	8377286
	CAPT3743*4A*+HSK	A*VM970804CNA*	23,600	17,500	14.0	11.5	800	8377222
	CHPF1824A6C*+EEP		23,000	17,000	13.0	11.0	800	8377351
	CHPF2430B6C*	G*EC960303ANA*	23,000	17,000	13.5	11.5	800	10515948
	CHPF2430B6C*	G*EC960403ANA*	23,000	17,000	13.5	11.5	800	10515953
	CHPF2430B6C*	G*EC960603ANA*	23,000	17,000	13.5	11.5	775	10515955
	CHPF2430B6C*	G*EC960403BNA*	23,200	17,200	14.0	11.5	800	10338180
	CHPF2430B6C*	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923177
	CHPF2430B6C*	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923190
	CHPF2430B6C*	A*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377186
	CHPF2430B6C*	A*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377247
	CHPF2430B6C*	G*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377258
	CHPF2430B6C*	A*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377196
	CHPF2430B6C*	G*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377249
	CHPF2430B6C*	G*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377317
	CHPF2430B6C*	A*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377261
	CHPF2430B6C*	G*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377221
	CHPF2430B6C*	A*EH800603B*A*	23,000	17,000	14.0	11.5	860	8377198
	CHPF2430B6C*	A*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377335
	CHPF2430B6C*	A*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377272
	CHPF2430B6C*	G*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377290
	CHPF2430B6C*	G*E80603B*B*	23,000	17,000	14.0	11.5	860	8377240
	CHPF2430B6C*	G*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377208
	CHPF2430B6C*	G*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377297
	CHPF2430B6C*	G*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377171
	CHPF2430B6C*	G*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377334
	CHPF2430B6C*	A*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377218
	CHPF2430B6C*	A*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377176
	CHPF2430B6C*	A*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377275
	CHPF2430B6C*+EEP		23,000	17,000	13.0	11.0	800	8377146
	CHPF2430B6C*+MBVC1200**-1A*		23,400	17,300	14.0	11.5	800	8377282
	CHPF2430B6C*+TXV+HSK	G*EC960303ANA*	23,000	17,000	14.0	11.5	800	10515949
	CHPF2430B6C*+TXV+HSK	G*EC960403ANA*	23,000	17,000	14.0	11.5	800	10515954
	CHPF2430B6C*+TXV+HSK	G*EC960603ANA*	23,000	17,000	14.0	11.5	775	10515956
	CHPF2430B6C*+TXV+HSK	G*EC960403BNA*	23,200	17,200	14.0	12.0	800	10338181
	CHPF2430B6C*+TXV+HSK	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923178
	CHPF2430B6C*+TXV+HSK	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923191
	CHPF2430B6C*+TXV+HSK	G*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377364
	CHPF2430B6C*+TXV+HSK	A*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377169
	CHPF2430B6C*+TXV+HSK	G*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377107
	CHPF2430B6C*+TXV+HSK	A*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377108
	CHPF2430B6C*+TXV+HSK	G*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377164
	CHPF2430B6C*+TXV+HSK	G*EC960302BNA*	23,000	17,000	14.0	11.5	800	8377358
	CHPF2430B6C*+TXV+HSK	A*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377288
	CHPF2430B6C*+TXV+HSK	A*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377195
	CHPF2430B6C*+TXV+HSK	A*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377229
	CHPF2430B6C*+TXV+HSK	G*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377159

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	CHPF2430B6C*+TXV+HSK	G*EC960803BNA*	23,000	17,000	14.0	11.5	775	8377216
	CHPF2430B6C*+TXV+HSK	G*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377139
	CHPF2430B6C*+TXV+HSK	A*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377157
	CHPF2430B6C*+TXV+HSK	A*EC960402BNA*	23,000	17,000	14.0	11.5	775	8377142
	CHPF2430B6C*+TXV+HSK	A*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377126
	CHPF2430B6C*+TXV+HSK	G*EC960603BNA*	23,000	17,000	14.0	11.5	775	8377150
	CHPF2430B6C*+TXV+HSK	G*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377301
	CHPF2430B6C*+TXV+HSK	A*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377291
	CHPF3636B6C*	G*VC80603B*B*	23,400	17,800	14.0	11.5	800	9923179
	CHPF3636B6C*	G*VC80803B*B*	23,400	17,800	14.0	11.5	750	9923192
	CHPF3636B6C*	G*VC960403BNA*	23,400	17,300	14.0	11.5	805	8377117
	CHPF3636B6C*	A*VM970603BNA*	23,400	17,300	14.0	11.5	815	8377132
	CHPF3636B6C*	A*VC960603BNA*	23,400	17,300	14.0	11.5	815	8377267
	CHPF3636B6C*	G*VC960803BNA*	23,400	17,300	14.0	11.5	810	8377148
	CHPF3636B6C*	G*VM970603BNA*	23,400	17,300	14.0	11.5	815	8377355
	CHPF3636B6C*	A*VC960803BNA*	23,400	17,300	14.0	11.5	810	8377112
	CHPF3636B6C*	G*VM970803BNA*	23,400	17,300	14.0	11.5	810	8377187
	CHPF3636B6C*	A*VM970803BNA*	23,400	17,300	14.0	11.5	810	8377353
	CHPF3636B6C*	A*VC960403BNA*	23,400	17,300	14.0	11.5	805	8377181
	CHPF3636B6C*	G*VC960603BNA*	23,400	17,300	14.0	11.5	815	8377337
	CHPF3636B6C*+TXV+HSK	G*VC80603B*B*	23,400	17,800	14.0	11.5	800	9923180
	CHPF3636B6C*+TXV+HSK	G*VC80803B*B*	23,400	17,800	14.0	11.5	750	9923193
	CHPF3636B6C*+TXV+HSK	A*VC960403BNA*	23,400	17,300	14.0	11.5	805	8377347
	CHPF3636B6C*+TXV+HSK	A*VC960803BNA*	23,400	17,300	14.0	11.5	810	8377127
	CHPF3636B6C*+TXV+HSK	G*VC960803BNA*	23,400	17,300	14.0	11.5	810	8377344
	CHPF3636B6C*+TXV+HSK	G*VM970603BNA*	23,400	17,300	14.0	11.5	815	8377268
	CHPF3636B6C*+TXV+HSK	G*VM970803BNA*	23,400	17,300	14.0	11.5	810	8377168
	CHPF3636B6C*+TXV+HSK	A*VC960603BNA*	23,400	17,300	14.0	11.5	815	8377125
	CHPF3636B6C*+TXV+HSK	G*VC960603BNA*	23,400	17,300	14.0	11.5	815	8377361
	CHPF3636B6C*+TXV+HSK	A*VM970603BNA*	23,400	17,300	14.0	11.5	815	8377279
	CHPF3636B6C*+TXV+HSK	G*VC960403BNA*	23,400	17,300	14.0	11.5	805	8377302
	CHPF3636B6C*+TXV+HSK	A*VM970803BNA*	23,400	17,300	14.0	11.5	810	8377312
	CHPF3642C6C*	G*VC960804CNA*	23,400	17,300	14.0	11.5	800	8377321
	CHPF3642C6C*	A*VM970804CNA*	23,400	17,300	14.0	11.5	800	8377296
	CHPF3642C6C*	G*VM970804CNA*	23,400	17,300	14.0	11.5	800	8377129
	CHPF3642C6C*	A*VC960804CNA*	23,400	17,300	14.0	11.5	800	8377204
	CHPF3642C6C*+TXV+HSK	A*VC960804CNA*	23,400	17,300	14.0	11.5	800	8377287
	CHPF3642C6C*+TXV+HSK	A*VM970804CNA*	23,400	17,300	14.0	11.5	800	8377178
	CHPF3642C6C*+TXV+HSK	G*VM970804CNA*	23,400	17,300	14.0	11.5	800	8377219
	CHPF3642C6C*+TXV+HSK	G*VC960804CNA*	23,400	17,300	14.0	11.5	800	8377277
	CSCF1824N6D*	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923181
	CSCF1824N6D*	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923194
	CSCF1824N6D*	A*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377293
	CSCF1824N6D*	G*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377189
	CSCF1824N6D*	G*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377357
	CSCF1824N6D*	G*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377300
	CSCF1824N6D*	A*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377352
	CSCF1824N6D*	G*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377350

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	CSCF1824N6D*	G*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377242
	CSCF1824N6D*	A*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377292
	CSCF1824N6D*	A*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377128
	CSCF1824N6D*	A*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377294
	CSCF1824N6D*	G*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377226
	CSCF1824N6D*	A*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377365
	CSCF1824N6D*	A*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377273
	CSCF1824N6D*	G*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377326
	CSCF1824N6D*+EEP		23,000	17,000	13.0	11.0	800	8377120
	CSCF1824N6D*+TXV+HSK	G*VC80603B*B*	23,000	17,500	14.0	11.5	800	9923182
	CSCF1824N6D*+TXV+HSK	G*VC80803B*B*	23,000	17,500	14.0	11.5	750	9923195
	CSCF1824N6D*+TXV+HSK	G*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377109
	CSCF1824N6D*+TXV+HSK	G*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377269
	CSCF1824N6D*+TXV+HSK	G*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377330
	CSCF1824N6D*+TXV+HSK	G*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377285
	CSCF1824N6D*+TXV+HSK	G*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377232
	CSCF1824N6D*+TXV+HSK	A*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377111
	CSCF1824N6D*+TXV+HSK	A*VC960804CNA*	23,000	17,000	14.0	11.5	800	8377113
	CSCF1824N6D*+TXV+HSK	G*VM970803BNA*	23,000	17,000	14.0	11.5	810	8377228
	CSCF1824N6D*+TXV+HSK	G*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377234
	CSCF1824N6D*+TXV+HSK	A*VM970603BNA*	23,000	17,000	14.0	11.5	815	8377245
	CSCF1824N6D*+TXV+HSK	A*VC960803BNA*	23,000	17,000	14.0	11.5	810	8377260
	CSCF1824N6D*+TXV+HSK	A*VC960403BNA*	23,000	17,000	14.0	11.5	805	8377266
	CSCF1824N6D*+TXV+HSK	A*VM970804CNA*	23,000	17,000	14.0	11.5	800	8377123
	CSCF1824N6D*+TXV+HSK	A*VC960603BNA*	23,000	17,000	14.0	11.5	815	8377174
	CSCF3036N6D*	G*VC80603B*B*	23,200	17,700	14.0	11.5	800	9923183
	CSCF3036N6D*	G*VC80803B*B*	23,200	17,700	14.0	11.5	750	9923196
	CSCF3036N6D*	G*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377271
	CSCF3036N6D*	A*VM970804CNA*	23,200	17,200	14.0	11.5	800	8377342
	CSCF3036N6D*	A*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377284
	CSCF3036N6D*	G*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377243
	CSCF3036N6D*	G*VC960804CNA*	23,200	17,200	14.0	11.5	800	8377252
	CSCF3036N6D*	G*VM970804CNA*	23,200	17,200	14.0	11.5	800	8377237
	CSCF3036N6D*	A*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377207
	CSCF3036N6D*	A*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377362
	CSCF3036N6D*	A*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377143
	CSCF3036N6D*	A*VC960804CNA*	23,200	17,200	14.0	11.5	800	8377119
	CSCF3036N6D*	A*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377206
	CSCF3036N6D*	G*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377152
	CSCF3036N6D*	G*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377348
	CSCF3036N6D*	G*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377162
	CSCF3036N6D*+TXV+HSK	G*VC80603B*B*	23,200	17,700	14.0	11.5	800	9923184
	CSCF3036N6D*+TXV+HSK	G*VC80803B*B*	23,200	17,700	14.0	11.5	750	9923197
	CSCF3036N6D*+TXV+HSK	G*VM970804CNA*	23,200	17,200	14.0	11.5	800	8377359
	CSCF3036N6D*+TXV+HSK	A*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377289
	CSCF3036N6D*+TXV+HSK	A*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377133
	CSCF3036N6D*+TXV+HSK	G*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377343
	CSCF3036N6D*+TXV+HSK	G*VC960803BNA*	23,200	17,200	14.0	11.5	810	8377149

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0241E* (Contd.)	CSCF3036N6D*+TXV+HSK	A*VM970804CNA*	23,200	17,200	14.0	11.5	800	8377190
	CSCF3036N6D*+TXV+HSK	A*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377327
	CSCF3036N6D*+TXV+HSK	A*VM970603BNA*	23,200	17,200	14.0	11.5	815	8377313
	CSCF3036N6D*+TXV+HSK	A*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377311
	CSCF3036N6D*+TXV+HSK	G*VC960603BNA*	23,200	17,200	14.0	11.5	815	8377180
	CSCF3036N6D*+TXV+HSK	G*VM970803BNA*	23,200	17,200	14.0	11.5	810	8377147
	CSCF3036N6D*+TXV+HSK	G*VC960804CNA*	23,200	17,200	14.0	11.5	800	8377205
	CSCF3036N6D*+TXV+HSK	G*VC960403BNA*	23,200	17,200	14.0	11.5	805	8377212
	CSCF3036N6D*+TXV+HSK	A*VC960804CNA*	23,200	17,200	14.0	11.5	800	8377329
GSX13 0301L*	ACNF30XX16D*		28,400	21,600	13.0	11.0	890	10258620
	ARUF29B14A*		28,600	21,800	13.0	11.0	1,020	10258621
	ASPT36C14A*+HSK		28,600	21,800	14.0	12.0	1,010	10258622
	ASPT37B14A*+HSK		28,800	21,900	14.0	12.0	945	10258623
	ASPT39C14A*+HSK		28,400	21,600	14.0	11.5	1,000	10446906
	AVPTC25B14A*+HSK		28,800	21,900	13.5	11.5	975	10258624
	AVPTC29B14A*+HSK		28,400	21,600	14.0	12.0	925	10258625
	AVPTC31C14A*+HSK		28,400	21,600	14.0	12.0	930	10258626
	AVPTC36C14A*+HSK		28,400	21,600	14.0	12.0	990	10258627
	AVPTC39C14A*+HSK		28,000	21,400	14.0	12.0	965	10446907
	AWUF30XX16B*		28,400	21,600	13.0	11.0	1,000	10258628
	AWUF36XX16B*		28,400	21,600	13.0	11.0	1,000	10258629
	AWUF37XX16B*		28,400	21,600	13.0	11.0	995	10258630
	CA*F3030*6D*	G*EC960303ANA*	28,000	21,800	13.5	11.5	975	10517440
	CA*F3030*6D*	G*EC960403ANA*	28,400	22,000	13.0	11.5	975	10517446
	CA*F3030*6D*	G*EC960403BNA*	28,400	22,000	13.5	11.5	1,000	10338182
	CA*F3030*6D*	G*EC960302BNA*	28,200	21,500	13.5	11.5	1,010	10258636
	CA*F3030*6D*	G*EC960402BNA*	28,000	21,300	13.5	11.5	1,010	10258643
	CA*F3030*6D*	G*EC960603BNA*	28,400	21,600	13.5	11.5	1020	10258654
	CA*F3030*6D*	G*EC960803BNA*	28,400	21,600	13.5	11.5	995	10258665
	CA*F3030*6D*	G*VC80603B*B*	28,400	21,600	13.5	11.5	1015	10258685
	CA*F3030*6D*	G*VC80604B*B*	28,400	21,600	13.5	11.3	995	10258686
	CA*F3030*6D*	G*VC80803B*B*	27,600	21,000	13.5	11.5	1,050	10258700
	CA*F3030*6D*	G*VC80804C*B*	28,400	21,600	13.5	11.3	1,035	10258702
	CA*F3030*6D*	G*VC960403BNA*	27,000	20,600	14.0	11.5	1,000	10258706
	CA*F3030*6D*	G*VC960603BNA*	27,600	21,000	14.0	11.5	990	10258716
	CA*F3030*6D*	G*VC960803BNA*	28,000	21,300	14.0	11.5	1,015	10258726
	CA*F3030*6D*	G*VC960804CNA*	29,000	22,100	14.0	11.5	1,025	10258736
	CA*F3030*6D*	G*VM970603BNA*	28,000	21,300	14.0	11.5	995	10258746
	CA*F3030*6D*	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258756
	CA*F3030*6D*	G*VM970804CNA*	29,000	22,100	14.0	11.5	1,025	10258766
	CA*F3030*6D*+EEP		28,400	21,300	13.0	11.0	1,050	10258601
	CA*F3030*6D*+TXV+HSK	G*EC960303ANA*	28,000	21,800	13.5	11.5	975	10517441
	CA*F3030*6D*+TXV+HSK	G*EC960403ANA*	28,200	22,000	13.5	11.5	975	10517447
	CA*F3030*6D*+TXV+HSK	G*EC960603ANA*	28,000	21,800	13.5	11.3	975	10517439
	CA*F3030*6D*+TXV+HSK	G*EC960403BNA*	28,400	22,000	13.5	11.5	1,000	10338183
	CA*F3030*6D*+TXV+HSK	G*EC960302BNA*	27,600	21,000	14.0	11.5	1,010	10258637
	CA*F3030*6D*+TXV+HSK	G*EC960402BNA*	27,800	21,200	14.0	11.5	1,010	10258644
	CA*F3030*6D*+TXV+HSK	G*EC960603BNA*	28,000	21,300	13.5	11.5	1,020	10258655

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0301L* (Contd.)	CA*F3030*6D*+TXV+HSK	G*EC960803BNA*	28,400	21,600	13.5	11.5	995	10258666
	CA*F3030*6D*+TXV+HSK	G*VC80603B*B*	28,400	21,600	14.0	11.5	1,015	10258684
	CA*F3030*6D*+TXV+HSK	G*VC80803B*B*	28,400	21,600	14.0	11.5	1,050	10258699
	CA*F3030*6D*+TXV+HSK	G*VC960403BNA*	29,000	22,100	14.0	11.5	1,000	10258707
	CA*F3030*6D*+TXV+HSK	G*VC960603BNA*	29,000	22,100	14.0	11.5	990	10258717
	CA*F3030*6D*+TXV+HSK	G*VC960803BNA*	28,000	21,300	14.0	11.5	1,015	10258727
	CA*F3030*6D*+TXV+HSK	G*VC960804CNA*	28,400	21,600	14.0	11.5	1,025	10258737
	CA*F3030*6D*+TXV+HSK	G*VM970603BNA*	28,600	21,800	14.0	11.5	995	10258747
	CA*F3030*6D*+TXV+HSK	G*VM970803BNA*	28,600	21,800	14.0	11.5	1,015	10258757
	CA*F3030*6D*+TXV+HSK	G*VM970804CNA*	28,600	21,800	14.0	11.5	1,025	10258767
	CA*F3131*6D*	G*EC960303ANA*	28,200	22,000	13.5	11.5	975	10517442
	CA*F3131*6D*	G*EC960403ANA*	28,400	22,000	13.5	11.5	975	10517448
	CA*F3131*6D*	G*EC960403BNA*	28,400	22,000	13.5	11.5	1,000	10338184
	CA*F3131*6D*	G*EC960302BNA*	28,400	21,600	13.5	11.3	1,010	10258638
	CA*F3131*6D*	G*EC960402BNA*	28,400	21,600	13.5	11.3	1,010	10258645
	CA*F3131*6D*	G*EC960603BNA*	28,400	21,600	13.5	11.3	1020	10258656
	CA*F3131*6D*	G*EC960803BNA*	28,400	21,600	13.5	11.3	995	10258667
	CA*F3131*6D*	G*VC80604B*B*	28,600	21,800	13.5	11.3	995	10258687
	CA*F3131*6D*+EEP		28,600	21,800	13.0	11.0	1,050	10258602
	CA*F3131*6D*+MBVC1200**-1A*		28,600	21,800	13.5	11.3	950	10258603
	CA*F3131*6D*+TXV+HSK	G*EC960303ANA*	28,000	21,800	13.5	11.5	975	10517443
	CA*F3131*6D*+TXV+HSK	G*EC960403ANA*	28,400	22,000	13.5	11.5	975	10517449
	CA*F3131*6D*+TXV+HSK	G*EC960603ANA*	28,200	22,000	13.5	11.3	975	10517454
	CA*F3131*6D*+TXV+HSK	G*EC960403BNA*	28,400	22,000	14.0	11.7	1,000	10338185
	CA*F3131*6D*+TXV+HSK	G*EC960302BNA*	28,600	21,800	14.0	11.5	1,010	10258639
	CA*F3131*6D*+TXV+HSK	G*EC960402BNA*	28,600	21,800	14.0	11.5	1,010	10258646
	CA*F3131*6D*+TXV+HSK	G*EC960603BNA*	28,600	21,800	13.5	11.5	1,020	10258657
	CA*F3131*6D*+TXV+HSK	G*EC960803BNA*	28,400	21,600	13.5	11.5	995	10258668
	CA*F3137*6A*	G*EC960403ANA*	28,600	22,200	13.5	11.5	975	10517450
	CA*F3137*6A*	G*EC960403BNA*	28,600	22,200	13.5	11.5	1,000	10338186
	CA*F3137*6A*	G*EC960402BNA*	28,400	21,600	13.5	11.5	1,010	10258647
	CA*F3137*6A*	G*EC960603BNA*	28,400	21,600	14.0	11.5	1,020	10258658
	CA*F3137*6A*	G*EC960803BNA*	28,400	21,600	13.5	11.5	995	10258669
	CA*F3137*6A*	G*VC80603B*B*	28,400	21,600	13.5	11.5	1,015	10258683
	CA*F3137*6A*	G*VC80604B*B*	28,600	21,800	14.0	11.5	995	10258688
	CA*F3137*6A*	G*VC80803B*B*	28,600	21,800	13.5	11.5	1,050	10258698
	CA*F3137*6A*	G*VC960403BNA*	28,600	21,800	14.0	11.5	1,000	10258708
	CA*F3137*6A*	G*VC960603BNA*	28,600	21,800	14.0	11.5	990	10258718
	CA*F3137*6A*	G*VC960803BNA*	28,800	21,900	14.0	11.5	1,015	10258728
	CA*F3137*6A*	G*VM970603BNA*	28,800	21,900	14.0	11.5	995	10258748
	CA*F3137*6A*	G*VM970803BNA*	28,600	21,800	14.0	11.5	1,015	10258758
	CA*F3137*6A*+EEP		28,400	21,600	13.0	11.0	1,000	10258604
	CA*F3137*6A*+EEP+TXV+HSK		28,400	21,600	13.5	11.0	1,000	10258605
	CA*F3137*6A*+MBVC1200**-1A*		28,400	21,600	14.0	11.5	1,015	10258606
	CA*F3137*6A*+MBVC1200**-1A*+TXV+HSK		28,400	21,600	14.0	11.5	1,015	10258607
	CA*F3137*6A*+TXV+HSK	G*EC960403ANA*	28,600	22,200	14.0	11.5	975	10517451
	CA*F3137*6A*+TXV+HSK	G*EC960603ANA*	28,400	22,000	13.5	11.3	975	10517455

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0301L* (Contd.)	CA*F3137*6A*+TXV+HSK	G*EC960403BNA*	28,600	22,200	14.0	11.7	1,000	10338187
	CA*F3137*6A*+TXV+HSK	G*EC960402BNA*	28,600	21,800	14.0	11.5	1,010	10258648
	CA*F3137*6A*+TXV+HSK	G*EC960603BNA*	28,600	21,800	14.0	11.5	1,020	10258659
	CA*F3137*6A*+TXV+HSK	G*EC960803BNA*	28,600	21,800	13.5	11.5	995	10258670
	CA*F3137*6A*+TXV+HSK	G*VC80603B*B*	28,600	21,800	14.0	11.5	1,015	10258682
	CA*F3137*6A*+TXV+HSK	G*VC80604B*B*	28,600	21,800	14.0	11.5	995	10258689
	CA*F3137*6A*+TXV+HSK	G*VC80803B*B*	28,600	21,800	14.0	11.5	1,050	10258697
	CA*F3137*6A*+TXV+HSK	G*VC960403BNA*	28,600	21,800	14.0	11.5	1,000	10258709
	CA*F3137*6A*+TXV+HSK	G*VC960603BNA*	28,400	21,600	14.0	11.5	990	10258719
	CA*F3137*6A*+TXV+HSK	G*VC960803BNA*	28,400	21,600	14.0	11.5	1,015	10258729
	CA*F3137*6A*+TXV+HSK	G*VM970603BNA*	28,400	21,600	14.0	11.5	995	10258749
	CA*F3137*6A*+TXV+HSK	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258759
	CA*F3636*6D*+EEP		28,400	21,600	13.0	11.0	1,000	10258608
	CA*F3636*6D*+EEP+TXV+HSK		28,400	21,600	13.0	11.0	1,000	10258609
	CA*F3642*6D*+EEP		28,200	21,500	13.0	11.0	1,000	10258610
	CA*F3642*6D*+EEP+TXV+HSK		28,200	21,500	13.0	11.0	1,000	10258611
	CA*F3743*6D*	G*EC960402BNA*	28,600	21,800	13.5	11.3	1,010	10258649
	CA*F3743*6D*	G*EC960603BNA*	28,600	21,800	13.5	11.3	1,020	10258660
	CA*F3743*6D*	G*EC960803BNA*	28,200	21,500	13.5	11.3	995	10258671
	CA*F3743*6D*	G*VC960804CNA*	28,200	21,500	14.0	11.5	1,025	10258738
	CA*F3743*6D*	G*VM970804CNA*	28,200	21,500	14.0	11.5	1,025	10258768
	CA*F3743*6D*+EEP		28,200	21,500	13.5	11.0	1,000	10258612
	CA*F3743*6D*+EEP+TXV+HSK		28,600	21,800	13.5	11.0	1000	10258613
	CA*F3743*6D*+TXV+HSK	G*EC960403BNA*	28,600	22,200	14.0	11.7	1,000	10338188
	CA*F3743*6D*+TXV+HSK	G*EC960402BNA*	28,600	21,800	14.0	11.5	1010	10258650
	CA*F3743*6D*+TXV+HSK	G*EC960603BNA*	28,200	21,500	14.0	11.5	1,020	10258661
	CA*F3743*6D*+TXV+HSK	G*EC960803BNA*	28,400	21,600	14.0	11.5	995	10258672
	CA*F3743*6D*+TXV+HSK	G*VC960804CNA*	28,400	21,600	14.0	11.5	1,025	10258739
	CA*F3743*6D*+TXV+HSK	G*VM970804CNA*	28,400	21,600	14.0	11.5	1,025	10258769
	CAPT3131*4A*+HSK	G*VC80603B*B*	28,400	21,600	13.5	11.5	1,015	10258681
	CAPT3131*4A*+HSK	G*VC80803B*B*	28,400	21,600	13.5	11.5	1,050	10258696
	CAPT3131*4A*+HSK	G*VC960403BNA*	28,200	21,500	13.5	11.5	1,000	10258710
	CAPT3131*4A*+HSK	G*VC960603BNA*	28,600	21,800	14.0	11.5	990	10258720
	CAPT3131*4A*+HSK	G*VC960803BNA*	28,600	21,800	13.5	11.5	1,015	10258730
	CAPT3131*4A*+HSK	G*VC960804CNA*	28,200	21,500	13.5	11.5	1,025	10258740
	CAPT3131*4A*+HSK	G*VM970603BNA*	28,200	21,500	14.0	11.5	995	10258750
	CAPT3131*4A*+HSK	G*VM970803BNA*	28,200	21,500	13.5	11.5	1,015	10258760
	CAPT3131*4A*+HSK	G*VM970804CNA*	28,200	21,500	13.5	11.5	1,025	10258770
	CAPT3743*4A*+EEP+HSK		28,400	21,600	13.0	11.0	1,000	10258614
	CAPT3743*4A*+HSK	G*EC960403BNA*	28,600	22,200	14.0	11.7	1,000	10338189
	CAPT3743*4A*+HSK	G*E80603B*B*	28,400	21,600	13.5	11.5	990	10258631
	CAPT3743*4A*+HSK	G*EC960302BNA*	28,400	21,600	14.0	11.5	1,010	10258640
	CAPT3743*4A*+HSK	G*EC960402BNA*	28,400	21,600	14.0	11.5	1,010	10258651
	CAPT3743*4A*+HSK	G*EC960603BNA*	28,400	21,600	13.5	11.5	1,020	10258662
	CAPT3743*4A*+HSK	G*EC960803BNA*	28,600	21,800	13.5	11.5	995	10258673
	CAPT3743*4A*+HSK	G*VC80603B*B*	28,600	21,800	14.0	11.5	1,015	10258680
	CAPT3743*4A*+HSK	G*VC80604B*B*	28,000	21,300	14.0	12.0	995	10258690
	CAPT3743*4A*+HSK	G*VC80803B*B*	28,200	21,500	14.0	11.5	1,050	10258695

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0301L* (Contd.)	CAPT3743*4A*+HSK	G*VC80804C*B*	28,400	21,600	14.0	12.0	1,035	10258701
	CAPT3743*4A*+HSK	G*VC80805C*B*	28,400	21,600	14.0	12.0	1000	10258703
	CAPT3743*4A*+HSK	G*VC80805D*B*	28,400	21,600	14.0	12.0	1000	10258704
	CAPT3743*4A*+HSK	G*VC81005C*B*	28,400	21,600	14.0	12.0	1,050	10258705
	CAPT3743*4A*+HSK	G*VC960403BNA*	28,400	21,600	14.0	11.5	1,000	10258711
	CAPT3743*4A*+HSK	G*VC960603BNA*	28,400	21,600	13.5	11.5	990	10258721
	CAPT3743*4A*+HSK	G*VC960803BNA*	28,600	21,800	14.0	11.5	1,015	10258731
	CAPT3743*4A*+HSK	G*VC960804CNA*	28,600	21,800	14.0	11.5	1,025	10258741
	CAPT3743*4A*+HSK	G*VM970603BNA*	28,400	21,600	13.5	11.5	995	10258751
	CAPT3743*4A*+HSK	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258761
	CAPT3743*4A*+HSK	G*VM970804CNA*	28,400	21,600	14.0	11.5	1,025	10258771
	CAPT3743*4A*+MBVC1200**-1A*+HSK		28,400	21,600	14.0	11.5	950	10258615
	CAPT3743*4A*+MBVC1600**-1A*+HSK		28,400	21,600	14.0	11.5	1,020	10258616
	CHPF2430B6C*	G*EC960303ANA*	28,400	22,000	13.5	11.5	975	10517444
	CHPF2430B6C*	G*EC960403ANA*	28,400	22,000	13.5	11.5	975	10517452
	CHPF2430B6C*	G*EC960403BNA*	28,400	22,000	13.5	11.5	1,000	10338190
	CHPF2430B6C*	G*E80603B*B*	28,400	21,600	13.5	11.3	990	10258632
	CHPF2430B6C*	G*EC960302BNA*	28,400	21,600	14.0	11.5	1,010	10258641
	CHPF2430B6C*	G*EC960402BNA*	28,400	21,600	14.0	11.5	1,010	10258652
	CHPF2430B6C*	G*VC80603B*B*	28,600	21,800	13.5	11.3	1,015	10258679
	CHPF2430B6C*	G*VC80803B*B*	28,600	21,800	13.5	11.3	1,050	10258694
	CHPF2430B6C*	G*VC960403BNA*	28,000	21,300	14.0	11.5	1,000	10258712
	CHPF2430B6C*	G*VC960603BNA*	28,200	21,500	14.0	11.5	990	10258722
	CHPF2430B6C*	G*VC960803BNA*	28,400	21,600	14.0	11.5	1,015	10258732
	CHPF2430B6C*	G*VM970603BNA*	28,400	21,600	14.0	11.5	995	10258752
	CHPF2430B6C*	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258762
	CHPF2430B6C*+EEP		28,400	21,600	13.0	11.0	1,050	10258617
	CHPF2430B6C*+MBVC1200**-1A*		28,400	21,600	14.0	11.5	1,045	10258618
	CHPF2430B6C*+TXV+HSK	G*EC960303ANA*	28,400	22,000	14.0	11.5	975	10517445
	CHPF2430B6C*+TXV+HSK	G*EC960403ANA*	28,400	22,000	13.5	11.5	975	10517453
	CHPF2430B6C*+TXV+HSK	G*EC960403BNA*	28,400	22,000	14.0	11.7	1,000	10338191
	CHPF2430B6C*+TXV+HSK	G*E80603B*B*	28,400	21,600	14.0	11.5	990	10258633
	CHPF2430B6C*+TXV+HSK	G*EC960302BNA*	28,600	21,800	14.0	11.5	1,010	10258642
	CHPF2430B6C*+TXV+HSK	G*EC960402BNA*	28,600	21,800	14.0	11.5	1,010	10258653
	CHPF2430B6C*+TXV+HSK	G*VC80603B*B*	28,000	21,300	14.0	11.5	1,015	10258678
	CHPF2430B6C*+TXV+HSK	G*VC80803B*B*	28,200	21,500	14.0	11.5	1,050	10258693
	CHPF2430B6C*+TXV+HSK	G*VC960403BNA*	28,400	21,600	14.0	11.5	1,000	10258713
	CHPF2430B6C*+TXV+HSK	G*VC960603BNA*	28,400	21,600	14.0	11.5	990	10258723
	CHPF2430B6C*+TXV+HSK	G*VC960803BNA*	28,400	21,600	14.0	11.5	1,015	10258733
	CHPF2430B6C*+TXV+HSK	G*VM970603BNA*	28,600	21,800	14.0	11.5	995	10258753
	CHPF2430B6C*+TXV+HSK	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258763
	CHPF3636B6C*	G*EC960603BNA*	28,400	21,600	13.5	11.5	1,020	10258663
	CHPF3636B6C*	G*EC960803BNA*	28,600	21,800	13.5	11.5	1,010	10258674
	CHPF3636B6C*+TXV+HSK	G*EC960603ANA*	28,400	22,000	13.5	11.3	975	10517456
	CHPF3636B6C*+TXV+HSK	G*EC960603BNA*	28,600	21,800	14.0	11.5	1,020	10258664
	CHPF3636B6C*+TXV+HSK	G*EC960803BNA*	28,400	21,600	14.0	11.5	1,010	10258675
	CHPF3642C6C*	G*VC960804CNA*	28,400	21,600	14.0	11.5	1,015	10258742
	CHPF3642C6C*	G*VM970804CNA*	28,400	21,600	14.0	11.5	1,015	10258772

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0301L* (Contd.)	CHPF3642C6C*+TXV+HSK	G*VC960804CNA*	28,400	21,600	14.0	11.5	1,015	10258743
	CHPF3642C6C*+TXV+HSK	G*VM970804CNA*	28,400	21,600	14.0	11.5	1015	10258773
	CHPF4860D6D*	G*E80805C*B*	28,400	21,600	13.5	11.3	1025	10258634
	CHPF4860D6D*+TXV+HSK	G*E80805C*B*	28,400	21,600	14.0	11.5	1,025	10258635
	CSCF3036N6D*	G*VC80603B*B*	28,400	21,600	13.5	11.2	1,015	10258677
	CSCF3036N6D*	G*VC80803B*B*	28,600	21,800	13.5	11.2	1,050	10258692
	CSCF3036N6D*	G*VC960403BNA*	28,600	21,800	14.0	11.5	1,000	10258714
	CSCF3036N6D*	G*VC960603BNA*	28,000	21,300	14.0	11.3	990	10258724
	CSCF3036N6D*	G*VC960803BNA*	28,400	21,600	14.0	11.5	1,015	10258734
	CSCF3036N6D*	G*VC960804CNA*	28,400	21,600	14.0	11.5	1,025	10258744
	CSCF3036N6D*	G*VM970603BNA*	28,400	21,600	14.0	11.3	995	10258754
	CSCF3036N6D*	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258764
	CSCF3036N6D*	G*VM970804CNA*	28,400	21,600	14.0	11.5	1,025	10258774
	CSCF3036N6D*+EEP		28,400	21,600	13.0	11.0	1,000	10258619
	CSCF3036N6D*+TXV+HSK	G*VC80603B*B*	28,400	21,600	13.5	11.2	1,015	10258676
	CSCF3036N6D*+TXV+HSK	G*VC80803B*B*	28,600	21,800	13.5	11.2	1,050	10258691
	CSCF3036N6D*+TXV+HSK	G*VC960403BNA*	28,600	21,800	14.0	11.5	1,000	10258715
	CSCF3036N6D*+TXV+HSK	G*VC960603BNA*	28,000	21,300	14.0	11.3	990	10258725
	CSCF3036N6D*+TXV+HSK	G*VC960803BNA*	28,400	21,600	14.0	11.5	1015	10258735
	CSCF3036N6D*+TXV+HSK	G*VC960804CNA*	28,400	21,600	14.0	11.5	1025	10258745
GSX13 0361E*	CSCF3036N6D*+TXV+HSK	G*VM970603BNA*	28,400	21,600	14.0	11.3	995	10258755
	CSCF3036N6D*+TXV+HSK	G*VM970803BNA*	28,400	21,600	14.0	11.5	1,015	10258765
	CSCF3036N6D*+TXV+HSK	G*VM970804CNA*	28,400	21,600	14.0	11.5	1,025	10258775
	ARUF36C14B*+TXV		34,000	26,400	13.0	11.0	1,165	5696621
	ARUF37C14A*		34,000	26,400	13.0	11.0	1,050	7984177
	ARUF42C14A*+TXV		34,200	26,600	13.0	11.0	1,150	5696623
	ASPT36C14A*		34,000	26,400	13.8	11.8	1,210	5722540
	ASPT37C14A*		34,200	26,600	14.0	12.0	1,120	8242045
	AVPTC36C14A*		34,000	26,400	13.8	11.8	1,215	5924444
	AVPTC37B14A*		34,600	27,000	13.5	11.5	1,080	8996117
	AVPTC37C14A*		35,000	27,200	14.0	12.0	1,130	8996118
	AVPTC37D14A*		35,400	27,600	14.0	12.0	1,145	8996119
	AVPTC42D14A*		34,600	27,000	14.0	12.0	1,225	5924445
	AVPTC48C14A*		34,000	26,400	14.0	12.0	1,100	7079217
	AWUF36XX16B*		33,400	26,000	13.0	11.0	1,150	5696626
	AWUF37XX16B*		33,600	26,200	13.0	11.0	1,150	5696627
	CA*F3137*6A*	G*VC80603B*B*	34,000	27,200	14.0	11.5	1200	9923222
	CA*F3137*6A*	G*VC80803B*B*	34,000	27,200	14.0	11.5	1150	9923224
	CA*F3137*6A*	A*VM970603BNA*	34,000	26,400	13.5	11.0	1,055	7489415
	CA*F3137*6A*	A*VC960403BNA*	34,000	26,400	13.5	11.0	1,050	7489412
	CA*F3137*6A*	A*VC80604B*B*	34,000	26,400	14.0	11.5	1,095	7489411
	CA*F3137*6A*	G*VM970603BNA*	34,000	26,400	13.5	11.0	1,055	7489425
	CA*F3137*6A*	G*VC960803BNA*	34,000	26,400	13.5	11.0	1,100	7489424
	CA*F3137*6A*	A*VC960603BNA*	34,000	26,400	13.5	11.0	1,055	7489413
	CA*F3137*6A*	A*EC960603BNA*	34,000	26,400	13.5	11.0	1,090	7489408
	CA*F3137*6A*	A*EC960803BNA*	34,000	26,400	13.5	11.0	1,090	7489409
	CA*F3137*6A*	A*EH800603B*A*	34,000	26,400	14.0	11.5	1,100	7489410
	CA*F3137*6A*	ADVC80603B*B*	34,000	26,400	13.5	11.0	1,075	7489417

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0361E* (Contd.)	CA*F3137*6A*	G*VC960603BNA*	34,000	26,400	13.5	11.0	1,055	7489423
	CA*F3137*6A*	G*EC960803BNA*	34,000	26,400	13.5	11.0	1,090	7489420
	CA*F3137*6A*	G*VC960403BNA*	34,000	26,400	13.5	11.0	1,050	7489422
	CA*F3137*6A*	G*VC80604B*B*	34,000	26,400	14.0	11.5	1,095	7489421
	CA*F3137*6A*	A*VC960803BNA*	34,000	26,400	13.5	11.0	1,100	7489414
	CA*F3137*6A*	A*VM970803BNA*	34,000	26,400	13.5	11.0	1,100	7489416
	CA*F3137*6A*	G*E80603B*B*	34,000	26,400	14.0	11.5	1,100	7489418
	CA*F3137*6A*	G*VM970803BNA*	34,000	26,400	13.5	11.0	1,100	7489426
	CA*F3137*6A*	G*EC960603BNA*	34,000	26,400	13.5	11.0	1,090	7489419
	CA*F3137*6A*+EEP		34,000	26,400	13.0	11.0	1,200	7489430
	CA*F3137*6A*+EEP+TXV		34,000	26,400	13.5	11.0	1,200	7489429
	CA*F3137*6A*+MBVC1200**-1A*		34,000	26,400	14.0	11.5	1,050	7489434
	CA*F3137*6A*+MBVC1200**-1A*+TXV		34,000	26,400	14.0	11.5	1,050	7489433
	CA*F3137*6A*+TXV	G*VC80603B*B*	34,000	27,200	14.0	11.5	1200	9923223
	CA*F3137*6A*+TXV	G*VC80803B*B*	34,000	27,200	14.0	11.5	1150	9923225
	CA*F3137*6A*+TXV	A*EC960803BNA*	34,000	26,400	13.5	11.0	1,090	7489390
	CA*F3137*6A*+TXV	A*VM970603BNA*	34,000	26,400	14.0	11.5	1,055	7489396
	CA*F3137*6A*+TXV	A*EC960603BNA*	34,000	26,400	13.5	11.0	1,090	7489389
	CA*F3137*6A*+TXV	A*VC80604B*B*	34,000	26,400	14.0	11.5	1,095	7489392
	CA*F3137*6A*+TXV	A*VC960403BNA*	34,000	26,400	14.0	11.5	1,050	7489393
	CA*F3137*6A*+TXV	A*EH800603B*A*	34,000	26,400	14.0	11.5	1,100	7489391
	CA*F3137*6A*+TXV	G*VC80604B*B*	34,000	26,400	14.0	11.5	1,095	7489402
	CA*F3137*6A*+TXV	G*VM970603BNA*	34,000	26,400	14.0	11.5	1,055	7489406
	CA*F3137*6A*+TXV	A*VC960803BNA*	34,000	26,400	14.0	11.5	1,100	7489395
	CA*F3137*6A*+TXV	A*VC960603BNA*	34,000	26,400	14.0	11.5	1,055	7489394
	CA*F3137*6A*+TXV	G*EC960603BNA*	34,000	26,400	13.5	11.0	1,090	7489400
	CA*F3137*6A*+TXV	G*VC960803BNA*	34,000	26,400	14.0	11.5	1,100	7489405
	CA*F3137*6A*+TXV	ADVC80603B*B*	34,000	26,400	14.0	11.5	1,075	7489398
	CA*F3137*6A*+TXV	A*VM970803BNA*	34,000	26,400	14.0	11.5	1,100	7489397
	CA*F3137*6A*+TXV	G*VM970803BNA*	34,000	26,400	14.0	11.5	1,100	7489407
	CA*F3137*6A*+TXV	G*VC960403BNA*	34,000	26,400	14.0	11.5	1,050	7489403
	CA*F3137*6A*+TXV	G*VC960603BNA*	34,000	26,400	14.0	11.5	1,055	7489404
	CA*F3137*6A*+TXV	G*EC960803BNA*	34,000	26,400	13.5	11.0	1,090	7489401
	CA*F3137*6A*+TXV	G*E80603B*B*	34,000	26,400	14.0	11.5	1,100	7489399
	CA*F3636*6D*+EEP		33,600	26,200	13.0	11.0	1,200	5696608
	CA*F3642*6D*+EEP		33,600	26,200	13.0	11.0	1,200	5696609
	CA*F3642*6D*+MBVC1600**-1A*		34,000	26,400	14.0	11.5	1,200	5696640
	CA*F3743*6D*	G*VC81005C*B*	34,000	27,200	13.5	11.3	1150	9923228
	CA*F3743*6D*	A*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353888
	CA*F3743*6D*	G*EC961004CNA*	33,600	26,200	13.5	11.5	1,100	7365299
	CA*F3743*6D*	G*VM970804CNA*	34,000	26,400	13.0	11.0	1,115	7353893
	CA*F3743*6D*	A*VM970804CNA*	34,000	26,400	13.0	11.0	1,115	7353887
	CA*F3743*6D*	G*VC960804CNA*	34,000	26,400	13.0	11.0	1,115	7353890
	CA*F3743*6D*	G*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353895
	CA*F3743*6D*	G*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353894
	CA*F3743*6D*	A*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353885
	CA*F3743*6D*	A*EC961004CNA*	33,600	26,200	13.5	11.5	1,100	7365407
	CA*F3743*6D*	G*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353892

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0361E* (Contd.)	CA*F3743*6D*	A*VC960804CNA*	34,000	26,400	13.0	11.0	1,115	7353884
	CA*F3743*6D*	G*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353891
	CA*F3743*6D*	A*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353889
	CA*F3743*6D*	A*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353886
	CA*F3743*6D*+EEP		34,200	26,600	13.0	11.0	1,200	5696610
	CA*F3743*6D*+EEP+TXV		34,200	26,600	13.5	11.0	1,200	5696611
	CA*F3743*6D*+MBVC1600**-1A*		34,000	26,400	14.0	11.5	1,210	5696641
	CA*F3743*6D*+TXV	G*VC81005C*B*	34,000	27,200	13.5	11.5	1150	9923229
	CA*F3743*6D*+TXV	A*EC960603BNA*	33,600	26,200	13.5	11.0	1,175	7365403
	CA*F3743*6D*+TXV	G*EC960603BNA*	33,600	26,200	13.5	11.0	1,175	7365295
	CA*F3743*6D*+TXV	G*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353906
	CA*F3743*6D*+TXV	A*EC960803BNA*	33,400	26,000	13.5	11.0	1,075	7365405
	CA*F3743*6D*+TXV	G*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353903
	CA*F3743*6D*+TXV	G*VC960804CNA*	34,000	26,400	13.5	11.3	1,115	7353902
	CA*F3743*6D*+TXV	A*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353898
	CA*F3743*6D*+TXV	A*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353900
	CA*F3743*6D*+TXV	G*EC961004CNA*	33,600	26,200	14.0	11.5	1,100	7365300
	CA*F3743*6D*+TXV	A*VC960804CNA*	34,000	26,400	13.5	11.3	1,115	7353896
	CA*F3743*6D*+TXV	G*EC960803BNA*	33,400	26,000	13.5	11.0	1,075	7365297
	CA*F3743*6D*+TXV	G*VM970804CNA*	34,000	26,400	13.5	11.3	1,115	7353905
	CA*F3743*6D*+TXV	G*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353907
	CA*F3743*6D*+TXV	A*VM970804CNA*	34,000	26,400	13.5	11.3	1,115	7353899
	CA*F3743*6D*+TXV	A*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353901
	CA*F3743*6D*+TXV	A*EC961004CNA*	33,600	26,200	14.0	11.5	1,100	7365408
	CA*F3743*6D*+TXV	A*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353897
	CA*F3743*6D*+TXV	G*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353904
	CAPT3743*4A*	G*VC80804C*B*	34,000	27,200	13.5	11.5	1250	9923226
	CAPT3743*4A*	G*VC80805D*B*	34,000	27,200	13.5	11.5	1200	9923227
	CAPT3743*4A*	A*VC960804CNA*	34,000	26,400	13.0	11.0	1,115	7353908
	CAPT3743*4A*	G*VM970804CNA*	34,000	26,400	13.0	11.0	1,115	7353917
	CAPT3743*4A*	G*EC961004CNA*	33,600	26,200	13.5	11.3	1,100	7365301
	CAPT3743*4A*	A*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353910
	CAPT3743*4A*	A*VM970804CNA*	34,000	26,400	13.0	11.0	1,115	7353911
	CAPT3743*4A*	G*VC80604B*B*	34,000	26,400	13.5	11.5	1,220	6494277
	CAPT3743*4A*	A*EH800603B*A*	34,000	26,400	13.0	11.0	1,150	6944884
	CAPT3743*4A*	ADVC81005C*B*	34,000	26,400	13.5	11.5	1,235	6494242
	CAPT3743*4A*	ADVC80805C*B*	34,000	26,400	13.5	11.5	1,190	6494241
	CAPT3743*4A*	A*VM971005CNA*	34,000	26,400	13.0	11.0	1,175	7353912
	CAPT3743*4A*	G*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353919
	CAPT3743*4A*	A*EC961004CNA*	33,600	26,200	13.5	11.3	1,100	7365409
	CAPT3743*4A*	G*VC80805C*B*	34,000	26,400	13.5	11.5	1,190	6494278
	CAPT3743*4A*	A*VC80805C*B*	34,000	26,400	13.5	11.5	1,190	6494226
	CAPT3743*4A*	G*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353916
	CAPT3743*4A*	G*E80603B*B*	34,000	26,400	13.0	11.0	1,150	6494243
	CAPT3743*4A*	A*VC81005C*B*	34,000	26,400	13.5	11.5	1,210	6494227
	CAPT3743*4A*	ADVC80603B*B*	34,000	26,400	13.5	11.5	1,165	6494240
	CAPT3743*4A*	A*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353913
	CAPT3743*4A*	A*VC80604B*B*	34,000	26,400	13.5	11.5	1,220	6494225

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0361E* (Contd.)	CAPT3743*4A*	A*EH800805C*A*	34,000	26,400	13.5	11.5	1,210	6944886
	CAPT3743*4A*	G*VC81005C*B*	34,000	26,400	13.5	11.5	1,210	6494279
	CAPT3743*4A*	G*VM971005CNA*	34,000	26,400	13.0	11.0	1,175	7353918
	CAPT3743*4A*	G*VC961005CNA*	34,000	26,400	13.0	11.0	1,175	7353915
	CAPT3743*4A*	G*VC960804CNA*	34,000	26,400	13.0	11.0	1,115	7353914
	CAPT3743*4A*	G*E81005C*B*	34,000	26,400	13.5	11.5	1,230	6494245
	CAPT3743*4A*	G*E80805C*B*	34,000	26,400	13.5	11.5	1,210	6494244
	CAPT3743*4A*	A*EH801005C*A*	34,000	26,400	13.5	11.5	1,230	6944888
	CAPT3743*4A*	A*VC961005CNA*	34,000	26,400	13.0	11.0	1,175	7353909
	CAPT3743*4A*+EEP		34,000	26,400	13.0	11.0	1,200	5696612
	CAPT3743*4A*+MBVC1200**-1A*		34,000	26,400	13.0	11.5	1,200	6494250
	CAPT3743*4A*+MBVC1600**-1A*		34,000	26,400	14.0	11.5	1,205	5696642
	CAPT3743*4A*+MBVC2000**-1A*		34,000	26,400	14.0	11.5	1,205	5696644
	CHPF3636B6C*+EEP		33,000	26,400	13.0	11.0	1,000	5696613
	CHPF3642C6C*	G*VC81005C*B*	34,000	27,200	13.5	11.3	1150	9923230
	CHPF3642C6C*	G*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353925
	CHPF3642C6C*	A*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353923
	CHPF3642C6C*	A*VM970804CNA*	33,800	26,400	13.0	11.0	1,115	7353922
	CHPF3642C6C*	G*VC960804CNA*	33,800	26,400	13.0	11.0	1,115	7353924
	CHPF3642C6C*	A*VC960804CNA*	33,800	26,400	13.0	11.0	1,115	7353920
	CHPF3642C6C*	G*E80805C*B*	34,000	26,400	14.0	11.5	1,100	7424249
	CHPF3642C6C*	A*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353921
	CHPF3642C6C*	G*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353927
	CHPF3642C6C*	G*VM970804CNA*	33,800	26,400	13.0	11.0	1,115	7353926
	CHPF3642C6C*+EEP		33,000	26,400	13.0	11.0	1,000	5696614
	CHPF3642C6C*+MBVC1600**-1A*		34,000	26,400	14.0	11.5	1,210	5696643
	CHPF3642C6C*+TXV	G*VC81005C*B*	34,000	27,200	13.5	11.5	1150	9923231
	CHPF3642C6C*+TXV	A*VM970804CNA*	33,800	26,400	13.5	11.3	1,115	7353930
	CHPF3642C6C*+TXV	A*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353931
	CHPF3642C6C*+TXV	A*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353929
	CHPF3642C6C*+TXV	G*VC961005CNA*	34,000	26,400	13.5	11.3	1,175	7353933
	CHPF3642C6C*+TXV	G*VM970804CNA*	33,800	26,400	13.5	11.3	1,115	7353934
	CHPF3642C6C*+TXV	G*VC960804CNA*	33,800	26,400	13.5	11.3	1,115	7353932
	CHPF3642C6C*+TXV	G*VM971005CNA*	34,000	26,400	13.5	11.3	1,175	7353935
	CHPF3642C6C*+TXV	A*VC960804CNA*	33,800	26,400	13.5	11.3	1,115	7353928
	CHPF3642D6C*	G*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353939
	CHPF3642D6C*	A*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353937
	CHPF3642D6C*	G*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353938
	CHPF3642D6C*	A*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353936
	CHPF3642D6C*+EEP		34,000	26,400	13.0	11.0	1,200	5696615
	CHPF3642D6C*+TXV	G*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353943
	CHPF3642D6C*+TXV	A*VM971205DNA*	34,000	26,400	13.5	11.3	1,150	7353941
	CHPF3642D6C*+TXV	A*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353940
	CHPF3642D6C*+TXV	G*VC961205DNA*	34,000	26,400	13.5	11.3	1,150	7353942
	CHPF3743C6B*	A*EC961004CNA*	33,600	26,200	13.5	11.3	1,100	7365410
	CHPF3743C6B*	G*EC961004CNA*	33,600	26,200	13.5	11.3	1,100	7365302
	CHPF3743C6B*+TXV	A*EC960603BNA*	33,600	26,200	13.5	11.0	1,175	7365404
	CHPF3743C6B*+TXV	G*EC960603BNA*	33,600	26,200	13.5	11.0	1,175	7365296

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0361E* (Contd.)	CHPF3743C6B*+TXV	A*EC961004CNA*	33,600	26,200	14.0	11.5	1,100	7365411
	CHPF3743C6B*+TXV	A*EC960803BNA*	33,400	26,000	13.5	11.0	1,075	7365406
	CHPF3743C6B*+TXV	G*EC960803BNA*	33,400	26,000	13.5	11.0	1,075	7365298
	CHPF3743C6B*+TXV	G*EC961004CNA*	33,600	26,200	14.0	11.5	1,100	7365303
	CSCF3036N6D*+EEP		34,000	26,400	13.0	11.0	1,200	6752560
	CSCF3642N6D*	G*VC81005C*B*	34,000	27,200	13.5	11.3	1,150	9923232
	CSCF3642N6D*	G*VC960804CNA*	33,600	26,200	13.0	11.0	1,115	7353950
	CSCF3642N6D*	A*VC961005CNA*	33,800	26,400	13.5	11.3	1,175	7353945
	CSCF3642N6D*	G*VC961205DNA*	33,600	26,200	13.5	11.3	1,150	7353952
	CSCF3642N6D*	G*VM971205DNA*	33,600	26,200	13.5	11.3	1,150	7353955
	CSCF3642N6D*	G*VM971005CNA*	33,800	26,400	13.5	11.3	1,175	7353954
	CSCF3642N6D*	G*VC961005CNA*	33,800	26,400	13.5	11.3	1,175	7353951
	CSCF3642N6D*	A*VC960804CNA*	33,600	26,200	13.0	11.0	1,115	7353944
	CSCF3642N6D*	A*VC961205DNA*	33,600	26,200	13.5	11.3	1,150	7353946
	CSCF3642N6D*	A*VM971205DNA*	33,600	26,200	13.5	11.3	1,150	7353949
	CSCF3642N6D*	G*VM970804CNA*	33,600	26,200	13.0	11.0	1,115	7353953
	CSCF3642N6D*	A*VM970804CNA*	33,600	26,200	13.0	11.0	1,115	7353947
	CSCF3642N6D*	A*VM971005CNA*	33,800	26,400	13.5	11.3	1,175	7353948
	CSCF3642N6D*+EEP		34,600	27,000	13.0	11.0	1,200	6752561
	CSCF3642N6D*+TXV	G*VC81005C*B*	34,000	27,200	13.5	11.5	1,150	9923233
	CSCF3642N6D*+TXV	A*VC960804CNA*	33,600	26,200	13.0	11.0	1,115	7353956
	CSCF3642N6D*+TXV	A*VM970804CNA*	33,600	26,200	13.0	11.0	1,115	7353959
	CSCF3642N6D*+TXV	G*VC960804CNA*	33,600	26,200	13.0	11.0	1,115	7353962
	CSCF3642N6D*+TXV	A*VC961005CNA*	33,800	26,400	13.5	11.3	1,175	7353957
	CSCF3642N6D*+TXV	G*VC961005CNA*	33,800	26,400	13.5	11.3	1,175	7353963
	CSCF3642N6D*+TXV	A*VM971205DNA*	33,600	26,200	13.5	11.3	1,150	7353961
	CSCF3642N6D*+TXV	G*VC961205DNA*	33,600	26,200	13.5	11.3	1,150	7353964
	CSCF3642N6D*+TXV	G*VM971005CNA*	33,800	26,400	13.5	11.3	1,175	7353966
	CSCF3642N6D*+TXV	A*VM971005CNA*	33,800	26,400	13.5	11.3	1,175	7353960
	CSCF3642N6D*+TXV	A*VC961205DNA*	33,600	26,200	13.5	11.3	1,150	7353958
	CSCF3642N6D*+TXV	G*VM971205DNA*	33,600	26,200	13.5	11.3	1,150	7353967
	CSCF3642N6D*+TXV	G*VM970804CNA*	33,600	26,200	13.0	11.0	1,115	7353965
GSX13 0421B*	ARUF42C14A*+TXV		39,500	30,200	13.0	11.0	1,280	5378539
	ARUF43C14A*		40,500	31,000	13.0	11.0	1,345	7984178
	ARUF43D14A*		40,500	31,000	13.0	11.0	1,270	8171719
	ASPT47D14A*		40,000	30,600	14.0	12.0	1,200	8242046
	ASPT49D14A*		40,500	31,000	14.0	12.0	1,290	8242047
	AVPTC42D14A*		40,500	31,000	14.0	12.0	1,495	5924343
	AVPTC48C14A*		39,500	30,200	13.5	11.5	1,300	7079219
	AVPTC49D14A*		41,000	31,400	14.0	12.0	1,320	8996122
	AVPTC59C14A*		40,000	30,600	14.0	12.0	1,290	8996120
	AVPTC59D14A*		40,500	31,000	14.0	12.0	1,365	8996121
	CA*F3642*6D*	A*EH800805C*A*	40,000	30,600	13.0	11.3	1,350	6944898
	CA*F3642*6D*	G*E80805C*B*	40,000	30,600	13.0	11.3	1,350	5038971
	CA*F3642*6D*+EEP		40,000	30,600	13.0	11.0	1,400	4946292
	CA*F3642*6D*+EEP+TXV		40,000	30,600	13.0	11.0	1,400	5561917
	CA*F3743*6D*	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923234
	CA*F3743*6D*	A*VM970804CNA*	40,500	31,000	14.0	11.5	1,300	7353971

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0421B* (Contd.)	CA*F3743*6D*	G*VC961005CNA*	40,500	31,000	14.0	11.5	1,300	7353975
	CA*F3743*6D*	G*VM971205DNA*	40,000	30,600	14.0	11.5	1,250	7353979
	CA*F3743*6D*	G*VM971005CNA*	40,500	31,000	14.0	11.5	1,300	7353978
	CA*F3743*6D*	A*VC961205DNA*	40,000	30,600	14.0	11.5	1,250	7353970
	CA*F3743*6D*	G*VC960804CNA*	40,500	31,000	14.0	11.5	1,300	7353974
	CA*F3743*6D*	A*VM971005CNA*	40,500	31,000	14.0	11.5	1,300	7353972
	CA*F3743*6D*	A*EH800805C*A*	40,000	30,600	13.0	11.3	1,350	6944900
	CA*F3743*6D*	A*VC960804CNA*	40,500	31,000	14.0	11.5	1,300	7353968
	CA*F3743*6D*	G*VC961205DNA*	40,000	30,600	14.0	11.5	1,250	7353976
	CA*F3743*6D*	G*E80805C*B*	40,000	30,600	13.0	11.3	1,350	5039232
	CA*F3743*6D*	G*VM970804CNA*	40,500	31,000	14.0	11.5	1,300	7353977
	CA*F3743*6D*	A*VC961005CNA*	40,500	31,000	14.0	11.5	1,300	7353969
	CA*F3743*6D*	A*VM971205DNA*	40,000	30,600	14.0	11.5	1,250	7353973
	CA*F3743*6D*+EEP		40,000	30,600	13.0	11.0	1,400	4415025
	CA*F3743*6D*+TXV	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923235
	CA*F3743*6D*+TXV	A*VM971005CNA*	40,500	31,000	14.0	11.5	1,300	7353984
	CA*F3743*6D*+TXV	G*VC960804CNA*	40,500	31,000	14.0	11.5	1,300	7353986
	CA*F3743*6D*+TXV	A*VM970804CNA*	40,500	31,000	14.0	11.5	1,300	7353983
	CA*F3743*6D*+TXV	G*VM971205DNA*	40,000	30,600	14.0	11.5	1,250	7353991
	CA*F3743*6D*+TXV	A*VC960804CNA*	40,500	31,000	14.0	11.5	1,300	7353980
	CA*F3743*6D*+TXV	G*VC961205DNA*	40,000	30,600	14.0	11.5	1,250	7353988
	CA*F3743*6D*+TXV	A*VC961005CNA*	40,500	31,000	14.0	11.5	1,300	7353981
	CA*F3743*6D*+TXV	G*VC961005CNA*	40,500	31,000	14.0	11.5	1,300	7353987
	CA*F3743*6D*+TXV	A*VM971205DNA*	40,000	30,600	14.0	11.5	1,250	7353985
	CA*F3743*6D*+TXV	G*VM970804CNA*	40,500	31,000	14.0	11.5	1,300	7353989
	CA*F3743*6D*+TXV	A*VC961205DNA*	40,000	30,600	14.0	11.5	1,250	7353982
	CA*F3743*6D*+TXV	G*VM971005CNA*	40,500	31,000	14.0	11.5	1,300	7353990
	CA*F4860*6D*	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923236
	CA*F4860*6D*	A*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7353996
	CA*F4860*6D*	A*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7353993
	CA*F4860*6D*	A*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7353995
	CA*F4860*6D*	A*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7353994
	CA*F4860*6D*	G*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354000
	CA*F4860*6D*	G*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7353998
	CA*F4860*6D*	A*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365412
	CA*F4860*6D*	G*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365304
	CA*F4860*6D*	A*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7353997
	CA*F4860*6D*	A*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7353992
	CA*F4860*6D*	G*EC961205DNA*	40,000	30,600	13.5	11.3	1,400	7365309
	CA*F4860*6D*	A*EH800805C*A*	41,000	31,400	13.5	11.5	1,510	6944902
	CA*F4860*6D*	G*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354002
	CA*F4860*6D*	G*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354001
	CA*F4860*6D*	G*E80805C*B*	41,000	31,400	13.5	11.5	1,510	5039124
	CA*F4860*6D*	G*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7353999
	CA*F4860*6D*	A*EC961205DNA*	40,000	30,600	13.5	11.3	1,400	7365417
	CA*F4860*6D*	G*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354003
	CA*F4860*6D*+EEP		41,000	31,400	13.0	11.0	1,400	3880267
	CA*F4860*6D*+MBVC1600**-1A*		41,000	31,400	14.0	11.5	1,400	3880314

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0421B* (Contd.)	CA*F4860*6D*+TXV	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923237
	CA*F4860*6D*+TXV	A*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354005
	CA*F4860*6D*+TXV	A*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365413
	CA*F4860*6D*+TXV	G*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354010
	CA*F4860*6D*+TXV	G*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354012
	CA*F4860*6D*+TXV	A*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354007
	CA*F4860*6D*+TXV	G*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354013
	CA*F4860*6D*+TXV	G*EC961205DNA*	40,000	30,600	14.0	11.5	1,400	7365310
	CA*F4860*6D*+TXV	A*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354004
	CA*F4860*6D*+TXV	A*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354006
	CA*F4860*6D*+TXV	A*EC961205DNA*	40,000	30,600	14.0	11.5	1,400	7365418
	CA*F4860*6D*+TXV	G*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354014
	CA*F4860*6D*+TXV	G*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365305
	CA*F4860*6D*+TXV	A*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354008
	CA*F4860*6D*+TXV	G*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354011
	CA*F4860*6D*+TXV	G*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354015
	CA*F4860*6D*+TXV	A*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354009
	CA*F4961*6D*+EEP		41,000	31,400	13.0	11.0	1,400	4887677
	CAPT4961*4A*	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923238
	CAPT4961*4A*	A*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354021
	CAPT4961*4A*	A*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354018
	CAPT4961*4A*	G*EC961205DNA*	40,500	31,000	14.0	11.5	1,400	7365311
	CAPT4961*4A*	A*VC80805C*B*	41,000	31,400	14.0	12.0	1,395	6945540
	CAPT4961*4A*	A*VC80604B*B*	41,000	31,400	14.0	12.0	1,410	6945534
	CAPT4961*4A*	G*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354026
	CAPT4961*4A*	A*VC81005C*B*	41,000	31,400	14.0	12.0	1,370	6945545
	CAPT4961*4A*	G*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354024
	CAPT4961*4A*	A*EC961205DNA*	40,500	31,000	14.0	11.5	1,400	7365419
	CAPT4961*4A*	G*E81005C*B*	41,000	31,400	14.0	12.0	1,300	6945529
	CAPT4961*4A*	A*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354019
	CAPT4961*4A*	A*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365414
	CAPT4961*4A*	ADVC81005C*B*	41,000	31,400	14.0	12.0	1,405	6945668
	CAPT4961*4A*	A*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354016
	CAPT4961*4A*	G*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354027
	CAPT4961*4A*	G*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354025
	CAPT4961*4A*	ADVC80805C*B*	41,000	31,400	14.0	12.0	1,380	6945664
	CAPT4961*4A*	G*E80603B*B*	41,000	31,400	13.5	11.5	1,355	6945520
	CAPT4961*4A*	G*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365306
	CAPT4961*4A*	G*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354023
	CAPT4961*4A*	A*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354017
	CAPT4961*4A*	G*E80805C*B*	41,000	31,400	14.0	12.0	1,350	6945522
	CAPT4961*4A*	G*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354022
	CAPT4961*4A*	A*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354020
	CAPT4961*4A*+EEP		40,500	31,000	13.0	11.0	1,400	5611311
	CAPT4961*4A*+MBVC1600**-1A*		41,000	31,400	14.0	11.5	1,375	5611312
	CAPT4961*4A*+MBVC2000**-1A*		41,000	31,400	14.0	11.5	1,400	5611313
	CHPF3642C6C*	G*E80805C*B*	40,000	30,600	13.0	11.3	1,350	5039027
	CHPF3642C6C*	A*EH800805C*A*	40,000	30,600	13.0	11.3	1,350	6944908

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0421B* (Contd.)	CHPF3642C6C*+EEP		38,500	30,600	13.0	11.0	1,075	3539875
	CHPF3642D6C*+EEP		40,000	30,600	13.0	11.0	1,400	3539877
	CHPF3743C6B*	G*VC81005C*B*	40,000	31,600	13.5	11.2	1300	9923239
	CHPF3743C6B*	A*VM971005CNA*	40,500	31,000	13.5	11.3	1,300	7354031
	CHPF3743C6B*	G*VM971005CNA*	40,500	31,000	13.5	11.3	1,300	7354035
	CHPF3743C6B*	A*VM970804CNA*	40,500	31,000	13.5	11.3	1,300	7354030
	CHPF3743C6B*	G*VC961005CNA*	40,500	31,000	13.5	11.3	1,300	7354033
	CHPF3743C6B*	A*VC960804CNA*	40,500	31,000	13.5	11.3	1,300	7354028
	CHPF3743C6B*	A*VC961005CNA*	40,500	31,000	13.5	11.3	1,300	7354029
	CHPF3743C6B*	G*VC960804CNA*	40,500	31,000	13.5	11.3	1,300	7354032
	CHPF3743C6B*	G*VM970804CNA*	40,500	31,000	13.5	11.3	1,300	7354034
	CHPF3743C6B*+EEP		39,000	30,600	13.0	11.0	1,075	6497574
	CHPF3743C6B*+TXV	G*VC81005C*B*	40,000	31,600	13.5	11.2	1300	9923240
	CHPF3743C6B*+TXV	A*VM970804CNA*	40,500	31,000	14.0	11.5	1,300	7354038
	CHPF3743C6B*+TXV	A*VM971005CNA*	40,500	31,000	14.0	11.5	1,300	7354039
	CHPF3743C6B*+TXV	A*VC960804CNA*	40,500	31,000	14.0	11.5	1,300	7354036
	CHPF3743C6B*+TXV	G*VM971005CNA*	40,500	31,000	14.0	11.5	1,300	7354043
	CHPF3743C6B*+TXV	G*VC960804CNA*	40,500	31,000	14.0	11.5	1,300	7354040
	CHPF3743C6B*+TXV	G*VC961005CNA*	40,500	31,000	14.0	11.5	1,300	7354041
	CHPF3743C6B*+TXV	A*VC961005CNA*	40,500	31,000	14.0	11.5	1,300	7354037
	CHPF3743C6B*+TXV	G*VM970804CNA*	40,500	31,000	14.0	11.5	1,300	7354042
	CHPF3743D6B*	A*VM971205DNA*	40,000	30,600	13.5	11.3	1,250	7355024
	CHPF3743D6B*	G*VC961205DNA*	40,000	30,600	13.5	11.3	1,250	7355025
	CHPF3743D6B*	G*VM971205DNA*	40,000	30,600	13.5	11.3	1,250	7355026
	CHPF3743D6B*	A*VC961205DNA*	40,000	30,600	13.5	11.3	1,250	7355023
	CHPF3743D6B*+TXV	G*VC961205DNA*	40,000	30,600	14.0	11.5	1,250	7355029
	CHPF3743D6B*+TXV	G*VM971205DNA*	40,000	30,600	14.0	11.5	1,250	7355030
	CHPF3743D6B*+TXV	A*VM971205DNA*	40,000	30,600	14.0	11.5	1,250	7355028
	CHPF3743D6B*+TXV	A*VC961205DNA*	40,000	30,600	14.0	11.5	1,250	7355027
	CHPF4860D6D*	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923241
	CHPF4860D6D*	G*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354055
	CHPF4860D6D*	A*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354044
	CHPF4860D6D*	A*EC961205DNA*	40,500	31,000	13.5	11.3	1,400	7365420
	CHPF4860D6D*	G*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354053
	CHPF4860D6D*	G*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354051
	CHPF4860D6D*	G*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354052
	CHPF4860D6D*	G*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354054
	CHPF4860D6D*	A*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365415
	CHPF4860D6D*	A*EH800805C*A*	41,000	31,400	13.5	11.5	1,510	6944910
	CHPF4860D6D*	A*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354047
	CHPF4860D6D*	A*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354048
	CHPF4860D6D*	G*EC961205DNA*	40,500	31,000	13.5	11.3	1,400	7365312
	CHPF4860D6D*	G*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365307
	CHPF4860D6D*	G*E80805C*B*	41,000	31,400	13.5	11.5	1,400	5038972
	CHPF4860D6D*	A*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354049
	CHPF4860D6D*	A*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354046
	CHPF4860D6D*	G*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354050
	CHPF4860D6D*	A*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354045

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0421B* (Contd.)	CHPF4860D6D*+EEP		41,000	31,400	13.0	11.0	1,400	3539879
	CHPF4860D6D*+MBVC1600**-1A*		41,000	31,400	14.0	11.5	1,400	3609448
	CHPF4860D6D*+TXV	G*VC81005C*B*	40,500	32,000	14.0	11.5	1300	9923242
	CHPF4860D6D*+TXV	G*E80805C*B*	41,000	31,400	14.0	11.5	1,400	7614641
	CHPF4860D6D*+TXV	G*EC961205DNA*	40,500	31,000	14.0	11.5	1,400	7365313
	CHPF4860D6D*+TXV	A*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354057
	CHPF4860D6D*+TXV	A*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354058
	CHPF4860D6D*+TXV	G*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354063
	CHPF4860D6D*+TXV	A*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354059
	CHPF4860D6D*+TXV	A*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354056
	CHPF4860D6D*+TXV	G*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354067
	CHPF4860D6D*+TXV	A*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354061
	CHPF4860D6D*+TXV	A*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365416
	CHPF4860D6D*+TXV	G*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354066
	CHPF4860D6D*+TXV	G*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354064
	CHPF4860D6D*+TXV	A*EC961205DNA*	40,500	31,000	14.0	11.5	1,400	7365421
	CHPF4860D6D*+TXV	G*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354062
	CHPF4860D6D*+TXV	A*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354060
	CHPF4860D6D*+TXV	G*EC961004CNA*	39,500	30,200	14.0	11.5	1,275	7365308
	CHPF4860D6D*+TXV	G*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354065
	CSCF3642N6D*+EEP		40,000	30,600	13.0	11.0	1,325	4767422
	CSCF4860N6D*	G*VC81005C*B*	41,000	32,400	13.5	11.5	1300	9923243
	CSCF4860N6D*	A*VC961205DNA*	40,500	31,000	13.5	11.3	1,250	7354070
	CSCF4860N6D*	G*VM971005CNA*	41,000	31,400	13.5	11.5	1,300	7354078
	CSCF4860N6D*	G*VC961205DNA*	40,500	31,000	13.5	11.3	1,250	7354076
	CSCF4860N6D*	A*VM970804CNA*	41,000	31,400	13.5	11.3	1,300	7354071
	CSCF4860N6D*	G*VC960804CNA*	41,000	31,400	13.5	11.3	1,300	7354074
	CSCF4860N6D*	A*VC961005CNA*	41,000	31,400	13.5	11.5	1,300	7354069
	CSCF4860N6D*	A*VM971205DNA*	40,500	31,000	13.5	11.3	1,250	7354073
	CSCF4860N6D*	G*VC961005CNA*	41,000	31,400	13.5	11.5	1,300	7354075
	CSCF4860N6D*	G*VM971205DNA*	40,500	31,000	13.5	11.3	1,250	7354079
	CSCF4860N6D*	A*VC960804CNA*	41,000	31,400	13.5	11.3	1,300	7354068
	CSCF4860N6D*	A*VM971005CNA*	41,000	31,400	13.5	11.5	1,300	7354072
	CSCF4860N6D*	G*VM970804CNA*	41,000	31,400	13.5	11.3	1,300	7354077
	CSCF4860N6D*+EEP		41,000	31,400	13.0	11.0	1,325	4767426
	CSCF4860N6D*+TXV	G*VC81005C*B*	41,000	32,400	14.0	11.5	1300	9923244
	CSCF4860N6D*+TXV	G*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354090
	CSCF4860N6D*+TXV	G*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354088
	CSCF4860N6D*+TXV	G*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354087
	CSCF4860N6D*+TXV	A*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354083
	CSCF4860N6D*+TXV	G*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354086
	CSCF4860N6D*+TXV	G*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354091
	CSCF4860N6D*+TXV	A*VC961005CNA*	41,000	31,400	14.0	11.5	1,300	7354081
	CSCF4860N6D*+TXV	G*VM970804CNA*	41,000	31,400	14.0	11.5	1,300	7354089
	CSCF4860N6D*+TXV	A*VM971005CNA*	41,000	31,400	14.0	11.5	1,300	7354084
	CSCF4860N6D*+TXV	A*VC960804CNA*	41,000	31,400	14.0	11.5	1,300	7354080
	CSCF4860N6D*+TXV	A*VM971205DNA*	40,500	31,000	14.0	11.5	1,250	7354085
	CSCF4860N6D*+TXV	A*VC961205DNA*	40,500	31,000	14.0	11.5	1,250	7354082

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0481B*	ARUF47D14A*		45,000	34,600	13.0	11.0	1,515	7984179
	ARUF48D14A*+TXV		44,500	34,200	13.0	11.0	1,550	5378542
	ARUF49D14A*		45,000	34,600	13.0	11.0	1,455	8171720
	ARUF60D14A*+TXV		44,500	34,200	13.0	11.0	1,460	5378543
	ASPT49D14A*		45,000	34,600	14.0	11.5	1,430	8242048
	AVPTC48C14A*		44,000	33,800	13.0	11.0	1,450	7079222
	AVPTC48D14A*		46,000	35,200	13.8	11.3	1,615	5924446
	AVPTC59C14A*		45,000	34,600	13.0	11.0	1,485	8996123
	AVPTC59D14A*		45,500	34,800	14.0	12.0	1,580	9000366
	AVPTC61D14A*		46,000	35,200	14.0	12.0	1,455	9000367
	CA*F4860*6D*+EEP		46,000	35,200	13.0	11.0	1,600	4214133
	CA*F4860*6D*+MBVC2000**-1A*		46,000	35,200	14.0	11.3	1,600	3880321
	CA*F4860*6D*+TXV	A*EH801005C*A*	46,000	35,200	13.5	11.3	1,570	6944918
	CA*F4860*6D*+TXV	G*E81005C*B*	46,000	35,200	13.5	11.3	1,570	5039261
	CA*F4860*6D*+TXV	A*EH800805C*A*	46,000	35,200	13.5	11.3	1,650	6944916
	CA*F4860*6D*+TXV	G*EC961004CNA*	46,000	35,200	14.0	11.5	1,550	7365314
	CA*F4860*6D*+TXV	G*E80805C*B*	46,000	35,200	13.5	11.3	1,650	5039233
	CA*F4860*6D*+TXV	A*EC961004CNA*	46,000	35,200	14.0	11.5	1,550	7365422
	CA*F4961*6D*	A*EC961205DNA*	45,500	34,800	14.0	11.5	1,525	7365427
	CA*F4961*6D*	G*EC961205DNA*	45,500	34,800	14.0	11.5	1,525	7365319
	CA*F4961*6D*+EEP		46,000	35,200	13.0	11.0	1,600	5685098
	CA*F4961*6D*+TXV	G*VC81005C*B*	45,000	35,400	14.0	11.5	1600	9923245
	CA*F4961*6D*+TXV	A*EC961004CNA*	46,000	35,200	14.0	11.5	1,550	7365423
	CA*F4961*6D*+TXV	G*VM971005CNA*	45,000	34,600	14.0	11.5	1,520	7354102
	CA*F4961*6D*+TXV	G*VC961205DNA*	46,000	35,200	14.0	11.5	1,575	7354100
	CA*F4961*6D*+TXV	A*VM971005CNA*	45,000	34,600	14.0	11.5	1,520	7354096
	CA*F4961*6D*+TXV	G*VC961005CNA*	45,000	34,600	14.0	11.5	1,520	7354099
	CA*F4961*6D*+TXV	A*EC961205DNA*	46,000	35,200	14.0	11.5	1,525	7365428
	CA*F4961*6D*+TXV	G*VC960804CNA*	45,000	34,600	14.0	11.5	1,585	7354098
	CA*F4961*6D*+TXV	G*VM970804CNA*	45,000	34,600	14.0	11.5	1,585	7354101
	CA*F4961*6D*+TXV	A*VM971205DNA*	46,000	35,200	14.0	11.5	1,575	7354097
	CA*F4961*6D*+TXV	A*VC961205DNA*	46,000	35,200	14.0	11.5	1,575	7354094
	CA*F4961*6D*+TXV	G*EC961004CNA*	46,000	35,200	14.0	11.5	1,550	7365315
	CA*F4961*6D*+TXV	A*VC961005CNA*	45,000	34,600	14.0	11.5	1,520	7354093
	CA*F4961*6D*+TXV	A*VM970804CNA*	45,000	34,600	14.0	11.5	1,585	7354095
	CA*F4961*6D*+TXV	G*EC961205DNA*	46,000	35,200	14.0	11.5	1,525	7365320
	CA*F4961*6D*+TXV	A*VC960804CNA*	45,000	34,600	14.0	11.5	1,585	7354092
	CA*F4961*6D*+TXV	G*VM971205DNA*	46,000	35,200	14.0	11.5	1,575	7354103
	CAPT4961*4A*	G*VC81005C*B*	47,000	37,000	13.5	11.5	1600	9923246
	CAPT4961*4A*	A*VC81005C*B*	47,000	36,000	13.5	11.5	1,600	6945546
	CAPT4961*4A*	G*VM970804CNA*	45,000	34,600	13.5	11.3	1,585	7354113
	CAPT4961*4A*	G*E80805C*B*	46,000	35,200	13.5	11.5	1,480	6945523
	CAPT4961*4A*	A*VC80805C*B*	47,000	36,000	13.5	11.5	1,590	6945541
	CAPT4961*4A*	G*EC961004CNA*	46,000	35,200	14.0	11.5	1,550	7365316
	CAPT4961*4A*	G*E81005C*B*	47,000	36,000	13.5	11.5	1,570	6945530
	CAPT4961*4A*	A*VM970804CNA*	45,000	34,600	13.5	11.3	1,585	7354107
	CAPT4961*4A*	G*VC960804CNA*	45,000	34,600	13.5	11.3	1,585	7354110
	CAPT4961*4A*	A*VC961205DNA*	46,000	35,200	14.0	11.5	1,575	7354106

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0481B* (Contd.)	CAPT4961*4A*	G*VC961005CNA*	45,000	34,600	14.0	11.5	1,520	7354111
	CAPT4961*4A*	G*EC961205DNA*	46,000	35,200	13.5	11.3	1,525	7365321
	CAPT4961*4A*	G*VM971205DNA*	46,000	35,200	14.0	11.5	1,575	7354115
	CAPT4961*4A*	G*VC961205DNA*	46,000	35,200	14.0	11.5	1,575	7354112
	CAPT4961*4A*	ADVC81005C*B*	47,000	36,000	13.5	11.5	1,620	6945669
	CAPT4961*4A*	A*VC80604B*B*	47,000	36,000	13.5	11.5	1,545	6945535
	CAPT4961*4A*	A*EC961004CNA*	46,000	35,200	14.0	11.5	1,550	7365424
	CAPT4961*4A*	A*VC961005CNA*	45,000	34,600	14.0	11.5	1,520	7354105
	CAPT4961*4A*	A*VM971005CNA*	45,000	34,600	14.0	11.5	1,520	7354108
	CAPT4961*4A*	A*EC961205DNA*	46,000	35,200	13.5	11.3	1,525	7365429
	CAPT4961*4A*	A*VC960804CNA*	45,000	34,600	13.5	11.3	1,585	7354104
	CAPT4961*4A*	A*VM971205DNA*	46,000	35,200	14.0	11.5	1,575	7354109
	CAPT4961*4A*	ADVC80805C*B*	47,000	36,000	13.5	11.5	1,585	6945665
	CAPT4961*4A*	G*VM971005CNA*	45,000	34,600	14.0	11.5	1,520	7354114
	CAPT4961*4A*+EEP		46,500	35,600	13.0	11.0	1,600	5611314
	CAPT4961*4A*+MBVC1600**-1A*		47,000	36,000	14.0	11.5	1,500	5611315
	CAPT4961*4A*+MBVC2000**-1A*		47,000	36,000	14.0	11.5	1,550	5611316
	CHPF4860D6D*	A*EC961004CNA*	45,500	34,800	13.5	11.5	1,550	7365425
	CHPF4860D6D*	A*EC961205DNA*	45,500	34,800	13.5	11.3	1,525	7365430
	CHPF4860D6D*	G*EC961205DNA*	45,500	34,800	13.5	11.3	1,525	7365322
	CHPF4860D6D*	G*EC961004CNA*	45,500	34,800	13.5	11.5	1,550	7365317
	CHPF4860D6D*+EEP		46,000	35,200	13.0	11.0	1,600	3539868
	CHPF4860D6D*+MBVC2000**-1A*		46,000	35,200	14.0	11.3	1,600	3609452
	CHPF4860D6D*+TXV	G*VC81005C*B*	45,000	35,400	14.0	11.5	1600	9923247
	CHPF4860D6D*+TXV	A*VC961005CNA*	45,000	34,600	14.0	11.5	1,520	7354117
	CHPF4860D6D*+TXV	G*EC961004CNA*	45,500	34,800	14.0	11.5	1,550	7365318
	CHPF4860D6D*+TXV	A*EC961004CNA*	45,500	34,800	14.0	11.5	1,550	7365426
	CHPF4860D6D*+TXV	G*VM970804CNA*	45,000	34,600	14.0	11.5	1,585	7354125
	CHPF4860D6D*+TXV	G*VC960804CNA*	45,000	34,600	14.0	11.5	1,585	7354122
	CHPF4860D6D*+TXV	A*EC961205DNA*	45,500	34,800	14.0	11.5	1,525	7365431
	CHPF4860D6D*+TXV	A*VM971205DNA*	46,000	35,200	14.0	11.5	1,575	7354121
	CHPF4860D6D*+TXV	G*EC961205DNA*	45,500	34,800	14.0	11.5	1,525	7365323
	CHPF4860D6D*+TXV	G*E81005C*B*	46,000	35,200	13.5	11.3	1,570	5038912
	CHPF4860D6D*+TXV	G*VM971005CNA*	45,000	34,600	14.0	11.5	1,520	7354126
	CHPF4860D6D*+TXV	G*VC961005CNA*	45,000	34,600	14.0	11.5	1,520	7354123
	CHPF4860D6D*+TXV	A*VM970804CNA*	45,000	34,600	14.0	11.5	1,585	7354119
	CHPF4860D6D*+TXV	A*VM971005CNA*	45,000	34,600	14.0	11.5	1,520	7354120
	CHPF4860D6D*+TXV	G*VC961205DNA*	46,000	35,200	14.0	11.5	1,575	7354124
	CHPF4860D6D*+TXV	A*VC960804CNA*	45,000	34,600	14.0	11.5	1,585	7354116
	CHPF4860D6D*+TXV	A*EH801005C*A*	46,000	35,200	13.5	11.3	1,570	6944925
	CHPF4860D6D*+TXV	G*E80805C*B*	46,000	35,200	13.5	11.3	1,650	5039110
	CHPF4860D6D*+TXV	A*VC961205DNA*	46,000	35,200	14.0	11.5	1,575	7354118
	CHPF4860D6D*+TXV	A*EH800805C*A*	46,000	35,200	13.5	11.3	1,650	6944923
	CHPF4860D6D*+TXV	G*VM971205DNA*	46,000	35,200	14.0	11.5	1,575	7354127
	CSCF4860N6D*+EEP		46,000	35,200	13.0	11.0	1,600	4767427
	CSCF4860N6D*+TXV	G*VC81005C*B*	44,500	35,000	14.0	11.5	1600	9923248
	CSCF4860N6D*+TXV	G*VC961005CNA*	44,500	34,200	14.0	11.5	1,520	7354135
	CSCF4860N6D*+TXV	A*VC960804CNA*	44,500	34,200	13.5	11.3	1,585	7354128

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0481B* (Contd.)	CSCF4860N6D*+TXV	A*VM971205DNA*	45,500	34,800	14.0	11.5	1,575	7354133
	CSCF4860N6D*+TXV	G*VM971205DNA*	45,500	34,800	14.0	11.5	1,575	7354139
	CSCF4860N6D*+TXV	G*VM971005CNA*	44,500	34,200	14.0	11.5	1,520	7354138
	CSCF4860N6D*+TXV	A*VM970804CNA*	44,500	34,200	13.5	11.3	1,585	7354131
	CSCF4860N6D*+TXV	G*VC961205DNA*	45,500	34,800	14.0	11.5	1,575	7354136
	CSCF4860N6D*+TXV	A*VC961005CNA*	44,500	34,200	14.0	11.5	1,520	7354129
	CSCF4860N6D*+TXV	G*VM970804CNA*	44,500	34,200	13.5	11.3	1,585	7354137
	CSCF4860N6D*+TXV	A*VC961205DNA*	45,500	34,800	14.0	11.5	1,575	7354130
	CSCF4860N6D*+TXV	A*VM971005CNA*	44,500	34,200	14.0	11.5	1,520	7354132
	CSCF4860N6D*+TXV	G*VC960804CNA*	44,500	34,200	13.5	11.3	1,585	7354134
GSX13 0601B*	AVPTC59D14A*		55,000	39,000	13.0	11.0	1,660	8996124
	AVPTC60D14A*		56,000	40,000	13.0	11.0	1,750	6349242
	AVPTC61D14A*		56,000	40,000	13.5	11.5	1,775	8996125
	CA*F4961*6D*+EEP		55,500	39,500	13.0	11.0	1,650	4945868
	CA*F4961*6D*+MBVC2000**-1A*		56,000	40,000	13.5	11.5	1,650	4431670
	CA*F4961*6D*+MBVC2000**-1A*+TXV		56,000	40,000	13.5	11.5	1,750	4431671
	CA*F4961*6D*+TXV	G*VC80805D*B*	55,500	40,500	13.3	11.2	1,650	9923249
	CA*F4961*6D*+TXV	G*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354150
	CA*F4961*6D*+TXV	A*VC80805C*B*	55,500	39,500	13.3	11.2	1,800	5039235
	CA*F4961*6D*+TXV	A*VC960804CNA*	54,000	38,500	13.5	11.0	1,585	7354140
	CA*F4961*6D*+TXV	G*VM971205DNA*	54,000	38,500	13.5	11.5	1,585	7354151
	CA*F4961*6D*+TXV	G*VC960804CNA*	54,000	38,500	13.5	11.0	1,585	7354146
	CA*F4961*6D*+TXV	A*VC961205DNA*	54,000	38,500	13.5	11.5	1,585	7354142
	CA*F4961*6D*+TXV	A*VC81005C*B*	55,500	39,500	13.3	11.2	1,800	5039112
	CA*F4961*6D*+TXV	A*EH801005C*A*	55,000	39,000	13.3	11.2	1,720	6944932
	CA*F4961*6D*+TXV	G*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354147
	CA*F4961*6D*+TXV	G*VC961205DNA*	54,000	38,500	13.5	11.5	1,585	7354148
	CA*F4961*6D*+TXV	A*VM970804CNA*	54,000	38,500	13.5	11.0	1,585	7354143
	CA*F4961*6D*+TXV	A*EH800805C*A*	54,500	38,500	13.3	11.2	1,650	6944930
	CA*F4961*6D*+TXV	G*EC961205DNA*	56,500	40,000	13.0	11.0	1,950	7365324
	CA*F4961*6D*+TXV	A*EC961205DNA*	56,500	40,000	13.0	11.0	1,950	7365432
	CA*F4961*6D*+TXV	A*VM971205DNA*	54,000	38,500	13.5	11.5	1,585	7354145
	CA*F4961*6D*+TXV	G*VC80805C*B*	55,500	39,500	13.3	11.2	1,700	5039111
	CA*F4961*6D*+TXV	G*E80805C*B*	54,500	38,500	13.3	11.2	1,650	5038979
	CA*F4961*6D*+TXV	G*E81005C*B*	55,000	39,000	13.3	11.2	1,720	5038893
	CA*F4961*6D*+TXV	G*VM970804CNA*	54,000	38,500	13.5	11.0	1,585	7354149
	CA*F4961*6D*+TXV	A*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354141
	CA*F4961*6D*+TXV	G*VC81005C*B*	55,500	39,500	13.3	11.2	1,700	5038945
	CA*F4961*6D*+TXV	A*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354144
	CAPT4961*4A*	G*VC80805D*B*	55,500	40,500	13.0	11.0	1,650	9923250
	CAPT4961*4A*	G*VM971205DNA*	54,000	38,500	13.0	11.0	1,585	7354163
	CAPT4961*4A*	G*VC80805C*B*	55,500	39,500	13.0	11.0	1,625	5520638
	CAPT4961*4A*	ADVC81005C*B*	55,500	39,500	13.0	11.0	1,625	5520635
	CAPT4961*4A*	A*EC961205DNA*	56,500	40,000	13.0	11.0	1,950	7365433
	CAPT4961*4A*	A*VM970804CNA*	54,000	38,500	13.0	11.0	1,585	7354155
	CAPT4961*4A*	A*EH800805C*A*	54,500	38,500	13.0	11.0	1,675	6944934
	CAPT4961*4A*	A*VC961205DNA*	54,000	38,500	13.0	11.0	1,585	7354154
	CAPT4961*4A*	A*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354156

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0601B* (Contd.)	CAPT4961*4A*	A*VC80805C*B*	55,500	39,500	13.0	11.0	1,625	5520629
	CAPT4961*4A*	A*VC960804CNA*	54,000	38,500	13.0	11.0	1,585	7354152
	CAPT4961*4A*	G*VM970804CNA*	54,000	38,500	13.0	11.0	1,585	7354161
	CAPT4961*4A*	G*E80805C*B*	54,500	38,500	13.0	11.0	1,675	5520636
	CAPT4961*4A*	G*VC960804CNA*	54,000	38,500	13.0	11.0	1,585	7354158
	CAPT4961*4A*	G*VC81005C*B*	55,500	39,500	13.0	11.0	1,625	5520639
	CAPT4961*4A*	G*E81005C*B*	55,000	39,000	13.0	11.0	1,625	5520637
	CAPT4961*4A*	G*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354159
	CAPT4961*4A*	G*EC961205DNA*	56,500	40,000	13.0	11.0	1,950	7365325
	CAPT4961*4A*	A*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354153
	CAPT4961*4A*	A*VM971205DNA*	54,000	38,500	13.0	11.0	1,585	7354157
	CAPT4961*4A*	G*VC961205DNA*	54,000	38,500	13.0	11.0	1,585	7354160
	CAPT4961*4A*	A*EH801005C*A*	55,000	39,000	13.0	11.0	1,625	6944936
	CAPT4961*4A*	A*VC81005C*B*	55,500	39,500	13.0	11.0	1,625	5520630
	CAPT4961*4A*	G*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354162
	CAPT4961*4A*		56,500	40,000	13.0	11.0	1,600	6945515
	CAPT4961*4A*	ADVC80805C*B*	55,500	39,500	13.0	11.0	1,625	5520634
	CAPT4961*4A*+MBVC1600**-1A*		57,000	40,500	13.0	11.0	1,700	6945516
	CAPT4961*4A*+MBVC2000**-1A*		56,000	40,000	13.5	11.5	1,625	5527435
	CHPF4860D6D*+EEP+TXV		55,500	39,500	13.0	11.0	1,500	5604754
	CHPF4860D6D*+MBVC2000**-1A*+TXV		56,000	40,000	13.5	11.5	1,625	3688586
	CHPF4860D6D*+TXV	G*VC80805D*B*	55,500	40,500	13.0	11.0	1,650	9923251
	CHPF4860D6D*+TXV	A*EH800805C*A*	54,500	38,500	13.3	11.2	1,650	6944938
	CHPF4860D6D*+TXV	A*VC80805C*B*	55,500	39,500	13.0	11.0	1,800	5038849
	CHPF4860D6D*+TXV	G*EC961205DNA*	56,500	40,000	13.0	11.0	1,950	7365326
	CHPF4860D6D*+TXV	G*VC961205DNA*	54,000	38,500	13.5	11.5	1,585	7354172
	CHPF4860D6D*+TXV	A*EC961205DNA*	56,500	40,000	13.0	11.0	1,950	7365434
	CHPF4860D6D*+TXV	A*VC81005C*B*	55,500	39,500	13.0	11.0	1,800	5039148
	CHPF4860D6D*+TXV	A*VM970804CNA*	54,000	38,500	13.5	11.0	1,585	7354167
	CHPF4860D6D*+TXV	G*VC960804CNA*	54,000	38,500	13.5	11.0	1,585	7354170
	CHPF4860D6D*+TXV	G*VM971205DNA*	54,000	38,500	13.5	11.5	1,585	7354175
	CHPF4860D6D*+TXV	G*VC81005C*B*	55,500	39,500	13.0	11.0	1,800	5038848
	CHPF4860D6D*+TXV	A*VC961205DNA*	54,000	38,500	13.5	11.5	1,585	7354166
	CHPF4860D6D*+TXV	A*VM971205DNA*	54,000	38,500	13.5	11.5	1,585	7354169
	CHPF4860D6D*+TXV	A*EH801005C*A*	55,000	39,000	13.3	11.2	1,720	6944940
	CHPF4860D6D*+TXV	G*E80805C*B*	54,500	38,500	13.3	11.2	1,650	5039181
	CHPF4860D6D*+TXV	A*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354168
	CHPF4860D6D*+TXV	A*VC960804CNA*	54,000	38,500	13.5	11.0	1,585	7354164
	CHPF4860D6D*+TXV	A*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354165
	CHPF4860D6D*+TXV	G*VM970804CNA*	54,000	38,500	13.5	11.0	1,585	7354173
	CHPF4860D6D*+TXV	G*E81005C*B*	55,000	39,000	13.3	11.2	1,720	5039194
	CHPF4860D6D*+TXV	G*VC80805C*B*	55,500	39,500	13.0	11.0	1,800	5038946
	CHPF4860D6D*+TXV	G*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354171
	CHPF4860D6D*+TXV	G*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354174
	CSCF4860N6D*+EEP		54,000	38,500	13.0	11.0	1,600	5446159
	CSCF4860N6D*+MBVC2000**-1A*		53,500	38,000	13.5	11.5	1,650	4767698
	CSCF4860N6D*+TXV	G*VC81005C*B*	54,000	39,500	13.0	11.0	1,600	9923252
	CSCF4860N6D*+TXV	G*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354186

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0601B* (Contd.)	CSCF4860N6D*+TXV	A*VC961205DNA*	53,500	38,000	13.5	11.0	1,585	7354178
	CSCF4860N6D*+TXV	G*VM971205DNA*	53,500	38,000	13.5	11.0	1,585	7354187
	CSCF4860N6D*+TXV	G*VM970804CNA*	54,000	38,500	13.0	11.0	1,585	7354185
	CSCF4860N6D*+TXV	A*VC960804CNA*	54,000	38,500	13.0	11.0	1,585	7354176
	CSCF4860N6D*+TXV	G*VC961205DNA*	53,500	38,000	13.5	11.0	1,585	7354184
	CSCF4860N6D*+TXV	G*VC960804CNA*	54,000	38,500	13.0	11.0	1,585	7354182
	CSCF4860N6D*+TXV	A*VM971005CNA*	54,000	38,500	13.0	11.0	1,600	7354180
	CSCF4860N6D*+TXV	A*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354177
	CSCF4860N6D*+TXV	A*VM970804CNA*	54,000	38,500	13.0	11.0	1,585	7354179
	CSCF4860N6D*+TXV	A*VM971205DNA*	53,500	38,000	13.5	11.0	1,585	7354181
	CSCF4860N6D*+TXV	G*VC961005CNA*	54,000	38,500	13.0	11.0	1,600	7354183
GSX13 0611A*	ARUF61D14A*		55,500	38,000	13.0	11.0	1,520	7984180
	ASPT61D14A*		56,000	38,500	14.0	11.5	1,645	8242049
	AVPTC59D14A*		56,000	38,500	13.5	11.5	1,660	8996126
	AVPTC60D14A*		56,000	38,500	14.0	11.5	1,620	5924344
	AVPTC61D14A*		57,000	39,000	14.0	11.5	1,775	8996127
	CA*F4860*6D*+EEP		55,000	37,600	13.0	11.0	1,500	5586534
	CA*F4860*6D*+MBVC2000**-1A*		56,000	38,500	13.5	11.5	1,575	5586537
	CA*F4860*6D*+MBVC2000**-1A*+TXV		56,000	38,500	14.0	11.5	1,575	5586540
	CA*F4860*6D*+TXV	G*VC80805D*B*	55,500	39,000	13.5	11.0	1500	9923253
	CA*F4860*6D*+TXV	ADVC81005C*B*	55,500	38,000	13.0	11.0	1,550	5586714
	CA*F4860*6D*+TXV	A*EH801005C*A*	55,000	37,600	13.5	11.0	1,525	6944944
	CA*F4860*6D*+TXV	A*EH800805C*A*	55,500	38,000	13.0	11.0	1,550	6944942
	CA*F4860*6D*+TXV	G*E81005C*B*	55,000	37,600	13.5	11.0	1,525	5586717
	CA*F4860*6D*+TXV	A*VC81005C*B*	55,500	38,000	13.5	11.0	1,520	5586543
	CA*F4860*6D*+TXV	G*VC80805C*B*	55,500	38,000	13.5	11.0	1,520	5586720
	CA*F4860*6D*+TXV	G*VC81005C*B*	55,500	38,000	13.5	11.0	1,520	5586564
	CA*F4860*6D*+TXV	A*VC80805C*B*	55,500	38,000	13.5	11.0	1,520	5586705
	CA*F4860*6D*+TXV	ADVC80805C*B*	55,500	38,000	13.0	11.0	1,500	5586558
	CA*F4860*6D*+TXV	G*E80805C*B*	55,500	38,000	13.0	11.0	1,550	5586561
	CA*F4961*6D*+EEP		56,500	38,500	13.0	11.0	1,500	5586582
	CA*F4961*6D*+MBVC2000**-1A*		57,000	39,000	14.0	11.5	1,575	5586856
	CA*F4961*6D*+MBVC2000**-1A*+TXV		57,000	39,000	14.0	12.0	1,575	5586585
	CA*F4961*6D*+TXV	G*VC80805D*B*	56,500	40,000	14.0	11.5	1500	9923254
	CA*F4961*6D*+TXV	A*VM971205DNA*	56,000	38,500	14.0	11.5	1,545	7354191
	CA*F4961*6D*+TXV	G*E81005C*B*	56,000	38,500	14.0	11.5	1,525	5586609
	CA*F4961*6D*+TXV	G*VM971005CNA*	56,000	38,500	13.5	11.5	1,520	7354194
	CA*F4961*6D*+TXV	G*VC961005CNA*	56,000	38,500	13.5	11.5	1,520	7354192
	CA*F4961*6D*+TXV	G*E80805C*B*	56,000	38,500	14.0	11.5	1,550	5586606
	CA*F4961*6D*+TXV	A*EH801005C*A*	56,000	38,500	14.0	11.5	1,525	6944952
	CA*F4961*6D*+TXV	A*EH800805C*A*	56,000	38,500	14.0	11.5	1,550	6944950
	CA*F4961*6D*+TXV	A*VC81005C*B*	56,500	38,500	14.0	11.5	1,520	5586591
	CA*F4961*6D*+TXV	A*EC961205DNA*	56,000	38,500	14.0	11.5	1,525	7365435
	CA*F4961*6D*+TXV	G*EC961205DNA*	56,000	38,500	14.0	11.5	1,525	7365327
	CA*F4961*6D*+TXV	G*VC80805C*B*	56,500	38,500	14.0	11.5	1,520	5586612
	CA*F4961*6D*+TXV	G*VC81005C*B*	56,500	38,500	14.0	11.5	1,520	5586615
	CA*F4961*6D*+TXV	A*VC961005CNA*	56,000	38,500	13.5	11.5	1,520	7354188
	CA*F4961*6D*+TXV	ADVC81005C*B*	57,000	39,000	13.5	11.0	1,550	5586603

See Notes on Page 53.


OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0611A* (Contd.)	CA*F4961*6D*+TXV	A*VC961205DNA*	56,000	38,500	14.0	11.5	1,545	7354189
	CA*F4961*6D*+TXV	G*VC961205DNA*	56,000	38,500	14.0	11.5	1,545	7354193
	CA*F4961*6D*+TXV	A*VC80805C*B*	56,500	38,500	14.0	11.5	1,520	5586588
	CA*F4961*6D*+TXV	A*VM971005CNA*	56,000	38,500	13.5	11.5	1,520	7354190
	CA*F4961*6D*+TXV	G*VM971205DNA*	56,000	38,500	14.0	11.5	1,545	7354195
	CA*F4961*6D*+TXV	ADVC80805C*B*	57,000	39,000	13.5	11.0	1,500	5586600
	CAPT4961*4A*	G*VC80805D*B*	56,500	40,000	14.0	11.5	1500	9923255
	CAPT4961*4A*	G*VM971205DNA*	56,000	38,500	13.5	11.5	1,545	7354203
	CAPT4961*4A*	ADVC80805C*B*	57,000	39,000	13.5	11.0	1,500	5586642
	CAPT4961*4A*	G*VC80805C*B*	56,500	38,500	14.0	11.5	1,520	5586654
	CAPT4961*4A*	G*VC81005C*B*	56,500	38,500	14.0	11.5	1,520	5586657
	CAPT4961*4A*	A*EH801005C*A*	56,000	38,500	14.0	11.5	1,525	6944960
	CAPT4961*4A*	G*VC961005CNA*	56,000	38,500	13.5	11.0	1,520	7354200
	CAPT4961*4A*	G*VM971005CNA*	56,000	38,500	13.5	11.0	1,520	7354202
	CAPT4961*4A*	A*VC961005CNA*	56,000	38,500	13.5	11.0	1,520	7354196
	CAPT4961*4A*	G*E80805C*B*	56,000	38,500	14.0	11.5	1,550	5586648
	CAPT4961*4A*	A*VM971005CNA*	56,000	38,500	13.5	11.0	1,520	7354198
	CAPT4961*4A*	A*EH800805C*A*	56,000	38,500	14.0	11.5	1,550	6944958
	CAPT4961*4A*	G*E81005C*B*	56,000	38,500	14.0	11.5	1,525	5586651
	CAPT4961*4A*	G*EC961205DNA*	56,000	38,500	13.5	11.5	1,525	7365328
	CAPT4961*4A*	A*EC961205DNA*	56,000	38,500	13.5	11.5	1,525	7365436
	CAPT4961*4A*	A*VC81005C*B*	56,500	38,500	14.0	11.5	1,520	5586633
	CAPT4961*4A*	G*VC961205DNA*	56,000	38,500	13.5	11.5	1,545	7354201
	CAPT4961*4A*	A*VC961205DNA*	56,000	38,500	13.5	11.5	1,545	7354197
	CAPT4961*4A*	ADVC81005C*B*	57,000	39,000	13.5	11.0	1,550	5586645
	CAPT4961*4A*	A*VM971205DNA*	56,000	38,500	13.5	11.5	1,545	7354199
	CAPT4961*4A*	A*VC80805C*B*	56,500	38,500	14.0	11.5	1,520	5586630
	CAPT4961*4A*+EEP		56,500	38,500	13.5	11.0	1,500	5586770
	CAPT4961*4A*+MBVC1600**-1A*		57,000	39,000	13.5	11.5	1,560	6945517
	CAPT4961*4A*+MBVC2000**-1A*		57,000	39,000	14.0	12.0	1,575	5586672
	CHPF4860D6D*+EEP		56,000	38,500	13.0	11.0	1,500	5586675
	CHPF4860D6D*+MBVC2000**-1A*		57,000	39,000	14.0	11.5	1,575	5586900
	CHPF4860D6D*+MBVC2000**-1A*+TXV		57,000	39,000	14.0	11.5	1,575	5586773
	CHPF4860D6D*+TXV	G*VC80805D*B*	56,000	39,500	14.0	11.5	1500	9923256
	CHPF4860D6D*+TXV	A*VM971205DNA*	56,000	38,500	14.0	11.5	1,545	7354207
	CHPF4860D6D*+TXV	G*EC961205DNA*	56,000	38,500	14.0	11.5	1,525	7365329
	CHPF4860D6D*+TXV	G*E80805C*B*	56,000	38,500	14.0	11.5	1,550	5586802
	CHPF4860D6D*+TXV	G*VC80805C*B*	56,000	38,500	14.0	11.5	1,520	5586808
	CHPF4860D6D*+TXV	A*VC81005C*B*	56,500	38,500	14.0	11.5	1,520	5586779
	CHPF4860D6D*+TXV	G*VC81005C*B*	56,500	38,500	14.0	11.5	1,520	5586811
	CHPF4860D6D*+TXV	A*VM971005CNA*	56,000	38,500	13.5	11.0	1,520	7354206
	CHPF4860D6D*+TXV	G*E81005C*B*	56,000	38,500	14.0	11.5	1,525	5586805
	CHPF4860D6D*+TXV	G*VM971005CNA*	56,000	38,500	13.5	11.0	1,520	7354210
	CHPF4860D6D*+TXV	G*VM971205DNA*	56,000	38,500	14.0	11.5	1,545	7354211
	CHPF4860D6D*+TXV	G*VC961005CNA*	56,000	38,500	13.5	11.0	1,520	7354208
	CHPF4860D6D*+TXV	A*VC961005CNA*	56,000	38,500	13.5	11.0	1,520	7354204
	CHPF4860D6D*+TXV	A*VC961205DNA*	56,000	38,500	14.0	11.5	1,545	7354205
	CHPF4860D6D*+TXV	G*VC961205DNA*	56,000	38,500	14.0	11.5	1,545	7354209

See Notes on Page 53.

OUTDOOR UNIT	INDOOR UNITS		COOLING RATINGS				CFM	AHRI #
	COILS/AIR HANDLERS	FURNACES	TOTAL ¹	SENS. ¹	SEER ²	EER ³		
GSX13 0611A* (Contd.)	CHPF4860D6D*+TXV	A*EH800805C*A*	56,000	38,500	14.0	11.5	1,550	6944966
	CHPF4860D6D*+TXV	A*EC961205DNA*	56,000	38,500	14.0	11.5	1,525	7365437
	CHPF4860D6D*+TXV	A*VC80805C*B*	56,000	38,500	14.0	11.5	1,520	5586776
	CHPF4860D6D*+TXV	A*EH801005C*A*	56,000	38,500	14.0	11.5	1,525	6944968
	CSCF4860N6D*+EEP		55,000	37,600	13.0	11.0	1,500	5589903
	CSCF4860N6D*+MBVC2000**-1A*		56,000	38,500	13.5	11.5	1,575	5589906
	CSCF4860N6D*+MBVC2000**-1A*+TXV		56,000	38,500	14.0	11.5	1,575	5586690
	CSCF4860N6D*+TXV	G*VC80805D*B*	56,500	40,000	13.5	11.5	1500	9923257
	CSCF4860N6D*+TXV	G*VC80805C*B*	56,500	38,500	13.5	11.5	1,520	5589936
	CSCF4860N6D*+TXV	A*VC961205DNA*	55,500	38,000	13.5	11.0	1,545	7354213
	CSCF4860N6D*+TXV	A*VC961005CNA*	55,500	38,000	13.5	11.0	1,520	7354212
	CSCF4860N6D*+TXV	G*VM971205DNA*	55,500	38,000	13.5	11.0	1,545	7354219
	CSCF4860N6D*+TXV	G*VC961005CNA*	55,500	38,000	13.5	11.0	1,520	7354216
	CSCF4860N6D*+TXV	G*VC81005C*B*	55,500	38,000	13.5	11.0	1,520	5589939
	CSCF4860N6D*+TXV	A*VM971205DNA*	55,500	38,000	13.5	11.0	1,545	7354215
	CSCF4860N6D*+TXV	A*VC81005C*B*	55,500	38,000	13.5	11.0	1,520	5589912
	CSCF4860N6D*+TXV	A*EH801005C*A*	55,500	38,000	13.5	11.0	1,525	6944976
	CSCF4860N6D*+TXV	G*VM971005CNA*	55,500	38,000	13.5	11.0	1,520	7354218
	CSCF4860N6D*+TXV	G*VC961205DNA*	55,500	38,000	13.5	11.0	1,545	7354217
	CSCF4860N6D*+TXV	G*E81005C*B*	55,500	38,000	13.5	11.0	1,525	5589933
	CSCF4860N6D*+TXV	A*EH800805C*A*	54,500	37,400	13.0	11.0	1,550	6944974
	CSCF4860N6D*+TXV	A*VC80805C*B*	56,500	38,500	13.5	11.5	1,520	5589909
	CSCF4860N6D*+TXV	G*E80805C*B*	54,500	37,400	13.0	11.0	1,550	5586829
	CSCF4860N6D*+TXV	A*VM971005CNA*	55,500	38,000	13.5	11.0	1,520	7354214

¹ BTU/h² Seasonal Energy Efficiency Ratio; Certified per AHRI 210/240 @ 80°F/ 67°F/ 95°F³ Energy Efficiency Ratio @ 80°F/ 67°F/ 95°F**NOTES**


- Always check the S&R plate for electrical data on the unit being installed.
- When matching the outdoor unit to the indoor unit, use the piston supplied with the outdoor unit or that specified on the piston kit chart supplied with the indoor unit.
- EEP - Order from Service Dept. Part No. B13707-38 or new Solid State Board B13707-35S. Part No. B13707-38 is not interchangeable with B13707-35S. The Goodman® brand gas furnace contains the EEP cooling time delay.
- HSK - Hard Start Kit: This is an additional capacitor to assist with compressor start-up, used with the standard "run" capacitor that is supplied in the unit. Order from a Goodman brand distributor or service department.



Wiring is subject to change. Always refer to the wiring diagram or the unit for the most up-to-date wiring.

WARNING

High Voltage: Disconnect all power before servicing or installing this unit. Multiple power sources may be present. Failure to do so may cause property damage, personal injury, or death.




Wiring is subject to change. Always refer to the wiring diagram or the unit for the most up-to-date wiring.



WARNING

High Voltage: Disconnect all power before servicing or installing this unit. Multiple power sources may be present. Failure to do so may cause property damage, personal injury, or death.

DIMENSIONS



ACCESSORIES

MODEL #	DESCRIPTION	GSX13 018D*	GSX13 018E*	GSX13 024D*/E*	GSX13 030B*/L*	GSX13 036E*	EGSX13 042**	GSX13 048**	GSX13 060**	GSX13 061**
ABK-20	Anchor Bracket Kit ^			X	X	X	X	X	X	X
ABK-21	Anchor Bracket Kit ^	X	X							
ASC-01	Anti-Short Cycle Kit	X	X	X	X	X	X	X	X	X
CSR-U-1	Hard-start Kit		X	X	X	X				
CSR-U-2	Hard-start Kit	X					X	X	X	X
CSR-U-3	Hard-start Kit							X	X	X
FSK01A ¹	Freeze Protection Kit	X	X	X	X	X	X	X	X	X
LSK02A ²	Liquid Line Solenoid Kit	X	X	X	X	X	X	X	X	X
0130R00000S	Low-Pressure Switch Kit	X	X	X	X	X	X	X	X	X
LAKT01A	Low-Ambient Kit	X	X	X	X	X	X	X	X	X
TX2N4 ²	TXV Kit	X	X							
TX2N4A ²	TXV Kit	X	X	X						
TX3N4 ²	TXV Kit				X	X				
TX5N4 ²	TXV Kit						X	X	X	X

[^] Contains 20 brackets; four brackets needed to anchor unit to pad

¹ Installed on indoor coil

² Field-installed, non-bleed, expansion valve kit: Condensing units and heat pumps with reciprocating compressors require the use of start-assist components when used in conjunction with an indoor coil using a non-bleed thermal expansion valve refrigerant metering device or liquid line solenoid kit.