

Architrac® at a Glance


To help determine which system is right for your project, use the guideline below to select the best fit.

ARCHITRAC® SERIES	94001 BEST SELLER	94003	94004 BEST SELLER	94005	9046	9600	K-RAIL
What is your preferred Draw type?							
Hand Baton Draw	•	•	•	•	•	•	•
Cord/Duplex Draw	•						
Motorized	•						
What is your preferred Drapery Heading type?							
Pleated	•	•	•	•	•	•	•
Cubicle		•	•	•	•	•	•
Ripplefold™	•	•	•	•			•
What is your mounting location?							
Ceiling Mount	•	•	•	•	•	•	•
Wall Mount	•	•				•	•
Recessed Mount	•	•	•	•	•	•	
Suspension Mount					•	•	
Is an Angular Bend or Curve needed?							
Can be bent*	•	•		•	•	•	
Can be curved*	•	•		•	•	•	
What is the Track Length?							
One-Way Draw Max Track Length	UP TO 20'	UP TO 20'	UP TO 16'	UP TO 16'	UP TO 16'	UP TO 20'	UP TO 16'
Two-Way Draw Max Track Length	UP TO 40'	UP TO 20'	UP TO 32'	UP TO 32'	UP TO 32'	UP TO 40'	UP TO 16'
*Architrac® Series 94001 with AMP™ Motorization max track length is 16'.							
What are the Fabric Weight requirements? (Weight shown is pounds per linear foot)							
One-Way	4 LBS	4 LBS	4 LBS	4 LBS	4 LBS	4 LBS	4 LBS
Two-Way	4 LBS	4 LBS	4 LBS	4 LBS	4 LBS	4 LBS	4 LBS


*Architrac® Series 94001 with AMP™ Motorization cannot be bent or curved.

Bends Styles


STYLE 1:
RECESS




STYLE 2:
BOW




STYLE 3:
BAY



STYLE 4:
CORNER



STYLE 5:
CURVED



Cubicle Bend Styles *(Architrac® 9046 & 9600 Only)*

CUBICLE STYLE 1:
L-SHAPED




CUBICLE STYLE 2:
LONG-U




CUBICLE STYLE 3:
J-TRACK




CUBICLE STYLE 4:
J-TRACK OFFSET RIGHT



CUBICLE STYLE 5:
J-TRACK OFFSET LEFT




CUBICLE STYLE 6:
OBTUSE J-TRACK RIGHT



CUBICLE STYLE 7:
OBTUSE J-TRACK LEFT




CUBICLE STYLE 8:
STRAIGHT OFFSET RIGHT



CUBICLE STYLE 9:
STRAIGHT OFFSET LEFT



CUBICLE STYLE 10:
CURVED



* Architrac Series 94001 with Briza™ Motorization cannot be bent or curved.