

Touch Probe TC54-10



- Workpiece measurement and tool setting in turning and milling machines
- Application in turret
- Pulling measurements


### Your benefit:

- Measuring speed up to 2 m/min
- Superior precision due to patented **shark**360 measuring mechanism
- No-wear optoelectronic measuring mechanism
- Use of two measuring systems with one IR receiver
- Extended battery life
- Shortened design
- Precise measurement even with coolant
- Compact and robust design



#### **DUO-Mode**


Sequential use of two measuring systems with one infrared receiver.








Example: Pulling measurement



Workpiece measurement in turning machine



Tool setting in turning machine



shark 360 measuring mechanism

# Technical data

Protection class	IP68
Approach direction	±X, ±Y, ±Z
Measuring force in XY   Z	1,3 N / 0,9 N / 0,7 N / 0,5 N*   5,9 N
Measuring force (LF) in XY   Z	0,4 N / 0,3 N / 0,2 N / 0,17 N*   2,0 N
Max. deflection XY   Z	± 15°   5 mm
Max. acceleration	50 m/s <sup>2</sup>
Repeatability	0,4 μm 2σ
Max. probing speed	2 m/min
Mass	230 g
Signal transmission   Range	Infrared   $\pm$ 60° in Z, 360° in XY
Battery (2 pieces)	Saft Lithium LS14250, (½ AA, 3,6V) 1200 mAh
Tool holder	BTH 25 (HSK, SK, BT, VDI,)
Storage/Operating temperature	-20 °C +50 °C   +5 °C +50 °C

<sup>\*</sup> Stylus L= 30 mm / 50 mm / 75 mm / 100 mm LF: Low Force



# Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

## Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 Fax: +44 1543 251746 E-Mail: info@blum-novotest.co.uk

# Blum LMT, Inc. 4144 Olympic Boulevard

Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com