ERMCO SINGLE PHASE PAD REQUEST FOR QUOTATION FORM

ERMCO

Customer:

Product Type: ☐ ANSI Type II ☐ ANSI Type 1 (32" tall) ☐ Trimline (24"H x 26"W) ☐ Microtrim

Evaluation Formula: SP($) ☐ NL ☐ $/watt LL ☐ $/watt

Purchasing Preference: ☐ Lowest Cost ☐ Best TOC Best TOC in ☐ 0% Window

KVA: ☐ 5 ☐ 10 ☐ 15 ☐ 25 ☐ 37.5 ☐ 50 ☐ 75 ☐ 100 ☐ 167 ☐ 250

Primary Voltage: ☐ BIL ☐ Configuration: ☐ Grdy ☐ Y ☐ Delta

Taps: ☐ None ☐ 2@2.5% above & below normal ☐ 4@2.5% below normal ☐ 4@2.5% above normal
☐ Other:

Secondary Voltage: ☐ 240/120 3 LV BU ☐ Interlace 240/120 3 LV BU ☐ 480/240 3 LV BU ☐ 277/480Y 2 LV BU
☐ Other:

HV Arrangement: ☐ Loop ☐ Radial ☐ Wells ☐ Wells w/ replaceable studs ☐ Inserts

Fusing: ☐ No Fusing ☐ Dry Well CL Fuse (Full Range) ☐ Partial Range CL Fuse & Weak Link
☐ Bayonet Fuse-Load Sensing ☐ Flapper Bayonet-Load Sensing ☐ Partial Range CL Fuse & Bayonet
☐ Bayonet Fuse-Dual Sensing ☐ Internal Expulsion Fuse ☐ Flapper Bayonet-Dual Sensing

Loadbreak Switch: ☐ None ☐ (1) 2 position on/off ☐ (2) 2 position on/off
☐ (3) 2 position on/off ☐ 4 position "T" blade type ☐ 4 position "V" blade type

Secondary Termination: ☐ Copper Studs ☐ 4 Hole NEMA Spade ☐ 4 Hole In-Line Spade ☐ 6 Hole Spade

LV Circuit Breaker: ☐ No Breaker ☐ Load Side Circuit Breaker ☐ Breaker w/ Emergency OL

Arrester: ☐ No Arrester ☐ Internal HV Arrester ☐ External LV Arrester

Drain Port: ☐ 1/2" NPT Drain Plug ☐ 1/2" Sampling Device ☐ 1/2" Drain Valve w/ Sampler
☐ 1" NPT Drain Plug ☐ 1" Drain Valve ☐ 1" Drain Vavle w/ Sampler

Gauges: ☐ Temperature ☐ Liquid Level ☐ Vacuum/Pressure ☐ Other

Tank Material: ☐ Mild Steel ☐ Mild Steel Tank w/ Stainless Base
☐ 304 Stainless Steel ☐ "Coastal" Mild Tank w/ SS Fitting

Markings: ☐ KVA Decal ☐ "Non PCB" Decal ☐ Other:

Fluid Coolant: ☐ FR3 ☐ Mineral Oil

Special Items or Instructions: