

**INNOVATIVE PRODUCTS TO
SIMPLIFY CONSTRUCTION**

	PART NUMBER
48" PANEL W/44" DOOR - LEVER STYLE LOCKSET	4003
48" PANEL W/44" DOOR - PUSHBUTTON COMBINATION LOCKSET	4003-PB
52" PANEL ASSEMBLY W/48" DOOR- LEVER STYLE LOCKSET	4008
52" PANEL ASSEMBLY W/48" DOOR- PUSHBUTTON COMBINATION LOCKSET	4008PB
36" PANEL ASSEMBLY W/32" DOOR- LEVER STYLE LOCKSET	4010
36" PANEL ASSEMBLY W/32" DOOR- PUSHBUTTON COMBINATION LOCKSET	4010PB
PUSHBUTTON COMBINATION LOCKSET	3006



DOORS AND ACCESSORIES

EDGE GUARD 100 E. BODMAN BEMENT, ILLINOIS

PHONE: (217)678-2228

dforan@edge-guard.com



The picture above shows the outside face of our door panel. The door can be ordered with a RH or LH swing.

The door panel consists of a 44" door mounted in a 48" frame. The door has a polyethylene continuous hinge which provides smooth quiet operation while forming an air tight seal. The strike side and top of the door have a 1" x 1" angle mounted to them with a gasket adhered to it to form a seal with the frame. The bottom of the door has a gasketed sweep.

Our door panel is 48" wide by 7'-8" tall and adjusts to 10'-0". We provide an adjustable hydraulic closer and a self-latching, locking handle, keyed outside, thumb-turn inside.

1/4" x 2" solid aluminum threshold strip with neoprene gasket material seal to the floor.

OPAL -\$995

TRANSPARENT \$995

CLEAR \$1,035



GUARD

48" DOOR PANEL W/ 44" DOOR P/N- 4003

DESCRIPTION	PART NUMBER	PRICE	
48" PANEL W/44" DOOR – OPAL	4003	\$995	<ul style="list-style-type: none"> • Our light weight modular panels assemble quickly without the use of tools. • Panels are Flame Resistant. ASTM E-84: Flame Spread – 0, Smoke Developed – 85. Class A. ASTM D-635 - Class CC1. • Reusable panels eliminate waste. • Panels adjust in height from 7'-8" to 10'-0" . • We offer 12", 24", 36" and 48" wide panels. • Door panels include a hydraulic closer and a lever style lockset standard. A pushbutton combination lockset is available. • Hinged corner posts allow for angled configurations. • We offer porting options on our 24" panels for 8" diameter and 10" diameter HEPA exhaust and differential pressure monitoring. • Custom Engineered camlock fasteners join panels together. Custom grid clips secure panels to ceiling. • One person can typically set up a 2' x 12' enclosure in less than an hour, breakdown in less than a half hour. • Our system's labor savings compared to using metal studs and drywall typically pay for the units in 2 to 3 uses. • Our panels allow light to pass through creating a pleasant, safe work environment without the need of added temporary lighting.
TRANSPARENT	4003-T	\$995	
CLEAR	4003-C	\$1,035	
48" PANEL W/44" DOOR			
W/PUSHBUTTON LOCK – OPAL	4003PB	\$1,195	
TRANSPARENT	4003PB-T	\$1,195	
CLEAR	4003PB-C	\$1,235	
52" PANEL ASSEMBLY W/48" DOOR – OPAL	4008	\$1,195	
TRANSPARENT	4008-T	\$1,195	
CLEAR	4008-C	\$1,235	
52" PANEL ASSEMBLY W/48" DOOR			
W/PUSHBUTTON LOCK – OPAL	4008PB	\$1,395	
TRANSPARENT	4008PB-T	\$1,395	
CLEAR	4008PB-C	\$1,435	
36" PANEL ASSEMBLY W/32" DOOR – OPAL	4010	\$895	
TRANSPARENT	4010-T	\$895	
CLEAR	4010-C	\$925	
36" PANEL ASSEMBLY W/32" DOOR			
W/PUSHBUTTON LOCK – OPAL	4010PB	\$1,095	
TRANSPARENT	4010PB-T	\$1,095	
CLEAR	4010PB-C	\$1,125	



Pushbutton Combination Lock

PN – 3006 - \$200

Mechanical and Programmable

ANSI Standard Commercial Grade Lock

- Solid Brass 6 pin tumbler cylinder
- All metal construction
- All necessary mounting Screws and latches included
- No exposed mounting screw
- Fits 1 3/8" and 1 3/4" doors
- Standard 2 3/4"(70mm) (center of the hole to the edge)

Standard 2 1/8" hole bore



Standard Lever Style Lock – Supplied with our doors.

Keyed on the outside pushbutton inside.

Normally they are used with a classroom function but can be changed to storeroom.

Our doors are prepped with a 2 3/4" backset. They are 1 1/4" thick so in some instances a spacer ring may be needed. The picture to the right is showing the edge of the door.

