



TECHNICAL SPECIFICATIONS	Power Source Cord Length	110V/20A, 220V Option Available 10' / 3.0M
	Cord Length	10' / 3.0M
	Drive Motor	4 HP DC
	Incline Motor	1,000 lbs. of thrust
	Speed Sensor	Magnetic
	Deck	1" / 0.8 cm Medium Density Fiberboard
		Siegling Multi-Ply with PVC Coating
	Rollers	3" / 8 cm w/ Sealed Bearings
	Impact System	True Soft System
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	
	Speed Range	0.5 to 12.0 MPH / 0.8 to 19.3 KMH
	Incline/Decline Range	0% to 15%
	Handrail Design	Extended Handrails and Moisture Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
CONSOLE	Display	LCD
	Programs	7
The English Allies	Saved Workouts	2
	HRC Workouts	1
	HRC Cruise Control	Standard
	CSAFE Power	Standard
	Diagnostic	Standard
SAFETY	Saftey Clip	Standard
	Extended Handrails	Standard
	Large Straddle Covers	Standard
REGULATORY APPROVALS		ETL UL1647, CSA, CE, EN957
EXTRAS	Accessories	Water Bottle Holder (2), Accessory Tray, Reading Rack, Optional Medical Handrails
PHYSICAL SPECIFICATIONS	Footprint	82.5" L x 35.5" W / 210 cm x 90 cm
	Running Surface	60" L x 22" W / 152 cm x 56 cm
	Machine Weight	302 lbs / 137 kg
	Shipping Weight	376 lbs / 171 kg
	Maximum User Weight	350 lbs / 159 kg
	Step-Up Height	6.25" / 16 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)
	Frame	Lifetime
	Motor	3 Years
	Parts	3 Years
	1 0.10	
		1 Year

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.













