### **GRINDING WHEELS**

Reinforced Wheels Depressed Center

FOR USE ON RIGHT ANGLE GRINDERS



- Aluminum oxide abrasive with a resin bond reinforced by layers of durable fabric to provide wheels of maximum strength and safety.
- **Fast cutting** flexible, extremely durable, and economical.





J&B #	MFG#	SIZE	ARBOR	MATERIAL	MAX RPM	QTY	CASE
~ 39061	20015	4 x 1/4	5/8 hole	A24N	13,500	EΑ	25
~ 38864	20163	4-1/2 x 1/4	5/8-11 nut	A24R	13,300	EΑ	10
* 49115	A1226H	4-1/2 x 1/4	5/8-11 nut	A24/30T	13,300	EΑ	10
* V41990	A1203H	4-1/2 x 1/4	5/8-11 nut	A24ALU	13,300	EΑ	10
* 38865	A1236	4-1/2 x 1/4	7/8 hole	A24T	13,300	EΑ	25
* V41991	A1203	4-1/2 x 1/4	7/8 hole	A24ALU	13,300	EΑ	25
~ 38866	20070	5 x 1/4	7/8 hole	A24N	12,200	EΑ	25
* V20097	A3236	6 x 1/4	7/8 hole	A30N	10,000	EΑ	25
~ 20098	20086	7 x 1/4	5/8-11 nut	A24R	8,500	EΑ	10
~ 20146	20195	9 x 1/4	5/8-11 nut	A24T	6,600	EΑ	10

<sup>\* =</sup> Flexovit Brand ~ = Sait Brand

#### **GENERAL PURPOSE - METAL - FAST CUT (A24N):**

- Aggressive grinding with excellent life.
- Grinds aggressively in a wide range of metal applications, including harder materials.
- Aluminum oxide grain. Soft bond for fast stock removal.

#### HIGH PERFORMANCE - METAL - LONG LIFE (A24R):

- Smooth grinding with maximum life for an aluminum oxide wheel.
- Weld grinding, surface conditioning, notching, cutting, and all general purpose stock removal.
- The standard for long life in metal work.

#### **EDGE GRINDING - METAL - LONG LIFE (A24T):**

- Aluminum oxide grain.
- Hard bond designed for edge & bevel grinding & other applications where a harder wheel is preferred.
- Farrous metals (iron, steel, welds, etc.)

#### ALUMINUM - LOAD RESISTANT - (A24ALU)

Ideal for grinding aluminum and nonferrous materials.



### METALHOG GRINDING WHEEL

Reinforced Wheels Depressed Center

\*\* Superior Productivity \*\* Higher Efficiency \*\* Longer Life

#### FOR USE ON RIGHT ANGLE GRINDERS



- Type 27 grinding wheels incorporate a blend of premium, semi-premium & standard abrasive grain with custom bond systems.
- Extremely aggressive & rapid grinding action without sacrificing wheel life.
- METALHOG grinds up to 30% faster & 3 times Longer than regular aluminum oxide products.



J&B #	MFG#	SIZE	ARBOR	MATERIAL	MAX RPM	QTY	CASE
41908	A1230	4-1/2 x 1/4	7/8 hole	AXT24S	13,300	EA	25

#### RAPID GRIND - METAL, STAINLESS - FAST CUT/LONG LIFE (AXT24S):

Fast, aggressive stock removal.

### **E.T. ERGONOMIC TECHNOLOGY**

#### **Flexovit**

#### FOR USE ON ANGLE GRINDERS



- New saucer shaped grinding wheel incorporating ergonomic technology. Allows more contact area between the wheel & the workpiece, resulting in more controlled grinding & blending without gouging & with less pressure required.
- Intended for flat surfaces & rugged edge grinding.
- Designed to fit under standard angle grinder guards.
- Built with 3 full layers of high tensile fiberglass reinforcement for maximum workplace safety.





J&B#	MFG#	SIZE	SPEC	MAX RPM	QTY
49100	A1237	4-1/2 x 1/4 x 7/8	A30S	13,300	EA

**CASE** 25

07-30-20 PAGE 499A



### **CHALLENGER II GRINDING WHEELS**

Semi-Flexible Wheels **ALUMINUM / STAINLESS / METAL** 

FOR USE ON RIGHT ANGLE GRINDERS







- Eliminate wheel-change downtime by grinding and finishing with the same wheel.
- Challenger II performs well in all metal fabrication applications.
- Challenger II runs virtually LOAD-FREE.
- Challenger II tackles stainless and hard alloy applications without glazing or dulling.
- Great for Metal, Stainless, or Aluminum.

J&B #	MFG#	SIZE	TYPE	ARBOR	GRIT	MAX RPM	QTY
*42200	27501	4-1/2 x 1/8	29	7/8 hole	60	13,280	EA

\* Use backing pad part # 95245 from United Abrasives.



25 in a case






### ZIRCOTEX PREMIUM FLAP DISCS


Fiberglass Backing Plate

#### FOR USE ON ANGLE GRINDERS



- Made with premium zirconia alumina abrasive cloth backed by a high strength fiberglass disc.
- Ideal for high production grinding, blending, deburring and finishing.
- Perform well on a wide variety of materials including stainless & carbon steel.







Ε

					MAX		]
J&B #	MFG#	SIZE	GRIT	TYPE	RPM	QTY	CASE
45401	Z4501FH	4-1/2 x 5/8-11	24	29	13,300	EA	10
45402	Z4500FH	4-1/2 x 5/8-11	40	29	13,300	EΑ	10
45416	Z4505FH	4-1/2 x 5/8-11	60	29	13,300	EΑ	10
45500	Z4510FH	4-1/2 x 5/8-11	80	29	13,300	EA	10
45422	Z4525F	4-1/2 x 7/8	24	27	13,300	EΑ	10
45406	Z4530F	4-1/2 x 7/8	40	27	13,300	EΑ	10
45398	Z4535F	4-1/2 x 7/8	60	27	13,300	EΑ	10
45408	Z4540F	4-1/2 x 7/8	80	27	13,300	EΑ	10
47005	Z4545F	4-1/2 x 7/8	120	27	13,300	EΑ	10
45412	Z4500F	4-1/2 x 7/8	40	29	13,300	EΑ	10
45409	Z4505F	4-1/2 x 7/8	60	29	13,300	EA	10
45420	Z4510F	4-1/2 x 7/8	80	29	13,300	EΑ	10

### SAIT ENCORE FLAP DISC

Fiberglass Backing Plate

- Heavy duty for long-life and high stock removal.
- Use on carbon and stainless steel, made with premium zirconium abrasive material which provides long-life & high stock removal.

J&B#	MFG#	SIZE	GRIT	TYPE	MAX RPM	QTY		
45399	71205	4-1/2 x 7/8	36	27	13,300	EA		
45400	71206	4-1/2 x 7/8	40	27	13,300	EA		
49102	71208	4-1/2 x 7/8	60	27	13,000	EA		



### TORNADO FLAP DISC

Nylon Backing

#### FOR USE ON ANGLE GRINDERS



- Nylon backing for easy, burn-free trimming.
- Safe & durable, vented for air cooling.
- Integrated, no strip thread –ready for mounting, no flange adaptor required.
- Premium zirconia cloth for high productivity.
- High performance & long life, resists loading & glazing.





Type 29

J&B#	MFG#	SIZE	GRIT	TYPE	MAX RPM	QTY	CASE
42201	Z4500NT	4-1/2 x 5/8-11	40	29	13,300	EA	10
42202	Z4505NT	4-1/2 x 5/8-11	60	29	13,300	EΑ	10
42203	Z4510NT	4-1/2 x 5/8-11	80	29	13,300	EA	10
42204	Z4520NT	4-1/2 x 5/8-11	120	29	13,300	EA	10

### **OVATION FLAP DISCS**

Fiberglass Backing Plate

#### FOR USE ON ANGLE GRINDERS



- High pressure is ideal for removing deeper scratches from the work surface.
- · Heavy duty / long life for tough applications.
- Premium zirconium grain on a tough, full polyester backing.
- Will not contaminate stainless steel.





Type 27

J&B#	MFG#	SIZE	GRIT	TYPE	MAX RPM	QTY
59125	78036	6 x 7/8	40	27	10,200	EA

**CASE** 10



### **GRINDING WHEELS**

FOR USE ON BENCH & PEDESTAL MACHINES



- ALUMINUM OXIDE for metal grinding carbon, stainless or alloys.
- Runs cool for long grinding life; maintains shape.
- May be used for general purpose grinding or finishing and sharpening.



				NESTED			MAX	
J&B #	MFG#	SIZE	ARBOR	BUSHINGS	STYLE	GRIT	RPM	QTY
39030	U4730	6 x 1	1	1/2, 5/8, 3/4	MED/FN	A60	4,138	EA
38460	U4710	6 x 1	1	1/2, 5/8, 3/4	COARSE	A24	4,138	EA
39032	U5130	8 x 1	1-1/4	1/2, 5/8, 3/4, 1	MED/FN	A60	3,600	EA
38462	U5110	8 x 1	1-1/4	1/2, 5/8, 3/4, 1	COARSE	A24	3,600	EA

### **BENCH WHEEL DRESSER**

- Designed to true bench wheels to correct shape.
- Quickly remove foreign material embedded in the face of the wheel.

J&B #	DIAMETER THICKNESS		QTY
39127	Up to 10" Up to 2"		EA
39128	Replacement C	EA	



### **RESIN FIBER ABRASIVE DISCS**

**Closed Coat** 

#### FOR USE ON RIGHT ANGLE GRINDERS



- Closed coat structure for more material removal & better finishing.
- Use for grinding mild steel or stainless, weld preparation, or blending and finishing.

J&B#	MFG#	SIZE	GRIT	QTY
41410	32218	4-1/2 x 7/8	50	25
41412	32220	4-1/2 x 7/8	80	25
*38963	32231	5 x 7/8	24	25
41416	32232	5 x 7/8	36	25
41418	32234	5 x 7/8	60	25
41419	32235	5 x 7/8	80	25
41421	32237	5 x 7/8	120	25

J&B #	B# MFG# SIZE		GRIT	QTY	
*38965	32246	7 x 7/8	24	25	
*38967	S4010G	9 x 7/8	24	25	
^43426	66906	9 x 7/8	36	25	

- \* These items are sold in box quantities only.
- ^ 43426 is 3M brand



### **RESIN FIBER ABRASIVE DISCS**

**Open Coat** 

FOR USE ON RIGHT ANGLE GRINDES



- Open coat structure prevents loading with fast material removal
- Use on ferrous and/or non-ferrous metals, wood and fiberglass.
- Discs come on handy dispenser to prevent bowing.

-				
J&B #	MFG#	SIZE	GRIT	QTY
46439	52480	4-1/2 x 7/8	80	100
46438	52460	4-1/2 x 7/8	60	100
46437	52450	4-1/2 x 7/8	50	100
46436	52436	4-1/2 x 7/8	36	100
*46445	69226	4-1/2 x 7/8	36	100
46430	52750	7 x 7/8	50	100
46429	52724	7 x 7/8	24	50
46440	52716	7 x 7/8	16	100



- Cannot break box quantities -

### SPIRALCOOL BACKING PAD

- Spiralcool backing pads exclusive rubber, fabric and fiber board construction provide extra strength and reliability.
- Spiral ribs provide contact points and form channels for air flow extending disc life 30% to 50%.



J&B #	MFG#	SIZE	ARBOR	GRADE	MAX RPM	QTY
41959	95011	4-1/2"	5/8	HARD	11,000	EA
41983	95016	5"	5/8	MEDIUM	10,000	EA
41972	95018	7"	5/8-11	MEDIUM	8,500	EA

07-30-20 PAGE 502A

<sup>\*</sup> Part# **46445** is a **closed coat zirconia** alumina abrasive material on an X-weight, water resistant polyester/cotton blended backing. For general purpose grinding and finishing on ferrous and nonferrous metals, cast iron, aluminum, stainless steel and wood materials.

### **ULTIMATE CUT CUT-OFF WHEELS**

#### FOR USE ON RIGHT ANGLE GRINDERS



- Best in class cutting a wide range of stainless thin & thick gauge, flat stock, bar stock, square tubing, etc.
- Exceptional cutting performance on metal & aluminum.
- Maximizes productivity.



		SIZE			
J&B #	MFG#	DIA THK ARBOR	TYPE	MAX RPM	QTY
49106	23152	3 x .035 x 1/4	1	25,000	10
38464	22230	4-1/2 x .045 x 7/8	1	13,300	10
38466	22240	6 x .045 x 7/8	1	10,200	10

NOTE: CUT-OFF WHEELS ARE FOR USE ON RIGHT ANGLE **GRINDERS EQUIPPED WITH PROPER TYPE 1 FLANGES.** DO NOT USE WITH TYPE 27 STYLE FLANGES.

J&B#	DESCRIPTION	QTY
41407	TYPE 1, ADAPTER FLANGE	EA



UNITED ABRASIVES, INC.

### **ALUMINUM CUT-OFF WHEELS**

#### FOR USE ON RIGHT ANGLE GRINDERS



- For cutting non-ferrous metals...aluminum, copper, brass, etc. Made of aluminum oxide grain.
- Soft bond for aggressive cutting without loading.
- Use with reusable 5/8-11 adapter to fit angle grinders.

		SIZE			
J&B #	MFG#	DIA THK ARBOR	TYPE	MAX RPM	QTY
42065	23314	4-1/2 x .045 x 7/8	1	13,300	10

07-30-20 PAGE 502B



### HIGH SPEED CUT-OFF WHEELS

#### FOR USE ON RIGHT ANGLE GRINDERS







- Cuts ferrous & non ferrous metals (iron, steel, welds, etc.)
- Thin wheel, fast cutting with long life.
- Cut-off wheels are dressed so they cut instantly.
- Premium cutting speed and life in sheet metal or solids. Outstanding in stainless or alloys.

	SIZE					
J&B #	DIA THK ARBOR	MFG	TYPE	GRADE	MAX RPM	QTY
41408	4-1/2 x .045 x 7/8	SAIT 23101	1	A60S	13,300	10
43500	4-1/2 x .045 x 7/8	FLEXOVIT F1207	1	A60S	13,300	10
40259	6 x .045 x 5/8	SAIT 23105	1	A60S	10,200	10
42122	6 x .045 x 7/8	SAIT 23106	1	A60S	10,200	10
42166	6 x .045 x 7/8	FLEXOVIT F1707	1	A60S	10,000	10

NOTE: CUT-OFF WHEELS ARE FOR USE ON RIGHT ANGLE GRINDERS EQUIPPED WITH PROPER TYPE 1 FLANGES DO NOT USE WITH TYPE 27 STYLE FLANGES.

J&B #	DESCRIPTION	QTY
41407	TYPE 1, ADAPTER FLANGE	EA



### HIGH SPEED CUT-OFF WHEELS

- Aluminum oxide grain.
- Hard bond for aggressive cutting on rough applications.
- Cuts ferrous metals (iron, steel, welds, etc.) and stainless.

6 x 035 x 7/8 A361 N33/10	MAX 10,186 RFM Hate in USA
AMONG T	ED STANDARDUS DIRCOV OSEU

	SIZE					
J&B #	DIA THK ARBOR	MFG	TYPE	GRADE	MAX RPM	QTY
41839	6 x .035 x 7/8	SAIT 23210	1	A36T	10,186	10



### **CUT-OFF WHEELS**

### **Depressed Center**

#### FOR USE ON RIGHT ANGLE GRINDERS



- The Razorblade 27 wheel combines fast, chatter free cutting with exceptional wheel life, making it the wheel of choice where wheel usage is high and wheel change downtime is a concern.
- Facilitates flush cutting on flat surfaces.



		SIZE						
J&B#	MFG#	DIA	THK	ARBOR	TYPE	GRADE	MAX RPM	QTY
42042	A0481	4-1/2	x .045	x 7/8	27	A60SST-27	13,300	10
V41989	A2481	6 x	.045 x	7/8	27	A60SST-27	10,000	10

## **CUT-OFF WHEEL**Depressed Center

- Unique, thin type 27/ type 42 shape can be used on all angle grinders in accordance with ANSI B7.1.
- Unique formulations offer the fastest cutting, longest lasting thin wheels.
- Externally reinforced with fiberglass layers to provide ultimate safety in a thin wheel.
- Proprietary bonding system allows for faster, burr free cuts.



		SIZE						
J&B#	MFG#	DIA	THK	ARBOR	TYPE	GRADE	MAX RPM	QTY
49108	22021	4-1/2	x .045	x 7/8	27 / 42	A60S	13,300	10

07-30-20 PAGE 503A



### PORTABLE SAW CUT-OFF WHEELS

**Extremely Fast Cutting** 

- Special aluminum oxide grain formula.
- Fast cutting action. Non-binding cutting formula.
- Externally reinforced with the highest quality fiberglass.
- Cuts ferrous metals, stainless steel, high tensile alloys.



		SIZE				
J&B #	MFG#	DIA THK ARBOR	TYPE	GRADE	MAX RPM	QTY
39149	24160	14 x 1/8 x 20mm	1	XFC	5,460	1



### **GREEN CORPS CUT-OFF WHEELS**

#### FOR USE ON PENCIL & DIE GRINDERS



 Green Corps Cut-Off Wheels are designed to provide high cut rates and long life on most all materials including fiberglass, stainless steel, mild steel and aerospace alloys.



 Green Corps Wheels incorporate 3M's patented Cubitron ceramic abrasive grain technology and are ideal for use on a wide variety of utility type cut-off tools.

J&B #	SIZE	HOLE	MAX RPM	QTY
*41860	3 x 1/16	3/8"	26,000	5
*45570	4 x 1/32	3/8"	26,250	5


\*No broken boxes

### **CUT-OFF WHEELS**

#### FOR USE ON PENCIL & DIE GRINDERS



- Aluminum oxide grain, hard bond for aggressive cutting on rough applications.
- Easily cuts through tubes, pipes, sheet metal.



J&B #	MFG #	SIZE	HOLE	MATERIAL	MAX RPM	QTY
*40249	F0220	2-1/2 x 1/16	3/8	A36T	24,446	10
40256	23051	3 x .035	3/8	A60T	25,000	10
*42168	F0310	3 x .035	3/8	A60T	25,000	10
40250	23040	3 x 1/16	3/8	A36T	25,000	10
40252	23065	4 x 1/16	3/8	A36T	19,000	10



<sup>\* =</sup> Flexovit Brand

J&B #	FITS WHEEL	SHANK	QTY	
	THICKNESS	ARBOR	SIZE	
40255	.035 to 1/2	3/8	1/4	EA
40251	.035 to 3/16	3/8 or 1/4	1/4	EA

\* These mandrel adapters fit 2" to 4" diameter wheels.






### **CHOPSAW WHEELS**

FOR USE ON CHOPSAWS



- General purpose for profiles and solids; carbon or alloy steels.
- Made of reinforced resinoid for longer life.



J&B #	MFG#	SIZE	HOLE	MATERIAL	MAX RPM	QTY	CASE
39062	24034	12 x 3/32	1"	A30RB	5,100	EA	10
39064	24039	14 x 3/32	1"	A30RB	4,400	EA	10

### **REDUCING BUSHINGS**

- For use with type 1 cut-off wheels.
- Reduces wheel arbor size.

J&B #	SIZE	QTY
13757	7/8 – 5/8	10
13756	1" - 7/8	10
13755	1" – 20mm	10



### **CIRCULAR SAW WHEELS**

FOR USE ON CIRCULAR SAWS



- Fast cut metal, stainless.
- A general purpose wheel, ideal on carbon or stainless steel shapes or profiles.
- Provides fast cutting action.



J&B #	MFG #	SIZE	HOLE	MATERIAL	MAX RPM	QTY
45630	23230	7 x 3/32	5/8	A24R	8,500	EA

CASE 25



### **SHOP ROLLS**

Aluminum Oxide

FOR HAND USE

- Aluminum oxide abrasive, cloth-backed, glue bonded.
- Comes in handy dispenser box.



J&B #	GRIT	LENGTH	WIDTH	QTY
20880	60	50 YDS	1-1/2	EA
20773	80	50 YDS	1-1/2	EA
20774	100	50 YDS	1-1/2	EA
20775	120	50 YDS	1-1/2	EA
20881	150	50 YDS	1-1/2	EA
20778	180	50 YDS	1-1/2	EA
20776	240	50 YDS	1-1/2	EA
20777	320	50 YDS	1-1/2	EA
20779	400	50 YDS	1-1/2	EA

### **REGULAR BELTS**

Aluminum Oxide





J&B #	GRIT	LENGTH	WIDTH	QTY
*41956	120	18 "	3/4	100

<sup>\*</sup> If breaking a box, must be done in multiples of 10.



### **ABRASIVE SCREEN**



- Made of nylon mesh impregnated with a silicone carbide abrasive.
- Can be used **wet or dry** on metal, wood, and plastic applications.
- Screen mesh design prevents loading.
- Can be used on both sides.




J&B #	SIZE	GRIT	QTY
20149	1-1/2 x 75 Ft.	120	EA

### **CROCUS CLOTH ROLL**



- Sharp, long lasting aluminum oxide abrasive.
- Excellent for extra **fine polishing** of metals.

J&B #	SIZE	QTY
20151	1-1/2 x 20 Yds.	EA





11-10-94 PAGE 507

### PSA SANDING DISCS Stikit

- Pressure sensitive adhesive for press-on, peel-off convenience.
- Discs resist loading and reduce "down time".
- For use on paint, primer, wood, metal and fiberglass.
- All discs below have no holes.

#### ORDER BY THE ROLL



J&B #	3M #	COLOR	SIZE	GRIT	QTY
40710	051144-21799	GOLD	5"	80F	100/RL
45730 45610	35412 (SAIT) 35413 (SAIT)	WHITE WHITE	5" 5"	P120 (6A) P150	100/RL 100/RL

<sup>\*</sup> Cannot break roll quantity.

ORDER BY THE ROLL

### **PSA BACKING PAD**

- For use with PSA adhesive backed sanding discs.
- Threaded pad for dual action/random orbital sanders and right angle grinders/sanders.

J&B #	SIZE	QTY
41961	5 x 5/16-24	EA











### ALUMINUM OXIDE PAPER

**Open Coat** 

- · Dry sanding only. Open coat resists loading.
- Effective for removing scratches and burrs on metal, shaping and finishing plastic filler, and stripping old paint or varnish off wood.

J&B #	SIZE	GRIT	QTY
9454	9 x 11	80D	50

### **EMERY CLOTH**

 Used for general purpose metal sanding such as light cleanup work and rust removal jobs.

J&B #	SIZE	GRIT	QTY
38058	9 x 11	FINE	EA
38969	9 x 11	MED	EA

### **CROCUS CLOTH**

- Sharp, long lasting aluminum oxide abrasive.
- Excellent for extra fine polishing of metals.

J&B #	SIZE	QTY
38968	9 x 11	EA

02-28-19 PAGE 509



### **TAPERED CARTRIDGE MANDRELS**

J&B #	SHANK DIA.	PILOT LENGTH	PILOT DIA.	QTY
41966	1/4"	1"	1/8	EA
41970	1/4"	1-1/2"	3/16	EA



### STEEL WOOL

- Heavy duty grade for removing rust, cleaning car engines & removing accumulations of paint & varnish on floors & furniture.
- Packaged in bags of 12.

J&B #	GRADE	STYLE	QTY
40393	#4	EXTRA COARSE	1 BAG

(ORDERING 1 = 1 BAG OF 12)

\*\* NO BROKEN BAGS



### STRIP DISC

- Fast, safe removal of surface contaminants.
- Excellent for cleaning welds, removing corrosion, rust, scaling and blending.
- Great for removing paints, varnishes & sealants from Difficult to reach surfaces.

J&B #	SIZE	MAX RPM	QTY
45732	2"	12,000	5
45733	3"	8,500	5
45960	4-1/2"	12,000	EA

J&B #	SIZE	QTY
40448	2" Arbor 1/4" Shank	EA
40449	3" Arbor 1/4" Shank	EΑ







05-27-21 PAGE 510

### **3M SCOTCH-BRITE HAND PADS**

General Purpose Pad



- Made of nylon web rinse clean can be used over and over again.
- Handy for doing many chores from Cleaning metal surfaces to sanding wood or ceramic materials.
- Use in a dry medium or with lubricants such as water or oil.



J&B #	SIZE	GRIT	COLOR	QTY
*40391	6 x 9	SUPER FINE	WHITE	20
*12250	6 x 9	FINE	LIGHT GRAY	20
*40700	6 x 9	MEDIUM	MAROON	20
*42063	6 x 9	COARSE	DARK GRAY	20

<sup>\*</sup> Sold in full boxes only.

### **ALUMINUM OXIDE MOUNTED FLAP WHEELS**



- For cleaning, deburring, finishing, and polishing of flat or contoured metal surfaces.
- Hugs concave or convex surfaces, allowing access to hard-to-reach areas.
- Non-loading; the flexibility provided by the coated abrasive flaps prevents loading which occurs with non-flexible grinding products.
- Mandrel mounted on fixed 1/4" solid shank.

	WHEEL	FACE		MAX	
J&B#	DIAMETER	WIDTH	GRIT	RPM	QTY
40654	1"	1"	60	30,000	EA
40655	1"	1"	80	30,000	EA
42385	1"	1"	120	30,000	EA
42387	1-1/2"	1"	60	25,000	EA
42388	1-1/2"	1"	80	25,000	EA
40665	1-1/2"	1"	120	25,000	EA
42391	2"	1"	60	25,000	EA
40660	2"	1"	80	25,000	EA
40662	2"	1"	120	25,000	EA
40664	2"	1"	180	25,000	EA
40667	2-1/2"	1"	60	23,000	EA
42393	2-1/2"	1"	80	23,000	EA
40668	2-1/2"	1"	120	23,000	EA
42395	3"	1"	60	23,000	EA
42397	3"	1"	120	23,000	EA



04-07-16 PAGE 511

### **ROL-ON SANDING DISCS**

#### FOR USE ON RIGHT ANGLE SANDERS & GRINDERS



- It is a handy quick change tool for disc grinding.
- Fits any 1/4" drill or air tool.
- Connects quickly and easily to its arbor with a 1/2" right twist and removes with a 1/2" left twist.

J&B #	SIZE	GRIT	QTY
* 41952	2"	120	50
38903	2"	80	25
* 41981	2"	80	50
38893	2"	50	25
* 41980	2"	50	50
38894	2"	36	25
^ 41899	2"	36	25
* 41950	2"	36	50
38895	2"	24	25
^ 41901	2"	24	25
* 41979	2"	24	50
39029	3"	120	25
38966	3"	80	25
* 41985	3"	50	50
38896	3"	50	25
* 41986	3"	36	50
38897	3"	36	25
* 41987	3"	24	50
38898	3"	24	25





J&B #	SIZE	QTY		
40448	2" Arbor 1/4" Shank	EA		
40449	3" Arbor 1/4" Shank	EA		

- \* 3M discs.
- ^ Shark discs.

### **ROL-ON BRISTLE DISCS**

- Ideal for cleaning, finishing, blending and deburring.
- Used on corners, welds and for rivet cleaning on all areas where conformability is required.
- Eliminate dangerous flying wires.

J&B #	SIZE	GRIT	COLOR	QTY
42164	2"	FINE	WHITE	5
42160	2"	MEDIUM	YELLOW	5
42162	2"	COARSE	GREEN	5
42163	3"	COARSE	GREEN	5







10-26-17 PAGE 512


### TRIM-KUT DISCS

#### FOR USE ON RIGHT ANGLE SANDERS & GRINDERS




- Trim-Kut abrasive discs are a unique one piece design with the grinding surface bonded to a hard copolymer backing.
- No backing pad required.
- Grinds, sands, levels weld seams and is an excellent rust/paint remover.
- Aluminum oxide discs.

J&B #	SIZE	PRINT COLOR	GRIT	QTY
20441	3"	WHITE	24	25
20442	3"	RED	36	25
20443	3"	ORANGE	60	25
20444	3"	GREEN	120	25



#### **HEX PREMIUM MANDREL**

J&B #	SIZE	QTY
20450	1/4"	EA



### MINI FLAP DISCS

- Long life performance of a flap disc for use in confined spaces.
- More material, longer life than a single layer laminated disc.
- Roloc style allows easy changeover.

J&B #	SIZE	GRIT	QTY
59114	2"	40	EA
59115	2"	80	EA
59117	3"	40	EA
59118	3"	80	EA
40448	2" Arbor (	1/4" shank)	EA
40449	3" Arbor (	1/4" shank)	EA



04-10-14 PAGE 512A



<sup>\*</sup> All boxes contain 1 mandrel.

### **ROLON SURFACE CONDITIONING DISCS**

#### FOR USE ON RIGHT ANGLE SANDERS & GRINDERS



- Non-woven surface conditioning products are ideal for deburring, cleaning, blending, and polishing.
- Use on mild steel, stainless, aluminum, plastic or wood.
- Connects quickly and easily to its arbor with a 1/2 right twist and removes with a 1/2 left twist.

J&B #	SIZE	GRIT	COLOR	QTY
38899	2"	FINE	BLUE	25
^ 41988	2"	FINE	BLUE	25
40440	2"	MEDIUM	MAROON	25
^ 41893	2"	MEDIUM	MAROON	25
^ 41894	2"	MEDIUM	MAROON	50
** 20449	2"	MEDIUM	MAROON	50
40442	2"	COARSE	BROWN	25
^ 41895	2"	COARSE	BROWN	25
^ 41896	2"	COARSE	BROWN	50
** 20448	2"	COARSE	BROWN	50
38900	3"	FINE	BLUE	25
^ 41932	3"	FINE	BLUE	25
40444	3"	MEDIUM	MAROON	25
^ 41897	3"	MEDIUM	MAROON	25
40446	3"	COARSE	BROWN	25
^ 41898	3"	COARSE	BROWN	25
40448	2"	EA		
40449	3"	Arbor (1/4"	shank)	EA





\*\* GEMTEX

^ SHARK

### **VELCRO SURFACE CONDITIONING DISCS**

#### FOR USE ON RIGHT ANGLE SANDERS & GRINDERS



- Non-woven surface conditioning products are ideal for deburring, cleaning, blending, and polishing.
- Use on mild steel, stainless, aluminum, plastic or wood.
- This disc pad connects quickly and easily to any power tool while holding surface conditioning discs securely and safely through the use of dual lock fastening system.

J&B #	SIZE	SIZE GRIT C		QTY
40420	2"	MEDIUM	MAROON	25
40422	2"	COARSE	BROWN	25
40430	2" /	EA		





06-28-18 PAGE 513

### INTERLEAF WHEELS

- Mandrel mounted on fixed 1/4" solid shank.
- Medium grade. Excellent for removing heavy oxidation, blending, cleaning and deburring.
- Very fine grade. Excellent for grain finishing, satin finishing and linear scratch patterns.

J&B #	DIA x THICKNESS	GRIT	GRADE	MAX RPM	QTY
46130	2 x 1	60	MEDIUM	15,000	EA
46131	2 x 1	80	MEDIUM	15,000	EA
46132	2 x 1	120	VERY FINE	15,000	EA

# NON WOVEN SURFACE CONDITIONING DISCS Hook & Loop

#### FOR USE ON RIGHT ANGLE GRINDERS



- Ideal for deburring, cleaning, blending and polishing.
- Use on mild steel, stainless, aluminum, plastic or wood.
- Gripper pad is made perfectly flat from high impact plastics to ensure maximum support and disc adhesion.

J&B #	SIZE	GRIT	COLOR	QTY
45680	7"	FINE	BLUE	10
45681	7"	MEDIUM	MAROON	10
45682	7"	COARSE	BROWN	10
45683	7" Gripp	EA		

### **ROLOC UNITIZED WHEEL**

- Roloc unitized wheels are strong, efficient products for edge deburring and finishing.
- They perform well in a variety of metal working applications and on intricate machined parts where close tolerances are important.
- The Roloc holding systems make changing unitized wheels quick and easy.

J&B #	SIZE	GRIT	COLOR	QTY		
40477	2"	MEDIUM	TAN	5		
40448	0448 2" Arbor (1/4" shank)					







07-15-15 PAGE 514


### **MOUNTED GRINDING STONES**

**Premium Quality** 

FOR USE ON DIE GRINDERS



- Aluminum oxide vitrified bonded wheels are for all kinds of grinding, deburring, blending and contouring of ferrous and non-ferrous metals.
- Different shapes give access to hard-to-reach areas.



		ABRASIVE SHAPE		MANDREL	MAX	
J&B #	IND#	DIAM	THICK	SIZE	RPM	QTY
40680	A3	1	2-3/4	1/4	16,100	2
40681	A11	7/8	2	1/4	19,860	2
40682	A21	1	1	1/4	34,500	2
40683	A31	1-3/8	1	1/4	27,780	2
40684	A36	1-5/8	3/8	1/4	23,520	2
40685	B52	3/8	3/4	1/8	45,370	2
40686	W163	1/4	1/2	1/8	60,000	2
40687	W185	1/2	1/2	1/8	34,500	2
40688	W215	1	1/8	1/8	38,200	2
40689	W220	1	1	1/4	25,500	2
40690	W235	1-1/2	1/4	1/4	25,470	2
40691	W236	1-1/2	1/2	1/4	25,470	2

**GROUP A SHAPES:** Use for medium to heavy duty blending and contouring.

**GROUP B SHAPES:** Best for light deburring and blending.


**GROUP W SHAPES:** Suited for off-handed and precision grinding where medium

to heavy stock removal is required.



### **WIRE END BRUSHES**

#### FOR USE ON STRAIGHT GRINDERS



- Use crimped for softer and knotted for more aggressive brushing.
- Use with portable tools or drill presses.
- Ideal for tight to get at areas and blind holes.

#### **APPLICATIONS:**

- Carbon Cleaning
- Die, Mold and Tool Polishing
- Rust or Paint Removal
- Burr Removal

- Weld Cleaning
- Rubber or Plastic Removal
- Spot Facing
- Cleaning Castings



42120 / 20960 / 20961 CRIMPED

45702 / 41192 KNOTTED

J&B #	DIA	SHANK	WIRE SIZE	TRIM LENGTH	MAX. SAFE FREE SPEED (RPM)	QTY
20960	1/2"	1/4"	.020	1"	22,000	EA
20961	1"	1/4"	.020	1"	20,000	EA
42120	1-3/4"	1/4"	.012	1"	20,000	EA
45702	3/4"	1/4"	.014	1"	20,000	EA
41192	1-1/8"	1/4"	.020	1"	20,000	EA

### **TUBE BRUSH**

• Deburring and cleaning drilled holes and internal threads, cleaning and finishing internal diameters of pipes and tubes, deburring and cleaning keyways and grooves.



J&B #	DIA	BRUSH LENGTH	OVERALL LENGTH	FILAMENT/ DIAMETER	QTY
41326	7/8"	1"	3-1/2"	.006 CARBON	EA



### **KNOT WIRE CUP BRUSH**

FOR USE ON ANGLE GRINDERS



• Knot wheels provide high impact brushing action for heavy surface conditioning applications.



J&B#	DIA	ARBOR	WIRE SIZE	MATERIAL	MAX. SAFE FREE SPEED (RPM)	QTY
V41877	2-3/4"	5/8-11	.020	Carbon	14,000	EA
41790	3-1/2"	5/8-11	.020	Carbon	12,500	EA
41193	4"	5/8-11	.020	Carbon	9,000	EA

### LARGE CRIMPED WIRE CUP BRUSH

FOR USE ON LARGE ANGLE GRINDERS



- For general purpose cleaning and deburring.
- Ideal for light cleaning and paint removal.
- Ideal for flat surfaces and edge cleaning.



J&B #	DIA	ARBOR	WIRE SIZE	MATERIAL	MAX. SAFE FREE SPEED (RPM)	QTY
41791	2-3/4"	5/8-11	.014	Carbon	14,000	EA
41872	3-1/2"	5/8-11	.014	Carbon	12,500	EA

### **CRIMPED WIRE CUP BRUSH**

FOR USE ON DIE GRINDERS, POWER DRILLS, RIGHT ANGLE AIR DIE GRINDERS



J&B#	DIA	ARBOR	WIRE SIZE	MATERIAL	MAX. SAFE FREE SPEED (RPM)	QTY
45729	2"	1/4"	.0118	Carbon	13,000	EA



06-18-15 PAGE 517

### **CRIMPED WIRE WHEEL**

#### FOR USE ON ANGLE GRINDERS



- For light rust and oxide removal, cleaning and conditioning.
- Crimped wire wheel brushes have higher flexibility than knotted wire for application on irregular surfaces and where lighter brushing is required.



J&B #	DIAM	FACE	ARBOR	WIRE SIZE	MAX. SAFE FREE SPEED (RPM)	QTY
40433	4"	1/2"	5/8-11	.014	15,000	EA

#### **KNOTTED WIRE WHEEL**

FOR USE ON ANGLE GRINDERS



- Provide high impact action to remove weld scale and splatter.
- Ideal for general cleaning.



J&B #	DIAM	FACE	ARBOR	WIRE SIZE	MAX. SAFE FREE SPEED (RPM)	QTY
40434	4"	3/8"	5/8-11	.020	20,000	EA

12-20-18 PAGE 517A



### **KNOTTED WIRE WHEEL**

FOR USE ON RIGHT ANGLE SANDERS & GRINDERS



• Cleaning, deburring, roughening.



J&B #	DIAM	FACE	ARBOR	WIRE SIZE	MAX. SAFE FREE SPEED (RPM)	QTY
45731	3"	3/8"	1/4"	.014	25,000	EA

### **CRIMPED WIRE WHEEL**

FOR USE ON RIGHT ANGLE SANDERS & GRINDERS



 For light to medium duty applications

J&B #	DIAM	ARBOR	WIRE SIZE	MAX. SAFE FREE SPEED (RPM)	QTY
38666	1-1/2	1/4"	.012	20,000	EA
38667	2"	1/4"	.012	5,000	EA
38668	3"	1/4"	.012	4,500	EA
38669	3"	1/4"	.008	4,500	EA



12-03-20 PAGE 517B



### **CRIMPED WIRE WHEELS**

Carbon Steel

FOR USE ON BENCH GRINDERS



- Designed for maximum productivity; good filament density and additional section construction for extra rigidity.
- Excellent for refining metal surfaces, preparing rubber in vulcanizing, blending surfaces, removing light burrs, paint and corrosion.



J&B #	DIAM.	WIRE SIZE	WIDTH	ARBOR	MAX RPM	QTY
39175	6"	.014	1/2"	1/2, 5/8	6,000	EA
39094	8"	.014	1"	1/2, 5/8	4,500	EA

\* Part #39094 comes with 1/2 and 5/8 arbor; 3/4 arbor must be ordered separately.

J&B #	ARBOR
1403	3/4 - (for 8" wheel)

### T-C CARBON STEEL WHEELS

FOR USE ON MINI GRINDERS





- Designed for use in restricted or hard-to-reach areas.
- Used for deburring, blending and cleaning of surfaces.

J&B #	DIAM.	WIRE SIZE	WIDTH	ARBOR	MAX RPM	QTY
40141	2"	.012	1/4	1/2	20,000	EA
40142	2-1/2"	.014	1/4	1/2	20,000	EA
40143	3"	.012	1/4	1/2	20,000	EA


### **ARBOR**


**J&B # QTY** 40140 EA


Metal arbor for use in portable tools and drill presses with 1/4" capacity chucks 1/4" shank, 1/2" diameter brush to be used in adapting small diameter brushes with 1/2" diameter hole. **DO NOT USE WITH GRINDING WHEELS.** 



08-08-96 PAGE 518











aluminum, plastic or wood.























22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411


























































### **J&B Fleet - Industrial Supply**

22428 Harrisburg-Westville Rd. Alliance, Ohio 44601 Phone: (330) 821-6342 Fax: (330) 821-0411

www.jbfleet.com



## 45731

3/8 x 1/4

**KNOTTED** 

**WIRE WHEEL** 

### **WIRE WHEEL ASSORTMENT** 38669



3" X 1/4 **CRIMP WIRE WHEEL WIRE SIZE .008**  38668



3" X 1/4 **CRIMP WIRE** WHEEL **WIRE SIZE .012**  38667



2" X 1/4 **CRIMP WIRE** WHEEL **WIRE SIZE .012** 

42120

1-3/4 X 1/4

**END BRUSH** 













20960 20961

2

2



1 X 1/4 **END BRUSH** 

41192



1-1/8 X 1/4 **END BRUSH** 

2

**END BRUSH** 

1/2 X 1/4

2

