

## 2 Bushel Operation Instructions

This machine is designed to run on a designated 30 amp breaker at 220v. If unsure, please consult an electrician.

Once machine is wired correctly, Please do the following steps in order before turning on the machine.

### **To Begin Shelling**

Step 1: Make sure Hull Slider Plate is removed and set aside.

Step 2: Make sure Flip Door is closed and tight. Will require 1/2" wrench to tighten.

Step 3: Open Doors. Remove one screen by releasing bungee straps. Set to side.

Step 4: Load 1 to 2 bushels into drum. (25 -50 lbs, may vary depending on product)

Step 5: Replace Screen and reattach bungee straps.

Step 6: Close and secure doors.

Step 7: Turn on switches from **LEFT** to Right. First turn on the Drum and let it rotate a few times to get the product moving. Then turn on the Paddles and then the Trough.

Step 8: Let the machine run 8 -15 minutes or until the product has completely shelled out.

Shelled Product will collect at the end of the machine.

Step 9: Turn off all switches.

### **Dumping Hulls**

Step 1: Make sure all switches are off and the machine is not running.

Step 2: Open Flip Door handle

Step 3: Insert Hull Slider Plate into designated slot.

Step 4: Open Doors and remove screen.

Step 5: Rotate Drum down and shake until all hulls have been removed.

Step 6: Rotate Drum up and reload with Product to begin another cycle.

Step 7: Replace Screen and Close Doors and secure clamps.

Step 8: Remove Slider Plate and close and tighten Flip Door.

*It takes approximately 8 - 15 minutes to shell 2 bushels depending on variety's shell ability. All peas and beans shell differently and some require different screen sizes. Not all varieties will fit 2 bushels in the drum. We make no guarantee that the sheller will shell all peas the same. Please contact us for support.*

T.I. Thomson Industries Inc

P.O. Box 562

335 1<sup>st</sup> ST NE


Cairo, Ga 39828

(229) 377-3074

[kthomsonus@yahoo.com](mailto:kthomsonus@yahoo.com)

[www.thomsonindustriesinc.com](http://www.thomsonindustriesinc.com)

**Hull Slide Plate Inserted**



**Hull Slide Plate Out of Machine**



**Flip Door Open, Hull Slide Plate Inserted Past Trough**



**Flip Door Closed, Slide Plate Removed**

