



PREMIUM TRAILER CABLE

PART #	GAUGE	LENGTH FT.
FW414-50	4/14 gauge	50'
FW414-100	4/14 gauge	100'
FW414-500	4/14 gauge	500'
FW614-50	6/14 gauge	50'
FW614-100	6/14 gauge	100'
FW614-500	6/14 gauge	500'
FW714-50	7/14 gauge	50'
FW714-100	7/14 gauge	100'
FW714-500	7/14 gauge	500'
FW710-50	6/14 - 1/12 gauge	50'
FW710-100	6/14 - 1/12 gauge	100'
FW710-500	6/14 - 1/12 gauge	500'
FW730-50	6/12 - 1/10 gauge	50'
FW730-100	6/12 - 1/10 gauge	100'
FW730-500	6/12 - 1/10 gauge	500'
FW750-50	ABS 4/12 - 2/10 - 1/8	50'
FW750-100	ABS 4/12 - 2/10 - 1/8	100'
FW750-500	ABS 4/12 - 2/10 - 1/8	500'

Premium Trailer Cables TPR

Cable remains flexible at -65°C (-85°F). High dielectric strength.

TPR (thermoplastic rubber) outer jacket resists abrasion and is oil-resistant.

Color-coded multiple conductors. Constructed with the highest grade

copper stranding available, recommended for rewiring trailers to ICC

regulations. Manufactured to provide superior performance.



NYLON AIR BRAKE TUBING

PART #	TUBE O.D.	TUBE I.D.	WALL THICKNESS	FT. PER ROLL
FW5085-100	1/8"	0.079	0.023	100ft
FW5085-1000	1/8"	0.079	0.023	1000ft
FW5086-100	1/4"	0.17	0.04	100ft
FW5086-1000	1/4"	0.17	0.04	1000ft
FW5087-100	5/16"	0.232	0.04	100ft
FW5087-500	5/16"	0.232	0.04	500ft
FW5088-100	3/8"	0.25	0.062	100ft
FW5088-500	3/8"	0.25	0.062	500ft
FW5089-100	1/2"	0.375	0.062	100ft
FW5089-500	1/2"	0.375	0.062	500ft
FW5090-100	5/8"	0.441	0.092	100ft
FW5090-250	5/8"	0.441	0.092	250ft
FW5091-100	3/4"	0.566	0.092	100ft
FW5091-250	3/4"	0.566	0.092	250ft
FW5092-100	5/32"	0.086	0.025	100ft

Nylon air brake tubing for use in air brake and air suspension systems
150 psi maximum working pressure, withstands temperatures
of -40°F to +200°F. Tubing meets SAE J844 and FMVSS 106 requirements.
Available colours: black, blue, green, red, yellow, orange.
Available in 100' spools.

Standard colors in all sizes is black. The 1/4" and 3/8" sizes are also stocked in red, blue, green, and yellow.
The 1/2" size is also stocked in red green.