

SAFETY DATA SHEET

Published DateRevision DateRevision NumberAug-17-2018Aug-17-20182

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product code 9724
Product name Black

Product category 9700 Series SV Screen Ink

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use
Recommended use Printing operations

Details of the supplier of the safety data sheet

UNITED STATES
UNITED KINGDOM
Nazdar Company
Nazdar Limited
8501 Hedge Lane Terrace
Shawnee, KS 66227
Barton Road
Heaton Mersey

Tel: +001-913-422-1888 Stockport, England SK4 3EG
Tel: +001-800-677-4657 Tel: +44 161 442 2111

Fax: +001-913-422-2294

www.nazdar.com

Emergency telephone number

USA: Chemtrec: +001-800-424-9300 Outside USA: Chemtrec: +001-703-527-3887

24 Hour Emergency Phone Number

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 4 - (H302)
Acute toxicity - Dermal	Category 4 - (H312)
Acute toxicity - Inhalation (Vapors)	Category 4 - (H332)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin Corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)

Label elements



Signal Word Warning

Hazard Statements

H302 - Harmful if swallowed H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P330 - Rinse mouth

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Hazards not otherwise classified (HNOC)

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Inhalation

Component	CAS-No	Weight %	Trade Secret	Note
2-Butoxyethanol	111-76-2	30 - 60	*	
Carbon black	1333-86-4	5 - 10	*	
Resin	Trade Secret	1 - 5	*	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Get medical attention if irritation develops and

persists.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes. Remove

contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention. Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or

stopped, administer artificial respiration. Get medical attention immediately.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a

physician or poison control center immediately.

Most important symptoms and effects, both acute and delayed

None under normal use conditions.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Foam. Carbon dioxide (CO2). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and

clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people

away from and upwind of spill/leak.

Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

HandlingUse personal protective equipment as required. Do not eat, drink or smoke when using this

product. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

open flames, hot surfaces and sources of ignition. Keep container closed when not in use.

Keep out of the reach of children.

Incompatible Products Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits

Component	ACGIH TLV
2-Butoxyethanol	TWA: 20 ppm
111-76-2 Carbon black	TWA: 3 mg/m³ inhalable particulate matter
1333-86-4	TWA. 3 mg/m* milalable particulate matter

Component	OSHA PEL
2-Butoxyethanol	TWA: 50 ppm
111-76-2	TWA: 240 mg/m ³
	Skin
Carbon black	TWA: 3.5 mg/m ³
1333-86-4	

Component	OSHA PEL (vacated)
2-Butoxyethanol	TWA: 25 ppm
111-76-2	TWA: 120 mg/m ³
	Skin
Carbon black	TWA: 3.5 mg/m ³
1333-86-4	

Component	Ontario TWAEV
2-Butoxyethanol	TWA: 20 ppm
111-76-2	
Carbon black	TWA: 3 mg/m³ inhalable
1333-86-4	-

Component	Mexico OEL (TWA)
2-Butoxyethanol	TWA/VLE-PPT: 26 ppm
111-76-2	TWA/VLE-PPT: 120 mg/m³
	STEL/PPT-CT: 75 ppm
	STEL/PPT-CT: 360 mg/m ³
Carbon black	TWA/VLE-PPT: 3.5 mg/m³
1333-86-4	STEL/PPT-CT: 7 mg/m³

Appropriate engineering controls

Engineering Measures Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In

case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur:. Wear

suitable face shield. Ensure that eyewash stations and safety showers are close to the

workstation location.

Skin Protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before

eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of

equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical StateLiquidAppearanceColored LiquidOdorCharacteristicOdor ThresholdNo information available

PropertyValuesRemarks • MethodpHNo data availableMelting Point / Freezing PointNo data available

Boiling Point / Boiling Range > 149 °C / 300 °F

Flash Point 62 °C / 143 °F Pensky Martens Closed Cup (PMCC)

Evaporation rate No data available

Flammability Limit in Air

Upper flammability limitNo data availableLower flammability limitNo data availableVapor PressureNo data availableVapor DensityNo data available

Specific Gravity 1

Water Solubility
Solubility in other solvents
Partition coefficient: n-octanol/water
Autoignition Temperature
No data available

Kinematic viscosity

No data available

Dynamic viscosity

No data available

Explosive PropertiesNo data available **Oxidizing Properties**No data available

Other Information

Photochemically Reactive No Weight Per Gallon (lbs/gal) 8.35

VOC by weight %	VOC by volume %	VOC lbs/gal	VOC grams/liter
(less water)	(less water)	(less water)	(less water)
58.53	60.46	4.89	586.32

10. STABILITY AND REACTIVITY

Reactivity

No information available.

Chemical stability

Stable under normal conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO2). Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Specific test data for the substance or mixture is not available. Harmful if inhaled. (based on

components).

Eye Contact Specific test data for the substance or mixture is not available.

Skin Contact Specific test data for the substance or mixture is not available. Harmful in contact with skin.

(based on components).

Ingestion Specific test data for the substance or mixture is not available. Harmful if swallowed. (based

on components).

Component	Oral LD50
2-Butoxyethanol	= 470 mg/kg (Rat)
111-76-2 Carbon black	> 15400 mg/kg (Rat)
1333-86-4	> 10-100 mg/kg (Nat)

Component	Dermal LD50
2-Butoxyethanol	= 99 mg/kg (Rabbit)
111-76-2	

Component	Inhalation LC50
2-Butoxyethanol	= 450 ppm (Rat) 4 h
111-76-2	= 486 ppm (Rat) 4 h

Information on toxicological effects

Symptoms Specific test data for the substance or mixture is not available.

9724 Black

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Specific test data for the substance or mixture is not available. Causes skin irritation (pain,

redness and swelling). (based on components).

Eye damage/irritation Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components).

Irritation Specific test data for the substance or mixture is not available. Corrosivity Specific test data for the substance or mixture is not available. Sensitization Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. **Mutagenic Effects** Specific test data for the substance or mixture is not available. Carcinogenic effects **Reproductive Effects** Specific test data for the substance or mixture is not available. STOT - single exposure Specific test data for the substance or mixture is not available. Specific test data for the substance or mixture is not available. STOT - repeated exposure **Chronic Toxicity** Specific test data for the substance or mixture is not available Specific test data for the substance or mixture is not available. **Aspiration hazard**

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.

our onrogornoity	The table below indicates whether each agency has neted any ingredient as a careinogen.	
Component	ACGIH	
2-Butoxyethanol 111-76-2	A3	
Carbon black	A3	
1333-86-4		

Component	IARC
Carbon black	Group 2B
1333-86-4	

Component	OSHA
Carbon black	Χ
1333-86-4	

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 860.00 mg/kg

 ATEmix (dermal)
 1,891.00 mg/kg mg/l

ATEmix (inhalation-dust/mist) 2.60 mg/l ATEmix (inhalation-vapor) 19.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Specific test data for the substance or mixture is not available.

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Fish
2-Butoxyethanol	96h LC50 Lepomis macrochirus: = 2950 mg/L
111-76-2	96h LC50 Lepomis macrochirus: = 1490 mg/L (static)

Component	Crustacea
2-Butoxyethanol	48h EC50 Daphnia magna: > 1000 mg/L
111-76-2	

Persistence and Degradability

No information available.

Revision Date Aug-17-2018

9724 Black

Bioaccumulation

No information available

Component	Partition coefficient
	0.81
111-76-2	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. TRANSPORT INFORMATION

Note: This information is not intended to convey all specific transportation requirements relating to

this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and

rules relating to the transportation of the material.

DOT Not regulated

Proper Shipping Name Printing Ink

ICAO / IATA / IMDG / IMO
Proper Shipping Name

Not Regulated
Printing Ink

15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact:. Supplier (manufacturer/importer/downstream user/distributor).

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
2-Butoxyethanol	111-76-2	30 - 60	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
2-Butoxyethanol	111-76-2	30 - 60
Xylenes (o-, m-, p- isomers)	1330-20-7	< 0.5

U.S. State Regulations

Component

Bassachusetts
Right To Know

2-Butoxyethanol
111-76-2

Carbon black
1333-86-4

X

X

X

	Minnesota Right To Know
2-Butoxyethanol 111-76-2	Х
Carbon black 1333-86-4	Х

	New Jersey Right To Know
2-Butoxyethanol 111-76-2	Х
Carbon black 1333-86-4	Х

•	Pennsylvania Right To Know
2-Butoxyethanol 111-76-2	X
Carbon black 1333-86-4	Х

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Carbon black	Carcinogen

⁻ This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

Canada

Component	NPRI - National Pollutant Release Inventory
2-Butoxyethanol	Part 5, Individual Substances; Part 4 Substance
111-76-2	

Pursuant to NOM-018-STPS-2015

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

16. OTHER INFORMATION				
HMIS:	Health	Flammability	Reactivity	Personal Protection

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)
STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

9724 Black Revision Date Aug-17-2018

Group 2B - Possibly Carcinogenic to Humans NTP: (National Toxicity Program)

Known - Known Carcinogen
Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Revision Date Aug-17-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet