

O.D. CHART FOR PVC COVERS
R/S A4A SERIES ADAPTOMODE REGULATORS
WITH AND WITHOUT STRAINERS

2"

4" A4A/A4AK A4AL/A4AR/A4AM	14.0 CROSS
4" A4A W/STRAINER A4AK W/STRAINER A4AL W/STRAINER A4AM W/STRAINER A4AR W/STRAINER	14.0 USE 3 TEES AND 5 CAPS
4" A4AD	14.0 CROSS W/A4AD TOP
4" A4AD W/STRAINER	14.0 W/A4AD TOP USE 3 TEES AND 4 CAPS
4" A4AB/A4AS	14.0 CROSS W/A4AB/A4AS TOP
4" A4AB W/STRAINER A4AS W/STRAINER	14.0 W/A4AB/A4AS TOP USE 3 TEES AND 4 CAPS

FOR SINGLE RSF TYPE STRAINER, USE ONE TEE AND THREE CAPS OF SAME O.D. AS REGULAR FLANGED VALVE.

PVC COVER NOT AVAILABLE FOR RSW TYPE STRAINERS.

FOR CK-1 AND CK-2 CHECK VALVES, USE SAME PVC CROSS OR COMBO AS SAME SIZE SOLENOID VALVE FOR A4A PVC REGULATOR VALVE.