



Flat-Panel LED Lighting

T22B3310DU40 – 2X2 (4K)

T22B3310DU50 – 2X2 (5K)

T24B3315DU40 – 2X4 (4K)

T24B3315DU50 – 2X4 (5K)

T14B3310DU40 – 1X4 (4K)

T14B3310DU50 – 1X4 (5K)



Dimmable



TAA
Compliant



UL-Listed



Sealed
Fixture



Eco-
Friendly



High
Luminance

Specifications

	T22B3310DU40	T22B3310DU50	T24B3315DU40	T24B3315DU50	T14B3310DU40	T14B3310DU50
Input Voltage	120 – 277 V~	120 – 277 V~	120 – 277 V~	120 – 277 V~	100 – 277 V~	100 – 277 V~
Input Current	0.35 A	0.35 A	0.48 A	0.48 A	0.35 A	0.35 A
Input Frequency	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Watts	37 W	37 W	54 W	54 W	37 W	37W
Luminous Flux	3230 lm	3250 lm	4750 lm	4800 lm	3250 lm	3280 lm
Luminous Efficacy	87.3 lm/W	87.8 lm/W	88 lm/W	88.9 lm/W	87.8 lm/W	88.6 lm/W
Dimmable	0V – 10 V	0V – 10 V	0V – 10 V	0V – 10 V	0V – 10 V	0V – 10 V
Color Temperature	4000 k	5000 k	4000 k	5000 k	4000 k	5000 k
Color Rendering Index	80 (↑) Ra	80 (↑) Ra	80 (↑) Ra	80 (↑) Ra	80 (↑) Ra	80 (↑) Ra
Weight	8.6 lbs.	8.6 lbs.	16.3 lbs.	16.3 lbs.	8.2 lbs.	8.2 lbs.
Length	23.6 in.	23.6 in.	47.8 in.	47.8 in.	47.8 in.	47.8 in.
Width	23.6 in.	23.6 in.	23.6 in.	23.6 in.	11.8 in.	23.6 in.
Depth	3.9 in.	3.9 in.	3.2 in.	3.2 in.	3.2 in.	3.2 in.
Operating Temperature	15 to 104° F	15 to 104° F	15 to 104° F	15 to 104° F	-10-40° F	-10-40° F
Storage Temperature	-4 to 140° F	-4 to 140° F	-4 to 140° F	-4 to 140° F	-20-60° F	-20-60° F
Warranty	Limited 5-Year	Limited 5-Year	Limited 5-Year	Limited 5-Year	Limited 5-Year	Limited 5-Year
RoHS	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant
Lifetime	80% lm - 50,000 hr.	80% lm - 50,000 hr.	80% lm - 50,000 hr.	80% lm - 50,000 hr.	80% lm - 50,000 hr.	80% lm - 50,000 hr.
Standards	UL/FCC/DLC/LM80	UL/FCC/DLC/LM80	UL/FCC/DLC/LM80	UL/FCC/DLC/LM80	UL/FCC/LM80	UL/FCC/LM80

2x2 - T22B3310DU40 (4K), T22B3310DU50 (5K)

2x4 - T24B3315DU40 (4K), T24B3315DU50 (5K)

1x4 - T14B3310DU40 (4K), T14B3310DU50 (5K)

