

**Published Date**  
May-15-2019

**Revision Date**  
May-15-2019

**Revision Number**  
2.5

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

**Product identifier**

**Product code** PA310  
**Product name** Green  
**Product category** PA Series SV Screen Ink

**Other means of identification**

**Synonyms** None

**Recommended use of the chemical and restrictions on use**

**Recommended use** Printing operations

**Details of the supplier of the safety data sheet**

UNITED STATES	UNITED KINGDOM
Nazdar Company	Nazdar Limited
8501 Hedge Lane Terrace	Barton Road
Shawnee, KS 66227	Heaton Mersey
Tel: +001-913-422-1888	Stockport, England SK4 3EG
Tel: +001-800-677-4657	Tel: +44 161 442 2111
Fax: +001-913-422-2294	
www.nazdar.com	

**Emergency telephone number**

USA: Chemtrec: +001-800-424-9300  
Outside USA: Chemtrec: +001-703-527-3887  
24 Hour Emergency Phone Number

**2. HAZARDS IDENTIFICATION**

**Classification**

Carcinogenicity	Category 2 - (H351)
Aspiration toxicity	Category 1 - (H304)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

**Label elements**



**Signal Word**  
Danger

**Hazard Statements**

H304 - May be fatal if swallowed and enters airways  
H351 - Suspected of causing cancer  
H411 - Toxic to aquatic life with long lasting effects  
H226 - Flammable liquid and vapor

**Precautionary Statements**

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P273 - Avoid release to the environment

P331 - Do NOT induce vomiting

P233 - Keep container tightly closed

P403 + P235 - Store in a well-ventilated place. Keep cool

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

**Hazards not otherwise classified (HNOC)**

Causes mild skin irritation. Toxic to aquatic life.

**3. COMPOSITION/INFORMATION ON INGREDIENTS****Mixture**

Component	CAS-No	Weight %	Trade Secret	Note
Solvent naphtha, petroleum, heavy aromatic	64742-94-5	30 - 60	*	
Titanium dioxide	13463-67-7	5 - 10	*	
Solvent naphtha, petroleum, light aromatic	64742-95-6	5 - 10	*	
Naphthalene (constituent)	91-20-3	1 - 5	*	1
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	*	1
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5	*	
2-Methylnaphthalene (constituent)	91-57-6	< 1	*	1
Ethyl benzene (constituent)	100-41-4	< 1	*	1
Cumene (constituent)	98-82-8	< 0.5	*	1

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

Note 1. Type of chemical: Constituent

**4. FIRST AID MEASURES****Description of first aid measures****General Advice**

Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

**Skin Contact**

Wash off immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation (redness, rash, blistering) develops, get medical attention.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

**Ingestion**

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

**Most important symptoms and effects, both acute and delayed**

None under normal use conditions.

**Indication of any immediate medical attention and special treatment needed****Notes to Physician**

Treat symptomatically.

**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media**

No information available.

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Sealed containers may rupture when heated.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches and waterways. Local authorities should be advised if significant spillages cannot be contained.

**Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling****Handling**

Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Ensure adequate ventilation.

**Conditions for safe storage, including any incompatibilities****Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of the reach of children.

**Incompatible Products**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure limits**

Component	ACGIH TLV
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>
Naphthalene (constituent) 91-20-3	TWA: 10 ppm Skin
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm
2-Methylnaphthalene (constituent) 91-57-6	TWA: 0.5 ppm Skin
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm
Cumene (constituent) 98-82-8	TWA: 50 ppm

Component	OSHA PEL

Titanium dioxide 13463-67-7	TWA: 15 mg/m <sup>3</sup> total dust
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin

Component	OSHA PEL (vacated)
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup> total dust
Naphthalene (constituent) 91-20-3	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup> STEL: 15 ppm STEL: 75 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 655 mg/m <sup>3</sup>
Ethyl benzene (constituent) 100-41-4	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
Cumene (constituent) 98-82-8	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> Skin

Component	Ontario TWAEV
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>
Naphthalene (constituent) 91-20-3	TWA: 10 ppm Skin
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 100 ppm STEL: 150 ppm
2-Methylnaphthalene (constituent) 91-57-6	TWA: 0.5 ppm Skin
Ethyl benzene (constituent) 100-41-4	TWA: 20 ppm
Cumene (constituent) 98-82-8	TWA: 50 ppm

Component	Mexico OEL (TWA)
Titanium dioxide 13463-67-7	TWA/VLE-PPT: 10 mg/m <sup>3</sup> STEL/PPT-CT: 20 mg/m <sup>3</sup>
Naphthalene (constituent) 91-20-3	TWA/VLE-PPT: 10 ppm TWA/VLE-PPT: 50 mg/m <sup>3</sup> STEL/PPT-CT: 15 ppm STEL/PPT-CT: 75 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA/VLE-PPT: 100 ppm TWA/VLE-PPT: 435 mg/m <sup>3</sup> STEL/PPT-CT: 150 ppm STEL/PPT-CT: 655 mg/m <sup>3</sup>
Ethyl benzene (constituent) 100-41-4	TWA/VLE-PPT: 100 ppm TWA/VLE-PPT: 435 mg/m <sup>3</sup> STEL/PPT-CT: 125 ppm STEL/PPT-CT: 545 mg/m <sup>3</sup>
Cumene (constituent) 98-82-8	TWA/VLE-PPT: 50 ppm TWA/VLE-PPT: 245 mg/m <sup>3</sup> STEL/PPT-CT: 75 ppm STEL/PPT-CT: 365 mg/m <sup>3</sup>

### Appropriate engineering controls

#### Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows

etc. Controlled ventilation means air is supplied or removed by a powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

#### **Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Wear safety glasses with side shields (or goggles). If splashes are likely to occur. Wear suitable face shield. Ensure that eyewash stations and safety showers are close to the workstation location.
<b>Skin Protection</b>	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
<b>Hand Protection</b>	Chemical resistant protective gloves. Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding >480 minutes of permeation time): eg. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers. Taking into account the varying conditions, the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Due to different glove types, the manufacturer's directions for use should be observed. Replace gloves immediately when torn or any change in appearance is noticed such as dimension, color, flexibility.
<b>Respiratory Protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material.
<b>General Hygiene Considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

### **Information on basic physical and chemical properties**

<b>Physical State</b>	Liquid	<b>Appearance</b>	Colored Liquid
<b>Odor</b>	Characteristic	<b>Odor Threshold</b>	No information available
<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>	
<b>pH</b>		No data available	
<b>Melting Point / Freezing Point</b>		No data available	
<b>Boiling Point / Boiling Range</b>	> 149 °C / 300 °F		
<b>Flash Point</b>	49 °C / 120 °F	Setaflash closed cup	
<b>Evaporation rate</b>		No data available	
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit</b>		No data available	
<b>Lower flammability limit</b>		No data available	
<b>Vapor Pressure</b>		No data available	
<b>Vapor Density</b>		No data available	
<b>Specific Gravity</b>	1.07		
<b>Water Solubility</b>		No data available	
<b>Solubility in other solvents</b>		No data available	
<b>Partition coefficient: n-octanol/water</b>		No data available	
<b>Autoignition Temperature</b>		No data available	
<b>Decomposition temperature</b>		No data available	
<b>Kinematic viscosity</b>		No data available	
<b>Dynamic viscosity</b>		No data available	
<b>Explosive Properties</b>	No data available		

**Oxidizing Properties** No data available

**Other Information**

**Photochemically Reactive** Yes  
**Weight Per Gallon (lbs/gal)** 8.93

VOC by weight % (less water)	VOC by volume % (less water)	VOC lbs/gal (less water)	VOC grams/liter (less water)
51.89	57.91	4.64	555.59

## 10. STABILITY AND REACTIVITY

**Reactivity**

No information available.

**Chemical stability**

Stable under normal conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents. Reducing agent.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available.
<b>Eye Contact</b>	Specific test data for the substance or mixture is not available.
<b>Skin Contact</b>	Specific test data for the substance or mixture is not available.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available.

Component	Oral LD50
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 5000 mg/kg ( Rat )
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )
Naphthalene (constituent) 91-20-3	= 1110 mg/kg ( Rat )
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 3280 mg/kg ( Rat )
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg ( Rat )
2-Methylnaphthalene (constituent) 91-57-6	= 1630 mg/kg ( Rat )
Ethyl benzene (constituent) 100-41-4	= 3500 mg/kg ( Rat )
Cumene (constituent) 98-82-8	= 1400 mg/kg ( Rat )

Component	Dermal LD50
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 2 mL/kg ( Rabbit )
Solvent naphtha, petroleum, light aromatic	> 2000 mg/kg ( Rabbit )

64742-95-6	
Naphthalene (constituent) 91-20-3	= 1120 mg/kg ( Rabbit )
1,2,4-Trimethylbenzene (constituent) 95-63-6	> 3160 mg/kg ( Rabbit )
Xylenes (o-, m-, p- isomers) 1330-20-7	> 4350 mg/kg ( Rabbit )
Ethyl benzene (constituent) 100-41-4	= 15400 mg/kg ( Rabbit )
Cumene (constituent) 98-82-8	= 12300 µL/kg ( Rabbit )

Component	Inhalation LC50
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	> 590 mg/m <sup>3</sup> ( Rat ) 4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 3400 ppm ( Rat ) 4 h
Naphthalene (constituent) 91-20-3	> 340 mg/m <sup>3</sup> ( Rat ) 1 h
1,2,4-Trimethylbenzene (constituent) 95-63-6	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Xylenes (o-, m-, p- isomers) 1330-20-7	= 29.08 mg/L ( Rat ) 4 h
Ethyl benzene (constituent) 100-41-4	= 17.4 mg/L ( Rat ) 4 h
Cumene (constituent) 98-82-8	> 3577 ppm ( Rat ) 6 h

### Information on toxicological effects

#### Symptoms

Specific test data for the substance or mixture is not available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Skin corrosion/irritation

Specific test data for the substance or mixture is not available.

#### Eye damage/irritation

Specific test data for the substance or mixture is not available.

#### Irritation

Specific test data for the substance or mixture is not available.

#### Corrosivity

Specific test data for the substance or mixture is not available.

#### Sensitization

Specific test data for the substance or mixture is not available.

#### Mutagenic Effects

Specific test data for the substance or mixture is not available.

#### Carcinogenic effects

Specific test data for the substance or mixture is not available. Suspected of causing cancer. (based on components).

#### Reproductive Effects

Specific test data for the substance or mixture is not available.

#### STOT - single exposure

Specific test data for the substance or mixture is not available.

#### STOT - repeated exposure

Specific test data for the substance or mixture is not available.

#### Chronic Toxicity

Specific test data for the substance or mixture is not available

#### Aspiration hazard

Specific test data for the substance or mixture is not available. May be fatal if swallowed and enters airways. (based on components).

#### Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	ACGIH
Naphthalene (constituent) 91-20-3	A3
Ethyl benzene (constituent) 100-41-4	A3

Component	IARC
Titanium dioxide 13463-67-7	Group 2B
Naphthalene (constituent) 91-20-3	Group 2B
Ethyl benzene (constituent) 100-41-4	Group 2B
Cumene (constituent) 98-82-8	Group 2B

Component	NTP
-----------	-----

Naphthalene (constituent) 91-20-3	Reasonably Anticipated
Cumene (constituent) 98-82-8	Reasonably Anticipated

Component	OSHA
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X
Ethyl benzene (constituent) 100-41-4	X
Cumene (constituent) 98-82-8	X

### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

<b>ATEmix (oral)</b>	14,954.00 mg/kg
<b>ATEmix (dermal)</b>	43,413.00 mg/kg mg/l
<b>ATEmix (inhalation-dust/mist)</b>	26.10 mg/l
<b>ATEmix (inhalation-vapor)</b>	191.00 mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Specific test data for the substance or mixture is not available. Toxic to aquatic life with long lasting effects. (based on components).

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Component	Algae/aquatic plants
Ethyl benzene (constituent) 100-41-4	96h EC50 Pseudokirchneriella subcapitata: > 438 mg/L 96h EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L static 72h EC50 Pseudokirchneriella subcapitata: = 4.6 mg/L 72h EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L static
Cumene (constituent) 98-82-8	72h EC50 Pseudokirchneriella subcapitata: = 2.6 mg/L

Component	Fish
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	96h LC50 Pimephales promelas: = 19 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 2.34 mg/L 96h LC50 Lepomis macrochirus: = 1740 mg/L (static) 96h LC50 Pimephales promelas: = 45 mg/L (flow-through) 96h LC50 Pimephales promelas: = 41 mg/L
Solvent naphtha, petroleum, light aromatic 64742-95-6	96h LC50 Oncorhynchus mykiss: = 9.22 mg/L
Naphthalene (constituent) 91-20-3	96h LC50 Pimephales promelas: 5.74 - 6.44 mg/L (flow-through) 96h LC50 Pimephales promelas: = 1.99 mg/L (static) 96h LC50 Lepomis macrochirus: = 31.0265 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 1.6 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: 0.91 - 2.82 mg/L (static)
1,2,4-Trimethylbenzene (constituent) 95-63-6	96h LC50 Pimephales promelas: 7.19 - 8.28 mg/L (flow-through)
Xylenes (o-, m-, p- isomers) 1330-20-7	96h LC50 Oncorhynchus mykiss: 2.661 - 4.093 mg/L (static) 96h LC50 Lepomis macrochirus: 7.711 - 9.591 mg/L (static) 96h LC50 Lepomis macrochirus: 13.1 - 16.5 mg/L (flow-through) 96h LC50 Poecilia reticulata: 30.26 - 40.75 mg/L (static) 96h LC50 Oncorhynchus mykiss: 13.5 - 17.3 mg/L 96h LC50 Lepomis macrochirus: = 19 mg/L 96h LC50 Cyprinus carpio: = 780 mg/L (semi-static) 96h LC50 Cyprinus carpio: > 780 mg/L



	96h LC50 Pimephales promelas: = 13.4 mg/L (flow-through) 96h LC50 Pimephales promelas: 23.53 - 29.97 mg/L (static)
Ethyl benzene (constituent) 100-41-4	96h LC50 Pimephales promelas: 7.55 - 11 mg/L (flow-through) 96h LC50 Poecilia reticulata: = 9.6 mg/L (static) 96h LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L (static) 96h LC50 Pimephales promelas: 9.1 - 15.6 mg/L (static) 96h LC50 Oncorhynchus mykiss: = 4.2 mg/L (semi-static) 96h LC50 Lepomis macrochirus: = 32 mg/L (static)
Cumene (constituent) 98-82-8	96h LC50 Oncorhynchus mykiss: = 4.8 mg/L (flow-through) 96h LC50 Poecilia reticulata: = 5.1 mg/L (semi-static) 96h LC50 Pimephales promelas: 6.04 - 6.61 mg/L (flow-through) 96h LC50 Oncorhynchus mykiss: = 2.7 mg/L (semi-static)

Component	Crustacea
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	48h EC50 Daphnia magna: = 0.95 mg/L
Solvent naphtha, petroleum, light aromatic 64742-95-6	48h EC50 Daphnia magna: = 6.14 mg/L
Naphthalene (constituent) 91-20-3	48h EC50 Daphnia magna: 1.09 - 3.4 mg/L Static 48h EC50 Daphnia magna: = 1.96 mg/L Flow through 48h LC50 Daphnia magna: = 2.16 mg/L
1,2,4-Trimethylbenzene (constituent) 95-63-6	48h EC50 Daphnia magna: = 6.14 mg/L
Xylenes (o-, m-, p- isomers) 1330-20-7	48h EC50 water flea: = 3.82 mg/L 48h LC50 Gammarus lacustris: = 0.6 mg/L
Ethyl benzene (constituent) 100-41-4	48h EC50 Daphnia magna: 1.8 - 2.4 mg/L
Cumene (constituent) 98-82-8	48h EC50 Daphnia magna: 7.9 - 14.1 mg/L Static 48h EC50 Daphnia magna: = 0.6 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

No information available

Component	Partition coefficient
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	2.9 - 6.1
Naphthalene (constituent) 91-20-3	3.6
1,2,4-Trimethylbenzene (constituent) 95-63-6	3.63
Xylenes (o-, m-, p- isomers) 1330-20-7	2.77 - 3.15
2-Methylnaphthalene (constituent) 91-57-6	3.86
Ethyl benzene (constituent) 100-41-4	3.2
Cumene (constituent) 98-82-8	3.7

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Waste Disposal Methods**

Contain and dispose of waste according to local regulations.

**Contaminated Packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. TRANSPORT INFORMATION**

**Note:** This information is not intended to convey all specific transportation requirements relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation information can be found in the specific regulations for your mode of transportation. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

**DOT** In the U.S. and Canada, this material may be reclassified as a combustible liquid and is not regulated, via surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/Clear Language Part 1.33].

**UN/ID no.** UN1210  
**Proper Shipping Name** Printing Ink  
**Hazard Class** 3  
**Packing Group** III

**ICAO / IATA / IMDG / IMO**

**UN/ID no.** UN1210  
**Proper Shipping Name** Printing Ink  
**Hazard Class** 3  
**Packing Group** III

## 15. REGULATORY INFORMATION

### International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/downstream user/distributor).

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Naphthalene (constituent)	91-20-3	1 - 5	0.1
1,2,4-Trimethylbenzene (constituent)	95-63-6	1 - 5	1.0
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5	1.0
Ethyl benzene (constituent)	100-41-4	< 1	0.1

#### **Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:.

Component	CAS-No	Weight %
Naphthalene (constituent)	91-20-3	1 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 5
Ethyl benzene (constituent)	100-41-4	< 1
Chlorobenzene	108-90-7	< 0.5
Xylenes (o-, m-, p- isomers) (constituent)	1330-20-7	< 0.5
Cumene (constituent)	98-82-8	< 0.5

### U.S. State Regulations

Component	Massachusetts Right To Know
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X

1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Ethyl benzene (constituent) 100-41-4	X
Cumene (constituent) 98-82-8	X

Component	Minnesota Right To Know
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Ethyl benzene (constituent) 100-41-4	X
Cumene (constituent) 98-82-8	X

Component	New Jersey Right To Know
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
2-Methylnaphthalene (constituent) 91-57-6	X
Ethyl benzene (constituent) 100-41-4	X
Cumene (constituent) 98-82-8	X

Component	Pennsylvania Right To Know
Titanium dioxide 13463-67-7	X
Naphthalene (constituent) 91-20-3	X
1,2,4-Trimethylbenzene (constituent) 95-63-6	X
Xylenes (o-, m-, p- isomers) 1330-20-7	X
Ethyl benzene (constituent) 100-41-4	X
Cumene (constituent) 98-82-8	X

**California Prop. 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Component	California Prop. 65
Titanium dioxide	Carcinogen
Naphthalene (constituent)	Carcinogen
Ethyl benzene (constituent)	Carcinogen
Cumene (constituent)	Carcinogen

- This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

**Canada**

Component	NPRI - National Pollutant Release Inventory
Solvent naphtha, petroleum, heavy aromatic 64742-94-5	Part 5, Other Groups and Mixtures; Part 4 Substance
Solvent naphtha, petroleum, light aromatic 64742-95-6	Part 5, Other Groups and Mixtures
Naphthalene (constituent) 91-20-3	Part 1, Group A Substance; Part 4 Substance
1,2,4-Trimethylbenzene (constituent) 95-63-6	Part 5, Individual Substances; Part 4 Substance
Xylenes (o-, m-, p- isomers) 1330-20-7	Part 5, Isomer Groups; Part 4 Substance
2-Methylnaphthalene (constituent) 91-57-6	Part 4 Substance
Ethyl benzene (constituent) 100-41-4	Part 1, Group A Substance; Part 4 Substance
Cumene (constituent) 98-82-8	Part 1, Group A Substance; Part 4 Substance

## 16. OTHER INFORMATION

<b>HMIS:</b>	<b>Health</b>	<b>Flammability</b>	<b>Reactivity</b>	<b>Personal Protection</b>
	2 *	2	0	X

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Legend - Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value

#### **ACGIH: (American Conference of Governmental Industrial Hygienists)**

- A1 - Known Human Carcinogen
- A2 - Suspected Human Carcinogen
- A3 - Animal Carcinogen

#### **IARC: (International Agency for Research on Cancer)**

- Group 1 - Carcinogenic to Humans
- Group 2A - Probably Carcinogenic to Humans
- Group 2B - Possibly Carcinogenic to Humans

#### **NTP: (National Toxicity Program)**

- Known - Known Carcinogen
- Reasonably Anticipated to be a Human Carcinogen

#### **OSHA: (Occupational Safety & Health Administration)**

- X - Present

**Revision Date** May-15-2019

#### **Pursuant to NOM-018-STPS-2015**

This information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**