

# The Magic is the Media

# A ISO 9001:2008 - ANSI-ISO-ASQ Q9001-2008 Company

#### **SECTION I**

PRODUCT NAME OR NUMBER (as it appears on label)				
Magic® II Composite Blast Media (Type VIII)				
MANUFACTURER'S NAME		EMERGENCY TELEPHONE		
U. S. Technology Media Inc.		<b>NO</b> . (330) 455-1181		
ADDRESS (Number, Street, City and Zip Code)  DATE PREPARED/REVISED				
509 Water ST., Bolivar OH. 44612 – NO. 02/19/2025				
MATERIAL DESCRIPTION, PROPER SHIPPING NAME				
Composite Blast Media				
HAZARD CLASSES (as applicable) N.A.				
CHEMICAL FAMILY Amino Thermoset Plastic FORMULA N.A.				

# SECTION II – INGREDIENTS

(list all ingredients)

CAS REG ISTR Y NO.	Approx. %W	Chemical Name(s)	OSHA PEL	ACGIH TLV	Other Limits Recommended
9003-08-1 9011-05-6 9004-34-6 1318-93-0	>1%	Polymerized Urea-Melamine Formaldehyde Compound w/Alpha Cellulose Filler and Montmorillonite Clay			
25852-37-3	>1%	Acrylate Polymer – Polymerized and Cross-linked Alpha Cellulose Filler			
2764-13-8	<1%	Anti-Static Agent – Cal Stat 600			
5280-80-8 13463-67-7 12769-96-9	<1%	Pigments and Additives			

Material is a blend of thermoset and thermoplastic plastic.

#### **SECTION III - PHYSICAL DATA**

BOILING POINT °F °C	SPECIFIC GRAVITY (H <sub>2</sub> O=1):		
N.A.	1.36 -1.46		
MELTING POINT°F °C -	PERCENT VOLATILE BY	PERCENT SOLID BY	
N.A	VOLUME (%) N.A.	WEIGHT (%) 100	
VAPOR DENSITY (AIR=1) N.A.	EVAPORATION RATE (=1) N.A.		
SOLUBILITY IN WATER: No	<b>pH=</b> 4-8		
<b>APPEARANCE AND ODOR: Mult</b>	MATERIAL FORM: Solid		
odor			

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	ºF	_ °C N.A.		FLAMMABLE: N.A.	LEL: N.A.	UEL: N.A.
EXTINGUISHING	MEDIA:	Carbon dioxide	e, dry chem	icals or water fog		
SPECIAL FIRE FIGHTING PROCEDURES: Do not use high-pressure water stream. Fog nozzles are						
preferable. Water may be used to cool closed containers.						

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Maintain normal good housekeeping for control of dust. High dust concentration could form explosive mixture with air.

#### **SECTION V – HEALTH HAZARD DATA**

EFFECTS OF OVEREXPOSURE – Conditions to avoid:  Mechanical injury to eyes and/or skin can occur.  Excessive dust inhalation may be harmful.	THRESHOLD LIMIT VALUE: PERMISSIBLE EXPOSURE LIMIT:		
PRIMARY ROUTES OF ENTRY: ☑ Inhalation ☑ S	kin Contact		
EMERGENCY AND FIRST AID PROCEDURES: In case of eye or skin irritation, flush with plenty of water			
for 15 minutes. Inhalation – remove to fresh air and contact physician if necessary.			

#### **SECTION VI - REACTIVITY DATA**

STABILITY: ☑ STABLE ☐ UNSTABLE	CONDITIONS TO AVOID: None known		
INCOMPATIBILITY (Materials to avoid): No specific	c incompatibility		
HAZARDOUS DECOMPOSITION or BYPRODUCTS: Smoke, carbon dioxide, carbon monoxide.			
HAZARDOUS POLYMERIZATION:	CONDITIONS TO AVOID: None known		
☑ MAY NOT OCCUR ☐ MAY OCCUR			

#### **SECTION VII – TRANSPORT INFORMATION**

U.S DEPARTMENT OF TRANSPORTATION
PROPER SHIPPING NAME: MAGIC II COMPOSITE ABRASIVE
HAZARD CLASS: NON-HAZARDOUS
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:
WATER TRANSPORTATION
PROPER SHIPPING NAME: MAGIC II COMPOSITE ABRASIVE
HAZARD CLASS: NON-HAZARDOUS
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:
AIR TRANSPORTATION
PROPER SHIPPING NAME: MAGIC II COMPOSITE ABRASIVE
HAZARD CLASS: NON-HAZARDOUS
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:

## **SECTION VIII - SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove open flame, sparks,
hot surfaces and oxidizing agents. Sweep up and place waste in disposal container.
WASTE DISPOSAL METHOD: Sanitary landfill in accordance with Federal, State and Local regulations.
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs.): N.A.
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33): N.A.
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water): N.A.

☐ Theoretical	lbs. /gal.	☐ Analytical	lbs. /gal.	

### **SECTION IX – SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION (Specify Type): Where required, use NIOSH/MSHA approved respiratory			
protection in comp	liance with OSHA regulations (i.e.19	10.134 et. al.).	
VENTILATION	LOCAL EXHAUST (Specify Rate): Where necessary to maintain exposure levels to		
	OSHA permissible levels.		
	MECHANICAL (General - Specify Rate): Acceptable		
	SPECIAL: Explosion proof may be necessary if aerated and airveyed.		
	OTHER: N.A.		
PROTECTIVE GLOVES (Specify Type): Normal			
		goggles	
OTHER PROTECTION EQUIPMENT: Respirator hood, if necessary.			

#### SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in closed, properly labeled containers in cool ventilated area. Keep away from heat, sparks, open flame and oxidizing agents. Do not transfer unmarked containers. **OTHER PRECAUTIONS: None** 

Prepared by:

Name (print): Casey Williams Title: Quality Assurance Manager Date Reviewed: 02/19/2025