

LUMAsite® fiberglass-reinforced acrylic sheets

COLOR	DESCRIPTION	THICKNESSES						
Frost-SOS	"Silken cobweb" effect, high trans.	.045"	.060"	.090"	.125"	.150"	.187"	.250"
Frost-SOS Type FR*	"Silken cobweb" effect, high trans., fire retardant			.090"	.125"		.187"	.250"
Parchment-SOS	Gentle "Shoji" effect, high trans. white			.090"	.125"		.187"	.250"
Linen-SOS	Subtle weave effect, high trans. off-white			.090"	.125"		.187"	
Rice-SOS	Gentle "Shoji" effect, med-high trans. off-white	.060"	.090"	.125"			.187"	.250"
Sky-SOS	Pale blue "Shoji" effect	.060"	.090"	.125"			.187"	.250"
Jade-SOS	Pale green "Shoji" effect	.060"	.090"	.125"			.187"	.250"
Tangerine-SOS	Orange "Shoji" effect	.060"	.090"	.125"				
Whisper River-SOS	Blue mesh tint, "Shoji" effect				.125"			
Whisper Hunter-SOS	Green mesh tint, "Shoji" effect				.125"			
Whisper Eggplant-SOS	Purple mesh tint, "Shoji" effect				.125"			
Whisper Copper-SOS	Peach mesh tint, "Shoji" effect				.125"			
White 1000-SOS	High diffusion, opalescent	.045"	.060"	.090"	.125"	.150"	.187"	.250"
White 1000-SOS Type FR*	High diffusion, opalescent, fire retardant			.090"	.125"		.187"	.250"
White 1020	Sign white, translucent			.090"	.125"	.150"		
White 2020	Display white, translucent	.045"	.060"					
White 1040	Porcelain white, opaque	.060"	.090"	.125"			.187"	.250"
White 1040-POS	Opaque white, pebbled one side			.090"	.125"			
Ivory 02146-SOS	Creamy white, translucent	.060"	.090"	.125"				
Yellow 02037	Bright yellow, translucent	.060"	.090"	.125"				
Orange 02119	Bright orange, translucent			.090"	.125"			
Red 315	Fire-engine red, translucent	.060"	.090"	.125"				
Blue 02051	Medium blue, translucent			.090"	.125"			
Brown 240-SOS	Chocolate brown, opaque			.090"	.125"			
Brown 239-SOS	Dark brown, opaque			.090"	.125"			
Black 02025	Black, opaque			.090"	.125"			
Hi-Lite Red	Efficient diffuser (for EXIT)	.040"	.060"					
Lite Emerald	Efficient diffuser (for EXIT)	.040"	.060"					
SOS indicates matte finish on one side POS indicates lightly pebbled texture one side								

*Type FR sheets exhibit burning characteristics meeting a Class C rating per NFPA 255.

LUMAsite® acrylic-modified fiberglass sheets:

COLOR	DESCRIPTION	THICKNESSES		
Crystal II	Near-clear	.060"	.090"	.125"
Crystal II-SOS	Lightly frosted	.060"	.090"	.125"
Crystal II-POS	Diffused, pebbled one side	.060"	.090"	.125"
Coco Reed	Brown cane-like embedment			.125"
Diamond Design	Metal embedment (large diamond opening)			.125"
SOS indicates matte finish on one side POS indicates lightly pebbled texture one side				