



OLD WESTERN PAINT CO., INC
2001 West Barberry Place
Denver, Colorado 80204

Phone: 303-825-5147/888-765-9827

Fax: 303-825-2437

www.oldwesternpaint.com

PRODUCT INFORMATION
ACRALO EXTERIOR SATIN LATEX ENAMEL

1088 530 WHITE

TYPE: 100% Acrylic Latex

DESCRIPTION: ACRALO is an acrylic exterior latex with a velvet sheen that has excellent adhesion and moisture resistance. ACRALO can be used as the prime coat on bare exterior wood surfaces and top coated with itself. Provides a long lasting coating with excellent crack resistance. May be tinted to desired color using universal colorants and proper bases.

CLEAN UP: Clean all equipment immediately after use with warm water or mild soap and water.

APPLICATION: Stir thoroughly before use. Apply by roller, brush or spray. Apply at temperatures above 50°F and to dry surface. Surface should be clean and free from dust, dirt, grease and peeling paint. Dull all glossy surfaces by sanding before painting. All nail holes should be caulked and primed with exterior primer before painting. All bare metal should be primed with proper primer before painting.

SPREADING RATE: Theoretical coverage 300-350 square feet per gallon, subject to surface porosity, texture and application method. For best results, always apply at recommended coverage rate.

DRYING TIME: Dries in 1-2 hours (dust free), recoat 4-6 hours. Excessive humidity, low temperature, failure of air movement and thickness of finish may affect drying time.

ANALYSIS: +2%

PIGMENT	40.00%
VEHICLE	<u>60.00%</u>
TOTAL	100.00%

PIGMENT	
Titanium Dioxide	49.00%
Selected Extenders	<u>51.00%</u>
Total	100.00%

Acrylic Resin	57.00%
Volatile, Surfactants	<u>43.00%</u>
Total	100.00%

VOC content: 122 grams/Liter

Solids by weight: 58.00%

Features:

- ❖ Superior Quality
- ❖ LOW VOC
- ❖ LOW Odor
- ❖ Self-priming
- ❖ Formulated for maximum durability
In harsh Colorado climate
- ❖ Made in the U.S.A.

LIMITED WARRANTY if used as directed, including proper application and surface preparation in accordance with label directions, this product is warranted to be free from defect when used for its intended application for a period of one year from the date of purchase. This limited warranty does not apply if the product is mixed with any other ingredient. Buyer assumes all risks of handling. Buyer's sole and exclusive remedy with respect to any defective product is replacement of product or refund of the purchase price, at Manufacturer's sole option and only after receipt of proof of purchase. THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND DESIGN. IN NO EVENT SHALL MANUFACTURER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LABOR COST. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.