

Polyhard Type III

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
 Revision date: 06/06/2018 Supersedes: not applicable Version: 1.0

SECTION 1: Identification of the substance/mixture

Product Identifier

Product form: Plastic Abrasive

Substance name: PolyhardPlastic Blast Abrasive (Type III)

CAS No.: 9003-08-1

Formula: C3H6N6

Synonyms: Melamine Polymer

Intended Use Of The Product

Use of the substance/mixture: Depainting

Name, Address, And Telephone Of The Responsible Party

US Technology Media Inc.
 509 Water ST., Bolivar OH. 44612
 330-455-1181

Emergency telephone number

Emergency number : 330-874-3094

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call US TECHNOLOGY – Day or Night

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Eye Irrit. 2A H319



Label elements GHS-US labeling

Hazard statements (GHS-US) : H319 - Abrasive Dust irritant: Causes serious eye irritation

Precautionary statements (GHS-US) : P280 - Wear PPE - Dust mask and eye protection.

SECTION 3: Composition/information on ingredients

Substances

Name	Product Identifier	%	GHS-US classification
Polymerized Melamine Molding Compound	(CAS No.)9003-08-1	98%	Amino Thermoset Molded Plastic
Anti-Static Agent – Cal Stat 600	2764-13-8	>1%	Amino Thermoset Molded Plastic
Pigments and Additives	5280-80-8 13463-67-7 12769-96-9	<2%	Amino Thermoset Molded Plastic

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general: If material is airborne, remove person from exposure.

First-aid measures after inhalation: Go to well ventilated area, keep in a position for comfortable breathing, call Physician if symptoms persist.

First-aid measures after skin contact: Flush skin with water and soap.

First-aid measures after eye contact: Rinse cautiously for several minutes with water, remove contact lenses, if possible.

First-aid measures after ingestion: Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries: Eye irritation.

Polyhard Type III

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after skin contact: Skin rash.

Symptoms/injuries after eye contact: Causes serious eye irritation.

Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media: Alcohol foam, water, carbon dioxide, dry chemical.

Unsuitable extinguishing media: None.

Special hazards arising from the substance or mixture

Fire hazard: Highly flammable liquid and vapor.

Explosion hazard: Flame will form toxic vapors; avoid inhalation of smoke or vapors.

Advice for firefighters

Firefighting instructions: Exercise caution when fighting any chemical fire.

Protection during firefighting: Firefighters should wear full protective gear with independent breathing air.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid breathing. Use only in a well-ventilated area. Handle in accordance with good industrial hygiene and safety practice.

For non-emergency personnel

Protective equipment: Use appropriate personal protection equipment (PPE).

Emergency procedures: Evacuate unnecessary personnel.

For emergency responders

Protective equipment: Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

Emergency procedures: Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters.

Methods and material for containment and cleaning up

For containment: Contain spill, then place in suitable container. Sweep or vacuum.

Methods for cleaning up: Clear up spills immediately and dispose of waste safely.

Reference to other sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed: None.

Precautions for safe handling: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid breathing. Use only in a well-ventilated area. Wear recommended personal protective equipment.

Hygiene measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for safe storage, including any incompatibilities

Technical measures: None.

Storage conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible products: Strong acids. Strong bases. Strong oxidizers.

Incompatible materials: Heat sources.

Storage area: Keep in dry place.

Special rules on packaging: None.

Specific end use(s): Filler.

Polyhard Type III

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

Control parameters

Polymerized Melamine (CAS No.) 9003-08-1	
USA ACGIH	ACGIH TWA (ppm)
USA ACGIH	ACGIH STEL (ppm)
USA OSHA	OSHA PEL (TWA) (mg/m3)
USA OSHA	OSHA PEL (TWA) (ppm)

Exposure controls

Appropriate engineering controls : Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Insufficient ventilation: wear respiratory protection. Protective goggles. Gloves.

Hand protection : Wear protective gloves.

Eye protection : Safety glasses.

Skin and body protection : Wear Long Sleeve Shirt.

Respiratory protection : If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Thermal hazard protection : Wear suitable protective clothing.

Other information : When using, do not eat, drink or smoke.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Dry powder
Appearance : Grey powder
Color : Grey
Odor : None
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : 500 °F
Freezing point : No data available
Boiling point : Not applicable
Flash Point : 390° F
Auto-ignition temperature : No data available
Decomposition Temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : Not applicable.
Relative vapor density at 20 °C : No data available
Relative density : No data available
Density : No data available
Solubility : Insolvable
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : Not applicable

Other information: No additional information available

Polyhard Type III

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

Reactivity Non-reactive.

Chemical Stability Stable under recommended handling and storage conditions (see section 7).

Possibility Of Hazardous Reactions Non-reactive.

Conditions To Avoid Avoid ignition sources. Heat. Sparks. Open flame.

Extremely high or low temperatures. Incompatible Materials Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products Carbon oxides (CO, CO₂). May release flammable and toxic gases.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : Not classified

Polymerized Melamine (CAS No.) 9003-08-1	
LD50 oral rat	No Data Available
LD50 dermal rabbit	No Data Available
LC50 inhalation rat (mg/l)	No Data Available

Skin corrosion/irritation: Not Applicable

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitisation: Not Applicable

Germ cell mutagenicity: Not Applicable

Carcinogenicity: Not Applicable

Reproductive toxicity: Not Applicable

Specific target organ toxicity (single exposure): Not Applicable

Specific target organ toxicity (repeated exposure): Not Applicable

Aspiration hazard: Not Applicable

Symptoms/injuries after inhalation: Causes coughing.

Symptoms/injuries after eye contact: Causes serious eye irritation.

Symptoms/injuries after ingestion: Ingestion may cause nausea, vomiting.

SECTION 12: Ecological information

Toxicity

Polymerized Melamine (CAS No.) 9003-08-1	
LC50 fishes 1	No Data Available
EC50 Daphnia 1	No Data Available
LC50 fish 2	No Data Available
EC50 Daphnia 2	No Data Available

Persistence and degradability

Polymerized Melamine (CAS No.) 9003-08-1	
Persistence and degradability	Not

Bioaccumulative potential

Polymerized Urea (CAS No.) 9004-34-6	
BCF fish 1	No Data Available
Log Kow	No Data Available
Bioaccumulative potential	Not established

Mobility in soil

No additional information available

Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

Regional legislation (waste): U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing – 40 CFR261.2

Characteristic solid hazardous waste for Cd if in excess of 1 ppm, Cr if in excess of 5 ppm, or Pb is in excess of 5 ppm.

Polyhard Type III

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ICAO/IATA/DOT/TDG

UN number : Not Applicable
UN-No.(DOT) : Not applicable
DOT NA no. Not applicable

DOT Packaging Exceptions (49 CFR 173.xxx) : No Limitation

DOT Packaging Non Bulk (49 CFR 173.xxx) : No Limitation

DOT Packaging Bulk (49 CFR 173.xxx) : No Limitation

Additional information

Emergency Response Guide (ERG) Number : No Limitation

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : Below deck

MFAG-No. : Not applicable

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Not applicable

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : Not applicable

SECTION 15: Regulatory information

US Federal regulations

RCRA – Disposal per 40CFR 261.2

Not Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State regulations

State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
-----------------------------------	---

Polyhard Type III

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Indication of changes : 11/13/2015

Other information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Eye Irrit. 1	Mild eye damage/eye irritation Category 1
H319	Causes serious eye irritation

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 0 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 0 Minimal Hazard

Physical : 0 Minimal Hazard

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom) - US Only