

Discover...

Key Banner™

Mesh

- 9 oz
- Roll widths 54" - 98" with liner
- Roll widths 126" - 196" without liner
- 1000 x 1000 denier
- Fire retardant, meets NFPA 701
- 12 x 12 scrim
- Indoor and outdoor use
- Used for building wraps, billboards, and wall hanging banners
- Printable with solvent and UV inks

Properties	Test Method	Unit	Result
Transmittance	ASTM E 424 6.5.2	%	43.1
Tensile Strength	ISO 13934-1:1999, C.R.E. Cut Strip Method	KGF/5CM	L: 202.6 W: 179.6
Tearing Strength	ISO 13937-2:2000, C.R.E. Single Tear Method	KGF	L: 23.8 W: 33.3
Elongation	ISO 13934-2:1999, C.R.E. Cut Strip Method	%	L: 27.0 W: 23.7
Adhesion Strength	ISO 2411. C.R.E.	KGF/5CM	L: 13.8 W: 17.3
Flexing Endurance at Low Temp	DIN53351	Cycles	340
Resistance to Low Temp	DIN53351		No Change
Resistance to High Temp	DIN53351		No Change
Resistance to Weathering	ASTM G26, Xenon ARClamp, 18 min Spray/2 hrs, 100 hrs. exposure		No Change
Color Fastness to Weathering	ASTM G26, Method A, Type B	Grade	4.5
Fire Retardant	Fire Test NFPA 701		Approved

Part#	Size	Liner
BMML5435W9	54" x 115'	Yes
BMML6335W9	63" x 115'	Yes
BMML8750W9	87" x 164'	Yes
BMML9850W9	98" x 164'	Yes
BMM12650W9	126" x 164'	No
BMM19650W9	196" x 164'	No



unlock the possibilities

800.542.9941 • www.grimco.com