



ARO-2500 Multi-Stage Oil Mist Collector

Multi-Stage

Progressive
Separation

Depth Filters

Reduced
potential of
plugging

Cross Flow Design

Fluid quickly
drains back to
sump

Long filter life

Low operating
costs

Low
maintenance

Clean air

For large size machine tools and central systems!

The ARO multi-stage oil mist collectors separate mist in progressive stages reducing the potential of plugging.

Filters are depth loading and designed to drain, suitable for 24/7 operation. Cross-flow filter design, air flow is horizontal, oil drains vertical down.

Ideal for high pressure coolant and oil.

Removes mist, smoke and bacteria.

Unique 1st and 2nd separation stages.

Optional On-Line Cleaning system

Separation Stages:

The innovative 1st stage `ME` Mechanical Element separates up to 90% of the oil mist and swarf. The smooth metal surfaces quickly drains fluid back to the sump.

The 2nd stage `AG` Agglomerator filter is very unique, manufactured in layers of stainless steel wire mesh weaved with oil attracting fibers. Efficiency is high as the air travels through a bed of coarse and fine fibers at low velocity. The AG media is very durable, lasting 10 – 15 years. Can be washed.

Used only for coolant applications.

The 3rd stage `CM` Coolant Mist filter is depth loading fiber bed filter that capture small mist particles. Typical life 1 – 3 years.

For oil applications, 2nd+3rd stage `OM` Oil Mist pack is an unique two stage depth loading fiber bed filter. The `OM` can be supplied in 3 efficiencies. Typical life 1 – 3 years.

Final 4th stage `HF` HEPA filter captures sub-micron mist, smoke and bacteria. Efficiency 95% @ 0.3 µm is standard, optional 99.9% @ 0.3 µm.

Typical life 2 – 4 years

HEPA filter is made with exclusive heavy duty filter media, no other product holds as much or lasts as long.

Specification:

Air Flow	2300 – 2700 cfm
Machine tool enclosure	Up to 1500 ft ³
Filter Pressure, Max	3.5" wg
Motor	5 hp
Voltage (amps)	230/3/60 (11.5) 460/3/60 (5.8) 575/3/60 (4.6)
Temperature (max)	160°F / 70°
Weight	605 lbs
Length	55"
Width	25"
Height	50"
Inlet connection	12" Ø
Sound	74 dB(A)
Clean air measurement	HEPA filter 95% < 0.050 mg/m ³ HEPA filter 99.9% < 0.010 mg/m ³

Options:

Coolant or Oil filters	Installation Kit	Motor starter
HEPA filter 95% or 99.9% @0.3 µm	Pillar stand	VFD motor starter
Right or left hand air flow	Wall mount	On-Line Cleaning system
	Portable unit	





ARO Filter Stages

Multi-Stage

*Progressive
Separation*

Depth Filters

*Reduced
potential of
plugging*

Cross Flow Design

*Fluid quickly
drains back to
sump*

Long filter life


*Low operating
costs*

*Low
maintenance*

Clean air

Coolant Filter Stages

- 1 ME Mechanical Elements
- 2 AF Agglomerator Filter
- 3...CM Coolant Filter
- 4...HF HEPA Filter



Oil Filtration Stages

- 1 ME Mechanical Elements
- 2+3...OM Oil Mist Pack
- 4...HF HEPA Filter

