



ATX GRIP TITAN LT Remote Stabilized Head

Austin Office:
9201 Brown Ln Suite 290
Austin, Tx 78754
Austin Office Phone:
512-537-4201
832-651-3053
Austin Office Email:
Rentals@atxgrip.com

**3 Axis Gyro Stabilization
(Pan, Tilt, Roll)**

48v Slotless Motors

Fiber Optic Gyro

**Wireless Control (Up To 1.8 Miles)
Titan Controller (Joystick, Single or Dual)
3 Axis Handwheels**

Shaky Cam Setting Available For All Controls

Construction: 6061-T6 Aluminum chassis

**Maximum operational speed: 130+mph
Max motor torque: 10Nm
Max pan speed: 360°/sec
Maximum Payload Capacity: 40lbs/ 18kg
70lbs/32kg recommended for dynamic tracking
Dry Weight: 18lbs/ 8.2kg
Weather rating: IP65 (water resistant)
Temperature rating: -30°F - 120°F
Gimbal Mounting: Mitchell mount adapter, LT quick disconnect
Payload mounting: DJI R2 Dovetail/Baseplate
Camera build volume: 270mm (L) x 225mm (W) x 236mm* (H)
*286mm height with 50mm Cage Extension accessory
System Voltage: 48V (42-52VDC)
Comms: CAN-BUS, hardwired + 2.4Ghz wireless**

Long range radio: 900Mhz/868mhz for EU

Power output: 3x 14.4V Dtap (125W) + 1x 24V 3-Pin XLR (125W), 250W combined

Lens Driver: 3-channel, digital 7-pin LEMO

TITAN LT holds strong in any setting. Underslung, Overslung, on Blackarm, Fixed Arm Jibs, Technocrane, Hydrascope, Scorio, MovieBird, Camera Car's, Electric Tracking Vehicle's, Dolly, Slider, MOCO. .











