TSA72

- 50GHz SOLUTIONS
- SUPER LOW LOSS
- HIGH SHIELDING
- KINK RESISTANT
- EASY-TIGHT COUPLING



TESTeLINK RF Cables

Professional High Frequency RF Test Cables.

2.4mm, 2.92mm(K), and 3.5mm Interfaces.

Key Features;

- Quick Finger Tight Coupling
- Kink Resistant Cable Construction
- Super Low Attn <1.04db/ft @ 50GHz
- Low VSWR < 1.20:1 (Max ≤ 1.40:1)
- RF Leakage ≤-100dB to 18GHz
- High Power 55W @ 50GHz

Configuration Chart

TSA72-D1D1-S18

TSA72-YYZZ-YYY

YYZZ = Connector Options
2.4mm Male (50GHz) = C1
2.4mm Female (50GHz) = CF
2.92mm Male (40GHz) = D1
2.92mm Female (40GHz) = DF
3.5mm Male (32GHz) = E1
3.5mm Female (32GHz) = EF

YYY = Length Options
FYY = Length in Feet(F06 = 6ft)
SYY = Length in Inches(S18 = 18")
YMY = Length in Meters(2M5 = 2.5m)
CYY = Length in Centimeters(C30 = 30cm)

Sales@ConductRF.com - Tel: +1 978 374 6840 - www.ConductRF.com