



### Technical Specifications

Transmitter type:	Crystal controlled 2-stage
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to 40°C
Pulse rate and width:	Typical on time 15ms, off time 1.5-4.0sec (controlled by astable circuit)
Pulse rate variation:	5%/volt, ± 20% for temperatures -20°C to +40°C
Battery:	Silver Oxide
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12

MODEL	BATTERY	BATTERY CAPACITY (days)				DIMENSIONS (mm)					WEIGHT (grams)	PRICE GROUP
		15 ppm	24 ppm	30 ppm	40 ppm	A	B	C	D	E		
	1.5V											
A2412	410	22	15	12	9	5	12	1.5	2.5	4	0.20	F
A2414	337	45	30	24	18	5	12	3	2.5	4	0.30	C
A2415	337	45	30	24	18	5	13	3	4	5	0.50	A
A2426	317	68	45	36	28	6	14	3	4	5	0.65	A
A2435	319	90	60	48	37	6	14	4	4	5	0.75	A
A2445	377	135	89	72	55	7	15	4	4	5	0.90	A
A2455	392	216	143	116	88	8	16	5	4	5	1.20	A

Above models available only in 48.00-50.66MHz, 144.06-151.98MHz, and 164.00-167.99MHz ranges.

Warranty life is 50% of battery capacity.

470 First Ave. No., Box 398 • Isanti, MN 55040  
763.444.9267 • fax:763.444.9384 • sales@atstrack.com • www.atstrack.com