

REFRIGERATION SPECIALTIES CONTROL VALVES
AMMONIA GAS POWERED SUCTION STOP VALVES

TYPES CK2, S9A, S9F, AND S9W

**Gas Powered Suction Stop Valves
 CK-2 and S9A**

Type	Port Size		Flange Styles and Sizes			
			Connections Available Sizes in Inches			
			FPT, SW, WN		ODS	
mm	inch	St'd	Also Avail.	St'd	Also Avail.	
CK2	32	1 1/4	1 1/4	1 1/2	1 3/8	1 5/8, 2 1/8
CK2A	40	1 5/8	1 1/2	2	1 5/8	2 1/8, 2 5/8
CK2	50	2	2	1 1/2	2 1/8	2 5/8
S9A	50	2	2	1 1/2	2 1/8	2 5/8
CK2	65	2 1/2	2 1/2		2 5/8	3 1/8
S9A	65	2 1/2	2 1/2		2 5/8	3 1/8
CK2	75	3	3		3 1/8	3 5/8
S9A	75	3	3		3 1/8	3 5/8
CK2	100	4	4		4 1/8	
S9A	100	4	4		4 1/8	
CK2	125	5	5*			N.A.
CK2	150	6	6*			N.A.

PLEASE NOTE THAT A VARIETY OF CONNECTIONS ARE AVAILABLE FOR MOST SIZES, (SEE CHART) THEREFORE, BE CAREFUL TO DETERMINE VALVE SIZE AS WELL AS PIPE SIZE.



Normally open.
 Gas pressure
 to close

TYPE CK2 1-1/4" - 6"
 COLOR, BLUE



Flange Union
 with Disc Strainer

Normally closed.
 Gas pressure
 to open

TYPE S9A 2" - 3"
 TYPE S9F 4" - 8"
 COLOR, BLUE



Type S9W

TYPE S9W 5" - 8" WELDED
 COLOR, BLUE (60° ANGLE)

NOTE: CK-2 ARE COMMONLY CALLED GAS POWERED CHECK VALVES.