



Foam Max
THICK FOAMING VEHICLE WASH
PRODUCT NO.: WH-310-HF

- Thick lather foam when using air injection
- Biodegradable
- Non-corrosive
- Economical dilutions
- Harmless to paint surfaces and vinyl tops
- Alkylphenol Ethoxylate (APE) Free

WH-310-HF Foam Max produces a thick lather foam when used with air injection systems in coin operated washes or auto wash salons. This product has excellent surface wetting agents and provides superior brush lubricity to protect paint surfaces. Foam Max is harmless to all paint surfaces and vinyl tops.

Applications & Uses	Directions
Automatic Car Wash Systems	Premix 5 gallons of MegaFoam in a 55 gallon drum and fill with water. Inject into your spray system at desired amount for good foam height. Normally 10 to 12 ounces per wash. Air Injection will enhance foaming.
Hand Wash Operations	Dilute 1 to 2 ounces per 1 gallon of water for good foaming lather. As with all cleaners, rinse thoroughly.
For Best Results, apply WH-380 C-Shine Rinse Agent with Carnauba Wax in the rinse cycle.	

Suggested Industry Applications:

Automotive
Dealerships
Fleet Operations
Highway Maintenance

Quick-Lube Facilities
Service Stations
Truck Dealerships

Auto Salon Washes
Coin Operated Washes
Tunnel Washes

Specifications:

Appearance	Fuchsia (pink) color
Odor	Detergent
pH	9-10
Flashpoint	None
%VOC	<4%
DOT Label	None

General Cautions For Use:

As with all cleaning agents, keep this product out of the reach of children. Dilutions are recommendations only, as you become familiar with the product's performance, adjust accordingly.

Container Sizes:

5 Gallon Pail
55 Gallon Drum
275 Gallon Totes Available Upon Request