

# FOUR WHEEL SERIES

## 4 GPM MODELS • 158' COIL

| MODEL  | 418X4                                     | 423X4                                     | 430X4                                     |
|--|---|---|---|
| <b>Capacity</b>  | 4.0 GPM                                   | 3.7 GPM                                   | 3.8 GPM                                   |
| <b>Pressure</b>  | 1800 PSI                                  | 2300 PSI                                  | 3000 PSI                                  |
| <b>Pump</b>  | Triplex, Oil Bath, Belt Drive             | Triplex, Oil Bath, Belt Drive             | Triplex, Oil Bath, Belt Drive             |
| <b>Motor/Voltage Fuse For</b>                                      | 5 HP, 230 V, 1 PH, Fuse for 30 Amp.       | 6 HP, 230 V, 1 PH, Fuse for 30 Amp.       | 8 HP, 230 V, 1 PH, Fuse for 40 Amp.       |
| <b>Coil (Steel Pipe) Cold Water Wrap, Spiral Heating Section</b>   | 158', Schedule 40                         | 158', Schedule 80                         | 158', Schedule 80                         |
| <b>Burner, Pressure Atomizing, Auto Ignition, Fuel Consumption</b> | Kero, or #1 Diesel, 385,000 BTU, 2.75 GPH | Kero, or #1 Diesel, 385,000 BTU, 2.75 GPH | Kero, or #1 Diesel, 385,000 BTU, 2.75 GPH |
| <b>Fuel Tank</b>   | Plastic, 8 Gal.                           | Plastic, 8 Gal.                           | Plastic, 8 Gal.                           |
| <b>Stack Size</b>  | 8"  | 8"  | 8"  |
| <b>Temp. Control</b>   | Optional                                  | Optional                                  | Optional                                  |
| <b>Chemical</b>  | Precise Metered                           | Precise Metered                           | Precise Metered                           |
| <b>Float Tank</b>  | Stainless Steel                           | Stainless Steel                           | Stainless Steel                           |
| <b>Steam Capacity (Optional)</b>                                   | 120 GPH                                   | 120 GPH                                   | 120 GPH                                   |
| <b>Dimensions</b>  | L - 54"<br>W - 32"<br>H - 49"             | L - 54"<br>W - 32"<br>H - 49"             | L - 54"<br>W - 32"<br>H - 49"             |
| <b>Shipping Weight</b>   | 615 lbs.                                  | 665 lbs.                                  | 685 lbs.                                  |



**Optional: Available UL or CSA approved**

**Xtreme models same specifications plus:**

- Schedule 80 coil • Stainless steel wrapper (X4X Models)
- Fuel solenoid • High-limit temperature control



|                        |                            |                    |   |
|------------------------|----------------------------|--------------------|---|
| LOCAL:<br>605.934.2222 | TOLL FREE:<br>800.255.6823 | WEB:<br>ALKOTA.COM | 105 Broad Street Alcester, South Dakota 57001 USA |
|------------------------|----------------------------|--------------------|---|