


# VIBRATION MANAGEMENT CORPORATION

5930 THOMAS ROAD , HOUSTON , TEXAS 77041 , U.S.A

INTERNET ADDRESS: [www.vimco.biz](http://www.vimco.biz)



MODEL	SIZE (inches)
3RFP 181801	18" x 18" x 1"
3RFP 121201	12" x 12" x 1"
3RFP 080801	8" x 8" x 1"
3RFP 060601	6" x 6" x 1"
3RFP 040401	4" x 4" x 1"
3RFP 030301	3" x 3" x 1"
3RFP 020201	2" x 2" x 1"
3RFP 181802	18" x 18" x 2"
3RFP 121202	12" x 12" x 2"
3RFP 080802	8" x 8" x 2"
3RFP 060602	6" x 6" x 2"
3RFP 040402	4" x 4" x 2"
3RFP 030302	3" x 3" x 2"
3RFP 020202	2" x 2" x 2"
3RFP SSSSSS	SPECIAL (contact factory)

## APPLICATION

- \* Wherever bolting is to be avoided and non-critical vibration conditions exist. (pumps, motors, airconditioning units, generators etc.)
- \* Recommended for acoustic problem applications.
- \* Suitable for outdoor use

## NOTES

1. Material: Closed cell, chemically cross-linked high density rubber foam (with lower density center core).
2. Maximum loading: 70 lbs/sq.in.
3. Working range: 15 to 60 lbs/sq.in.

## FEATURES

- \* Higher deflection than conventional rubber-cork and all rubber pads.
- \* Closed cell construction with excellent sound attenuation capability
- \* No bolting required, simple field installation.
- \* Free from sulphur, halogens, formaldehydes, phthalates and other toxins.
- \* Excellent resistance to oil, water and ozone (recommended for outdoor use)
- \* Lifetime warranty against core separation.
- \* 100% surface contact with equipment.



Notes / Remarks :

Project :  
Client :  
Consultant :  
Representative :

Title :

**3RFP**  
**Green Triple-Core™**  
**Rubber Foam Pad**

Drawing no.  
**S-2200.51**

Rev. 1