



Xtreme Hard™ Densifier

Technical Data/Spec Sheet

Concrete Finishes Section 3300, 3600

Angela L. Hensley
www.XtremeHardDensifier.com
Toll free – 1-888-203-6791
Cell – 540-226-9336
AngelaHensley@XtremeHardDensifier.com

Product Description

Xtreme Hard Densifier is a blend of inorganic polymer materials that penetrates slab concrete to increase surface density and hardness. Utilizing a proprietary and “green” manufacturing process, Xtreme Hard Densifier’s unique formulation of uniform, concentrated, nano-sized particles, suspended in an ultra low surface tension liquid, penetrates deeply into concrete surfaces bonding with the cement components of the slab. Xtreme Hard Densifier makes an extremely hard, dense floor surface that has increased wear resistance to foot and fork lift traffic. It is water based and environmentally friendly and is VOC compliant in all states.

Primary Applications

- Interior or exterior concrete
- Warehouses/Distribution center floors
- Manufacturing plants
- Medical and Research
- Residential garages and floors
- Commercial floors

Features/Benefits

- Fills porosity/capillaries of concrete creating a permanent bond that makes floors and walls harder, less prone to dusting and absorption of most liquids.
- Meets all VOC regulations including California.
- Meets LEED qualifying standards.
- Resists penetration of many liquids including oils and many chemicals.
- Helps minimize many rubber tire marks in warehouse applications.
- Application equipment may be cleaned with water.
- Will not discolor or blush over time.
- Not affected by bond breaker systems when used as directed.
- Will not leave a white cast on floor if over used or not removed.
- Reduces operating costs by increased ease of maintenance and cleaning.



Performance Advantages

- Lower pH improves reactivity and stability of materials.
- Low viscosity and smaller molecular size provides deeper and more complete penetration.
- Will not peel.
- Reduces dusting.
- Can be applied to newly trowel green slabs.

Packaging

5 gallon pails (19L)

55 gallon drums (209L)

Technical Information

| | |
|------------------------------|--|
| Drying Time | 20 min to 1 hour |
| VOC Content | 0 g/l |
| Total Solids | 18% |
| Active Ingredients | 100% of total solids |
| pH | 9 |
| Freeze point | 32°F |
| Slip Resistance | Does not change floor friction coefficient |
| Shelf Life | 1 year |
| Coverage | 500sf/gal |
| Density | Makes it 6-10 times more wear resistant |
| Depth of Surface Penetration | 4-10mm |

Application/Directions

Xtreme Hard Densifier has two primary methods of application. The first method is designed for application while the slab is still green just after final trowel. The second is designed for use with existing or cured concrete.

New Concrete (Green)

Xtreme Hard Densifier may be applied to newly installed concrete after final trowel while slab is still green. Slab must be clean and free of all materials such as curing compounds, bond breakers, form release oils or construction dust and debris, etc. Dilute 6 gallons of water to one gallon of Xtreme Hard concentrate. Use a low pressure sprayer to achieve a consistent, even application and to ensure consistent coverage of the surface. Re-apply as necessary to keep surface wet for 20 minutes. Let surface dry. No cleaning, flooding, neutralizing or rinsing is necessary. If curing agent is to be applied, it can now be applied over dried application of Xtreme Hard Densifier.



Existing, Cured Concrete

Xtreme Hard Densifier can be applied to concrete of any age. Surface must be clean and structurally sound. Surface also must be clear of membrane forming curing compounds, sealers, oils, dust and other surface contaminants. For best results use a black scrubbing pad with Xtreme Hard Cleaner. If more aggressive surface preparation is needed to remove surface contaminants, 60-100 grit sanding screens can be used. A thorough cleaning is needed after additional scrubbing

Diamond grinding/ polishing to an 800 grit finish with Xtreme Hard Densifier, will provide the most durable and stain resistant floor surface.

Dilute 4 gallons of water to 1 gallon of Xtreme Hard concentrate solution. Use a low pressure sprayer to apply Xtreme Hard Densifier to form an even sheen across surface to ensure complete saturation of surface. Apply enough Xtreme Hard to keep the surface wet for 15 to 20 minutes. Let surface dry 1 hour before heavy traffic.

Clean-Up

Clean tools and equipment with water immediately after use. Residue from application and clean-up is non-toxic. Protect metals, glass, wood, paint or brick from contact with Xtreme Hard Densifier. If surface is accidentally over sprayed, wash immediately with potable water.

Maintenance

Routine sweeping, mopping and periodic mechanical scrubbing with a neutral pH, non-rinsing cleaner or water is needed. We recommend using Xtreme Hard Cleaner for all cleaning regimes.

Avoid any acidic cleaners. Acidic cleaners may etch the surface over time and cause a dulling of the finish. No aggressive scrubbing brushes such as stragrit, nylogrit or other aggressive scrubbing brush should be used. Avoid detergents containing hydroxides or sulfates.

Warranty:

When applied as directed, Xtreme Hard Densifier will reduce abrasion and wear to the surface of the concrete. Regular sweeping and cleaning of the concrete surface with Xtreme Hard Cleaner will maintain its performance and increase longevity. If applied by a certified applicator, Xtreme Hard Densifier is warranted to penetrate and chemically strengthen the surface of concrete to reduce dusting for 25 years.

This warranty does not cover incidental or consequential damages nor does it cover failure of mix design, penetrating curing compounds, cracking or conditions that are a result of poor concrete finishing. Damage from faulty maintenance procedures or accidental damage to the slab is not covered.

www.XtremeHardDensifier.com