

59100**MATERIAL SAFETY DATA SHEET****Identity:** RADNOR® LENS CLEAN**Company Product Code:** 64051441, 64051442, 64051433, 64051434, 64051435, 64051436, 64051438, 64051439,**Document Number:** 004040**Sizes:** 3.8L (128 fl. oz.), 473 ml (16 fl. oz.), 103 ml (3.5 fl. oz.), 59 ml (2 fl. oz.)**Product Use:** Lens Cleaner**Supplier:** H. L. Bouton Co.
11 Kendrick Rd.
Wareham, Ma. 02571**Information Phone** 1-800-426-1881 (business hours)
Fax 1-508-295-3521**Emergency Phone** 1-800-268-9017 (Poison Information Center)**Date Prepared** March 25, 2006**Prepared by** H. L. Bouton Co.**Section II Material Identification and Information**

Components (Chemical Names & Common Names) (Hazardous Components 1 % or greater, Carcinogens 0.1% or greater)	CAS #'s	%	OSHA	ACGIH	OTHER
Isopropanol	67-63-0	10			
Sodium Dodecyl Sulphate	151-21-3	2.5			
Hydrogen Hydroxide	7732-18-5	87.5			
Pylaklor Turquoise Blue S-400	N/A mixture	.0036			

Section III Physical / Chemical Characteristics

Physical State: Liquid	Specific Gravity (H ₂ O=1) 1.00
PH Factor: N/A	Freezing point: -6°C (21°F)
Boiling Point: 93°C (200°F)	Melting Point: -6°C (21°F)
Vapor Pressure 20 mmHg at 20°(68°F)	Evaporation Rate: 0.99
Vapor Density 1	Water Reactive: None
Solubility in Water: 100%	Specific Gravity (Relative Density): 0.98
Percent Volatile: 10%	

Appearance and Odor: Clear blue solution. Slight alcoholic odor**Section IV Fire and Explosion Data**

Flash Point (Method Used): 82° C (180°F)	Auto-Ignition Temperature: N/A
Flammability Classification (29 CFR 1910.1200): Combustible Liquid	
Flammability Limits in Air Lower: 2.5-12.0 (Isopropanol)	LEL: N/A
Autoflammability and Autoignition Temperature: 456°C (852°F) (Isopropanol)	

Extinguisher Media: Carbon Dioxide, Water, Foam**Special Fire Fighting Procedures:** None**Unusual Fire and Explosion Hazards:** None**Extinguishing Media****Suitable Extinguishing Media:** Alcohol foam, dry chemical, carbon dioxide, water fog.

Section V		Reactivity Data
Stability	Unstable: No Stable: Yes	Conditions to Avoid: High temperatures, flame and other ignition sources
Incompatibility (Materials to Avoid): Strong Oxides of carbon		
Hazardous Decomposition Products: Oxides of carbon (CO _x).		
Significance of change in physical appearance: Under severely cold temperatures product may begin to turn cloudy which may degrade its functionality.		
Conditions Of Reactivity: Do not heat above 80°C (176°F).		
Section VI		Health Hazard Data-Potential Acute Health Affects
<u>INHALATION</u>		
Single Exposure Severity, Target Organs and Type of Effect: High levels may cause headache, nausea, dizziness.		
Repeated Exposure Severity, Target Organs and Type of Effect: No longterm effects expected.		
<u>INGESTION</u>		
Single Exposure Severity, Target Organs and Type of Effect: Mildly toxic by ingestion. May cause nausea, headache and vomiting.		
<u>SKIN ABSORPTION</u>		
Single Exposure Severity, Target Organs and Type of Effect: No effects expected.		

Section VII - Health Hazard Data		
Eye Contact: Flush with plenty of water for at least fifteen minutes. If irritation persists, consult a physician.		
Repeated Exposure Severity, Target Organs and Type of Effect: Corneal thickening leading to scarring from repeated eye contact.		
Skin Contact: May cause mild irritations, drying out of skin. Wash thoroughly with soap and water.		
Inhalation: Move to fresh air. If dizziness persists, consult physician.		
Ingestion: May cause stomach discomfort if ingested. Seek medical advice.		
Section VIII – Control and Protective Measures		
Respiratory Protection (Specify Type): None		
Hygiene recommendations to prevent continued exposure: Use normal good industrial hygiene Practices		
Protection Gloves: None	Eye Protection: Safety Glasses	
Ventilation to be used: N/A	Local Exhaust: N/A	Special: N/A
	Mechanical (General): N/A	Other: N/A
Other Protective Clothing and Equipment: Not required.		
Hygienic Work Practices: Always read label before use.		
Section IX- Precautions for Safe Handling and Use/Leak Procedures		
Steps to be taken if Material is Spilled or Released: Mop up using large amounts of water. Flush Down sanitary sewer.		

Waste Disposal Methods: In accordance with municipal, provincial and federal regulations.	
Precautions to be taken in handling and storage: Keep away from excessive heat.	
Other Precautions and/or Special Hazards: Keep from freezing. Read label before using.	
HMIS Rating: Health: 1 Flammability: 1 Reactivity: 0 Personal Protection: b	
NFPA Rating: Health: 1 Flammability: 1 Reactivity: 0 Special: 0	
CANADIAN REGULATIONS	
WHMIS Class: B3 – Combustible liquid	
WHMIS Class: D2B- Toxic: Eye/Skin Irritant.	
FIRE FIGHTING MEASURES	
FLAMMABLE PROPERTIES	
Flammability Classification (29 CFR 1910.1200): Combustible liquid.	
Flash Point and Method: 82° C (180°F)	
Flammable Limits in Air- 2.5% -12.0% (Isopropanol)	
AutoFlammability and Autoignition Temperature: 456°C (852°F) (Isopropanol)	
EXTINGUISHING MEDIA	
Suitable Extinguishing Media: Alcohol foam, dry chemical, carbon dioxide, water fog.	
ACCIDENTAL RELEASE MEASURES	
Containment Technique:	Prevent from entering waterways and storm sewers.
Clean-Up Technique:	Contain spill. Cover spill with inert absorbent (absorbent, vermiculate). Using non-sparking tools, shovel or sweep up into a clean container. Remove from area. F spill area with water.
Evacuation Procedures:	Follow normal Emergency Response Plan (ERP).
HANDLING AND STORAGE	
HANDLING	
Handling Practices:	Use grounding wires if transferring large quantities. Keep away from oxidizers, heat and other ignition sources. Do not allow to freeze.
STORAGE	
Conditions For Safe Storage:	Keep away from oxidizers, heat and other ignition sources. Do not store in direct sunlight. Store in cool, dry well-ventilated area. Do not allow to freeze.
Ventilation Requirements	
For Storage:	None required.
Storage Temperature	
Range:	Below 40°C (104°F)
Storage Humidity Range:	Not applicable
Quantity Limits for Safe Storage: Not applicable	
Special Materials To Be Used For Packaging or Containers: Not applicable	
Transport Information: Not regulated	
NOTE	
Training Requirements: Workplace Hazardous Materials Information System training is required for handling and using this product in Canadian workplaces. U.S. OSHA requirements for handling chemical substances must be in place for handling and using this product in the United States.	
Recommended Uses and Restrictions: Cleaning of clear surfaces. Check for compatibility with material to be cleaned prior to use.	

DISCLAIMER: This information is furnished without warranty, representation, or license of any kind, except that it is accurate to the best of H. L. Bouton Co., Inc.'s knowledge, or obtained from sources believed to be accurate. H. L. Bouton Co., Inc. does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests and investigations. Before using the product, please read and understand the label and the Material Safety Data Sheet.