

Bash 4 Cash

Full Size & Compact Trucks 2020

10/29/2019

Rule Questions Call:

Billy Estep: 567-230-3608

Jeff Fatty Clark: 614-753-2393

Tim Clark: 740-272-1188

General:

- Any American made pick up, suburban, and blazer type vehicles permitted.
 - Hybrid, Crossover or SUV vehicles like Pt Cruiser, HHR, Honda Pilot and so no NOT ALLOWED.
- Helmet, seat belt, long sleeves/pant and eye protection must be worn at all times on the track.
- Any questions call first. If it doesn't say you can don't do it.
- ABSOLUTELY No painting of the frames.
- Must have a 12" x 12" roof sign that does not strengthen the truck in any way. It may **NOT** attach to the halo bar.
- Truck must be swept clean of debit & glass both inside and out before coming to event.
- JUDGES DECISION IS FINAL. All cars are subjected to re-inspection at ANY time.

Truck Building:

1. Factory fuel tanks must be removed. Fuel tanks must be located in the bed of truck in the center of the bed and directly behind the cab. NO STOCK FUEL TANKS ALLOWED. Fuel cells must be secured, fastened and covered for safety.
2. You may use engine of choice.
3. No kickers to distributor protector.
4. Batteries must be moved to front floor of cab and be securely fastened to floor and covered.
5. All trucks MUST have seatbelts.
6. Doors must be secured by wire, chain or welded shut. No loose doors allowed.
7. Tail gates may be welded shut. They may be welded to the bumper on the read of the truck.
8. Bed Seams where the bed sides meet the floor may be welded inside of the bed ONLY. No metal may be added.
9. Box & Cab mounts may be replaced with up to 1" bolts, body mounts may be removed. The body bolts may go all the way through the frame and floor of the truck.
10. No trailer hitches ore reinforcements of frame or body of any kind permitted. May use car bumpers; for mounting of car bumpers you may use factory bumper shocks and brackets or a 3" x 3" x 5" long box steel or like wise material.
11. Hoods must be in place and operable. Must have a 12" by 12" hole cut in hood over carburetor.
12. Hoods must be wired or bolted shut. Only 8 double strands of wire allowed. All can go to frame or bumper.
13. NO 4-Wheel drives allowed. 4-wheel drives must have front drive shaft removed.
14. Tires: No split rims. No Tractor Treads or solid tires allowed. Any other time is ok.
15. Beds must be welded to the cab of the truck with a 3" strap directly behind doors.
16. 8 strands of #9 wire allowed on front and rear of truck all is permitted to go to the frame.
17. Suspension may be solid. Bumpers can be no higher than 22" from bottom of bumper to ground- front & rear.
 - a. Truck must set level.
18. A 4-point cage is HIGHLY recommended in drivers compartment for drivers safety. The cage in the cab may be 4 down legs from front and rear bar straight down to the top of the frame. Also, a gas tank protector is highly recommended. Protector may attach to the frame but may not extend further than 24" from the front of the bed.
19. Truck must set level. No pulling down rear of the truck. No smashing of the bed sides will be allowed. You must use factory springs for make and model of truck. You may use all thread for shocks.
20. On trucks with out front leaf springs you can have kickers from the dash bar to frame behind A-Arms 2" x 2" square tubing or 2" pipe only 1 per side.

JUDGES DECISION ARE FINAL!!!