

Hydro-Shark 3TM

(UL 834 Listing)

RADIANT ELECTRIC FLOOR HEATING SYSTEMS

"Your Solution for Residential and Commercial Space Heating"



NEW FEATURES

- Manufactured to UL 834 Standard
- Higher Boiler Flow Rate
- Hinged Cover
- No Minimum Flow Rate on all Models
- Temperature Output 86° - 140° F
- Heavy Duty Controller Triacs
- All Models Same Enclosure Size
- Advanced Modulation Control

FLEX PRO PANELS - PRIMARY

MODEL	KW	VOLTS	AMPS	BRKR	BTU	SHIP WT.	FIG.
FPP-07	7.2	240	30	(1) 40	24,573	80	A
FPP-10	10.0		40	(1) 50	32,765	80	
FPP-12	12.0		50	(1) 70	40,956	80	
FPP-14	14.4		60	(2) 40	49,147	84	
FPP-19	19.2		80	(2) 50	65,526	84	
FPP-24	24.0		100	(2) 70	81,912	84	

Panel Size - 34.5" Wide - 32.75" High - 10" Deep*

FLEX PRO PANELS - PRIMARY/SECONDARY

MODEL	KW	VOLTS	AMPS	BRKR	BTU	SHIP WT.	FIG.
FPP-07 P/S	7.2	240	30	(1) 40	24,573	94	B
FPP-10 P/S	10.0		40	(1) 50	32,765	94	
FPP-12 P/S	12.0		50	(1) 70	40,956	94	
FPP-14 P/S	14.4		60	(2) 40	49,147	98	
FPP-19 P/S	19.2		80	(2) 50	65,526	98	
FPP-24 P/S	24.0		100	(2) 70	81,912	98	
FPP-29 P/S	28.8		120	(3) 50	98,977	102	
FPP-36 P/S	36.0		150	(3) 70	122,868	102	

Panel Size - 34.5" Wide - 32.75" High - 10" Deep*

* Boxed dimensions for Flex Pro Panels 17" x 43" x 37"

HYDRO SHARK 3 - BOILERS ONLY

MODEL	KW	VOLTS	AMPS	BRKR	BTU	SHIP WT.	WATER DELIVERY TEMP.	FIG.
SH3-07	7.2	240	30	(1) 40	24,573	16	125°	C
SH3-10	10.0		40	(1) 50	32,765	16	125°	
SH3-12	12.0		50	(1) 70	40,956	16	140°	
SH3-14	14.4		60	(2) 40	49,147	20	140°	
SH3-19	19.2		80	(2) 50	65,526	20	140°	
SH3-24	24.0		100	(2) 70	81,912	20	140°	
SH3-29	28.8		120	(3) 50	98,977	24	140°	
SH3-36	36.0		150	(3) 70	122,868	24	140°	

Boiler Size - 16.63" Wide - 14.50" High - 4.00" Deep

Our FLEX PRO PANELS are the *finest* HEATING SYSTEMS in the WORLD!

"The Perfect Solution for Residential and Commercial Radiant Floor Heating"

New UL
834 Listing



FIG. A



FIG. B



FIG. C

FLEX PRO PANEL FEATURES & BENEFITS

- Time Saving Installation
- Powder Coated Steel Panel
- Pump Isolation Flanges/Drains
- Slotted Holes for Easy Mounting
- Available in Primary/Secondary
- Pressure/Temperature Gauges
- Clear "Y" Strainer
- High Quality Air Elimination
- Purge "T"
- Closed Loop Expansion Tank
- 30# Relief Valve
- Boiler Union Disconnects



STIEBEL ELTRON

BOILER FEATURES & BENEFITS

- No Minimum Flow Rate
- Same Enclosure Size on all Models
- Temperature Output 86° - 140° F
- Manufactured to UL 834 Standard
- Higher Boiler Flow Rate
- Advanced Modulation Control
- Modulation Status LED
- Hinged Cover

DISTRIBUTOR:

763-441-8303
763-241-9628
sales@energyproducts.biz
www.energyproducts.biz

