Tsurumi trash pumps are designed with oversized pump casing, and a cleanout door which can removed from the pump casing without having to remove the suction hose.


Powered by quality, dependable Honda (EPT-HA) and Subaru (EPT-RX) gas engines.



EPT3-HA / EPT3-RX Gas Engine Trash Pumps Feartures:

- Heavy-duty Honda gas engine with oil sensor delivers high power from a compact, reliable design. Silicon Carbide mechanical seal provides longer life in this class.
- High Chrome impeller, Cast Iron volute casing plus Stainless Steel wear plate promise increased durability and decreased maintenance.
- Pump/engine set mounted to cage frame on Rubber Vibration Cushions to buffer stress and wear.
- Durable Rolled-Steel frame provides pump/engine with maximum protection, perfect ease
 of handling or transport and safe operation.
- Galvanized Steel hose couplings promise longer thread life.





| Model | EPT3-50HA | EPT3-80HA |
|------------------------------------|--------------------------|-----------------|
| | 2" Trash Pump | 3" Trash Pump |
| Max. Capacity (GPM) | 190 | 360 |
| Max. Head (ft.) | 90 | 96 |
| Impeller Material | High Chrome Iron Casting | |
| Volute Casting Material | Cast Iron | |
| Wear Plate Material | Stainless Steel | |
| Pump Casing Material | Cast Aluminum | |
| Discharge Connection | 2" NPT Coupling | 3" NPT Coupling |
| Suction Connection | 2" NPT Coupling | 3" NPT Coupling |
| Max. Suction Lift (ft.) | | |
| Brand | Honda | Honda |
| Model | GX160 | GX240 |
| Max. Output (hp/rpm) | 5.5/3600 | 8.0/3600 |
| Fuel Tank Capacity (US gal.) | 0.95 | 1.6 |
| Continuous Run Time Per Tank (hr.) | 3.3 | 3.2 |
| Length (in.) | 23 1/4 | 27 1/2 |
| Width (in.) | 18 1/4 | 20 1/8 |
| Height (in.) | 17 3/8 | 25 5/8 |
| Shipping Weight (lbs.) | 82 | 136 |