



Fabric Specification Sheet

Style: **4-Ply 17oz Wideshade IV**

Available Widths: 98", 120"
(249 cm, 305cm)
(Other widths and colors available, MOQ's may apply)

Roll Lengths: 25 yard standard (Other lengths available upon request)
(23 m)

Shipping: Rolls shipped on 3" (7.62 cm) ID paper core

Construction: 4 ply laminate (70% Vinyl and 30% Fiberglass)
(Each vinyl is equal thickness and weight)

Surface Texture: As Laminated – Various embossing patterns available

Thread Count: 68 threads per square inch
(26 per square cm)

Weight: 17.9 oz per square yard (+ or - 2.0)
(606 grams per square meter) (+ or - 68)

Thickness: 16.9 mil (+ or - 2.0)
(.42 mm) (+ or - .05)

Instron Tear Strength: Warp 9 Lbs/In Fill 10 Lbs/In

Instron Breaking Strength: Warp 339 Lbs/In Fill 256 Lbs/In

Opacity: Blackout

Visual check

Washability: Material may be dusted with a damp cloth. When scrubbing is necessary, warm water, mild detergents and gentle rubbing are recommended.

Flammability: NFPA Standard 701/2015 Edition Test Method 1 (Small Scale)

Other Tests Passed: AATCC 183 – Blocking Ultraviolet
AATCC 16E-1993 – Colorfastness to Light
ASHRAE Standard 74-1988 – Fenestration
SW 846-7000B-7420 (Pb) – Lead
UL GreenGuard Gold Certified

No.	Description	Ts	Rs	As	Tv	Rv	Av	Tv	O-F	SC (Single Glass)			SC (Insulating Glass)		
										1/8" CI	1/4" CI	1/4" H.A.	1/2" CI	1" CI	1" H.A.
11	White 4 Ply	Tr	79	21	Tr	67	33	Tr	0.2	0.19	0.21	0.25	0.19	0.22	0.2



Revised 1/2020

MAILING ADDRESS
P.O. Box 1017
Warsaw, IN 46581

STREET ADDRESS
102 Enterprise Drive
Warsaw, IN 46580

PHONE
(574) 269-1280

FAX
(574) 269-7747

E-MAIL
Mail@indianacoatedfabrics.com

WEBSITE
www.indianacoatedfabrics.com