

Product Number 457

Issuing Date No data available

Revision Date 05/28/15

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name Sunnyside Lacquer Thinner

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Thinning Lacquers

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name Sunnyside Corporation  
 Supplier Address 225 Carpenter Avenue  
 Wheeling  
 IL  
 60090  
 US  
 Supplier Phone Number Phone:8003238611  
 Fax:8475419043  
 Supplier Email sscontact@sunnysidecorp.com  
 Emergency telephone number Chem Trec 8004249300

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 2



Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>	
<b>Hazard Statements</b>	Harmful if swallowed Harmful in contact with skin Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause genetic defects Suspected of causing cancer Suspected of damaging fertility or the unborn child Causes damage to organs May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Highly flammable liquid and vapor	
		
<b>Appearance</b> Clear	<b>Physical State</b> Liquid	<b>Odor</b> Mild

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge

**Precautionary Statements - Response**

- Specific treatment (see supplemental first aid instructions on this label)
- IF exposed: Call a POISON CENTER or doctor/physician



**Skin**

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation occurs: Get medical advice/attention  
Call a POISON CENTER or doctor/physician if you feel unwell  
Wash contaminated clothing before reuse

**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell

**Ingestion**

Rinse mouth  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

0% of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Harmful to aquatic life with long lasting effects  
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION  
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

**Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%	Trade Secret
Ethylacetate	141-78-6	15 - 40	
Methyl alcohol	67-56-1	10 - 30	
Acetone	67-64-1	10 - 30	
Toluene	108-88-3	7 - 13	
Aliphatic Naphtha	64742-89-8	7 - 13	
Xylene	1330-20-7	5 - 10	
Methyl Ethyl Ketone	78-93-3	3 - 7	
Ethylbenzene	100-41-4	1 - 5	

\*The exact percentage (concentration) of composition has been withheld as a trade secret

**4. FIRST AID MEASURES**



**First aid measures**

**General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. If symptoms persist, call a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.

**Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen.

**Ingestion**

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

**Self-protection of the first aider**

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects**

Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Dizziness.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician**

Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO2). Alcohol resistant foam.

### Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

### Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

#### Uniform Fire Code

Flammable Liquid: I-B  
Irritant: Liquid

### Hazardous Combustion Products

Carbon oxides.

### Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

#### Personal Precautions

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Full encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Stop leak if you can do it without risk.

#### Other Information

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### Environmental Precautions

#### Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

### Methods and material for containment and cleaning up

#### Methods for Containment

A vapor suppressing foam may be used to reduce vapors. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

#### Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.



## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid breathing vapors or mists. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

### Conditions for safe storage, including any incompatibilities

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

#### Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylacetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 325 mg/m <sup>3</sup> STEL: 250 ppm
Acetone	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>

Methyl Ethyl Ketone	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m <sup>3</sup> (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL = 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	
Ethylbenzene 100-41-4	STEL = 125 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm 10% LEL TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 545 mg/m <sup>3</sup> STEL: 125 ppm

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** If splashes are likely to occur. Tight sealing safety goggles.

**Skin and Body Protection** Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

**Respiratory Protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical State</b>	Liquid	<b>Odor</b>	Mild
<b>Appearance</b>	Clear	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		
<b>Property</b>	<b>Values</b>	<b>Remarks/ Method</b>	
<b>pH</b>	N/A	None known	
<b>Melting / freezing point</b>	No data available	None known	
<b>Boiling point / boiling range</b>	56 °C / 133 °F	None known	



Flash Point	-18 C / 0 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Moderate	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	

**Other Information**

Softening Point	No data available
VOC Content (%)	90%
Particle Size	No data available
Particle Size Distribution	

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Excessive heat. Heat, flames and sparks.

**Incompatible materials**

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

**Product Information**                      Product does not present an acute toxicity hazard based on known or supplied information.





<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.
<b>Eye Contact</b>	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. May cause irritation.
<b>Skin Contact</b>	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. May be absorbed through the skin in harmful amounts. Harmful in contact with skin. (based on components). Repeated exposure may cause skin dryness or cracking.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed. (based on components). Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylacetate 141-78-6	= 5620 mg/kg ( Rat )	> 20 mL/kg ( Rabbit )	-
Methyl alcohol 67-56-1	= 5628 mg/kg ( Rat )	-	= 83.2 mg/L ( Rat ) 4 h
Acetone 67-64-1	-	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Toluene 108-88-3	= 636 mg/kg ( Rat )	= 8390 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h > 26700 ppm ( Rat ) 1 h
Aliphatic Naphtha 64742-89-8	-	-	= 23500 mg/m <sup>3</sup> ( Rat ) 8 h
Xylene 1330-20-7	= 4300 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit )	= 47635 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Methyl Ethyl Ketone 78-93-3	-	= 3000 mg/kg ( Rabbit )	-
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15354 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing. Asthma-like and/ or skin allergy-like symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** There is no data available for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		
Xylene 1330-20-7		Group 3		



Ethylbenzene 100-41-4	A3	Group 2B		X
--------------------------	----	----------	--	---

**ACGIH (American Conference of Governmental Industrial Hygienists)**  
**A3 - Animal Carcinogen**  
**IARC (International Agency for Research on Cancer)**  
**Group 2B - Possibly Carcinogenic to Humans**  
**Group 3 - Not Classifiable as to Carcinogenicity in Humans**  
**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**  
**X - Present**

<b>Reproductive Toxicity</b>	Product is or contains a chemical which is a known or suspected reproductive hazard. Contains a known or suspected reproductive toxin.
<b>STOT - single exposure</b>	Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if swallowed. Causes damage to organs in contact with skin. Causes damage to organs if inhaled.
<b>STOT - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
<b>Chronic Toxicity</b>	No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. Aspiration may cause pulmonary edema and pneumonitis. Effects from this product caused by acute exposure may cause permanent damage to target organs and/or may cause chronic conditions. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects. Contains toluene. Exposure to toluene in animals via inhalation and intentional overexposure to toluene in humans has caused adverse fetal development effects.
<b>Target Organ Effects</b>	Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Central Nervous System (CNS). Kidney. Liver. Blood. Systemic Toxicity.
<b>Aspiration Hazard</b>	No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

- ATEmix (oral)  
427.00 mg/kg
- ATEmix (dermal)  
1,275.00 mg/kg (ATE)
- ATEmix (inhalation-gas)  
3,193.00 ppm (4 hr)
- ATEmix (inhalation-dust/mist)  
2.00 mg/l
- ATEmix (inhalation-vapor)  
13.00 ATEmix



**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Harmful to aquatic life with long lasting effects.

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical Name	Log Pow
Ethylacetate 141-78-6	0.6
Methyl alcohol 67-56-1	-0.77
Acetone 67-64-1	-0.24
Toluene 108-88-3	2.65
Methyl Ethyl Ketone 78-93-3	0.29
Xylene 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.118

**Other adverse effects**

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.

**US EPA Waste Number** D001 D035 U220 U002 U154 U159 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylacetate 141-78-6		Included in waste stream: F039		U112
Methyl alcohol 67-56-1		Included in waste stream: F039		U154
Acetone 67-64-1				U002
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Methyl Ethyl Ketone 78-93-3	waste number U159	Included in waste streams: F005, F039	= 200.0 mg/L regulatory level	U159
Xylene 1330-20-7		Included in waste stream: F039		U239
Ethylbenzene 100-41-4		Included in waste stream: F039		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

**California Hazardous Waste Codes 214**

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethylacetate 141-78-6	Toxic Ignitable
Methyl alcohol 67-56-1	Toxic Ignitable
Acetone 67-64-1	Ignitable



Toluene 108-88-3	Toxic Ignitable
Methyl ethyl Ketone 78-93-3	Toxic Ignitable
Xylene 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN-No. UN1263  
 Proper Shipping Name PAINT RELATED MATERIAL  
 Hazard Class 3  
 Packing Group II  
 Description UN1263, PAINT RELATED MATERIAL, 3, PGII

**TDG**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Subsidiary class (6.1)  
 Packing Group II  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

**MEX**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Subsidiary class 6.1  
 Packing Group II  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

**ICAO**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Subsidiary class 6.1  
 Packing Group II  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

**IATA**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Subsidiary class 6.1  
 Packing Group II  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II

**IMDG/IMO**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Subsidiary class 6.1



Packing Group II  
 EmS No. F-E, S-D  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II, FP -18C

**RID**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Packing Group II  
 Classification code FT1  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II  
 ADR/RID-Labels 6.1

**ADR**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Packing Group II  
 Classification code FT1  
 Description UN1992 FLAMMABLE LIQUID, TOXIC, N.O.S.(METHYL ALCOHOL ), 3(6.1), II  
 ADR/RID-Labels 6.1

**ADN**

UN-No. UN1992  
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, N.O.S.  
 Hazard Class 3  
 Packing Group II  
 Classification code FT1  
 Special Provisions 274, 802  
 Description UN1992, FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL ACETATE, METHANOL), 3 (6.1), II  
 Hazard Labels 3 + 6.1  
 Limited Quantity 1 L  
 Ventilation VE01, VE02

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	10 - 30	1.0
Toluene - 108-88-3	108-88-3	7 - 13	1.0
Xylene - 1330-20-7	1330-20-7	5 - 10	1.0
Ethylbenzene - 100-41-4	100-41-4	1 - 5	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X
Xylene 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylacetate 141-78-6			RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl Ethyl Ketone 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylene 1330-20-7	100 lb		RQ= 100 lb final RQ RQ= 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ= 1000 lb final RQ RQ= 454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methyl alcohol - 67-56-1	Developmental
Toluene - 108-88-3	Developmental
Ethylbenzene - 100-41-4	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethylacetate 141-78-6	X	X	X	X	
Methyl alcohol 67-56-1	X	X	X	X	X
Acetone 67-64-1	X	X	X	X	
Toluene 108-88-3	X	X	X	X	X
Methyl Ethyl Ketone 78-93-3	X	X	X	X	X



Sunnyside Lacquer Thinner

Xylene 1330-20-7	X	X	X	X	X
Ethylbenzene 100-41-4	X	X	X	X	X

**International Regulations**

**Mexico**

**National occupational exposure limits**

Component	Carcinogen Status	Exposure Limits
Ethylacetate 141-78-6 ( 15 - 40 )		Mexico: TWA 400 ppm Mexico: TWA 1400 mg/m <sup>3</sup>
Methyl alcohol 67-56-1 ( 10 - 30 )		Mexico: TWA= 200 ppm Mexico: TWA= 260 mg/m <sup>3</sup> Mexico: STEL= 250 ppm Mexico: STEL= 310 mg/m <sup>3</sup>
Acetone 67-64-1 ( 10 - 30 )		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m <sup>3</sup> Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m <sup>3</sup>
Toluene 108-88-3 ( 7 - 13 )		Mexico: TWA 50 ppm Mexico: TWA 188 mg/m <sup>3</sup>
Methyl Ethyl Ketone 78-93-3 ( 7 - 13 )		Mexico: TWA= 590 mg/m <sup>3</sup> Mexico: TWA= 200 ppm Mexico: STEL= 885 mg/m <sup>3</sup> Mexico: STEL= 300 ppm
Xylene 1330-20-7 ( 5 - 10 )		Mexico: TWA= 100 ppm Mexico: TWA= 435 mg/m <sup>3</sup> Mexico: STEL= 150 ppm Mexico: STEL= 655 mg/m <sup>3</sup>
Ethylbenzene 100-41-4 ( 1 - 5 )		Mexico: TWA= 435 mg/m <sup>3</sup> Mexico: TWA= 100 ppm Mexico: STEL= 125 ppm Mexico: STEL= 545 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada**

**WHMIS Hazard Class**

B2 - Flammable liquid

D2A - Very toxic materials



**16. OTHER INFORMATION**

NFPA	Health Hazards 3	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 3 *	Flammability 3	Physical Hazard 0	Personal Protection X

Chronic Hazard Star Legend \* = Chronic Health Hazard





**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Revision Date**  
**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

