

CHAPTER 21
STORM WATER MANAGEMENT

- 21.1 Authority
- 21.2 Findings of Fact
- 21.3 Purpose and Intent
- 21.4 Applicability and Jurisdiction
- 21.5 Definitions
- 21.6 Maximum Extent Practicable
- 21.7 Technical Standards
- 21.8 Performance Standards
- 21.9 Storm Water Management Plan
- 21.10 Financial Guarantee
- 21.11 Maintenance Agreement
- 21.12 Enforcement
- 21.13 Permit Requirements
- 21.14 Pre-Existing Storm Water Management Violations
- 21.15 Appeals

Chapter 21 Board Action

Adopted December 20, 2011 as part of Village Incorporation
(as Chapter 20)

Chapter 21 Created, April 11, 2016, Ordinance No. 2016-O-03

Chapter 21 Re-Created, April 10, 2017, Ordinance No. 2017-O-03

21.1 AUTHORITY

- (1) This ordinance is adopted by the Village of Bloomfield under the authority granted by s.61.354, Wis. Stats. This ordinance supersedes all provisions of an ordinance previously enacted under s. 61.35, Wis. Stats., that relate to storm water management regulations. Except as otherwise specified in s. 61.354, Wis. Stats. applies to this ordinance and to any amendments to this ordinance.
- (2) The provisions of this ordinance are deemed not to limit any other lawful regulatory powers of the same governing body.
- (3) The Village of Bloomfield hereby designates the Village Engineer to administer and enforce the provisions of this ordinance.
- (4) The requirements of this ordinance do not pre-empt more stringent storm water management requirements that may be imposed by any of the following:
 - (a) Wisconsin Department of Natural Resources administrative rules, permits or approvals including those authorized under ss. 281.16 and 283.33, Wis. Stats.
 - (b) Targeted non-agricultural performance standards promulgated in rules by the Wisconsin Department of Natural Resources under s. NR 151.004, Wis. Adm. Code.

21.2 FINDINGS OF FACT

The Village of Bloomfield acknowledges that uncontrolled, post-construction runoff has a significant impact upon water resources and the health, safety and general welfare of the community and diminishes the public enjoyment and use of natural resources. Specifically, uncontrolled post-construction runoff can:

- (1) Degrade physical stream habitat by increasing stream bank erosion, increasing streambed scour, diminishing groundwater recharge, diminishing stream base flows and increasing stream temperature.
- (2) Diminish the capacity of lakes and streams to support fish, aquatic life, recreational and water supply uses by increasing pollutant loading of sediment, suspended solids, nutrients, heavy metals, bacteria, pathogens and other urban pollutants.
- (3) Alter wetland communities by changing wetland hydrology and

by increasing pollutant loads.

- (4) Reduce the quality of groundwater by increasing pollutant loading.
- (5) Threaten public health, safety, property and general welfare by overtaxing storm sewers, drainage ways, and other minor drainage facilities.

21.3 PURPOSE AND INTENT

- (1) **PURPOSE:** The general purpose of this ordinance is to establish long-term, post-construction runoff management requirements that will diminish the threats to public health, safety, welfare and the aquatic environment. Specific purposes are to:
 - (a) Further the maintenance of safe and healthful conditions.
 - (b) Prevent and control the adverse effects of storm water; prevent and control soil erosion; prevent and control water pollution; protect spawning grounds, fish and aquatic life; control building sites, placement of structures and land uses; preserve ground cover and scenic beauty; and promote sound economic growth.
 - (c) Control exceedance of the safe capacity of existing drainage facilities and receiving water bodies; prevent undue channel erosion; and control increases in the scouring and transportation of particulate matter.
 - (d) Minimize the amount of pollutants discharged from the separate storm sewer to protect the waters of the state.
- (2) **INTENT.** It is the intent of the Village that this ordinance regulates post-construction storm water discharges to waters of the state. This ordinance may be applied on a site-by-site basis. The Village recognizes, however, that the preferred method of achieving the storm water performance standards set forth in this ordinance is through the preparation and implementation of comprehensive, systems-level storm water management plans that cover hydrologic units, such as watersheds, on a municipal and regional scale. Such plans may prescribe regional storm water devices, practices or systems, any of which may be designed to treat runoff from more than one site prior to discharge to waters of the state. Where such plans are in conformance with the performance standards

developed under s. 281.16, Wis. Stats., for regional storm water management measures and have been approved by the Village, it is the intent of this ordinance that the approved storm water management plan be used to identify post-construction management measures acceptable for the community.

21.4 APPLICABILITY AND JURISDICTION

(1) APPLICABILITY.

- (a) Except as provided under par. (b), this ordinance applies to a post-construction site whereupon one acre or more of land disturbing construction activity occurs during construction.

- (b) A site that meets any of the criteria in this paragraph is exempt from the requirements of this ordinance:
 - 1. A post-construction site with less than ten percent connected imperviousness, based on the area of land disturbance, provided the cumulative area of all impervious surfaces is less than one acre. However, the exemption of this paragraph does not include exemption from the protective area standard of this ordinance.

 - 2. Agricultural facilities and practices.

 - 3. Underground utility construction, but not including the construction of any above ground structures associated with utility construction.

- (c) Notwithstanding the applicability requirements in par. (a), this ordinance applies to post-construction sites of any size that, as determined by the are likely to result in runoff that exceeds the safe capacity of the existing drainage facilities or receiving body of water, causes undue channel erosion, or increases water pollution by scouring or the transportation of particulate matter.

(2) JURISDICTION.

This ordinance applies to post construction sites within the boundaries and jurisdiction of the Village of Bloomfield.

(3) EXCLUSIONS.

This ordinance is not applicable to activities conducted by a state agency, as defined under s.227.01 (1), Wis. Stats

21.5 DEFINITIONS

For the purposes of this Chapter, the following words have the following meanings:

(1) "Adequate sod, or self-sustaining vegetative cover" means maintenance of sufficient vegetation types and densities such that the physical integrity of the streambank or lakeshore is preserved. Self-sustaining vegetative cover includes grasses, forbs, sedges and duff layers of fallen leaves and woody debris.

(2) "Administering authority" means a governmental employee, or a regional planning commission empowered under s. 61.354 Wis. Stats., that is designated by the Village of Bloomfield to administer this ordinance.

(3) "Agricultural facilities and practices" means a structure associated with an agricultural practice. Practices include beekeeping; commercial feedlots; dairying; egg production; floriculture; fish or fur farming; grazing; livestock raising; orchards; poultry raising; raising of grain, grass, mint and seed crops; raising of fruits, nuts and berries; sod farming; placing land in federal programs in return for payments in kind; owning land, at least 35 acres of which is enrolled in the conservation reserve program under 16 USC 3831 to 3836; and vegetable raising.

(4) "Atlas 14" means the National Oceanic and Atmospheric Administration (NOAA) Atlas 14 Precipitation-Frequency Atlas of the United States, Volume 8 (Midwestern States), published in 2013.

(5) "Average annual rainfall" means a typical calendar year of precipitation as determined by the Wisconsin Department of Natural Resources for users of models such as WinSLAMM, P8 or equivalent methodology. The average annual rainfall is chosen from a department publication for the location closest to the municipality.

(6) "Best management practice" or "BMP" means structural or non-structural measures, practices, techniques or devices employed to avoid or minimize sediment or pollutants carried in runoff to waters of the state.

(7) "Business day" means a day the office of the Village of

Bloomfield is routinely and customarily open for business.

(8) "Cease and desist order" means a court-issued order to halt land disturbing construction activity that is being conducted without the required permit or in violation of a permit issued by the Village of Bloomfield.

(9) "Combined sewer system" means a system for conveying both sanitary sewage and storm water runoff.

(10) "Connected imperviousness" means an impervious surface connected to the waters of the state via a separate storm sewer, an impervious flow path, or a minimally pervious flow path

(11) "Design storm" means a hypothetical discrete rainstorm characterized by a specific duration, temporal distribution, rainfall intensity, return frequency and total depth of rainfall

(12) "Development" means residential, commercial, industrial or institutional land uses and associated roads.

(13) "Direct conduits to groundwater" means wells, sinkholes, swallets, fractured bedrock at the surface, mine shafts, non-metallic mines, tile inlets discharging to groundwater, quarries, or depressional groundwater recharge areas over shallow fractured bedrock.

(14) "Effective infiltration area" means the area of the infiltration system that is used to infiltrate runoff and does not include the area used for site access, berms or pretreatment.

(15) "Erosion" means the process by which the land's surface is worn away by the action of wind, water, ice or gravity.

(16) "Exceptional resource waters" means waters listed in s. NR 102.11, Wis. Adm. Code.

(17) "Gross aggregate area" means the total area, in acres, of all land located within the interior property boundary containing a proposed land development, redevelopment, or property subdivision activity.

(18) "Filtering layer" means soil that has at least a 3-foot deep layer with at least 20 percent fines; or at least a 5-foot deep layer with at least 10 percent fines; or an engineered soil with an equivalent level of protection as determined by

the regulatory authority for the site.

(19) "Final stabilization" means that all land disturbing construction activities at the construction site have been completed and that a uniform perennial vegetative cover has been established with a density of at least 70 percent of the cover for the unpaved areas and areas not covered by permanent structures or that employ equivalent permanent stabilization measures.

(20) "Financial guarantee" means a performance bond, maintenance bond, surety bond, irrevocable letter of credit, or similar guarantees submitted to the Village of Bloomfield by the responsible party to assure that requirements of the ordinance are carried out in compliance with the storm water management plan.

(21) "Governing body" means town board of supervisors, county board of supervisors, city council, village board of trustees or village council

(22) "Impervious surface" means an area that releases as runoff all or a large portion of the precipitation that falls on it, except for frozen soil. Rooftops, sidewalks, driveways, gravel or paved parking lots and streets are examples of areas that typically are impervious.

(23) "In-fill" means an undeveloped area of land located within an existing urban sewer service area, surrounded by development or development and natural or man-made features where development cannot occur.

(24) "Infiltration" means the entry of precipitation or runoff into or through the soil.

(25) "Infiltration system" means a device or practice such as a basin, trench, rain garden or swale designed specifically to encourage infiltration, but does not include natural infiltration in pervious surfaces such as lawns, redirecting of rooftop downspouts onto lawns or minimal infiltration from practices, such as swales or road side channels designed for conveyance and pollutant removal only.

(26) "Land disturbing construction activity" means any man-made alteration of the land surface resulting in a change in the topography or existing vegetative or non-vegetative soil cover, that may result in runoff and lead to an increase in soil erosion and movement of sediment into waters of the state. Land disturbing construction activity includes clearing and grubbing, demolition, excavating, pit trench dewatering,

filling and grading activities.

(27) "Landowner" means any person holding fee title, an easement or other interest in property, which allows the person to undertake cropping, livestock management, land disturbing construction activity or maintenance of storm water BMPs on the property.

(28) "Maintenance agreement" means a legal document that provides for long-term maintenance of storm water management practices.

(29) "Maximum extent practicable" means the highest level of performance that is achievable but is not equivalent to a performance standard identified in this ordinance as determined in accordance with section 21.6 of this ordinance.

(30) "New development" means development resulting from the conversion of previously undeveloped land or agricultural land uses.

(31) "NRCS MSE3 or MSE4 distribution" means a specific precipitation distribution developed by the United States Department of Agriculture, Natural Resources Conservation Service, using precipitation data from Atlas 14.

(32) "Off-site" means located outside the property boundary described in the permit application.

(33) "On-site" means located within the property boundary described in the permit application.

(34) "Ordinary high-water mark" has the meaning given in s. NR 115.03 (6), Wis. Adm. Code.

(35) "Outstanding resource waters" means waters listed in s. NR 102.10, Wis. Adm. Code.

(36) "Percent fines" means the percentage of a given sample of soil, which passes through a #200 sieve.

(37) "Performance standard" means a narrative or measurable number specifying the minimum acceptable outcome for a facility or practice.

(38) "Permit" means a written authorization made by the Village of Bloomfield to the applicant to conduct land disturbing construction activity or to discharge post-construction runoff to waters of the state.

(39) "Permit administration fee" means a sum of money paid to the Village of Bloomfield by the permit applicant for the purpose of recouping the expenses incurred by the authority in administering the permit.

(40) "Pervious surface" means an area that releases as runoff a small portion of the precipitation that falls on it. Lawns, gardens, parks, forests or other similar vegetated areas are examples of surfaces that typically are pervious.

(41) "Pollutant" has the meaning given in s. 283.01 (13), Wis. Stats.

(42) "Pollution" has the meaning given in s. 281.01 (10), Wis. Stats.

(43) "Post-construction site" means a construction site following the completion of land disturbing construction activity and final site stabilization.

(44) "Pre-development condition" means the extent and distribution of land cover types present before the initiation of land disturbing construction activity, assuming that all land uses prior to development activity are managed in an environmentally sound manner.

(45) "Preventive action limit" has the meaning given in s. NR 140.05 (17), Wis. Adm. Code.

(46) "Protective area" means an area of land that commences at the top of the channel of lakes, streams and rivers, or at the delineated boundary of wetlands, and that is the greatest of the following widths, as measured horizontally from the top of the channel or delineated wetland boundary to the closest impervious surface.

(47) "Redevelopment" means areas where development is replacing older development.

(48) "Responsible party" means the landowner or any other entity performing services to meet the requirements of this ordinance through a contract or other agreement. "Runoff" means storm water or precipitation including rain, snow or ice melt or similar water that moves on the land surface via sheet or channelized flow.

(49) "Separate storm sewer" means a conveyance or system of conveyances including roads with drainage systems, streets,

catch basins, curbs, gutters, ditches, constructed channels or storm drains, which meets all the following criteria:

- (a) Is designed or used for collecting water or conveying runoff.
- (b) Is not part of a combined sewer system.
- (c) Is not part of a publicly owned wastewater treatment works that provides secondary or more stringent treatment.
- (d) Discharges directly or indirectly to waters of the state.

(50) "Silviculture activity" means activities including tree nursery operations, tree harvesting operations, reforestation, tree thinning, prescribed burning, and pest and fire control. Clearing and grubbing of an area of a construction site is not a Silviculture activity.

(51) "Site" means the entire area included in the legal description of the land on which the land disturbing construction activity occurred.

(52) "Stop work order" means an order issued by the Village of Bloomfield which requires that all construction activity on the site be stopped.

(53) "Storm water management plan" means a comprehensive plan designed to reduce the discharge of pollutants from storm water, after the site has undergone final stabilization, following completion of the construction activity.

(54) "Storm water management system plan" is a comprehensive plan designed to reduce the discharge of runoff and pollutants from hydrologic units on a regional or municipal scale.

(55) "Technical standard" means a document that specifies design, predicted performance and operation and maintenance specifications for a material, device or method.

(56) "Top of the channel" means an edge, or point on the landscape landward from the ordinary high-water mark of a surface water of the state, where the slope of the land begins to be less than 12 percent continually for at least 50 feet. If the slope of the land is 12 percent or less continually for the initial 50 feet landward from the ordinary high-water mark, the top of the channel is the ordinary high-water mark.

(57) "Total maximum daily load" or "TMDL" means the amount of pollutants specified as a function of one or more water quality parameters, that can be discharged per day into a water quality

limited segment and still ensure attainment of the applicable water quality standard.

(58) "TP-40" means Technical Paper No. 40, Rainfall Frequency Atlas of the United States, published in 1961.

(59) "TR-55" means the United States department of agriculture, natural resources conservation service (previously soil conservation service), Urban Hydrology for Small Watersheds, Second Edition, Technical Release 55, June 1986, which is incorporated by reference for this chapter.

(60) "Transportation facility" means a highway, a railroad, a public mass transit facility, a public-use airport, a public trail or any other public work for transportation purposes such as harbor improvements under s. 85.095 (1)(b), Wis. Stats. "Transportation facility" does not include building sites for the construction of public buildings and buildings that are places of employment that are regulated by the Department pursuant to s. 281.33, Wis. Stats.

(61) "TSS" means total suspended solids.

(62) "Type II distribution" means a rainfall type curve as established in the "United States Department of Agriculture, Soil Conservation Service, Technical Paper 149, published in 1973".

(63) "Waters of the state" includes those portions of Lake Michigan and Lake Superior within the boundaries of this state, and all lakes, bays, rivers, streams, springs, ponds, wells, impounding reservoirs, marshes, watercourses, drainage systems and other surface water or groundwater, natural or artificial, public or private, within this state or its jurisdiction.

21.6 MAXIMUM EXTENT PRACTABLE

Maximum extent practicable applies when a person who is subject to a performance standard of this ordinance demonstrates to the Village Engineer's satisfaction that a performance standard is not achievable and that a lower level of performance is appropriate. In making the assertion that a performance standard is not achievable and that a level of performance different from the performance standard is the maximum extent practicable, the responsible party shall consider the best available technology, cost effectiveness, geographic features, and other competing interests such as protection of public safety and welfare, protection of endangered and threatened resources, and preservation of historic properties.

21.7 TECHNICAL STANDARDS

The following methods shall be used in designing the water quality, peak discharge, and infiltration components of storm water practices needed to meet the water quality standards of this ordinance:

- (1) Consistent with the technical standards identified, developed or disseminated by the Wisconsin Department of Natural Resources under subchapter V of chapter NR 151, Wis. Adm. Code Where technical standards have not been identified, or developed by the Wisconsin Department of Natural Resources, other technical standards may be used provided that the methods have been approved by the Village of Bloomfield.

21.8 PERFORMANCE STANDARDS

- (1) RESPONSIBLE PARTY. The responsible party shall comply with this section.
- (2) STORM WATER MANAGEMENT PLAN. A written storm water management plan in accordance with S. 21.11 shall be developed and implemented for each post-construction site.
- (3) MAINTENANCE OF EFFORT. For redevelopment sites where the redevelopment will be replacing older development that was subject to post-construction performance standards of NR 151 in effect on or after October 1, 2004, the responsible party shall meet the total suspended solids reduction, peak flow control, infiltration, and protective areas standards applicable to the older development or meet the redevelopment standards of this ordinance, whichever is more stringent.
- (4) REQUIREMENTS. The storm water management plan required under sub. (2) shall include the following:
 - (a) TOTAL SUSPENDED SOLIDS. BMPs shall be designed, installed and maintained to control total suspended solids carried in runoff from the post-construction site as follows:
 1. BMPs shall be designed in accordance with Table 1. or to the maximum extent practicable as provided in subd. 2. The design shall be based on an average annual rainfall, as compared to

no runoff management controls.

| Development Type | TSS Reduction |
|-------------------------|---|
| New Development | 80 percent |
| In-fill development | 80 percent |
| Redevelopment | 40 percent of load from parking areas and roads |

2. Maximum Extent Practicable. If the design cannot meet a total suspended solids reduction performance standard of Table 1., the storm water management plan shall include a written, site-specific explanation of why the total suspended solids reduction performance standard cannot be met and why the total suspended solids load will be reduced only to the maximum extent practicable.
3. Off-Site Drainage. When designing BMPs, runoff draining to the BMP from off- site shall be taken into account in determining the treatment efficiency of the practice. Any impact on the efficiency shall be compensated for by increasing the size of the BMP accordingly.

(b) PEAK DISCHARGE.

1. By design, BMPs shall be employed to maintain or reduce the 1-year, 24-hour; the 2-year, 24-hour; and the 10-year, 24-hour post-construction peak runoff discharge rates to the 1- year, 24-hour; 2-year, 24-hour; and the 10-year; 24-hour pre-development peak runoff discharge rates respectively, or to the maximum extent practicable. Storage shall be provided to accommodate up to a 100- year, 24-hour design storm for post-development land cover with a maximum discharge rate of the 10-year predevelopment rate. The runoff curve numbers in Table 2. shall be used to represent the actual pre-development conditions. Peak discharges shall be calculated using TR-55 runoff curve number methodology, Atlas 14 precipitation depths, and the appropriate NRCS

Wisconsin MSE3 or MSE4 precipitation distribution. On a case-by-case basis, the Village Engineer may allow the use of TP-40 precipitation depths and the Type II distribution.

| Runoff Curve Number | Hydrologic Soil Group | | | |
|---------------------|-----------------------|----|----|----|
| | A | B | C | D |
| Woodland | 30 | 55 | 70 | 77 |
| Grassland | 39 | 61 | 71 | 78 |
| Cropland | 55 | 69 | 78 | 83 |

2. This subsection of the ordinance does not apply to any of the following:
 - a. A post-construction site where the discharge is directly into a lake over 5,000 acres or a stream or river segment draining more than 500 square miles.
 - b. Except as provided under S. 21.8 (3), a redevelopment post-construction site.
 - c. An in-fill development area less than 5 acres.

(c) INFILTRATION.

1. Best Management Practices. BMPs shall be designed, installed, and maintained to infiltrate runoff in accordance with the following or to the maximum extent practicable:
 - a. *Low imperviousness.* For development up to 40 percent connected imperviousness, such as parks, cemeteries, and low density residential development, infiltrate sufficient runoff volume so that the post-development infiltration volume shall be at least 90 percent of the pre-development infiltration volume, based on an average annual rainfall. However, when designing appropriate infiltration systems to meet this requirement, no more than one percent of the post-construction site is required as

- an effective infiltration area.
- b. *Moderate imperviousness.* For development with more than 40 percent and up to 80 percent connected imperviousness, such as medium and high density residential, multi-family development, industrial and institutional development, and office parks, infiltrate sufficient runoff volume so that the post-development infiltration volume shall be at least 75 percent of the pre-development infiltration volume, based on an average annual rainfall. However, when designing appropriate infiltration systems to meet this requirement, no more than 2 percent of the post- construction site is required as an effective infiltration area.
 - c. *High imperviousness.* For development with more than 80 percent connected imperviousness, such as commercial strip malls, shopping centers, and commercial downtowns, infiltrate sufficient runoff volume so that the post-development infiltration volume shall be at least 60 percent of the pre-development infiltration volume, based on an average annual rainfall. However, when designing appropriate infiltration systems to meet this requirement, no more than 2 percent of the post-construction site is required as an effective infiltration area.
- 2. Pre-development. The pre-development condition shall be the same as specified in Table 2 of the Peak Discharge section of this ordinance.
 - 3. Source Areas.
 - a. *Prohibitions.* Runoff from the following areas may not be infiltrated and may not qualify as contributing to meeting the requirements of this section unless demonstrated to meet the conditions identified in S. 21.8 (4) (c)6.:
 - i. Areas associated with a tier 1 industrial facility identified in s. NR 216.21 (2) (a), including storage, loading and parking. Rooftops may be infiltrated with the concurrence of the regulatory authority.
 - ii. Storage and loading areas of a tier 2 industrial facility identified in s. NR

216.21 (2) (b).

- iii. Fueling and vehicle maintenance areas. Runoff from rooftops of fueling and vehicle maintenance areas may be infiltrated with the concurrence of the regulatory authority.
- b. *Exemptions.* Runoff from the following areas may be credited toward meeting the requirement when infiltrated, but the decision to infiltrate runoff from these source areas is optional:
 - i. Parking areas and access roads less than 5,000 square feet for commercial development.
 - ii. Parking areas and access roads less than 5,000 square feet for industrial development not subject to the Prohibitions under par a.
 - iii. Except as provided under S. 28.1 (3), redevelopment post-construction sites.
 - iv. In-fill development areas less than 5 acres.
 - v. Roads on commercial, industrial and institutional land uses, and arterial residential roads.
- 4. Location of Practices.
 - a. *Prohibitions.* Infiltration practices may not be located in the following areas:
 - i. Areas within 1000 feet upgradient or within 100 feet downgradient of direct conduits to groundwater.
 - ii. Areas within 400 feet of a community water system well as specified in s. NR 811.16 (4) or within the separation distances listed in s. NR 812.08 for any private well or non-community well for runoff infiltrated from commercial, including multi-family residential, industrial and institutional land uses or regional devices for one- and two-family residential development.
 - iii. Areas where contaminants of concern, as defined in s. NR 720.03 (2), are present in the soil through which infiltration

- will occur.
- b. *Separation distances.*
- i. Infiltration practices shall be located so that the characteristics of the soil and the separation distance between the bottom of the infiltration system and the elevation of seasonal high groundwater or the top of bedrock are in accordance with Table 3:

| Table 3. Separation Distances and Soil | | |
|---|-------------------|---|
| Source Area | Separation | Soil |
| Industrial, Commercial, Institutional Parking Lots | 5 feet or more | Filtering Layer |
| Residential Arterial Roads | 5 feet or more | Filtering Layer |
| Roofs Draining to Subsurface Infiltration Practices | 1 foot or more | Native or Engineered Soil with Particles Finer than Coarse Sand |
| Roofs Draining to Surface Infiltration Practices | Not Applicable | Not Applicable |
| All Other Impervious | 3 feet or more | Filtering Layer |

- ii. Notwithstanding par. b., applicable requirements for injection wells classified under ch. NR 815 shall be followed.
- c. *Infiltration rate exemptions.*
Infiltration practices located in the following areas may be credited toward meeting the requirements under the following conditions, but the decision to infiltrate under these conditions is optional:
- i. Where the infiltration rate of the soil measured at the proposed bottom of the infiltration system is less than 0.6 inches per hour using a scientifically credible field test method.
- ii. Where the least permeable soil horizon to 5 feet below the proposed bottom of

the infiltration system using the U.S. Department of Agriculture method of soils analysis is one of the following: sandy clay loam, clay loam, silty clay loam, sandy clay, silty clay, or clay.

5. Alternate Use. Where alternate uses of runoff are employed, such as for toilet flushing, laundry, or irrigation or storage on green roofs where an equivalent portion of the runoff is captured permanently by rooftop vegetation, such alternate use shall be given equal credit toward the infiltration volume required by this section.
6. Groundwater Standards.
 - a. Infiltration systems designed in accordance with this section shall, to the extent technically and economically feasible, minimize the level of pollutants infiltrating to groundwater and shall maintain compliance with the preventive action limit at a point of standards application in accordance with ch. NR 140. However, if site specific information indicates that compliance with a preventive action limit is not achievable, the infiltration BMP may not be installed or shall be modified to prevent infiltration to the maximum extent practicable.
 - b. Notwithstanding par. a., the discharge from BMPs shall remain below the enforcement standard at the point of standards application.
7. Pretreatment. Before infiltrating runoff, pretreatment shall be required for parking lot runoff and for runoff from new road construction in commercial, industrial and institutional areas that will enter an infiltration system. The pretreatment shall be designed to protect the infiltration system from clogging prior to scheduled maintenance and to protect groundwater quality in accordance with subd. 6. Pretreatment options may include, but are not limited to, oil and grease separation, sedimentation, biofiltration, filtration, swales or filter strips.
8. Maximum Extent Practicable. Where the conditions

of subd. 3. and 4. limit or restrict the use of infiltration practices, the performance standard of S. 21.8 (4)(c) shall be met to the maximum extent practicable.

(d) PROTECTIVE AREAS.

1. Definition. In this section, "protective area" means an area of land that commences at the top of the channel of lakes, streams and rivers, or at the delineated boundary of wetlands, and that is the greatest of the following widths, as measured horizontally from the top of the channel or delineated wetland boundary to the closest impervious surface. However, in this section, "protective area" does not include any area of land adjacent to any stream enclosed within a pipe or culvert, so that runoff cannot enter the enclosure at this location.
 - a. For outstanding resource waters and exceptional resource waters, 75 feet.
 - b. For perennial and intermittent streams identified on a U.S. Geological Survey 7.5-minute series topographic map, or a county soil survey map, whichever is more current, 50 feet.
 - c. For lakes, 50 feet.
 - d. For wetlands not subject to par. e. or f., 50 feet.
 - e. For highly susceptible wetlands, 75 feet. Highly susceptible wetlands include the following types: calcareous fens, sedge meadows, open and coniferous bogs, low prairies, coniferous swamps, lowland hardwood swamps, and ephemeral ponds.
 - f. For less susceptible wetlands, 10 percent of the average wetland width, but no less than 10 feet nor more than 30 feet. Less susceptible wetlands include: degraded wetland dominated by invasive species such as reed canary grass; cultivated hydric soils; and any gravel pits, or dredged material or fill material disposal sites that take on the attributes of a wetland.
 - g. In pars. d. to f., determinations of the extent of the protective area adjacent to wetlands shall be made on the basis of the

sensitivity and runoff susceptibility of the wetland in accordance with the standards and criteria in s. NR 103.03.

- h. Wetland boundary delineation shall be made in accordance with s. NR 103.08 (1m). This paragraph does not apply to wetlands that have been completely filled in compliance with all applicable state and federal regulations. The protective area for wetlands that have been partially filled in compliance with all applicable state and federal regulations shall be measured from the wetland boundary delineation after a fill has been placed. Where there is a legally authorized wetland fill, the protective area standard need not be met in that location.
- i. For concentrated flow channels with drainage areas greater than 130 acres, 10 feet.
- j. Notwithstanding pars. a. to i., the greatest protective area width shall apply where rivers, streams, lakes and wetlands are contiguous.

2. Applicability. This section applies to post-construction sites located within a protective area, except those areas exempted pursuant to subd. 4.

3. Requirements. The following requirements shall be met:

- a. Impervious surfaces shall be kept out of the protective area entirely or to the maximum extent practicable. If there is no practical alternative to locating an impervious surface in the protective area, the storm water management plan shall contain a written, site-specific explanation.
- b. Where land disturbing construction activity occurs within a protective area, adequate sod or self-sustaining vegetative cover of 70 percent or greater shall be established and maintained where no impervious surface is present. The adequate sod or self-sustaining vegetative cover shall be sufficient to provide for bank stability, maintenance of

fish habitat, and filtering of pollutants from upslope overland flow areas under sheet flow conditions. Non-vegetative materials, such as rock riprap, may be employed on the bank as necessary to prevent erosion such as on steep slopes or where high velocity flows occur.

- c. BMPs such as filter strips, swales, or wet detention ponds, that are designed to control pollutants from non-point sources, may be located in the protective area.

4. Exemptions. This section does not apply to any of the following:

- a. Except as provided under S. 21.8 (3), redevelopment post-construction sites.
- b. In-fill development areas less than 5 acres.
- c. Structures that cross or access surface water such as boat landings, bridges, and culverts.
- d. Structures constructed in accordance with s. 59.692 (1v), Stats.
- e. Areas of post-construction sites from which the runoff does not enter the surface water, including wetlands, without first being treated by a BMP to meet the local ordinance requirements for total suspended solids and peak flow reduction, except to the extent that vegetative ground cover is necessary to maintain bank stability.

- (e) FUELING AND MAINTENANCE AREAS. Fueling and vehicle maintenance areas shall have BMPs designed, installed, and maintained to reduce petroleum within runoff, so that the runoff that enters waters of the state contains no visible petroleum sheen, or to the maximum extent practicable.

- (f) SWALE TREATMENT FOR TRANSPORTATION FACILITIES.

- 1. Requirement. Except as provided in subd. 2., transportation facilities that use swales for runoff conveyance and pollutant removal are exempt from the requirements of local ordinance requirements for peak flow control, total suspended solids control, and infiltration, if

the swales are designed to do all of the following or to the maximum extent practicable:

- a. Swales shall be vegetated. However, where appropriate, non-vegetative measures may be employed to prevent erosion or provide for runoff treatment, such as rock riprap stabilization or check dams.
- b. Swales shall comply with sections V.F. (Velocity and Depth) and V.G. (Slope Geometry Criteria) with a swale treatment length as long as that specified in section V.C. (Pre-Treatment) of the Wisconsin Department of Natural Resources technical standard 1005 "Vegetated Infiltration Swales", dated May 2007, or a superseding document. Transportation facility swale treatment does not have to comply with other sections of technical standard 1005.

2. Other requirements.

- a. Notwithstanding subd. 1., the Village may, consistent with water quality standards, require that other requirements, in addition to swale treatment, be met on a transportation facility with an average daily traffic rate greater than 2,500 and where the initial surface water of the state that the runoff directly enters is one of the following:
 - i. An outstanding resource water.
 - ii. An exceptional resource water.
 - iii. Waters listed in section 303 (d) of the Federal Clean Water Act that are identified as impaired in whole or in part, due to non-point source impacts.
 - iv. Water where targeted performance standards are developed pursuant to s. NR 151.004, Wis. Adm. Code.
- b. The transportation facility authority shall contact the Village Engineer to determine if additional BMPs beyond a water quality swale are needed under this subsection.

(5) GENERAL CONSIDERATIONS FOR STORM WATER MANAGEMENT MEASURES. The following considerations shall be

observed in on-site and off-site runoff management:

- (a) Natural topography and land cover features such as natural swales, natural depressions, native soil infiltrating capacity, and natural groundwater recharge areas shall be preserved and used, to the extent possible, to meet the requirements of this section.
 - (b) Emergency overland flow for all storm water facilities shall be provided to prevent exceeding the safe capacity of downstream drainage facilities and prevent endangerment of downstream property or public safety.
- (6) BMP LOCATION.
- (a) To comply with the performance standards required under S. 21.8 of this ordinance, BMPs may be located on-site or off-site as part of a regional storm water device, practice or system, but shall be installed in accordance with s. NR 151.003, Wis. Adm. Code.
 - (b) The Village Engineer may approve off-site management measures provided that all of the following conditions are met:
 - 1. The Village Engineer determines that the post-construction runoff is covered by a storm water management system plan that is approved by the Village and that contains management requirements consistent with the purpose and intent of this ordinance.
 - 2. The off-site facility meets all the following conditions:
 - a. The facility is in place.
 - b. The facility is designed and adequately sized to provide a level of storm water control equal to or greater than that which would be afforded by on-site practices meeting the performance standards of this ordinance.
 - c. The facility has a legally obligated entity responsible for its long-term operation and maintenance.
 - (c) Where a regional treatment option exists such that the exempts the applicant from all or part of the minimum on-site storm water management requirements, the applicant shall be required to pay a fee in an

amount determined in negotiation with the Village. In determining the fee for post-construction runoff, the Village Engineer shall consider an equitable distribution of the cost for land, engineering design, construction, and maintenance of the regional treatment option.

- (7) ADDITIONAL REQUIREMENTS. The Village may establish storm water management requirements more stringent than those set forth in this ordinance if the Village Engineer determines that the requirements are needed to control storm water quantity or control flooding, comply with federally approved total maximum daily load requirements, or control pollutants associated with existing development or redevelopment.

21.9 STORM WATER MANAGEMENT PLAN

- (1) STORM WATER MANAGEMENT PLAN REQUIREMENTS. The storm water management plan required under S. 21.8 (2) shall contain at a minimum the following information:
 - (a) Name, address, and telephone number for the following or their designees: landowner; developer; project engineer for practice design and certification; person(s) responsible for installation of storm water management practices; and person(s) responsible for maintenance of storm water management practices prior to the transfer, if any, of maintenance responsibility to another party.
 - (b) A proper legal description of the property proposed to be developed, referenced to the U.S. Public Land Survey system or to block and lot numbers within a recorded land subdivision plat.
 - (c) Pre-development site conditions, including:
 - 1. One or more site maps at a scale of not less than 1 inch equals 100 feet. The site maps shall show the following: site location and legal property description; predominant soil types and hydrologic soil groups; existing cover type and condition; topographic contours of the site at a scale not to exceed one foot; topography and drainage network including enough of the contiguous properties to show runoff patterns onto, through, and from the

site; watercourses that may affect or be affected by runoff from the site; flow path and direction for all storm water conveyance sections; watershed boundaries used in hydrology determinations to show compliance with performance standards; lakes, streams, wetlands, channels, ditches, and other watercourses on and immediately adjacent to the site; limits of the 100 year floodplain; location of wells and wellhead protection areas covering the project area and delineated pursuant to s. NR 811.16, Wis. Adm. Code.

2. Hydrology and pollutant loading computations as needed to show compliance with performance standards. All major assumptions used in developing input parameters shall be clearly stated. The geographic areas used in making the calculations shall be clearly cross-referenced to the required map(s).

(d) Post-development site conditions, including:

1. Explanation of the provisions to preserve and use natural topography and land cover features to minimize changes in peak flow runoff rates and volumes to surface waters and wetlands.
2. Explanation of any restrictions on storm water management measures in the development area imposed by wellhead protection plans and ordinances.
3. One or more site maps at a scale of not less than 1 inch equals 100 feet showing the following:
post-construction pervious areas including vegetative cover type and condition; impervious surfaces including all buildings, structures, and pavement; post-construction topographic contours of the site at a scale not to exceed one foot; post-construction drainage network including enough of the contiguous properties to show runoff patterns onto, through, and from the site; locations and dimensions of drainage easements; locations of maintenance easements specified in the maintenance agreement; flow path and direction for all storm water conveyance sections; location and type of all storm water management conveyance and treatment practices, including the on-site and off-site tributary drainage area; location and type of conveyance system that will carry runoff from the drainage and treatment practices to the

nearest adequate outlet such as a curbed street, storm drain, or natural drainage way; watershed boundaries used in hydrology and pollutant loading calculations and any changes to lakes, streams, wetlands, channels, ditches, and other watercourses on and immediately adjacent to the site.

4. Hydrology and pollutant loading computations as needed to show compliance with performance standards. The computations shall be made for each discharge point in the development, and the geographic areas used in making the calculations shall be clearly cross-referenced to the required map(s).
 5. Results of investigations of soils and groundwater required for the placement and design of storm water management measures. Detailed drawings including cross-sections and profiles of all permanent storm water conveyance and treatment practices.
 - (e) A description and installation schedule for the storm water management practices needed to meet the performance standards in S. 21.8.
 - (f) A maintenance plan developed for the life of each storm water management practice including the required maintenance activities and maintenance activity schedule.
 - (g) Cost estimates for the construction, operation, and maintenance of each storm water management practice.
 - (h) Other information requested in writing by the Village Engineer to determine compliance of the proposed storm water management measures with the provisions of this ordinance.
 - (i) All site investigations, plans, designs, computations, and drawings shall be certified by a [licensed professional engineer] to be prepared in accordance with accepted engineering practice and requirements of this ordinance.
- (2) ALTERNATE REQUIREMENTS. The Village Engineer may prescribe alternative submittal requirements for applicants seeking an exemption to on-site storm water management performance standards under S. 21.8 (5).

21.10 FINANCIAL GUARANTEE

- (1) ESTABLISHMENT OF THE GUARANTEE. The Village may require the submittal of a financial guarantee, in the form an irrevocable letter of credit, certified check, surety bond or other from acceptable to the Village. The financial guarantee shall be in an amount determined by the Village Engineer to be the estimated cost of construction and the estimated cost of maintenance of the storm water management practices during the period which the designated party in the maintenance agreement has maintenance responsibility. The financial guarantee shall give the Village of Bloomfield the authorization to use the funds to complete the storm water management practices if the responsible party defaults or does not properly implement the approved storm water management plan, upon written notice to the responsible party by the Village Engineer that the requirements of this ordinance have not been met.
- (2) CONDITIONS FOR RELEASE. Conditions for the release of the financial guarantee are as follows:
 - (a) The Village shall release the portion of the financial guarantee established under this section, less any costs incurred by the Village to complete installation of practices, upon submission of "as built plans" or "record" drawings by a licensed professional engineer. The Village may make provisions for a partial pro-rata release of the financial guarantee based on the completion of various development stages.
 - (b) The Village shall release the portion of the financial guarantee established under this section to assure maintenance of storm water practices, less any costs incurred by the Village, at such time that the responsibility for practice maintenance is passed on to another entity via an approved maintenance agreement.

21.11 MAINTENANCE AGREEMENT

- (1) MAINTENANCE AGREEMENT REQUIRED. The maintenance agreement required under S. 21.13(2) for storm water management practices shall be an agreement between the Village of Bloomfield and the responsible party to provide for maintenance of storm water practices beyond the duration period of this permit. The maintenance agreement shall be filed with the Walworth County

Register of Deeds as a property deed restriction so that it is binding upon all subsequent owners of the land served by the storm water management practices.

- (2) AGREEMENT PROVISIONS. The maintenance agreement shall contain the following information and provisions and be consistent with the maintenance plan required by S. 21.09 (1)(f):
- (a) Identification of the storm water facilities and designation of the drainage area served by the facilities.
 - (b) A schedule for regular maintenance of each aspect of the storm water management system consistent with the storm water management plan required under S. 21.13 (2).
 - (c) Identification of the responsible party(s), organization or village responsible for long term maintenance of the storm water management practices identified in the storm water management plan required under S. 21.13 (2).
 - (d) Requirement that the responsible party(s), organization, or city, county, town or village shall maintain storm water management practices in accordance with the schedule included in par. (b).
 - (e) Authorization for the Village Engineer or their representatives to access the property to conduct inspections of storm water management practices as necessary to ascertain that the practices are being maintained and operated in accordance with the agreement.
 - (f) A requirement of the Village Board to maintain public records of the results of the site inspections, to inform the responsible party responsible for maintenance of the inspection results, and to specifically indicate any corrective actions required to bring the storm water management practice into proper working condition.
 - (g) Agreement that the party designated under par. (c), as responsible for long term maintenance of the storm water management practices, shall be notified by the Village Engineer of maintenance problems which require correction. The specified corrective actions shall be undertaken within a reasonable time frame as set by the Village Board.
 - (h) Authorization of the Village Board to perform the corrected actions identified in the inspection report if the responsible party designated under par. (c)

does not make the required corrections in the specified time. The Village Clerk shall enter the amount due on the tax rolls and collect the money as a special charge against the property pursuant to subch. VII of ch. 66, Wis. Stats.

21.12 ENFORCEMENT

Unless otherwise stated herein, any violation of this Chapter may be punished pursuant to Chapter 25.04 of these Ordinances.

- (1) Any land disturbing construction activity or post-construction runoff initiated after the effective date of this ordinance by any person, firm, association, or corporation subject to the ordinance provisions shall be deemed a violation unless conducted in accordance with the requirements of this ordinance.
- (2) The Village shall notify the responsible party by certified mail of any non-complying land disturbing construction activity or post-construction runoff. The notice shall describe the nature of the violation, remedial actions needed, a schedule for remedial action, and additional enforcement action which may be taken.
- (3) Upon receipt of written notification from the Village under sub. (2), the responsible party shall correct work that does not comply with the storm water management plan or other provisions of this permit. The responsible party shall make corrections as necessary to meet the specifications and schedule set forth by the Village of Bloomfield in the notice.
- (4) If the violations to a permit issued pursuant to this ordinance are likely to result in damage to properties, public facilities, or waters of the state, the Village of Bloomfield may enter the land and take emergency actions necessary to prevent such damage. The costs incurred by the Village plus interest and legal costs shall be billed to the responsible party.
- (5) The Village is authorized to post a stop work order on all land disturbing construction activity that is in violation of this ordinance, or to request the Village attorney to obtain a cease and desist order in any court with jurisdiction.
- (6) The Village may revoke a permit issued under this ordinance for non-compliance with ordinance provisions.
- (7) Any permit revocation, stop work order, or cease and desist order shall remain in effect unless retracted by

the Village of Bloomfield or by a court with jurisdiction.

- (8) The Village of Bloomfield is authorized to refer any violation of this ordinance, or a stop work order or cease and desist order issued pursuant to this ordinance, to the village attorney for the commencement of further legal proceedings in any court with jurisdiction.
- (9) Any person, firm, association, or corporation who does not comply with the provisions of this ordinance shall be subject to a forfeiture of not less than \$10.00 dollars or more than \$5,000.00 dollars per offense, together with the costs of prosecution. Each day that the violation exists shall constitute a separate offense.
- (10) Compliance with the provisions of this ordinance may also be enforced by injunction in any court with jurisdiction. It shall not be necessary to prosecute for forfeiture or a cease and desist order before resorting to injunctive proceedings.

When the Village determines that the holder of a permit issued pursuant to this ordinance has failed to follow practices set forth in the storm water management plan, or has failed to comply with schedules set forth in said storm water management plan, the Village Engineer or a party designated by the Village may enter upon the land and perform the work or other operations necessary to bring the condition of said lands into conformance with requirements of the approved storm water management plan. The Village shall keep a detailed accounting of the costs and expenses of performing this work. These costs and expenses shall be deducted from any financial security posted pursuant to chapter 21.10 of this ordinance. Where such a security has not been established, or where such a security is insufficient to cover these costs, the costs and expenses shall be entered on the tax roll as a special charge against the property

21.13 PERMIT REQUIREMENTS

- (1) PERMIT REQUIRED. No person shall undertake a land development, redevelopment or property subdivision activity subject to the requirements of this Ordinance without receiving a permit from the Village Engineer prior to commencing the proposed land development, redevelopment or property subdivision activity.
- (2) PERMIT APPLICATION AND FEE. Any person desiring a permit shall submit to the Village Engineer a permit application made on a form provided by the Village. A permit application must be accompanied by a storm water management plan, a

maintenance agreement; the financial guarantee required under the provisions of this Ordinance; and a nonrefundable permit administration fee of \$200.00. The applicant shall also be required to pay engineering fees associated with the review of the storm water management plan, and inspection of the constructed facilities for conformance with the plan requirements. The storm water management plan shall be prepared to meet the requirements of S. 21.8 and S. 21.9, the maintenance agreement shall be prepared to meet the requirements of S. 21.11, the financial guarantee shall meet the requirements of s. 21.10, and fees shall be those established by the Village as set forth in S. 21.12.

- (3) APPLICATION REVIEW. The Village Engineer shall, within 30 calendar days of the receipt of a permit application or re-submittal, review the application for compliance with the requirements of this Ordinance and shall inform the applicant whether the application plan and financial guarantee are approved or disapproved. If the application is approved, the permit shall be issued by the Village. If the application is disapproved, the applicant shall be advised in writing of the reasons for disapproval.
- (4) PERMIT REQUIREMENTS. All permits issued under this Ordinance shall be subject to the following conditions and holders of permits issued under this Ordinance shall be deemed to have accepted these conditions. The Village Board may suspend or revoke a permit for violation of a permit condition following written notification to the responsible party.
 - (a) Compliance with a permit issued under this Ordinance does not relieve the responsible party of responsibility to comply with other applicable Federal, State and municipal laws and regulations.
 - (b) The responsible party shall properly install all structural and nonstructural storm water management measures recommended in the approved site-specific storm water management plan.
 - (c) The responsible party shall notify the Village Engineer at least three working days before commencing any work to implement the approved site-specific storm water management plan, and within the next working day upon completion of the work.
 - (d) Upon completion of the storm water management facilities

and other measures required by the approved plan, the Village Engineer shall conduct an inspection of those facilities and measures to determine if they were constructed in accordance with the approved plan and the requirements of this Ordinance. The Village Engineer shall notify the responsible party in writing of any changes required in the facilities and measures to bring them into compliance with the approved plan and the requirements of this Ordinance.

- (e) Upon final approval of the constructed storm water management facilities, the developer or subdivider shall have an "as-built" plan prepared by a licensed professional engineer or registered land surveyor correctly showing the locations, configurations, and elevations of the completed facilities and measures. The "as-built" plan shall be prepared to the same scale, contour interval and vertical datum as the approved site-specific storm water management plan and shall be subject to the approval of the Village Engineer.
- (f) If so directed by the Village Engineer, the responsible party shall repair at the responsible party's own expense any and all damage to adjoining municipal facilities and drainage ways caused by storm water runoff where such damage was caused by activities not in compliance with the approved site-specific storm water management plan.
- (g) The responsible party shall permit property access to the Village Engineer or its designee for the purpose of inspecting the property for compliance with the approved storm water management plan and this permit.
- (h) The responsible party shall notify the Village Engineer of any significant modifications it intends to make to an approved storm water management plan. The Village Engineer may require that the proposed modifications be submitted for approval prior to incorporation into the storm water management plan and execution by the responsible party.
- (i) The responsible party shall maintain all storm water management practices in accordance with the storm water management plan until the practices either become the responsibility of the Village or are transferred to subsequent private owners as specified in the approved maintenance agreement.

- (j) Where site development or redevelopment involves changes in direction, increases in peak rate and/or total volume of runoff from a site, the Village may require the responsible party to make appropriate legal arrangements with affected property owners concerning the prevention of endangerment to property or public safety.
- (5) PERMIT CONDITIONS. Permits issued under this subsection may include conditions established by Village Engineer in addition to the requirements needed to meet the performance standards in S. 21.8 or a financial guarantee as provided for in S. 21.10.
- (6) PERMIT VALIDITY. Permits issued under this Ordinance shall be valid from the date of issue through the date upon which the Village Engineer notifies the responsible party that all storm water management facilities and measures have satisfactorily met final inspection by the Village Engineer.

21.14 PRE-EXISTING STORM WATER MANAGEMENT VIOLATIONS

- (1) CONDITIONS CONSTITUTING A NUISANCE. It is hereby declared that the following conditions in existence prior to the adoption of this Ordinance hereby constitute a public nuisance with affects the health, safety and property values within the Village of Bloomfield:
 - (a) Any bodies of water existing for longer than 12 hours as a direct or proximate result of human intervention in the natural diversion or drainage of storm water or snowmelt water.
- (2) EXCEPTIONS. Nuisance conditions as described above shall not include the following:
 - (a) Natural occurring water courses or bodies of water.
 - (b) Any bodies of water protected and/or regulated by the United States or the State of Wisconsin.
 - (c) Any body of water existing less than 12 hours before such body of water drains away, evaporates, or otherwise dissipates.
 - (d) Intentionally created man-made bodies of water including, but not limited to swimming/wading pools, decorative ponds, man-made ponds/lakes, man-made waterfalls or other water courses or any other container of water

capable of being moved.

- (e) Any naturally occurring permanent or temporary bodies of water, including, but not limited to the flood plains, depressions, kettles, wetlands, marshes, swamps, lakes, ponds, creeks, rivers, or springs, so long as such body of water is not substantially created to the man-made divergence or diversion of storm water, or unless otherwise accepted herein.
- (3) NOTICE TO ABATE. The Village, in its discretion, may give notice to any owner of property on which is found a pre-existing storm water violation. Such notice shall be in written form in a format created by the Village, notifying the property owner of the nature of the violation and of procedures for contesting the alleged violation, remediation, penalties, and including references to appropriate municipal ordinances.
- (a) Any person alleged to be the property owner of an alleged pre-existing storm water nuisance violation shall be given the above stated notice, and shall be afforded an opportunity to personally speak to the Village Board at a formal hearing to contest or otherwise discuss the alleged violation. Such hearing shall be afforded the property owner if the property owner files a written request for such a hearing within 10 days of receiving the notice of the alleged pre-existing storm water management violation. The notice to the property owner shall include notice of each of these rights and procedures.
 - (b) If the property owner fails to remedy the storm water nuisance condition or to submit a plan to the Village detailing how the condition will be remedied in a timely manner, then the Village may, with the permission of the property owner, enter upon the property and remedy the nuisance condition therein. Any costs incurred by the Village in correcting the nuisance condition shall be paid by the property owner, and upon failure to do so within 30 days of written notice of those costs, then the Village may add such costs to the subject property's tax bill as a special assessment. If the property owner submits a remediation plan in a timely manner, but the Village deems it unacceptable, then the property owner shall be afforded and notified of the right to appeal the decision of the Village Board to the County Circuit Court by the filing with the Village a notice of appeal of the Village Board's decision,

within 30 days of such decision.

- (c) If the property owner fails to remedy a nuisance condition or provide a plan for timely remediation of such condition, and also refuses to allow the Village or its designee to enter the subject property to remedy such condition, then the Village may apply to any Court of competent jurisdiction for an order declaring that the Village may, with the assistance of law enforcement if necessary, enter upon the subject property and remedy the nuisance condition therein, with such costs of remediation to be assessed as a special assessment against the property taxes on the subject property.

21.15 APPEALS

- (1) BOARD OF APPEALS. The board of appeals, created pursuant to section [number] of the Village ordinances pursuant to s. 62.23 (7)(e), Wis. Stats., shall hear and decide appeals where it is alleged that there is error in any order, decision or determination made by the Village in administering this ordinance. The board shall also use the rules, procedures, duties, and powers authorized by statute in hearing and deciding appeals. Upon appeal, the board may authorize variances from the provisions of this ordinance that are not contrary to the public interest, and where owing to special conditions a literal enforcement of the ordinance will result in unnecessary hardship.
- (2) WHO MAY APPEAL. Appeals to the board of appeals may be taken by any aggrieved person or by an officer, department, board, or bureau of the Village affected by any decision of the Village of Bloomfield