

PROJECT PLUS BY MEDALLION
12 mil Wearlayer - Gluedown LVT

Use		Residential & Commercial
Wearlayer	UV Urethane	12 mils (.30 mm)
Plank Size	ASTM F 2055	2mm (.80") x 7" x 48"
Total thickness	ASTM F 386	2mm
Material		100% Virgin Vinyl
Sq.ft. per Carton		46.72
Cartons Pallet / Pallet Cont.		50 / 20
Weight Carton		36 lbs.
Warranty	Lifetime Residential & 10 year Commercial Limited Warranties	
Edge		Square Edge
Recommended Adhesives	Mapei 360 or 373	
Sound Underlayment	Double Stick with dBarrier	IIC 66 Rating over 6" concrete
Material		100% Virgin Vinyl
Classification	EN ISO 10582 ASTM F 1700	22+: Domestic General Class II Type A
Reaction to fire	EN13501-1 EN ISO 11925-2 EN ISO 9239-1	Bfi-S1 Pass Pass
Resistance to Chemicals	EN 423 ASTM F 925	Class O Pass
Resistance to Light	EN ISO 105-B02 ASTM F 1515	≥ 6 <8
Wear Resistance	EN 660-2 ASTM F 510	Wear Group : T
Dimensional stability	EN 434 ASTM F 2199	≤ 0.25% Pass
Acoustic Impact noise reduction	EN ISO 717-2 EN ISO 140-8	LW = 4 dB
Static electrical propensity	EN 1815	Voltage: 0.5kV
Residual Indentation	EN 433 ASTM F 1914	≤ 0.1mm <8%
Anti-slip property	DIN 51130	R10
VOC emission	ISO 16000	A+
Phthalates	EN 14372 CPSC -CH-C 1001-09.3	N.D. Pass
Castor chair continuous use	ISO 4918	Pass
Squareness	ASTM F 2055	Pass



Phthalate Free
Important Notice

2434 Polvorosa Ave, San Leandro, CA 94577 Ph. (510) 351-8104 - Fax (510) 351-7480
 839 F Street, West Sacramento, CA 95605 Ph. (916) 372-8501 - Fax (916) 372-2175
 645 Ahua Street, Honolulu, HI 96819 Ph. (808) 836-3585 - Fax (808) 834-4722

www.medallion1.com