
Professional

Filter Fabric • Patio/Paver Underliner • Weed Control • Soil Separator 3.1 oz. Nonwoven





AVAILABLE SIZES


Retail Cases 3 x 25 1

3 x 50	12 per case	45#*
3 x 100	6 per case	45#*
Bulk Rolls		
3 x 250	750 sq. ft.	22#*
4 x 250	1000 sq. ft.	29#*
5 x 250	1250 sq. ft.	36#*
6 x 250	1500 sq. ft.	44#*
8 x 250	2000 sq. ft.	58#*
10 x 250	2500 sq. ft.	72#*
12 x 250	3000 sq. ft.	88#*
15 x 250	3750 sq. ft	110#*

15 per case

32#*

* Roll sizes & weights may vary.
For best results the use of a pre and post emergent herbicide is advised.



NO SAG PATIO/PAVER UNDERLINER

- Sand or aggregate won't sink into and intermix with soil
- Aggregate or sand base thickness can be reduced
- Prevents ground shifting, cracking, buckling and heaving
- Increases life of patio & driveway

WEED CONTROL FABRIC

- Stops approx. 95% of weed growth
- Lets air, water and fertilizer pass through to plant roots
- Saves you time (no more weeding)
- · Permanent when covered from sunlight

FILTER FABRIC

- Protects native soil and silt from clogging drainage septic systems
- Drainage protection to maintain flow and percolation
- Prolongs life of septic drain fields and drainage pipes
- Proven alternative to graded aggregate or sand filters

BENEFITS

- Maximum water flow
- Holds decorative stone and bark in place on slopes and hills
- · Cuts easy, installs quickly
- Retail & professional sizes available
- Permanent when covered from sunlight

USE UNDER OR AROUND

- Drainage & Septic Systems
- Filter Applications
- Patio Blocks
- Pavers
- Decorative Stone & Bark
- Retaining Wall Filter Fabric
- Sloped Landscape Sites

TYPICAL SPECIFICATIONS

Properties	Test Method	3.1 oz.
Unit Weight (oz/yd²)	ASTM D-3776	3.1
Tensile Strength (lbs)	ASTM D-4632	80
Elongation at Break (%)	ASTM D-4632	50
Puncture Strength (lbs)	ASTM D-4833	40
Mullen Burst (psi)	ASTM D-3786	145
A.O.S. (US Sieve Size)		50
Trap Tear (lbs)	ASTM D-4533	30
Flux (gal/ft²/min)	ASTM D-4491	155
Permittivity (sec-1)	ASTM D-4491	2.1
Thickness (mils)	ASTM D-5199	38
Material	Polyp	ropylene
	Unit Weight (oz/yd²) Tensile Strength (lbs) Elongation at Break (%) Puncture Strength (lbs) Mullen Burst (psi) A.O.S. (US Sieve Size) Trap Tear (lbs) Flux (gal/ft²/min) Permittivity (sec⁻¹) Thickness (mils)	Unit Weight (oz/yd²) ASTM D-3776 Tensile Strength (lbs) ASTM D-4632 Elongation at Break (%) ASTM D-4632 Puncture Strength (lbs) ASTM D-4833 Mullen Burst (psi) ASTM D-3786 A.O.S. (US Sieve Size) Trap Tear (lbs) ASTM D-4533 Flux (gal/ft²/min) ASTM D-4491 Permittivity (sec⁻¹) ASTM D-4491 Thickness (mils) ASTM D-5199



PROVIDES
MAXIMUM
WATER
PERMEABILITY





6398 W. 74TH ST. • BEDFORD PARK, ILLINOIS 60638 (708) 728-7180 • 1-800-992-0550 • FAX: (708) 728-0482 www.fabriscape.com • e-mail: info@fabriscape.com

^{*} Refer to page 18 for installation instructions