

T8 Ballast Compatible LED Tube



Advantages:

1. Works at 100-277Vac with or without ballast.
2. Works well no matter if powered by one or double ends .
3. Compatible with over 95% ballast brands.
4. Easy to replace by hand.



Product Features :

Type	Aluminum				Glass	Plastic
Model	SPZT8210	SPZT8413	SPZT8418A	SPZT8422A	SPZT8B418G	SPZT8B418P
Lumens Delivered (lm)	1100LM	1450LM	2190LM	2440LM	1960LM	1960LM
Efficiency (lm/W)	100-130LM/W				110-120LM/W	100-120LM/W
CCT	3000K, 4000K, 4500K, 5000K, 6000K					
CRI	Ra>85					
Power	10W	13W	18W	22W	18W	18W
Input Voltage (V)	100-277V					
Compatible	Compatible with Magnetic ballast and Electronic ballast					
Power Factor	>.96 @ 120VAC; >.96 @ 277VAC					
Certification	ETL; DLC; FCC; CE; RoHS(LM79,LM80)					
Housing	6063 Aluminum				Glass	Plastic
Power	single end powered and double ends powered					
Warranty	3 years					
Working Lifetime	>50,000H					
Operating Temperature	Operating Temperature -20°C to 40°C (-4°F to 104°F)					
PC Cover	Frosted and Clear				Frosted	Frosted
Dimensions(mm)	L600*D26 MM	L1200*D26 MM	L1200*D26 MM	L1200*D26 MM	L1200*D26 MM	L1200*D26 MM